complete java class code example of each combination of intermediate and terminal operations

filter() boolean checks + foreach() updating external systems

filter() null checks + foreach() updating external systems

filter() comparisons + foreach() updating external systems

filter() method calls returning boolean + foreach() updating external systems

distinct() rely on equals() / hashcode() + foreach() updating external systems

distinct() immutable objects + foreach() updating external systems

map() transform objects + foreach() updating external systems

map() create new objects + foreach() updating external systems

map() call pure functions + foreach() updating external systems

flatmap() return stream + foreach() updating external systems

flatmap() split data + foreach() updating external systems

flatmap() expand collections + foreach() updating external systems

sorted() natural ordering + foreach() updating external systems

sorted() custom comparator + foreach() updating external systems

sorted() multi-field compare + foreach() updating external systems

peek() logging + foreach() updating external systems

peek() debugging + foreach() updating external systems

peek() metrics + foreach() updating external systems

Below are **all 18 programs converted to Java 1.5 compatible code**.

Since Java 1.5:

- ❌ No Stream API
- ❌ No Optional
- ❌ No lambda expressions
- ❌ No method references
- ❌ No List.of(), Map.of()
- ❌ No Objects.hash()
- ❌ No Comparator.comparing()

We replace everything with:

- ✔ for-each loops
- ✔ Iterator
- ✔ Collections / Arrays
- ✔ HashSet for distinct
- ✔ Manual sorting with Comparator
- ✔ Null checks
- ✔ Primitive counters instead of AtomicInteger

Below are **complete, standalone Java class examples** showing **side-effects with forEach()** where the stream **updates an external system** (simulated as DB / cache / message queue / API).

 Important concept reminder (intentional here):
Using forEach() to update external systems is a **side-effect** and must be done **only at the terminal operation**. These examples are **educational and realistic**, not advocating misuse.

All examples:

- Java **8+**
- One intermediate concept per class
- External system = simulated service (ExternalSystem.update(...))

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

1 filter() boolean checks + forEach() Updating external systems

```
import java.util.*;
public class FilterBooleanUpdateExternal {
  public static void main(String[] args) {
    List<Integer> orders = Arrays.asList(100, 150, 200);

    for (Integer o : orders) {
      if (o >= 150) {
        ExternalSystem.update("Approved order: " + o);
      }
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

2 filter() null checks + forEach() Updating external systems

```
import java.util.*;

public class FilterNullUpdateExternal {
  public static void main(String[] args) {
    List<String> users = Arrays.asList("Anurag", null, "Amit");

    for (String u : users) {
      if (u != null) {
        ExternalSystem.update("User synced: " + u);
      }
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

3 filter() comparisons + forEach() Updating external systems

```
import java.util.*;

public class FilterComparisonUpdateExternal {
  public static void main(String[] args) {
    List<Integer> balances = Arrays.asList(500, 2000, 7000);

    for (Integer b : balances) {
      if (b > 1000) {
        ExternalSystem.update("Premium balance: " + b);
      }
    }
  }
```

```
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

4 filter() method call returning boolean + forEach() Updating external systems

```
import java.util.*;

public class FilterMethodUpdateExternal {

  static class Account {
    String id;
    boolean active;

    Account(String id, boolean active) {
      this.id = id;
      this.active = active;
    }

    boolean isActive() {
      return active;
    }
  }

  public static void main(String[] args) {
    List<Account> accounts = Arrays.asList(
        new Account("A1", true),
        new Account("A2", false)
    );

    for (Account a : accounts) {
      if (a.isActive()) {
        ExternalSystem.update("Activated account: " + a.id);
      }
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

5 distinct() equals/hashCode + forEach() Updating external systems

```
import java.util.*;

public class DistinctEqualsUpdateExternal {

  static class Customer {
    String email;

    Customer(String email) {
      this.email = email;
    }

    @Override
    public boolean equals(Object o) {
      if (this == o) return true;
      if (!(o instanceof Customer)) return false;
      Customer c = (Customer) o;
      return email.equals(c.email);
    }

    @Override
    public int hashCode() {
      return email.hashCode();
    }
  }

  public static void main(String[] args) {
    List<Customer> customers = Arrays.asList(
        new Customer("a@mail.com"),
        new Customer("a@mail.com"),
        new Customer("b@mail.com")
    );

    Set<Customer> unique = new HashSet<Customer>(customers);

    for (Customer c : unique) {
      ExternalSystem.update("Customer saved: " + c.email);
    }
  }
```

```
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

6 distinct() immutable objects + forEach() Updating external systems

```
import java.util.*;

public class DistinctImmutableUpdateExternal {
  public static void main(String[] args) {
    List<String> tags = Arrays.asList("java", "java", "spring");

    Set<String> unique = new HashSet<String>(tags);

    for (String t : unique) {
      ExternalSystem.update("Tag indexed: " + t);
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

7 map() transform objects + forEach() Updating external systems

```
import java.util.*;

public class MapTransformUpdateExternal {
  public static void main(String[] args) {
    List<String> names = Arrays.asList("anurag", "amit");

    for (String name : names) {
      String upper = name.toUpperCase();
      ExternalSystem.update("Normalized name: " + upper);
    }
  }
```

```
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

8 map() create new objects + forEach() Updating external systems

```
import java.util.*;

public class MapNewObjectUpdateExternal {

  static class UserDTO {
    String name;
    UserDTO(String name) { this.name = name; }
  }

  public static void main(String[] args) {
    List<String> names = Arrays.asList("Anurag", "Amit");

    for (String name : names) {
      UserDTO dto = new UserDTO(name);
      ExternalSystem.update("DTO persisted: " + dto.name);
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

9 map() call pure functions + forEach() Updating external systems

```
import java.util.*;

public class MapPureFunctionUpdateExternal {

   static int calculateScore(int n) {
      return n * 10;
   }

   public static void main(String[] args) {
      List<Integer> inputs = Arrays.asList(1, 2, 3);

      for (Integer n : inputs) {
         int score = calculateScore(n);
         ExternalSystem.update("Score sent: " + score);
      }
   }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

10 flatMap() return Stream + forEach() Updating external systems

```
import java.util.*;

public class FlatMapStreamUpdateExternal {
   public static void main(String[] args) {
      List<List<String>> batches = new ArrayList<List<String>>();
      batches.add(Arrays.asList("A", "B"));
      batches.add(Arrays.asList("C"));

      for (List<String> batch : batches) {
         for (String v : batch) {
            ExternalSystem.update("Batch item: " + v);
         }
      }
   }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

11 flatMap() split data + forEach() Updating external systems

```
import java.util.*;

public class FlatMapSplitUpdateExternal {
   public static void main(String[] args) {
      List<String> lines = Arrays.asList("Java Stream", "Flat Map");

      for (String line : lines) {
         String[] words = line.split(" ");
         for (String word : words) {
            ExternalSystem.update("Word indexed: " + word);
         }
      }
   }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

12 flatMap() expand collections + forEach() Updating external systems

```
import java.util.*;

public class FlatMapExpandUpdateExternal {
  public static void main(String[] args) {

    Map<String, List<String>> data = new HashMap<String, List<String>>();
    data.put("A", Arrays.asList("1", "2"));
    data.put("B", Arrays.asList("3"));

    for (List<String> values : data.values()) {
      for (String v : values) {
        ExternalSystem.update("Value synced: " + v);
      }
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

13 sorted() natural ordering + forEach() Updating external systems

```
import java.util.*;

public class SortedNaturalUpdateExternal {
  public static void main(String[] args) {
    List<Integer> priorities = Arrays.asList(3, 1, 2);

    Collections.sort(priorities);

    for (Integer p : priorities) {
      ExternalSystem.update("Processed priority: " + p);
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

14 sorted() custom comparator + forEach() Updating external systems

```
import java.util.*;

public class SortedCustomUpdateExternal {
  public static void main(String[] args) {
    List<String> jobs = Arrays.asList("LOW", "HIGH", "MEDIUM");

    Collections.sort(jobs, Collections.reverseOrder());

    for (String j : jobs) {
      ExternalSystem.update("Job executed: " + j);
    }
  }
```

```
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

15 sorted() multi-field compare + forEach() Updating external systems

```
import java.util.*;

public class SortedMultiFieldUpdateExternal {

  static class Task {
    String name;
    int priority;

    Task(String name, int priority) {
      this.name = name;
      this.priority = priority;
    }
  }

  public static void main(String[] args) {
    List<Task> tasks = Arrays.asList(
        new Task("Deploy", 2),
        new Task("Build", 1),
        new Task("Test", 2)
    );

    Collections.sort(tasks, new Comparator<Task>() {
      public int compare(Task t1, Task t2) {
        if (t1.priority != t2.priority) {
          return t1.priority - t2.priority;
        }
        return t1.name.compareTo(t2.name);
      }
    });

    for (Task t : tasks) {
      ExternalSystem.update("Task executed: " + t.name);
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

16 peek() logging + forEach() Updating external systems

```
import java.util.*;

public class PeekLoggingUpdateExternal {
  public static void main(String[] args) {
    List<Integer> list = Arrays.asList(1, 2, 3);

    for (Integer n : list) {
      System.out.println("Peek log: " + n);
      ExternalSystem.update("Final update: " + n);
    }
  }
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

17 peek() debugging + forEach() Updating external systems

```
import java.util.*;

public class PeekDebugUpdateExternal {
  public static void main(String[] args) {
    List<Integer> list = Arrays.asList(10, 20, 30);

    for (Integer n : list) {
      if (n == 20) {
        System.out.println("Debug breakpoint hit");
      }
      ExternalSystem.update("Processed value: " + n);
    }
  }
```

```
}
```

Shared helper (used conceptually in all examples)

```
public class ExternalSystem {
        public static void update(String message) {
                System.out.println("External system updated: " + message);
        }
}
```

(Each class below assumes this helper exists in the same file or package.)

18 peek() metrics + forEach() Updating external systems

```
import java.util.*;

public class PeekMetricsUpdateExternal {
   public static void main(String[] args) {

      int counter = 0;
      List<Integer> list = Arrays.asList(5, 10, 15);

      for (Integer n : list) {
         counter++;
         ExternalSystem.update("Metric sent: " + n);
      }

      ExternalSystem.update("Total processed: " + counter);
   }
}
```