complete java class code example of each combination of intermediate and terminal operations

filter() boolean checks + reduce() combine values

filter() null checks + reduce() combine values

filter() comparisons + reduce() combine values

filter() method calls returning boolean + reduce() combine values

distinct() rely on equals() / hashcode() + reduce() combine values

distinct() immutable objects + reduce() combine values

map() transform objects + reduce() combine values

map() create new objects + reduce() combine values

map() call pure functions + reduce() combine values

flatmap() return stream + reduce() combine values

flatmap() split data + reduce() combine values

flatmap() expand collections + reduce() combine values

sorted() natural ordering + reduce() combine values

sorted() custom comparator + reduce() combine values

sorted() multi-field compare + reduce() combine values

peek() logging + reduce() combine values

peek() debugging + reduce() combine values

peek() metrics + reduce() combine values

Below are **all 18 programs converted to Java 1.5 compatible code**.

Since Java 1.5:

- ❌ No Stream API
- ❌ No Optional
- ❌ No lambda expressions
- ❌ No method references
- ❌ No List.of(), Map.of()
- ❌ No Objects.hash()
- ❌ No Comparator.comparing()

We replace everything with:

- ✔ for-each loops
- ✔ Iterator
- ✔ Collections / Arrays
- ✔ HashSet for distinct
- ✔ Manual sorting with Comparator
- ✔ Null checks
- ✔ Primitive counters instead of AtomicInteger

Below are **complete, standalone Java class examples** for **every requested Stream combination**, where:

- **One primary intermediate operation** is demonstrated
- **reduce() is the terminal operation**
- **Goal = combine values** (sum, concat, merge)
- Java **8+ compatible**
- Clean, deterministic, interview-ready
- No collectors, no forEach

 Mental model
reduce(identity, accumulator) ⇒ **Combine stream elements into ONE result**

---

1 filter() boolean checks + reduce() Combine values

```
import java.util.*;

public class FilterBooleanReduce {
   public static void main(String[] args) {

      List<Integer> numbers = new ArrayList<Integer>();
      numbers.add(10);
      numbers.add(15);
      numbers.add(20);
      numbers.add(25);

      int sum = 0;

      for (Integer n : numbers) {
         if (n % 2 == 0) {                                    // filter
            sum += n;                                         // reduce
         }
      }

      System.out.println(sum);
   }
}
```

---

2 filter() null checks + reduce() Combine values

```
import java.util.*;

public class FilterNullReduce {
   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("Anurag");
      names.add(null);
      names.add("Amit");

      String combined = "";

      for (String name : names) {
         if (name != null) {                                    // filter
            combined += name;                                   // reduce
         }
      }

      System.out.println(combined);
   }
}
```

---

3 filter() comparisons + reduce() Combine values

```
import java.util.*;

public class FilterComparisonReduce {
   public static void main(String[] args) {

      List<Integer> salaries = new ArrayList<Integer>();
      salaries.add(20000);
      salaries.add(40000);
      salaries.add(60000);

      int total = 0;

      for (Integer s : salaries) {
         if (s >= 30000) {
            total += s;
         }
      }

      System.out.println(total);
   }
```

```
}
```

---

4 filter() method call boolean + reduce() Combine values

```
import java.util.*;

public class FilterMethodReduce {

   static class User {
      String name;
      boolean active;

      User(String name, boolean active) {
         this.name = name;
         this.active = active;
      }

      boolean isActive() {
         return active;
      }
   }

   public static void main(String[] args) {

      List<User> users = new ArrayList<User>();
      users.add(new User("Anurag", true));
      users.add(new User("Amit", true));
      users.add(new User("Ravi", false));

      int count = 0;

      for (User u : users) {
         if (u.isActive()) {
            count += 1;
         }
      }

      System.out.println(count);
   }
}
```

---

5 distinct() equals/hashCode + reduce() Combine values

```
import java.util.*;

public class DistinctEqualsReduce {

   static class Person {
      String name;

      Person(String name) {
         this.name = name;
      }

      public boolean equals(Object o) {
         if (this == o) return true;
         if (!(o instanceof Person)) return false;
         Person p = (Person) o;
         return name.equals(p.name);
      }

      public int hashCode() {
         return name.hashCode();
      }
   }

   public static void main(String[] args) {

      List<Person> people = new ArrayList<Person>();
      people.add(new Person("Anurag"));
      people.add(new Person("Anurag"));
      people.add(new Person("Ravi"));

      Set<Person> unique = new HashSet<Person>(people);  // distinct

      int totalLength = 0;

      for (Person p : unique) {
         totalLength += p.name.length();
      }

      System.out.println(totalLength);
   }
}
```

---

6 distinct() immutable objects + reduce() Combine values

```
import java.util.*;

public class DistinctImmutableReduce {
   public static void main(String[] args) {

      List<String> values = new ArrayList<String>();
      values.add("Java");
      values.add("Java");
      values.add("Go");

      Set<String> unique = new HashSet<String>(values);

      int lengthSum = 0;

      for (String s : unique) {
         lengthSum += s.length();
      }

      System.out.println(lengthSum);
   }
}
```

---

7 map() transform objects + reduce() Combine values

```
import java.util.*;

public class MapTransformReduce {
   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("anurag");
      names.add("amit");

      int totalChars = 0;

      for (String name : names) {
         String upper = name.toUpperCase();                    // map
         totalChars += upper.length();                         // reduce
      }

      System.out.println(totalChars);
   }
}
```

---

8 map() create new objects + reduce() Combine values

```
import java.util.*;

public class MapNewObjectReduce {

   static class UserDTO {
      String name;
      UserDTO(String name) {
         this.name = name;
      }
   }

   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("Anurag");
      names.add("Amit");

      int count = 0;

      for (String name : names) {
         UserDTO dto = new UserDTO(name);                    // map
         count += 1;                                         // reduce
      }

      System.out.println(count);
   }
}
```

---

9 map() pure functions + reduce() Combine values

```
import java.util.*;

public class MapPureFunctionReduce {

   static int square(int n) {
      return n * n;
   }

   public static void main(String[] args) {

      List<Integer> numbers = new ArrayList<Integer>();
      numbers.add(2);
      numbers.add(3);
      numbers.add(4);

      int sumOfSquares = 0;

      for (Integer n : numbers) {
         sumOfSquares += square(n);
      }

      System.out.println(sumOfSquares);
   }
}
```

---

10 flatMap() return Stream + reduce() Combine values

```
import java.util.*;

public class FlatMapStreamReduce {
   public static void main(String[] args) {

      List<List<Integer>> lists = new ArrayList<List<Integer>>();

      lists.add(Arrays.asList(1, 2));
      lists.add(Arrays.asList(3, 4));

      int total = 0;

      for (List<Integer> inner : lists) {
         for (Integer n : inner) {
            total += n;
         }
      }

      System.out.println(total);
   }
}
```

---

11 flatMap() split data + reduce() Combine values

```
import java.util.*;

public class FlatMapSplitReduce {
   public static void main(String[] args) {

      List<String> sentences = new ArrayList<String>();
      sentences.add("Java Stream");
      sentences.add("Flat Map");

      int wordCount = 0;

      for (String s : sentences) {
         String[] words = s.split(" ");
         wordCount += words.length;
      }

      System.out.println(wordCount);
   }
}
```

---

12 flatMap() expand collections + reduce() Combine values

```
import java.util.*;

public class FlatMapExpandReduce {
   public static void main(String[] args) {

      Map<String, List<Integer>> data = new HashMap<String, List<Integer>>();
      data.put("A", Arrays.asList(1, 2));
      data.put("B", Arrays.asList(3));

      int sum = 0;

      for (List<Integer> list : data.values()) {
         for (Integer n : list) {
            sum += n;
         }
      }

      System.out.println(sum);
   }
}
```

---

13 sorted() natural ordering + reduce() Combine values

```
import java.util.*;

public class SortedNaturalReduce {
   public static void main(String[] args) {

      List<Integer> numbers = new ArrayList<Integer>();
      numbers.add(5);
      numbers.add(1);
      numbers.add(3);

      Collections.sort(numbers);                    // sorted

      int total = 0;

      for (Integer n : numbers) {
         total += n;
      }

      System.out.println(total);
   }
}
```

---

14 sorted() custom comparator + reduce() Combine values

```
import java.util.*;

public class SortedCustomReduce {
   public static void main(String[] args) {

      List<String> names = new ArrayList<String>();
      names.add("Anurag");
      names.add("Ravi");
      names.add("Amit");

      Collections.sort(names, Collections.reverseOrder());

      String combined = "";

      for (String name : names) {
         combined += name;
      }

      System.out.println(combined);
   }
}
```

---

15 sorted() multi-field compare + reduce() Combine values

```
import java.util.*;

public class SortedMultiFieldReduce {

   static class Employee {
      String name;
      int age;

      Employee(String name, int age) {
         this.name = name;
         this.age = age;
      }
   }

   public static void main(String[] args) {

      List<Employee> employees = new ArrayList<Employee>();
      employees.add(new Employee("Anurag", 30));
      employees.add(new Employee("Anurag", 25));
      employees.add(new Employee("Ravi", 35));

      Collections.sort(employees, new Comparator<Employee>() {
         public int compare(Employee e1, Employee e2) {
            int nameCompare = e1.name.compareTo(e2.name);
            if (nameCompare != 0) return nameCompare;
            return e1.age - e2.age;
         }
      });

      int ageSum = 0;

      for (Employee e : employees) {
         ageSum += e.age;
      }

      System.out.println(ageSum);
   }
}
```

---

16 peek() logging + reduce() Combine values

```
import java.util.*;

public class PeekLoggingReduce {
   public static void main(String[] args) {

      List<Integer> list = Arrays.asList(1, 2, 3);

      int sum = 0;

      for (Integer n : list) {
         System.out.println("Peek: " + n);
         sum += n;
      }

      System.out.println(sum);
   }
}
```

---

17 peek() debugging + reduce() Combine values

```
import java.util.*;

public class PeekDebugReduce {
   public static void main(String[] args) {

      List<Integer> list = Arrays.asList(10, 20, 30);

      int sum = 0;

      for (Integer n : list) {
         if (n == 20) {
            System.out.println("Debug hit");
         }
         sum += n;
      }

      System.out.println(sum);
   }
}
```

---

18 peek() metrics + reduce() Combine values

```
import java.util.*;

public class PeekMetricsReduce {
   public static void main(String[] args) {

      List<Integer> list = Arrays.asList(5, 10, 15);

      int sum = 0;
      int counter = 0;

      for (Integer n : list) {
         counter++;
         sum += n;
      }

      System.out.println("Sum: " + sum);
      System.out.println("Processed: " + counter);
   }
}
```