Here's a comprehensive list of GitHub parameters used in the context of GitHub Actions and Workflows. This includes commonly used parameters and variables that you might encounter while setting up CI/CD pipelines:

Workflow Syntax Parameters

1. **name**:
   - **Description**: The name of the workflow.
   - **Example**: `name: CI/CD Pipeline`

2. **on**:
   - **Description**: The events that trigger the workflow.
   - **Example**:
     ```yaml
     on:
       push:
         branches:
           - main
       pull_request:
         branches:
           - main
     ```

3. **jobs**:
   - **Description**: A map of all the jobs in the workflow.
   - **Example**:
     ```yaml
     jobs:
       build:
         runs-on: ubuntu-latest
         steps:
     ```

```
    - name: Checkout repository
      uses: actions/checkout@v2
```

4. **runs-on**:
   - **Description**: The type of machine to run the job on.
   - **Example**: `runs-on: ubuntu-latest`

5. **steps**:
   - **Description**: A sequence of tasks to be executed in the job.
   - **Example**:
     ```yaml
     steps:
       - name: Checkout repository
         uses: actions/checkout@v2
     ```

6. **uses**:
   - **Description**: Specifies an action to run as part of a step.
   - **Example**: `uses: actions/checkout@v2`

7. **run**:
   - **Description**: Executes a command as part of a step.
   - **Example**: `run: npm install`

8. **env**:
   - **Description**: Sets environment variables for the job.
   - **Example**:
     ```yaml
     env:
```

```
    NODE_ENV: 'production'
```

GitHub Context and Variables

1. **github.actor**:
   - **Description**: The name of the person or app that initiated the workflow.
   - **Example**: `github.actor`

2. **github.event_name**:
   - **Description**: The name of the event that triggered the workflow.
   - **Example**: `github.event_name`

3. **github.event_path**:
   - **Description**: The path to the event payload file.
   - **Example**: `github.event_path`

4. **github.ref**:
   - **Description**: The branch or tag ref that triggered the workflow.
   - **Example**: `github.ref`

5. **github.repository**:
   - **Description**: The owner and repository name.
   - **Example**: `github.repository`

6. **github.sha**:
   - **Description**: The commit SHA that triggered the workflow.
   - **Example**: `github.sha`

7. **github.workflow**:

- **Description**: The name of the workflow.
- **Example**: `github.workflow`

8. **github.head_ref**:
   - **Description**: The head ref or source branch of the pull request in a workflow run.
   - **Example**: `github.head_ref`

9. **github.base_ref**:
   - **Description**: The base ref or target branch of the pull request in a workflow run.
   - **Example**: `github.base_ref`

Job-specific Parameters

1. **name**:
   - **Description**: The name of the job.
   - **Example**: `name: Build Job`

2. **needs**:
   - **Description**: Specifies the jobs that must complete successfully before this job runs.
   - **Example**: `needs: [build]`

3. **timeout-minutes**:
   - **Description**: The maximum time a job can run before GitHub automatically cancels it.
   - **Example**: `timeout-minutes: 10`

4. **strategy**:
   - **Description**: Defines a matrix of different configurations for a job.
   - **Example**:
     ```yaml
     strategy:
     ```

```
    matrix:
      node-version: [10, 12, 14]
```

Step-specific Parameters

1. **name**:
   - **Description**: The name of the step.
   - **Example**: `name: Install Dependencies`

2. **if**:
   - **Description**: A condition that must be true for the step to run.
   - **Example**: `if: success()`

3. **continue-on-error**:
   - **Description**: Specifies whether to continue running the job if this step fails.
   - **Example**: `continue-on-error: true`

4. **timeout-minutes**:
   - **Description**: The maximum time a step can run before GitHub automatically cancels it.
   - **Example**: `timeout-minutes: 5`

5. **with**:
   - **Description**: Provides inputs to actions.
   - **Example**:
     ```yaml
     with:
       node-version: '14'
     ```

6. **env**:

   - **Description**: Sets environment variables for a step.

   - **Example**:

     ```yaml

     env:

       NODE_ENV: 'development'

     ```

Common Actions and Parameters

1. **actions/checkout**:

   - **Description**: Checks out the repository under `$GITHUB_WORKSPACE` so that the workflow can access it.

   - **Example**:

     ```yaml

     uses: actions/checkout@v2

     ```

2. **actions/setup-node**:

   - **Description**: Sets up a specific version of Node.js.

   - **Example**:

     ```yaml

     uses: actions/setup-node@v2

     with:

       node-version: '14'

     ```

3. **actions/cache**:

   - **Description**: Caches dependencies to speed up workflows.

   - **Example**:

     ```yaml
     ```

```
    uses: actions/cache@v2
    with:
      path: ~/.npm
      key: ${{ runner.os }}-node-${{ hashFiles('**/package-lock.json') }}
      restore-keys: |
        ${{ runner.os }}-node-
```

Environment Variables and Secrets

1. **GITHUB_TOKEN**:
   - **Description**: An automatically generated secret to authenticate in a workflow run.
   - **Example**: `${{ secrets.GITHUB_TOKEN }}`

2. **Secrets**:
   - **Description**: Encrypted environment variables created in the GitHub repository settings.
   - **Example**:
     ```yaml
     env:
       AWS_ACCESS_KEY_ID: ${{ secrets.AWS_ACCESS_KEY_ID }}
       AWS_SECRET_ACCESS_KEY: ${{ secrets.AWS_SECRET_ACCESS_KEY }}
     ```

Artifacts and Caching

1. **actions/upload-artifact**:
   - **Description**: Uploads artifacts from your workflow.
   - **Example**:
     ```yaml
     uses: actions/upload-artifact@v2
```

```
    with:
      name: my-artifact
      path: path/to/artifact
```

2. **actions/download-artifact**:
   - **Description**: Downloads artifacts from previous workflow runs.
   - **Example**:
    ```yaml
    uses: actions/download-artifact@v2
    with:
      name: my-artifact
      path: path/to/download
    ```

This list covers the most commonly used parameters and settings for creating and managing GitHub Actions workflows. You can find more detailed information and advanced configurations in the [GitHub Actions documentation](https://docs.github.com/en/actions).