Terraform is a powerful tool for building, changing, and versioning infrastructure safely and efficiently. It uses a declarative configuration language called HashiCorp Configuration Language (HCL) to define resources. Here's a comprehensive list of common Terraform parameters, including their definitions and descriptions:

General Parameters

1. **provider**

   - **Definition**: Specifies the provider (e.g., AWS, Google Cloud, Azure) that Terraform should use.

   - **Description**: Providers are responsible for understanding API interactions and exposing resources. Each provider can require its own set of configuration variables.

2. **variable**

   - **Definition**: Defines a variable for configuration.

   - **Description**: Variables allow you to customize aspects of your configuration without modifying the source code.

3. **output**

   - **Definition**: Defines an output value.

   - **Description**: Outputs are used to display information about your infrastructure after a Terraform run has completed.

4. **locals**

   - **Definition**: Defines local values (locals).

   - **Description**: Locals can be used to simplify expressions or reduce the number of variables you need to pass around.

5. **module**

   - **Definition**: Defines a module.

   - **Description**: Modules are containers for multiple resources that are used together.

6. **resource**

- **Definition**: Defines a resource.

- **Description**: Resources are the most important element in the Terraform language. Each resource corresponds to a component of your infrastructure.

7. **data**

- **Definition**: Defines a data source.

- **Description**: Data sources allow you to fetch data from existing resources in your infrastructure.

Resource Parameters

1. **name**

- **Definition**: The logical name of the resource.

- **Description**: This name is used to reference the resource within your Terraform configuration.

2. **type**

- **Definition**: The type of the resource.

- **Description**: Specifies the kind of resource being managed (e.g., `aws_instance` for an AWS EC2 instance).

3. **count**

- **Definition**: Specifies the number of instances to create.

- **Description**: Allows you to create multiple instances of a resource using a single configuration block.

4. **lifecycle**

- **Definition**: Defines lifecycle settings.

- **Description**: Controls how Terraform handles the resource during creation, updates, and deletion.

5. **depends_on**

- **Definition**: Specifies dependencies on other resources.
- **Description**: Ensures resources are created or destroyed in the correct order.

Provisioners

1. **file**
   - **Definition**: Specifies a file to upload.
   - **Description**: Copies files from the local machine to a remote machine.

2. **local-exec**
   - **Definition**: Executes a command on the local machine.
   - **Description**: Useful for running local scripts or commands.

3. **remote-exec**
   - **Definition**: Executes a command on a remote machine.
   - **Description**: Useful for running scripts or commands on the resource being provisioned.

Expressions

1. **condition**
   - **Definition**: A boolean expression.
   - **Description**: Used in conditional statements to create resources only if the condition is met.

2. **for_each**
   - **Definition**: Iterates over a map or list.
   - **Description**: Creates resources for each item in the map or list.

Meta-Parameters

1. **provider**

- **Definition**: Specifies which provider to use for the resource.
- **Description**: Useful when you have multiple provider configurations.

2. **depends_on**
   - **Definition**: Specifies dependencies.
   - **Description**: Ensures resources are created in the correct order.

3. **count**
   - **Definition**: Creates multiple instances of a resource.
   - **Description**: Controls the number of instances to create.

4. **lifecycle**
   - **Definition**: Lifecycle customizations.
   - **Description**: Customize the creation and destruction of resources.

Backend Parameters

1. **type**
   - **Definition**: The backend type.
   - **Description**: Specifies where Terraform state is stored (e.g., S3, Consul).

2. **config**
   - **Definition**: Configuration for the backend.
   - **Description**: Provides settings such as bucket name, access credentials, etc.

Variable Parameters

1. **type**
   - **Definition**: The type of the variable.
   - **Description**: Specifies the data type (e.g., string, list, map).

2. **default**

- **Definition**: The default value.
- **Description**: If not specified, this value will be used.

3. **description**

- **Definition**: A description of the variable.
- **Description**: Helps users understand what the variable is for.

4. **validation**

- **Definition**: Validation rules.
- **Description**: Specifies conditions that the variable must meet.

5. **sensitive**

- **Definition**: Marks a variable as sensitive.
- **Description**: Prevents the variable value from being displayed in output.

Output Parameters

1. **value**

- **Definition**: The value to output.
- **Description**: The data to be returned.

2. **description**

- **Definition**: A description of the output.
- **Description**: Provides context for what the output represents.

3. **sensitive**

- **Definition**: Marks an output as sensitive.
- **Description**: Prevents the output value from being displayed in output.

This list covers many of the essential parameters in Terraform. Specific providers and resources may have additional parameters and configurations. Always refer to the [Terraform documentation](https://www.terraform.io/docs) for the most comprehensive and up-to-date information.