Here's a comprehensive list of **Kubernetes commands** categorized by purpose, along with their **description and usage** in **table format**:

Kubernetes CLI (kubectl) Commands Table

Category	Command	Description / Use	Example
Cluster Info	kubectl cluster-info	Display cluster info	kubectl cluster-info
	kubectl version	Show client and server version	kubectl version –short
	kubectl config view	Show kubeconfig settings	kubectl config view
	kubectl config use-context	Switch between clusters/contexts	kubectl config use-context my-cluster

---

Get / List Resources

Command	Description / Use	Example
kubectl get nodes	List all nodes	kubectl get nodes
kubectl get pods	List all pods in current namespace	kubectl get pods
kubectl get all	Get all resources in the namespace	kubectl get all
kubectl get svc	List all services	kubectl get svc
kubectl get deployments	List deployments	kubectl get deployments
kubectl get namespaces	List namespaces	kubectl get namespaces

---

Describe Resources

Command	Description / Use	Example
kubectl describe pod	Detailed info of a pod	kubectl describe pod pod-name

kubectl describe svc	Detailed info of a service	kubectl describe svc svc-name
kubectl describe deployment	Describe a deployment	kubectl describe deployment deploy-name

---

Create Resources

Command	Description / Use	Example
kubectl apply -f	Create/update from YAML file	kubectl apply -f deployment.yaml
kubectl create deployment	Create a deployment	kubectl create deployment nginx --image=nginx
kubectl create service	Create a service	kubectl expose deployment nginx --type=LoadBalancer --port=80

Update / Edit Resources

Command	Description / Use	Example
kubectl edit	Edit live resource in editor	kubectl edit deployment nginx
kubectl scale	Scale pods up/down	kubectl scale deployment nginx --replicas=3
kubectl rollout restart	Restart pods	kubectl rollout restart deployment nginx

---

Debug / Logs / Exec

Command	Description / Use	Example
kubectl logs	View pod logs	kubectl logs pod-name
kubectl exec	Run command in pod	kubectl exec -it pod-name –bash
kubectl port-forward	Forward pod port to local	kubectl port-forward pod-name 8080:80

kubectl cp	Copy files to/from pod	kubectl cp file.txt pod-name:/tmp/

Rollbacks / Rollouts

Command	Description / Use	Example
kubectl rollout status	Watch rollout status	kubectl rollout status deployment nginx
kubectl rollout undo	Rollback to previous version	kubectl rollout undo deployment nginx

---

Delete Resources

Command	Description / Use	Example
kubectl delete pod	Delete a specific pod	kubectl delete pod pod-name
kubectl delete svc	Delete a service	kubectl delete svc svc-name
kubectl delete -f	Delete from YAML file	kubectl delete -f deployment.yaml

---

Namespace Management

Command	Description / Use	Example
kubectl get ns	List namespaces	kubectl get ns
kubectl create namespace	Create a new namespace	kubectl create namespace dev
kubectl delete namespace	Delete a namespace	kubectl delete namespace dev
kubectl config set-context	Set default namespace	kubectl config set-context --current --namespace=dev

---

Configuration Management

Command	Description / Use	Example
kubectl config view	Show config settings	kubectl config view
kubectl config current-context	Show current context	kubectl config current-context
kubectl config set-context	Change default namespace/context	kubectl config set-context my-context --namespace=dev