SQL (Structured Query Language) is used to manage and manipulate relational databases. Below is a list of common SQL commands along with their definitions and descriptions:

Data Query Language (DQL)

- **`SELECT`**
  - **Definition**: Retrieve data from a database.
  - **Description**: Used to query the database and retrieve selected data that match the criteria specified.

Data Definition Language (DDL)

- **`CREATE TABLE`**
  - **Definition**: Create a new table.
  - **Description**: Defines a new table and its columns in the database.

- **`DROP TABLE`**
  - **Definition**: Delete a table.
  - **Description**: Removes a table and all of its data from the database.

- **`ALTER TABLE`**
  - **Definition**: Modify an existing table.
  - **Description**: Changes the structure of an existing table, such as adding, deleting, or modifying columns.

- **`CREATE INDEX`**
  - **Definition**: Create an index on a table.
  - **Description**: Adds an index to a table to improve the speed of data retrieval.

- **`DROP INDEX`**
  - **Definition**: Delete an index.

- **Description**: Removes an index from the database.

Data Manipulation Language (DML)

- **`INSERT INTO`**
  - **Definition**: Add new data to a table.
  - **Description**: Inserts new rows of data into a table.

- **`UPDATE`**
  - **Definition**: Modify existing data.
  - **Description**: Changes existing data within a table based on specified conditions.

- **`DELETE`**
  - **Definition**: Remove data from a table.
  - **Description**: Deletes rows of data from a table based on specified conditions.

Data Control Language (DCL)

- **`GRANT`**
  - **Definition**: Give privileges to users.
  - **Description**: Assigns permissions to users or roles to access database objects.

- **`REVOKE`**
  - **Definition**: Remove privileges from users.
  - **Description**: Removes permissions from users or roles.

Transaction Control Language (TCL)

- **`COMMIT`**
  - **Definition**: Save work done.

  - **Description**: Makes all changes made in the current transaction permanent.

- **`ROLLBACK`**
  - **Definition**: Undo work done.
  - **Description**: Reverts all changes made in the current transaction.

- **`SAVEPOINT`**
  - **Definition**: Set a savepoint within a transaction.
  - **Description**: Marks a point within a transaction to which you can later roll back.

- **`SET TRANSACTION`**
  - **Definition**: Define transaction properties.
  - **Description**: Sets the characteristics of the current transaction.

Additional SQL Commands

- **`SELECT INTO`**
  - **Definition**: Copy data from one table into a new table.
  - **Description**: Creates a new table and inserts the result set of the SELECT query into it.

- **`INSERT INTO SELECT`**
  - **Definition**: Copy data from one table into another existing table.
  - **Description**: Inserts data from one table into another existing table based on a SELECT query.

- **`CREATE DATABASE`**
  - **Definition**: Create a new database.
  - **Description**: Sets up a new database in the database management system.

- **`DROP DATABASE`**
  - **Definition**: Delete a database.

- **Description**: Removes an entire database and all of its data.

- **`TRUNCATE TABLE`**

  - **Definition**: Remove all data from a table.

  - **Description**: Deletes all rows from a table without logging the individual row deletions.

- **`DESCRIBE`**

  - **Definition**: Display the structure of a table.

  - **Description**: Provides details about the columns and data types in a table.

- **`SHOW`**

  - **Definition**: Display database, table, or column information.

  - **Description**: Used to display various pieces of information, such as available databases, tables, or columns.

- **`USE`**

  - **Definition**: Select a database.

  - **Description**: Chooses a specific database to work with.

Conditional and Join Statements

- **`WHERE`**

  - **Definition**: Filter records.

  - **Description**: Specifies the conditions for selecting rows in a query.

- **`ORDER BY`**

  - **Definition**: Sort records.

  - **Description**: Arranges the result set of a query by specified columns.

- **`GROUP BY`**

- **Definition**: Group records.
- **Description**: Groups rows that have the same values in specified columns into aggregate data.

- **`HAVING`**
- **Definition**: Filter groups.
- **Description**: Specifies conditions on groups created by the GROUP BY clause.

- **`JOIN`**
- **Definition**: Combine rows from two or more tables.
- **Description**: Combines rows from different tables based on a related column.

- **`INNER JOIN`**
- **Definition**: Combine rows from two tables when there is a match in both tables.
- **Description**: Retrieves rows that have matching values in both tables.

- **`LEFT JOIN` (or **`LEFT OUTER JOIN`**)
- **Definition**: Combine rows from two tables and include all rows from the left table.
- **Description**: Retrieves all rows from the left table and matched rows from the right table. Non-matching rows will have NULLs.

- **`RIGHT JOIN` (or **`RIGHT OUTER JOIN`**)
- **Definition**: Combine rows from two tables and include all rows from the right table.
- **Description**: Retrieves all rows from the right table and matched rows from the left table. Non-matching rows will have NULLs.

- **`FULL JOIN` (or **`FULL OUTER JOIN`**)
- **Definition**: Combine rows from two tables and include all rows from both tables.
- **Description**: Retrieves all rows when there is a match in one of the tables. Non-matching rows will have NULLs.

- **`UNION`**

- **Definition**: Combine the results of two queries.
- **Description**: Combines the result sets of two or more SELECT statements into a single result set, removing duplicates.

- **`UNION ALL`**
- **Definition**: Combine the results of two queries, including duplicates.
- **Description**: Combines the result sets of two or more SELECT statements into a single result set, including duplicates.

Subqueries and Set Operations

- **`EXISTS`**
- **Definition**: Check for the existence of rows.
- **Description**: Tests for the existence of any record in a subquery.

- **`IN`**
- **Definition**: Specify multiple possible values for a column.
- **Description**: Allows you to specify multiple values in a WHERE clause.

- **`ANY`**
- **Definition**: Compare a value to any value in a list or subquery.
- **Description**: Used to compare a value to any value in a list or subquery.

- **`ALL`**
- **Definition**: Compare a value to all values in a list or subquery.
- **Description**: Used to compare a value to all values in a list or subquery.

This list includes many of the essential SQL commands for interacting with relational databases. Each command can have various options and clauses that significantly alter its behavior, so consulting the specific database's documentation is always useful for more detailed information.