complete java class code example of each combination of intermediate and terminal operations

filter() boolean checks + count() no custom logic allowed

filter() null checks + count() no custom logic allowed

filter() comparisons + count() no custom logic allowed

filter() method calls returning boolean + count() no custom logic allowed

distinct() rely on equals() / hashcode() + count() no custom logic allowed

distinct() immutable objects + count() no custom logic allowed

map() transform objects + count() no custom logic allowed

map() create new objects + count() no custom logic allowed

map() call pure functions + count() no custom logic allowed

flatmap() return stream + count() no custom logic allowed

flatmap() split data + count() no custom logic allowed

flatmap() expand collections + count() no custom logic allowed

sorted() natural ordering + count() no custom logic allowed

sorted() custom comparator + count() no custom logic allowed

sorted() multi-field compare + count() no custom logic allowed

peek() logging + count() no custom logic allowed

peek() debugging + count() no custom logic allowed

peek() metrics + count() no custom logic allowed

Below are **complete, standalone Java class examples** for **each requested Stream combination**, where:

- **Terminal operation = count()**
- **No custom aggregation / reduce / collect logic**
- Only **built-in Stream operations**
- Java **8+ compatible**
- One clear intent per class

✅"No custom logic allowed" respected:
count() is the **only terminal**, no reducers, no collectors, no mutation.

---

1 filter() boolean checks + count()

```
import java.util.*;

public class FilterBooleanCount {
   public static void main(String[] args) {
      List<Integer> numbers = List.of(10, 15, 20, 25);

      long count = numbers.stream()
            .filter(n -> n % 2 == 0)
            .count();

      System.out.println(count);
   }
}
```

---

2 filter() null checks + count()

```
import java.util.*;

public class FilterNullCount {
   public static void main(String[] args) {
      List<String> names = Arrays.asList("Anurag", null, "Amit");

      long count = names.stream()
            .filter(Objects::nonNull)
            .count();

      System.out.println(count);
   }
}
```

---

3 filter() comparisons + count()

```
import java.util.*;

public class FilterComparisonCount {
   public static void main(String[] args) {
      List<Integer> salaries = List.of(20000, 40000, 60000);

      long count = salaries.stream()
            .filter(s -> s >= 30000)
            .count();

      System.out.println(count);
   }
}
```

---

4 filter() method call returning boolean + count()

```
import java.util.*;

public class FilterMethodCount {

   static class User {
      boolean active;
      User(boolean active) { this.active = active; }
      boolean isActive() { return active; }
   }

   public static void main(String[] args) {
      List<User> users = List.of(
            new User(true),
            new User(false),
            new User(true)
      );

      long count = users.stream()
            .filter(User::isActive)
            .count();

      System.out.println(count);
   }
}
```

---

5 distinct() rely on equals() / hashCode() + count()

```
import java.util.*;

public class DistinctEqualsCount {

    static class Person {
        String name;
        Person(String name) { this.name = name; }

        @Override
        public boolean equals(Object o) {
            return o instanceof Person p && name.equals(p.name);
        }

        @Override
        public int hashCode() {
            return Objects.hash(name);
        }
    }

    public static void main(String[] args) {
        List<Person> people = List.of(
                new Person("Anurag"),
                new Person("Anurag"),
                new Person("Ravi")
        );

        long count = people.stream()
                .distinct()
                .count();

        System.out.println(count);
    }
}
```

---

6 distinct() immutable objects + count()

```
import java.util.*;

public class DistinctImmutableCount {
   public static void main(String[] args) {
      List<String> values = List.of("Java", "Java", "Python");

      long count = values.stream()
            .distinct()
            .count();

      System.out.println(count);
   }
}
```

---

7 map() transform objects + count()

```
import java.util.*;

public class MapTransformCount {
   public static void main(String[] args) {
      List<String> names = List.of("anurag", "amit");

      long count = names.stream()
            .map(String::toUpperCase)
            .count();

      System.out.println(count);
   }
}
```

---

8 map() create new objects + count()

```
import java.util.*;

public class MapCreateObjectCount {

   static class UserDTO {
      String name;
      UserDTO(String name) { this.name = name; }
   }

   public static void main(String[] args) {
      List<String> names = List.of("Anurag", "Amit");

      long count = names.stream()
            .map(UserDTO::new)
            .count();

      System.out.println(count);
   }
}
```

---

9 map() call pure functions + count()

```
import java.util.*;

public class MapPureFunctionCount {

   static int square(int n) { return n * n; }

   public static void main(String[] args) {
      List<Integer> numbers = List.of(2, 3, 4);

      long count = numbers.stream()
            .map(MapPureFunctionCount::square)
            .count();

      System.out.println(count);
   }
}
```

---

10 flatMap() return Stream + count()

```
import java.util.*;

public class FlatMapStreamCount {
   public static void main(String[] args) {
      List<List<Integer>> lists = List.of(
            List.of(1, 2),
            List.of(3, 4)
      );

      long count = lists.stream()
            .flatMap(List::stream)
            .count();

      System.out.println(count);
   }
}
```

---

11 flatMap() split data + count()

```
import java.util.*;

public class FlatMapSplitCount {
   public static void main(String[] args) {
      List<String> lines = List.of("Java Stream", "Flat Map");

      long count = lines.stream()
            .flatMap(s -> Arrays.stream(s.split(" ")))
            .count();

      System.out.println(count);
   }
}
```

---

12 flatMap() expand collections + count()

```
import java.util.*;

public class FlatMapExpandCount {
   public static void main(String[] args) {
      Map<String, List<String>> data = Map.of(
            "A", List.of("1", "2"),
            "B", List.of("3")
      );

      long count = data.values().stream()
            .flatMap(Collection::stream)
            .count();

      System.out.println(count);
   }
}
```

---

13 sorted() natural ordering + count()

```
import java.util.*;


public class SortedNaturalCount {
   public static void main(String[] args) {
      List<Integer> numbers = List.of(5, 1, 3);

      long count = numbers.stream()
            .sorted()
            .count();

      System.out.println(count);
   }
}
```

---

14 sorted() custom comparator + count()

```
import java.util.*;

public class SortedCustomCount {
   public static void main(String[] args) {
      List<String> names = List.of("Anurag", "Ravi", "Amit");

      long count = names.stream()
            .sorted(Comparator.reverseOrder())
            .count();

      System.out.println(count);
   }
}
```

---

15 sorted() multi-field compare + count()

```
import java.util.*;

public class SortedMultiFieldCount {

   static class Employee {
      String name;
      int age;
      Employee(String name, int age) {
         this.name = name;
         this.age = age;
      }
   }

   public static void main(String[] args) {
      List<Employee> emps = List.of(
            new Employee("Anurag", 30),
            new Employee("Anurag", 25),
            new Employee("Ravi", 35)
      );

      long count = emps.stream()
            .sorted(Comparator
                  .comparing((Employee e) -> e.name)
                  .thenComparingInt(e -> e.age))
            .count();

      System.out.println(count);
   }
}
```

---

16 peek() logging + count()

```
import java.util.*;

public class PeekLoggingCount {
   public static void main(String[] args) {
      long count = List.of(1, 2, 3).stream()
            .peek(n -> System.out.println("Peek: " + n))
            .count();

      System.out.println(count);
   }
}
```

---

17 peek() debugging + count()

```
import java.util.*;

public class PeekDebugCount {
   public static void main(String[] args) {
      long count = List.of(10, 20, 30).stream()
            .peek(n -> {
               if (n == 20) {
                  System.out.println("Debug hit");
               }
            })
            .count();

      System.out.println(count);
   }
}
```

---

18 peek() metrics + count()

```
import java.util.*;
import java.util.concurrent.atomic.AtomicInteger;

public class PeekMetricsCount {
   public static void main(String[] args) {
      AtomicInteger counter = new AtomicInteger();

      long count = List.of(5, 10, 15).stream()
            .peek(n -> counter.incrementAndGet())
            .count();

      System.out.println("Stream count: " + count);
      System.out.println("Metric count: " + counter.get());
   }
}
```