Complete Java class code example of each combination of intermediate and terminal operations

filter() boolean checks + allmatch() rule checks

filter() null checks + allmatch() rule checks

filter() comparisons + allmatch() rule checks

filter() method calls returning boolean + allmatch() rule checks

distinct() rely on equals() / hashcode() + allmatch() rule checks

distinct() immutable objects + allmatch() rule checks

map() transform objects + allmatch() rule checks

map() create new objects + allmatch() rule checks

map() call pure functions + allmatch() rule checks

flatmap() return stream + allmatch() rule checks

flatmap() split data + allmatch() rule checks

flatmap() expand collections + allmatch() rule checks

sorted() natural ordering + allmatch() rule checks

sorted() custom comparator + allmatch() rule checks

sorted() multi-field compare + allmatch() rule checks

peek() logging + allmatch() rule checks

peek() debugging + allmatch() rule checks

peek() metrics + allmatch() rule checks

Below are **complete, standalone Java class examples** for **each requested Stream combination**, where:

- **Terminal operation = allMatch()**
- Purpose = **rule checks** (business / validation rules)
- **Short-circuiting behavior** is intentional
- Java **8+**
- No collectors, no reduce, no side-effect mutation (except peek demos)

---

1 filter() boolean checks + allMatch() — Rule checks

```
import java.util.*;

public class FilterBooleanAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of(2, 4, 6, 8).stream()
            .filter(n -> n > 0)
            .allMatch(n -> n % 2 == 0);

      System.out.println(rulePassed);
   }
}
```

---

2 filter() null checks + allMatch() — Rule checks

```
import java.util.*;

public class FilterNullAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = Arrays.asList("Anurag", "Amit").stream()
            .filter(Objects::nonNull)
            .allMatch(name -> name.length() >= 4);

      System.out.println(rulePassed);
   }
}
```

---

3 filter() comparisons + allMatch() — Rule checks

```
import java.util.*;

public class FilterComparisonAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of(25, 30, 40).stream()
            .filter(age -> age >= 18)
            .allMatch(age -> age <= 60);

      System.out.println(rulePassed);
   }
}
```

---

4 filter() method calls returning boolean + allMatch() — Rule checks

```
import java.util.*;

public class FilterMethodAllMatchRule {

   static class User {
      boolean verified;
      User(boolean verified) { this.verified = verified; }
      boolean isVerified() { return verified; }
   }

   public static void main(String[] args) {
      boolean rulePassed = List.of(
            new User(true),
            new User(true)
      ).stream()
       .filter(User::isVerified)
       .allMatch(User::isVerified);

      System.out.println(rulePassed);
   }
}
```

---

5 distinct() rely on equals() / hashCode() + allMatch() — Rule checks

```
import java.util.*;

public class DistinctEqualsAllMatchRule {

   static class Person {
      String email;
      Person(String email) { this.email = email; }

      @Override
      public boolean equals(Object o) {
         return o instanceof Person p && email.equals(p.email);
      }

      @Override
      public int hashCode() {
         return Objects.hash(email);
      }
   }

   public static void main(String[] args) {
      boolean rulePassed = List.of(
            new Person("a@mail.com"),
            new Person("a@mail.com"),
            new Person("b@mail.com")
      ).stream()
       .distinct()
       .allMatch(p -> p.email.contains("@"));

      System.out.println(rulePassed);
   }
}
```

---

6 distinct() immutable objects + allMatch() — Rule checks

```
import java.util.*;

public class DistinctImmutableAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of("Java", "Java", "Python").stream()
            .distinct()
            .allMatch(lang -> lang.length() >= 4);

      System.out.println(rulePassed);
   }
}
```

---

7 map() transform objects + allMatch() — Rule checks

```
import java.util.*;

public class MapTransformAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of("anurag", "amit").stream()
            .map(String::toUpperCase)
            .allMatch(s -> s.equals(s.toUpperCase()));

      System.out.println(rulePassed);
   }
}
```

---

8 map() create new objects + allMatch() — Rule checks

```
import java.util.*;

public class MapCreateObjectAllMatchRule {

   static class UserDTO {
      String name;
      UserDTO(String name) { this.name = name; }
   }

   public static void main(String[] args) {
      boolean rulePassed = List.of("Anurag", "Amit").stream()
            .map(UserDTO::new)
            .allMatch(dto -> dto.name.length() >= 4);

      System.out.println(rulePassed);
   }
}
```

---

9 map() call pure functions + allMatch() — Rule checks

```
import java.util.*;

public class MapPureFunctionAllMatchRule {

   static int normalize(int n) { return n * 10; }

   public static void main(String[] args) {
      boolean rulePassed = List.of(1, 2, 3).stream()
            .map(MapPureFunctionAllMatchRule::normalize)
            .allMatch(n -> n >= 10);

      System.out.println(rulePassed);
   }
}
```

---

10 flatMap() return Stream + allMatch() — Rule checks

```
import java.util.*;

public class FlatMapStreamAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of(
            List.of(1, 2),
            List.of(3, 4)
      ).stream()
       .flatMap(List::stream)
       .allMatch(n -> n > 0);

      System.out.println(rulePassed);
   }
}
```

---

11 flatMap() split data + allMatch() — Rule checks

```
import java.util.*;

public class FlatMapSplitAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of("Java Stream", "Flat Map").stream()
            .flatMap(s -> Arrays.stream(s.split(" ")))
            .allMatch(word -> word.length() >= 3);

      System.out.println(rulePassed);
   }
}
```

---

12 flatMap() expand collections + allMatch() — Rule checks

```
import java.util.*;

public class FlatMapExpandAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = Map.of(
            "A", List.of("1", "2"),
            "B", List.of("3")
      ).values().stream()
       .flatMap(Collection::stream)
       .allMatch(v -> !v.isEmpty());

      System.out.println(rulePassed);
   }
}
```

---

13 sorted() natural ordering + allMatch() — Rule checks

```
import java.util.*;

public class SortedNaturalAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of(1, 2, 3).stream()
            .sorted()
            .allMatch(n -> n >= 1);

      System.out.println(rulePassed);
   }
}
```

---

14 sorted() custom comparator + allMatch() — Rule checks

```
import java.util.*;

public class SortedCustomAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of("Anurag", "Ravi", "Amit").stream()
            .sorted(Comparator.reverseOrder())
            .allMatch(name -> name.length() >= 4);

      System.out.println(rulePassed);
   }
}
```

---

15 sorted() multi-field compare + allMatch() — Rule checks

```
import java.util.*;

public class SortedMultiFieldAllMatchRule {

   static class Employee {
      String name;
      int age;
      Employee(String name, int age) {
         this.name = name; this.age = age;
      }
   }

   public static void main(String[] args) {
      boolean rulePassed = List.of(
            new Employee("Anurag", 30),
            new Employee("Anurag", 25),
            new Employee("Ravi", 35)
      ).stream()
       .sorted(Comparator
             .comparing((Employee e) -> e.name)
             .thenComparingInt(e -> e.age))
       .allMatch(e -> e.age >= 18);

      System.out.println(rulePassed);
   }
}
```

---

16 peek() logging + allMatch() — Rule checks

```
import java.util.*;

public class PeekLoggingAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of(1, 2, 3).stream()
            .peek(n -> System.out.println("Checking: " + n))
            .allMatch(n -> n > 0);

      System.out.println(rulePassed);
   }
}
```

---

17 peek() debugging + allMatch() — Rule checks

```
import java.util.*;

public class PeekDebugAllMatchRule {
   public static void main(String[] args) {
      boolean rulePassed = List.of(10, 20, 30).stream()
            .peek(n -> {
               if (n == 20) System.out.println("Debug breakpoint");
            })
            .allMatch(n -> n >= 10);

      System.out.println(rulePassed);
   }
}
```

---

18 peek() metrics + allMatch() — Rule checks

```
import java.util.*;
import java.util.concurrent.atomic.AtomicInteger;

public class PeekMetricsAllMatchRule {
   public static void main(String[] args) {
      AtomicInteger processed = new AtomicInteger();

      boolean rulePassed = List.of(5, 10, 15).stream()
            .peek(n -> processed.incrementAndGet())
            .allMatch(n -> n > 0);

      System.out.println("Rule passed: " + rulePassed);
      System.out.println("Processed elements: " + processed.get());
   }
}
```