

Here's a **complete, structured guide to Java Stream API methods** (Java 8 → 21), with **examples + real-time use cases**.

❑ 1. Stream Creation Methods

Method	Description	Example
Collection.stream()	Sequential stream	list.stream()
Collection.parallelStream()	Parallel stream	list.parallelStream()
Stream.of()	Create from values	Stream.of(1,2,3)
Arrays.stream()	From array	Arrays.stream(arr)
Stream.generate()	Infinite stream	Stream.generate(Math::random)
Stream.iterate()	Iterative stream	Stream.iterate(1, n -> n+1)

✓ Example

```
List<Integer> list = List.of(1,2,3,4);  
list.stream().forEach(System.out::println);
```

❑ Real-time Use Case

- Reading data from DB, file, or API and processing sequentially/parallel
-

❑ 2. Intermediate Operations

❑ These return a **new stream** (lazy execution)

❑ Filtering

Method	Description
filter()	Apply condition
distinct()	Remove duplicates
limit()	Limit elements
skip()	Skip elements

✓ Example

```
list.stream()
    .filter(x -> x % 2 == 0)
    .distinct()
    .forEach(System.out::println);
```

□ Use Case

- Filtering active users, valid records, etc.
-

□ Mapping

Method	Description
map()	Transform elements
flatMap()	Flatten nested data

✓ Example

```
List<String> names = List.of("Anurag", "Java");
```

```
names.stream()
    .map(String::toUpperCase)
    .forEach(System.out::println);
```

□ Use Case

- Convert DTO → Entity, lowercase → uppercase, etc.
-

□ Sorting

Method	Description
sorted()	Natural sorting
sorted(Comparator)	Custom sorting

✓ Example

```
list.stream()
```

```
.sorted((a,b) -> b - a)
.forEach(System.out::println);
```

☐ Use Case

- Sorting products by price, users by name

☐ Peek (Debugging)

Method	Description
peek()	Debug/intermediate logging

```
list.stream()
    .peek(System.out::println)
    .map(x -> x * 2)
    .forEach(System.out::println);
```

☐ 3. Terminal Operations

☐ These produce **final result**

☐ Iteration

Method	Description
forEach()	Iterate
forEachOrdered()	Ordered iteration

```
list.stream().forEach(System.out::println);
```

☐ Collecting

Method	Description
collect()	Convert to collection

```
List<Integer> result = list.stream()
    .filter(x -> x > 2)
    .collect(Collectors.toList());
```

☐ Use Case

- Convert processed data into List/Map for API response
-

☐ Reduction

Method	Description
reduce()	Aggregate values

```
int sum = list.stream()  
    .reduce(0, Integer::sum);
```

☐ Use Case

- Total salary, total sales, etc.
-

☐ Matching

Method	Description
anyMatch()	Any match
allMatch()	All match
noneMatch()	No match

```
boolean hasEven = list.stream().anyMatch(x -> x % 2 == 0);
```

☐ Finding

Method	Description
findFirst()	First element
findAny()	Any element

```
Optional<Integer> first = list.stream().findFirst();
```

☐ Counting

```
long count = list.stream().count();
```

❑ Min / Max

```
int max = list.stream().max(Integer::compare).get();
```

❑ 4. Specialized Streams

Type	Methods
IntStream	range(), rangeClosed()
LongStream	Same
DoubleStream	Same

```
IntStream.range(1,5).forEach(System.out::println);
```

❑ 5. Advanced Collectors

Method	Description
groupingBy()	Group data
partitioningBy()	Split true/false
joining()	Join strings
counting()	Count elements
mapping()	Transform in collect

✓ Example

```
Map<Integer, List<String>> grouped =  
    names.stream()  
        .collect(Collectors.groupingBy(String::length));
```

❑ Use Case

- Group employees by department
- Partition users active/inactive

□ 6. Parallel Stream

```
list.parallelStream()
    .forEach(System.out::println);
```

□ Use Case

- Large data processing (Big Data, logs, analytics)

□ 7. Real-Time End-to-End Example

□ Scenario: E-commerce Order Processing

```
class Order {
    String name;
    double price;

    Order(String name, double price) {
        this.name = name;
        this.price = price;
    }
}
```

```
List<Order> orders = List.of(
    new Order("Laptop", 50000),
    new Order("Mobile", 20000),
    new Order("Tablet", 15000)
);
```

```
// Get total price of orders > 20000
double total = orders.stream()
    .filter(o -> o.price > 20000)
    .map(o -> o.price)
    .reduce(0.0, Double::sum);
```

```
System.out.println(total);
```

□ 8. Summary (Quick View)

Category	Methods
Creation	stream(), of(), iterate(), generate()

Intermediate	filter, map, flatMap, sorted, distinct
Terminal	forEach, collect, reduce, count
Matching	anyMatch, allMatch, noneMatch
Finding	findFirst, findAny
Advanced	groupingBy, partitioningBy
Parallel	parallelStream

□ Key Points

- Streams are **lazy** (execute only on terminal operation)
- Do not store data — they process pipelines
- Support **functional programming**
- Can run **parallel (ForkJoinPool)**

If you want, I can also provide:

- ✓ Internal working of Stream API
- ✓ Performance comparison (Stream vs Loop)
- ✓ All Collectors with deep examples
- ✓ Interview questions on Stream API

Just tell me □

Here's a **deep, practical performance comparison of Java Streams vs Traditional Loops**, including **benchmarks, internals, and when to use what**.

□ 1. Basic Difference

Feature	Stream API	Traditional Loop
Style	Functional	Imperative
Readability	High	Medium
Performance	Slight overhead	Faster (usually)

Parallelism	Easy (parallelStream)	Manual (Threads)
Debugging	Harder	Easier

❑ 2. Benchmark Comparison (Typical Results)

❑ Based on common JMH-style benchmarks (10M elements)

Operation	Loop (ms)	Stream (ms)	Parallel Stream (ms)
Filter + Sum	20–30 ms	35–50 ms	10–25 ms
Simple Iteration	10–15 ms	25–40 ms	15–30 ms
Complex Mapping	30–50 ms	40–70 ms	20–35 ms
Small Dataset (1K)	0.1 ms	0.5 ms	2–5 ms

❑ 3. Code Comparison

✔ Example: Sum of Even Numbers

❑ Loop

```
int sum = 0;
for (int i = 0; i < list.size(); i++) {
    if (list.get(i) % 2 == 0) {
        sum += list.get(i);
    }
}
```

❑ Stream

```
int sum = list.stream()
    .filter(x -> x % 2 == 0)
    .mapToInt(Integer::intValue)
    .sum();
```

❑ 4. Performance Analysis

❑ Why Loops Are Faster?

- No object creation (no lambda)

- No pipeline overhead
- Direct CPU execution
- Better JVM optimizations (JIT)

□ Result: **Best for small & critical performance code**

□ **Why Streams Are Slower?**

- Lambda creation
 - Method call overhead
 - Internal iteration
 - Boxing/Unboxing (Integer vs int)
-

□ **Why Parallel Streams Can Be Faster?**

- Uses **ForkJoinPool**
- Splits data into chunks
- Multi-core execution

□ But only when:

- Data is large
 - Task is CPU-heavy
-

□ **5. Internal Working Difference**

□ **Loop (External Iteration)**

You control iteration

↓

One-by-one processing

↓

Immediate execution

□ **Stream (Internal Iteration)**

Pipeline creation

↓

Lazy evaluation

↓

Terminal operation triggers execution

↓

Optimized traversal

❑ 6. Real-Time Use Cases

✔ Use LOOP when:

- Low latency systems (Trading, Gaming)
- Small datasets
- Tight performance constraints
- Complex control flow (break, continue)

❑ Example:

```
for (Order o : orders) {  
    if (o.price > 50000) break;  
}
```

✔ Use STREAM when:

- Data transformation pipelines
- Clean, readable code required
- Working with collections (filter/map/group)
- Parallel processing needed

❑ Example:

```
orders.stream()  
    .filter(o -> o.price > 10000)  
    .collect(Collectors.toList());
```

❑ 7. Parallel Stream Deep Insight

Factor	Impact
CPU cores	More cores = better performance
Data size	Small → worse performance
I/O operations	Not suitable
Thread overhead	High

☐ When Parallel Streams are BAD

```
list.parallelStream()
    .forEach(System.out::println); // unordered + slow for small data
```

☐ 8. Memory & GC Impact

Factor	Loop	Stream
Memory usage	Low	Higher
GC pressure	Low	Moderate
Object creation	Minimal	More (lambda, streams)

☐ 9. Key Performance Rules

☐ Rule 1

☐ Small data → **Loop is faster**

☐ Rule 2

☐ Large data + CPU work → **Parallel Stream wins**

☐ Rule 3

☐ Readability matters → **Use Stream**

☐ Rule 4

☐ Performance critical → **Use Loop**

☐ 10. Final Verdict

Scenario	Best Choice
High performance critical	✓ Loop
Clean functional code	✓ Stream
Big data processing	✓ Parallel Stream

Simple iteration	✓ Loop
Complex transformation	✓ Stream

□ 11. Interview Summary (One Line)

□ “Loops are faster, Streams are cleaner, Parallel Streams are powerful—but only with large data.”

If you want next level:

- ✓ JMH Benchmark setup code
- ✓ Internal working of parallel streams (ForkJoinPool)
- ✓ Stream optimization tricks
- ✓ Fail-fast vs fail-safe deep performance

Just tell me □

Great—this is exactly the **advanced level** most developers miss. Let’s go step by step with **practical + internal + interview-ready clarity**.

□ 1. ✓ JMH Benchmark Setup Code (Accurate Performance Testing)

□ Why JMH?

Because System.nanoTime() is **unreliable** (JIT, warmup, dead code elimination issues)

□ Maven Dependency

```
<dependencies>
  <dependency>
    <groupId>org.openjdk.jmh</groupId>
    <artifactId>jmh-core</artifactId>
    <version>1.37</version>
  </dependency>
  <dependency>
    <groupId>org.openjdk.jmh</groupId>
    <artifactId>jmh-generator-annprocess</artifactId>
    <version>1.37</version>
  </dependency>
</dependencies>
```

```
</dependency>
</dependencies>
```

□ Benchmark Code (Loop vs Stream)

```
import org.openjdk.jmh.annotations.*;

import java.util.*;
import java.util.concurrent.TimeUnit;
import java.util.stream.*;

@BenchmarkMode({Mode.AverageTime})
@OutputTimeUnit(TimeUnit.MILLISECONDS)
@State({Scope.Thread})
public class StreamVsLoopBenchmark {

    List<Integer> list;

    @Setup
    public void setup() {
        list = IntStream.range(1, 1_000_000)
            .boxed()
            .collect(Collectors.toList());
    }

    // □ Loop Benchmark
    @Benchmark
    public int loopSum() {
        int sum = 0;
        for (int i : list) {
            if (i % 2 == 0) {
                sum += i;
            }
        }
        return sum;
    }

    // □ Stream Benchmark
    @Benchmark
    public int streamSum() {
        return list.stream()
            .filter(i -> i % 2 == 0)
            .mapToInt(Integer::intValue)
            .sum();
    }

    // □ Parallel Stream Benchmark
    @Benchmark
```

```
public int parallelStreamSum() {  
    return list.parallelStream()  
        .filter(i -> i % 2 == 0)  
        .mapToInt(Integer::intValue)  
        .sum();  
}
```

□ **Run Command**

```
mvn clean install  
java -jar target/benchmarks.jar
```

□ **What JMH Handles Automatically**

- Warmup iterations
 - JVM optimizations
 - Dead code elimination prevention
 - Accurate multi-thread measurement
-

□ **2. ✔ Internal Working of Parallel Streams (ForkJoinPool)**

□ **Core Concept**

□ Parallel Stream uses:

➔ `ForkJoinPool.commonPool()`

□ **Flow Diagram**

```
Data Source  
↓  
Spliterator (splits data)  
↓  
ForkJoinTask (RecursiveTask)  
↓  
Worker Threads (CPU cores)  
↓  
Combine Results (Join)
```

□ Internal Steps

1. Splitting (Divide)

`list.parallelStream()`

- Uses Spliterator
 - Splits data into chunks recursively
-

2. Fork (Parallel Execution)

`ForkJoinPool.commonPool()`

- Each chunk → separate thread
 - Work-stealing algorithm used
-

3. Processing

`.filter()`
`.map()`

- Each thread processes its chunk independently
-

4. Join (Merge Results)

`.reduce()`
`.collect()`

- Results combined
-

□ Work-Stealing Concept

□ Idle thread steals tasks from busy threads

Thread1 → busy
Thread2 → idle → steals work

❑ Key Insight

Feature	Impact
Splititerator	Efficient splitting
ForkJoinPool	Parallel execution
Work-stealing	Load balancing
Common pool	Shared resource

❑ Important Warning

`System.setProperty("java.util.concurrent.ForkJoinPool.common.parallelism", "8");`

- Affects ALL parallel streams globally
-

❑ 3. ✔ Stream Optimization Tricks (Very Important)

❑ 1. Use Primitive Streams

✗ Bad

```
list.stream().map(i -> i * 2)
```

✔ Good

```
list.stream().mapToInt(i -> i * 2)
```

❑ Avoid boxing/unboxing → huge performance gain

❑ 2. Avoid Unnecessary Streams

✗ Bad

```
Stream.of(list).flatMap(Collection::stream)
```

✓ Good

```
list.stream()
```

☐ 3. Use `forEach` Carefully

✗ Parallel unsafe

```
list.parallelStream().forEach(list2::add);
```

✓ Safe

```
list.parallelStream().collect(Collectors.toList());
```

☐ 4. Prefer `mapToInt().sum()` over `reduce()`

✗

```
.reduce(0, Integer::sum)
```

✓

```
.mapToInt(Integer::intValue).sum()
```

☐ 5. Limit Parallel Streams

☐ Use only when:

- Large dataset (>10K–100K)
 - CPU-intensive work
-

☐ 6. Avoid Stateful Lambda

✗ BAD

```
int[] sum = {0};  
list.stream().forEach(i -> sum[0] += i);
```

☐ Breaks parallel safety

❑ Golden Rule

❑ Stateless + Associative + Large Data = Best Stream Performance

❑ 4. ✔ Fail-Fast vs Fail-Safe (Deep Performance)

❑ Fail-Fast Iterator

❑ Used in:

- ArrayList
 - HashMap
-

❑ Example

```
List<Integer> list = new ArrayList<>(List.of(1,2,3));
```

```
for (Integer i : list) {  
    list.add(4); // ✖ Exception  
}
```

❑ Output

ConcurrentModificationException

❑ Internal Working

- Uses modCount
 - If modified → throws exception
-

❑ Performance

Factor	Impact
Speed	Fast

Memory	Low
Safety	Not thread-safe

☐ **Fail-Safe Iterator**

☐ Used in:

- CopyOnWriteArrayList
- ConcurrentHashMap

☐ **Example**

```
List<Integer> list = new CopyOnWriteArrayList<>(List.of(1,2,3));
```

```
for (Integer i : list) {
    list.add(4); // ✓ Safe
}
```

☐ **Internal Working**

- Works on **copy of collection**
- No exception

☐ **Performance**

Factor	Impact
Speed	Slower
Memory	High (copy)
Safety	Thread-safe

☐ **Deep Comparison**

Feature	Fail-Fast	Fail-Safe
Exception	Yes	No

Thread-safe	✗	✓
Memory	Low	High
Speed	Fast	Slower
Iterator type	Original data	Copy

❑ 5. ❑ Final Interview Summary

- ❑ **JMH** → Accurate benchmarking tool
- ❑ **Parallel Stream** → ForkJoinPool + Work-stealing
- ❑ **Optimization** → Use primitive streams + avoid boxing
- ❑ **Fail-Fast** → Fast but unsafe
- ❑ **Fail-Safe** → Safe but slower

❑ One-Line Expert Answer

❑

“Use JMH for accurate benchmarks, loops for raw speed, streams for readability, and parallel streams only when data is large and CPU-bound.”

If you want next level:

- ✓ ForkJoinPool internal code walkthrough
- ✓ Spliterator deep internals
- ✓ Stream pipeline bytecode analysis
- ✓ Real-world system design using streams

When people say “JMH tools,” they usually mean the **ecosystem around the Java Microbenchmark Harness (JMH)**—including profilers, build tools, runners, and analysis utilities. Below is a **complete, practical list with real-time use cases**.

☐ 1. Core Benchmarking Tool

Tool	Description	Real-Time Use Case
JMH (Java Microbenchmark Harness)	Official Java benchmarking framework	Measure performance of loops vs streams, GC impact

☐ 2. Build & Integration Tools

Tool	Description	Use Case
Apache Maven	Dependency + build	Run benchmarks via mvn clean install
Gradle	Faster builds	Automate benchmarking in CI/CD
Maven Shade Plugin	Create fat JAR	Run JMH benchmarks easily
JMH Gradle Plugin	JMH integration	Simplify benchmark execution

☐ 3. Profiling Tools (VERY IMPORTANT)

☐ These tools help you understand **why performance is slow**

☐ CPU & Memory Profilers

Tool	Description	Real-Time Use Case
Java Flight Recorder (JFR)	Built-in JVM profiler	Analyze CPU, memory, GC during JMH
Java Mission Control (JMC)	Visual analysis	Detect bottlenecks in streams
VisualVM	Lightweight profiler	Monitor heap, threads

YourKit Java Profiler	Advanced profiling	Deep performance debugging
JProfiler	CPU + memory profiling	Optimize enterprise apps

❑ **Low-Level Profilers**

Tool	Description	Use Case
Async Profiler	Flame graphs	Analyze CPU hotspots in JMH
Perf (Linux)	OS-level profiling	Kernel + JVM performance
Flame Graphs	Visual call stacks	Identify bottlenecks

❑ **4. JMH Built-in Profilers**

❑ JMH itself supports profiling!

Profiler	Description	Use Case
-prof gc	GC profiling	Measure GC overhead
-prof stack	Stack traces	Method-level analysis
-prof perf	Linux perf	CPU-level insights
-prof async	Async profiler	Flame graph analysis

✔ **Example**

```
java -jar benchmark.jar -prof gc
```

❑ **5. JVM Analysis Tools**

Tool	Description	Use Case
jstack	Thread analysis	Debug parallel streams
jmap	Heap dump	Memory leak detection
jcmd	Advanced diagnostics	Runtime tuning

☐ **6. Visualization & Reporting Tools**

Tool	Description	Use Case
JMH Visualizer	Graphs & charts	Compare results visually
Excel	Manual analysis	Create performance reports
Grafana	Dashboard	Track performance trends
Prometheus	Metrics storage	Store benchmark results

☐ **7. CI/CD Integration Tools**

Tool	Description	Use Case
Jenkins	Automation	Run benchmarks on every build
GitHub Actions	Workflow automation	Prevent performance regressions

☐ **8. IDE Support**

Tool	Description	Use Case
IntelliJ IDEA	Run/debug JMH	Developer-friendly execution
Eclipse IDE	JMH integration	Development + testing

☐ **9. Real-Time Use Cases (Industry Level)**

☐ **1. Stream vs Loop Optimization**

// Benchmarking performance difference

☐ Used in:

- Banking systems
- Trading platforms

☐ 2. API Performance Testing

☐ Compare:

- JSON parsing libraries
- Serialization speed

☐ 3. Database Query Optimization

☐ Benchmark:

- JDBC vs Hibernate
- Query execution time

☐ 4. Multithreading Optimization

☐ Test:

- Parallel streams vs Executors
- Thread pool tuning

☐ 5. Garbage Collection Analysis

☐ Measure:

- Object allocation rate
- GC pauses

☐ 6. Microservices Performance

☐ Compare:

- REST vs gRPC
 - Caching strategies
-

☐ 7. Algorithm Benchmarking

☐ Compare:

- Sorting algorithms
 - Search performance
-

☐ 10. Complete Ecosystem Flow

JMH Benchmark



Profilers (JFR / Async Profiler)



JVM Tools (jstack / jmap)



Visualization (Grafana / Excel)



CI/CD (Jenkins)

☐ Final Summary

Category	Best Tool
Benchmarking	JMH
Profiling	JFR, Async Profiler
Build	Maven, Gradle
Visualization	Grafana
CI/CD	Jenkins

☐ One-Line Expert Answer

☐

“JMH measures performance, profilers explain why, and CI/CD ensures performance stays optimized.”

If you want next level:

- ✓ Full real-world project using JMH
- ✓ Benchmark report generation (PDF/Excel)
- ✓ Advanced JVM tuning with JMH
- ✓ Live comparison: Stream vs Parallel vs Executor

Here's a **complete, structured guide** to Java 8+ **Stream API methods**, categorized by whether they **accept lambda expressions (functional interfaces)** or **do NOT accept lambdas**, along with **clear Java code examples**.

□ 1. INTERMEDIATE OPERATIONS

✓ A. Intermediate Methods that ACCEPT Lambda Expressions

These methods require **functional interfaces** like Predicate, Function, Consumer, etc.

Method	Functional Interface	Lambda Example
filter()	Predicate	<code>x -> x > 10</code>
map()	Function	<code>x -> x * 2</code>
flatMap()	Function	<code>x -> x.stream()</code>
mapToInt()	ToIntFunction	<code>x -> x.length()</code>
mapToLong()	ToLongFunction	<code>x -> x</code>
mapToDouble()	ToDoubleFunction	<code>x -> x * 1.0</code>
flatMapToInt()	Function	<code>x -> IntStream.of(...)</code>
flatMapToLong()	Function	same
flatMapToDouble()	Function	same
peek()	Consumer	<code>x -> System.out.println(x)</code>
sorted(Comparator)	Comparator	<code>(a,b) -> a - b</code>
takeWhile() (Java 9)	Predicate	<code>x -> x < 100</code>
dropWhile() (Java 9)	Predicate	<code>x -> x < 100</code>

✓ Example

```
List<Integer> list = List.of(10, 20, 30, 40);
```

```
list.stream()  
  .filter(x -> x > 20)  
  .map(x -> x * 2)  
  .peek(x -> System.out.println("Processed: " + x))  
  .sorted((a, b) -> b - a)  
  .forEach(System.out::println);
```

✗ B. Intermediate Methods that DO NOT ACCEPT Lambda

These methods either:

- take **no arguments**, or
- take **non-functional arguments**

Method	Reason
distinct()	No parameter
sorted()	Uses natural ordering
limit()	Takes long
skip()	Takes long
parallel()	No parameter
sequential()	No parameter
unordered()	No parameter
onClose()	Actually takes lambda (Consumer) → special case

✗ Example

```
list.stream()  
  .distinct()  
  .limit(3)  
  .skip(1)  
  .sorted()  
  .forEach(System.out::println);
```

❑ 2. TERMINAL OPERATIONS

✔ A. Terminal Methods that ACCEPT Lambda Expressions

Method	Functional Interface	Example
forEach()	Consumer	x -> print(x)
forEachOrdered()	Consumer	Same
reduce()	BinaryOperator	(a,b) -> a + b
collect()	Collector / Supplier/Accumulator	Custom
anyMatch()	Predicate	x -> x > 10
allMatch()	Predicate	x -> x > 10
noneMatch()	Predicate	x -> x > 10
findFirst()	No lambda	
findAny()	No lambda	
min()	Comparator	(a,b)->a-b
max()	Comparator	(a,b)->a-b
toArray(IntFunction)	IntFunction	size -> new int[size]

✔ Example

```
int sum = List.of(1,2,3,4)
    .stream()
    .filter(x -> x % 2 == 0)
    .reduce(0, (a, b) -> a + b);
```

```
System.out.println(sum);
```

✗ B. Terminal Methods that DO NOT ACCEPT Lambda

Method	Reason
count()	No argument
toArray()	No argument

findFirst()	No argument
findAny()	No argument
iterator()	No argument
splititerator()	No argument

✖ Example

```
long count = list.stream()
    .filter(x -> x > 10)
    .count();
```

```
System.out.println(count);
```

❑ 3. SPECIAL CASES (IMPORTANT FOR INTERVIEWS)

❑ Method Overloads (Lambda Optional)

Method	Lambda Optional?	Explanation
sorted()	Yes	sorted() vs sorted(Comparator)
reduce()	Yes	multiple overloads
collect()	Yes	predefined collectors vs custom
toArray()	Yes	default vs generator

❑ 4. REAL-TIME USE CASE

Scenario: Process Employee Data

```
class Employee {
    String name;
    int salary;

    Employee(String name, int salary) {
        this.name = name;
        this.salary = salary;
    }
}
```

```
List<Employee> employees = List.of(
```

```
new Employee("A", 50000),
new Employee("B", 70000),
new Employee("C", 60000)
);

// Get names of employees with salary > 55000
List<String> result = employees.stream()
    .filter(e -> e.salary > 55000)
    .map(e -> e.name)
    .sorted()
    .collect(Collectors.toList());

System.out.println(result);
```

❑ 5. FINAL SUMMARY (INTERVIEW READY)

✔ Methods USING Lambda

- filter, map, flatMap
- peek
- sorted(Comparator)
- reduce
- collect
- forEach
- anyMatch, allMatch, noneMatch
- min, max

✗ Methods NOT USING Lambda

- distinct, limit, skip
 - count, findFirst, findAny
 - iterator, spliterator
-

❑ Pro Tip (Very Important)

- ❑ If a method requires a **Functional Interface**, you can use a **Lambda Expression**
 - ❑ If it takes **primitive / no argument**, you **cannot use Lambda**
-

If you want next:

- ✔ 100+ Stream API interview questions (FAANG level)
- ✔ Internal working of Stream pipeline (deep dive)
- ✔ Parallel Stream internals (ForkJoinPool)