ROMHEX14 CALIBRATION PACKAGE CERTIFICATE

Stock Factory Baseline | Factory Stock Firmware Hlutna

00_STOCK_ORIGINAL_FACTORY

1. VEHICLE PROFILE

Motor Chanchin

MODEL	VIN	ECU TYPE	BOSCH SW
Mahindra Pik-Up BS4 4WD	MA1ZC4TBKK1A11163	Bosch EDC17C55	1037560611

2. CALIBRATION TARGETS

Thahrui & Map Hlutna

Metric	Factory Value	Package Target	Net Gain
Engine Power	70 HP @ 3,200 RPM	**70 HP**	Stock Baseline
Engine Torque	200 Nm @ 1,800	**200 Nm**	Stock Baseline
Fuel Limit (IQ)	43.54 mg/hub	**43.54 mg/hub**	Stock Baseline
Boost Target	2,200 mbar	**2200 mbar**	Stock Baseline
Rail Pressure	1,550 bar	**1550 bar**	Stock Baseline

3. DTC & SECURITY MATRIX

Fault Code & Security Thliarna

Code / Identifier	Subsystem	Address	Status
Factory Standard OBD Matrix (No DTCs modified)			

4. BINARY FILES & INTEGRITY

File Hlutna & Checksum

Type	Filename	SHA-256 Hash
Flash (2 MB)	Original_Flash_1037560611.bin	`4EDF9D683F0627EBF3E69584FF8D01BECC4B28CA5479B41028014BAF875631D1`
EEPROM (64 KB)	Original_EEPROM.bin	`09CD990A3C39462FD31A0E37B671A0892FF3AB6F6D88528338611522FF9F9550`

5. INSTRUCTIONS & ADVISORY

Hriattur Pawimawh Te

CHECKSUM PROTOCOL: Bosch EDC17C55 requires Bench Flasher auto-checksum calculation on write (PCMFlash Mod 71 / Foxflash / KT200 / KTAG automatically correct CRC32 on load).
STANDARD FLASHING: Flash via Bench mode. Ensure battery voltage is >= 12.5V during programming.