ROMHEX14 CALIBRATION PACKAGE CERTIFICATE

01_STAGE1_POWER_ONLY

Stage 1 Safe Power Remap | Stage 1 Thahrui Tihpunna (Stock Emissions & Immo)

1. VEHICLE PROFILE

Motor Chanchin

MODEL	VIN	ECU TYPE	BOSCH SW
Mahindra Pik-Up BS4 4WD	MA1ZC4TBKK1A11163	Bosch EDC17C55	1037560611

2. CALIBRATION TARGETS

Thahrui & Map Hlutna

Metric	Factory Value	Package Target	Net Gain
Engine Power	70 HP @ 3,200 RPM	**95 HP**	+25 HP (+35%)
Engine Torque	200 Nm @ 1,800	**260 Nm**	+60 Nm (+30%)
Fuel Limit (IQ)	43.54 mg/hub	**53.5 mg/hub**	+10.0 mg/hub
Boost Target	2,200 mbar	**2320 mbar**	+120 mbar
Rail Pressure	1,550 bar	**1600 bar**	+50 bar

3. DTC & SECURITY MATRIX

Fault Code & Security Thliarna

Code / Identifier	Subsystem	Address	Status
Factory Standard OBD Matrix (No DTCs modified)			

4. BINARY FILES & INTEGRITY

File Hlutna & Checksum

Type	Filename	SHA-256 Hash
Flash (2 MB)	Mahindra_PikUp_BS4_Stage1_Power_Only_Flash.bin	`E33981DC1FC209CC31E60C62533CCE3AD180E2612F4432D38005E5107B7C9B50`

5. INSTRUCTIONS & ADVISORY

Hriattur Pawimawh Te

CHECKSUM PROTOCOL: Bosch EDC17C55 requires Bench Flasher auto-checksum calculation on write (PCMFlash Mod 71 / Foxflash / KT200 / KTAG automatically correct CRC32 on load).
STANDARD FLASHING: Flash via Bench mode. Ensure battery voltage is >= 12.5V during programming.