ROMHEX14 CALIBRATION PACKAGE CERTIFICATE

Stage 1 Remap + EGR Deactivation | Stage 1 Remap + EGR Khar Hmak

02_STAGE1_EGR_OFF

1. VEHICLE PROFILE

Motor Chanchin

MODEL	VIN	ECU TYPE	BOSCH SW
Mahindra Pik-Up BS4 4WD	MA1ZC4TBKK1A11163	Bosch EDC17C55	1037560611

2. CALIBRATION TARGETS

Thahrui & Map Hlutna

Metric	Factory Value	Package Target	Net Gain
Engine Power	70 HP @ 3,200 RPM	**95 HP**	+25 HP (+35%)
Engine Torque	200 Nm @ 1,800	**260 Nm**	+60 Nm (+30%)
Fuel Limit (IQ)	43.54 mg/hub	**53.5 mg/hub**	+10.0 mg/hub
Boost Target	2,200 mbar	**2320 mbar**	+120 mbar
Rail Pressure	1,550 bar	**1600 bar**	+50 bar

3. DTC & SECURITY MATRIX

Fault Code & Security Thliarna

Code / Identifier	Subsystem	Address	Status
P0401	EGR Flow Insufficient	0x10E7D2	DEACTIVATED (00 00)
P0405	EGR Sensor A Low Input	0x10E7D4	DEACTIVATED (00 00)

4. BINARY FILES & INTEGRITY

File Hlutna & Checksum

Type	Filename	SHA-256 Hash
Flash (2 MB)	Mahindra_PikUp_BS4_Stage1_EGR_OFF_Flash.bin	6A08EAA5D86F75F0AD661F2193F0C78C598543E1BBA6606D0C3995F43A2C0020

5. INSTRUCTIONS & ADVISORY

Hriattur Pawimawh Te

CHECKSUM PROTOCOL: Bosch EDC17C55 requires Bench Flasher auto-checksum calculation on write (PCMFlash Mod 71 / Foxflash / KT200 / KTAG automatically correct CRC32 on load).
STANDARD FLASHING: Flash via Bench mode. Ensure battery voltage is >= 12.5V during programming.