



Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . :
IP Address. : 10.0.0.10
Subnet Mask : 255.0.0.0
Default Gateway : 10.0.0.1

C:\Documents and Settings\user>ping 15.0.0.10

Pinging 15.0.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 15.0.0.10:


Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>

Other Places

- Control Panel
- My Network Places
- My Documents
- My Computer

(Win-2)



Network Tasks

- Create a new connection
- Set up a home or office network
- Change Windows Firewall settings
- Disable this network device
- Repair this connection
- Rename this connection
- View status of connection
- Change settings of connection

Other Places

- Control Panel
- My Network Places
- My Documents
- My Computer

C:\WINDOWS\system32\cmd.exe

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix	:	:
IP Address	:	15.0.0.10
Subnet Mask	:	255.0.0.0
Default Gateway	:	15.0.0.1

C:\Documents and Settings\user>ping 162.14.0.10

Pinging 162.14.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 162.14.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 10.0.0.10

QEMU (Win-3)

Address My

Network T

Windows IP Configuration

C:\WINDOWS\system32\cmd.exe

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . :
IP Address. : 162.14.0.10
Subnet Mask : 255.255.0.0
Default Gateway : 162.14.0.1

C:\Documents and Settings\user>

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.0.0.10:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

Other Place C:\Documents and Settings\user>

Control Panel

My Network Places

My Documents

My Computer

Details

Local Area Connection

R1

```
S 10.0.0.0/8 [1/0] via 20.0.0.2
S 10.0.0.0/8 [1/0] via 20.0.0.2
S 10.0.0.0/16 [1/0] via 20.0.0.2
S 10.0.0.0/16 [1/0] via 20.0.0.2
S 192.168.0.0/24 [1/0] via 20.0.0.2
```

R1#

R1#

R1#sh ip int br

Interface	IP-Address	OK?	Method	Status	Prot
Ethernet0/0	10.0.0.1	YES	manual	up	up
Ethernet0/1	20.0.0.1	YES	manual	up	up
Ethernet0/2	unassigned	YES	TFTP	down	down
Ethernet0/3	unassigned	YES	TFTP	down	down

R1#sh ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PBR

Gateway of last resort is not set

```
10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
  10.0.0.0/8 is directly connected, Ethernet0/0
  10.0.0.1/32 is directly connected, Ethernet0/0
15.0.0.0/8 [1/0] via 20.0.0.2
20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
  20.0.0.0/8 is directly connected, Ethernet0/1
  20.0.0.1/32 is directly connected, Ethernet0/1
21.0.0.0/8 [1/0] via 20.0.0.2
20.0.0.0/8 [1/0] via 20.0.0.2
10.0.0.0/16 [1/0] via 20.0.0.2
10.0.0.0/16 [1/0] via 20.0.0.2
192.168.0.0/24 [1/0] via 20.0.0.2
```


R26sh ip int br

Interface	IP-Address	OK Method Status	Prot
Ethernet0/0	20.0.0.2	YES manual up	up
Ethernet0/1	20.0.0.1	YES manual up	up
Ethernet0/2	unassigned	YES TFTP down	down
Ethernet0/3	unassigned	YES TFTP down	down

R26sh ip route

Legend: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - HSRP, I - IGMP
s - application route
+ - replicated route, % - next hop override, p - overrides from IFM

away of last resort is not set

10.0.0.0/8 [1/0] via 20.0.0.1

15.0.0.0/8 [1/0] via 20.0.0.2

Ca 20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

20.0.0.0/8 is directly connected, Ethernet0/0

20.0.0.0/8 is directly connected, Ethernet0/1

20.0.0.0/8 [1/0] via 20.0.0.2

20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

20.0.0.0/8 is directly connected, Ethernet0/1

20.0.0.0/8 is directly connected, Ethernet0/3

20.0.0.0/8 [1/0] via 20.0.0.2

20.0.0.0/8 [1/0] via 20.0.0.1

20.0.0.0/8 [1/0] via 20.0.0.2

```

Router>sh ip int br
Interface                IP-Address      OK? Method Status      Prot
Ethernet0/0              30.0.0.2        YES manual up          up
Ethernet0/1              172.19.0.1      YES manual up          up
Ethernet0/2              21.0.0.1        YES manual up          up
Ethernet0/3              unassigned      YES unset  administratively down down

```

```
Router>sh ip route
```

```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

```

```
Gateway of last resort is not set
```

```

S    10.0.0.0/8 [1/0] via 30.0.0.1
S    15.0.0.0/8 [1/0] via 172.19.0.2
S    20.0.0.0/8 [1/0] via 30.0.0.1
    21.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    21.0.0.0/8 is directly connected, Ethernet0/2
L    21.0.0.1/32 is directly connected, Ethernet0/2
    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    30.0.0.0/8 is directly connected, Ethernet0/0
L    30.0.0.2/32 is directly connected, Ethernet0/0
S    162.14.0.0/16 [1/0] via 21.0.0.2
    172.19.0.0/16 is variably subnetted, 2 subnets, 2 masks
C    172.19.0.0/16 is directly connected, Ethernet0/1
L    172.19.0.1/32 is directly connected, Ethernet0/1
S    192.168.168.0/24 [1/0] via 21.0.0.2

```


C:\WINDOWS\system32\cmd.exe

Pinging 20.0.0.2 with 32 bytes of data:

Reply from 20.0.0.2: bytes=32 time=1ms TTL=253
Reply from 20.0.0.2: bytes=32 time=1ms TTL=253
Reply from 20.0.0.2: bytes=32 time=2ms TTL=253
Reply from 20.0.0.2: bytes=32 time=1ms TTL=253

Ping statistics for 20.0.0.2:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>ping 162.14.0.10

Pinging 162.14.0.10 with 32 bytes of data:

Reply from 162.14.0.10: bytes=32 time=2ms TTL=124
Reply from 162.14.0.10: bytes=32 time=1ms TTL=124
Reply from 162.14.0.10: bytes=32 time=2ms TTL=124
Reply from 162.14.0.10: bytes=32 time=2ms TTL=124

Ping statistics for 162.14.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=2ms TTL=124
Reply from 10.0.0.10: bytes=32 time=1ms TTL=124
Reply from 10.0.0.10: bytes=32 time=1ms TTL=124
Reply from 10.0.0.10: bytes=32 time=1ms TTL=124

Ping statistics for 10.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>