

Exam Revision Lecture

Approx. 1hr.

Dr. Thomas Christy

thomas.christy@unimelb.edu.au

Example revision areas

- Sorted(), Split(), len
- Iteration for each in 'list'
- 'word' in 'another word'
- Operators
 - ie 'something' == 'something'
- .format(key arguments)
- "{ } ".format(with key/arguments)
- Tuple, List, Dictionary
- While, For, If, Break, continue
- Data types, String, int, char, boolean, float
- Pseudocode
- Arguments, parameters
- Fix code
 - Syntax, runtime
 - Functions
- Describe code
- Ascii table, ordinal to char, char to ordinal
- Global vs local variables
- Coding:
 - Pseudocode
 - Solution
 - Problem

Key arguments: examples

```
def main():  
    show_interest(rate = 0.01, periods = 10, principal = 100.0)  
  
def show_interest(principal, rate, periods):  
    interest = principal * rate * periods  
    print('The simple interest will be {:.2}'.format(interest))  
  
main()
```

Logical Operators and Compound Boolean Expressions (continued)

TYPE OF OPERATOR	OPERATOR SYMBOL
Exponentiation	**
Arithmetic negation	-
Multiplication, division, remainder	*, /, %
Addition, subtraction	+, -
Comparison	==, !=, <, >, <=, >=
Logical negation	not
Logical conjunction and disjunction	and, or
Assignment	=

[TABLE 3-4] Operator precedence, from highest to lowest

American Standard Code for Information Interchange - **ASCII**

...	0	1	2	3	4	5	6	7	8	9
4	()	*	+	,	-	.	/	0	1
5	2	3	4	5	6	7	8	9	:	;
6	<	=	>	?	@	A	B	C	D	E
7	F	G	H	I	J	K	L	M	N	O
8	P	Q	R	S	T	U	V	W	X	Y
9	Z	[\]	^	_	'	a	b	c
10	d	e	f	g	h	i	j	k	l	m
11	n	o	p	q	r	s	t	u	v	w
12	x	y	z	{		}	~			

Basic for and while loop

```
# for loop using list
```

```
for i in range(10):
```

```
    # do something 10 times from range 0 to 9
```

```
    print('Hello', i)
```

```
# while loop using range
```

```
i = 0
```

```
while i < 10:
```

```
    print ('hello' , i)
```

```
    i += 1
```

Basic For loop

```
# for loop using list
```

```
for i in [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]:
```

```
    print('Hello', i)
```

```
# What are break, continue, pass used for?
```

Data types

- string (str)
 - “Something” or ‘Something’ etc.
- Int
 - 1, 2, 3, 4, 1002, etc.
- Char (chr)
 - A, or b, or C, or \$, or (etc.
- Float
 - 12.1, or 1.0001, or 199.99 etc.
- Boolean
 - True or False, 1 or 0 (binary)

Tuple, List, Dictionary

- (Tuple)
 - (1, 2, 3, 'Bob')
- [List]
 - [1, 2, 3, 'Bob']
- {Dictionary}
 - {'a': 1, 'b': 2, 'c': 3, 'd': 'Bob'}

Global vs Local


```
number = 1
```

```
def something():  
    number = 10
```

```
something()
```

```
print(number)
```

Basic functions



Basic function

```
def name():  
    print("Running function")
```

Input parameters

Basic function with input parameter

```
def name(any_num_of_vars):  
    print("Running function")
```

Return

Basic function with return value

```
def name():  
    print("Running function")  
    return 'something'
```

Basic function with input parameter and return value

```
def name(any_num_of_vars):  
    print("Running function")  
    return 'something'
```

Example revision areas

- Sorted(), Split(), len
- Iteration for each in 'list'
- 'word' in 'another word'
- Operators
 - ie 'something' == 'something'
- .format(key arguments)
- "{ } ".format(with key/arguments)
- Tuple, List, Dictionary
- While, For, If, Break, continue
- Data types, String, int, char, boolean, float
- Pseudocode
- Arguments, paramaters
- Fix code
 - Syntax, runtime
 - Functions
- Describe code
- Ascii table, ordinal to char, char to ordinal
- Global vs local variables
- Coding:
 - Pseudocode
 - Solution
 - Problem

Dr. Thomas Christy
thomas.christy@unimelb.edu.au