

# Class 16 DESeq2 mini-project

Groot (PID: A15485151)

11/16/2021

load DESeq2

```
library(DESeq2)
```

```
## Loading required package: S4Vectors
```

```
## Loading required package: stats4
```

```
## Loading required package: BiocGenerics
```

```
##
```

```
## Attaching package: 'BiocGenerics'
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
##      IQR, mad, sd, var, xtabs
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      anyDuplicated, append, as.data.frame, basename, cbind, colnames,  
##      dirname, do.call, duplicated, eval, evalq, Filter, Find, get, grep,  
##      grepl, intersect, is.unsorted, lapply, Map, mapply, match, mget,  
##      order, paste, pmax, pmax.int, pmin, pmin.int, Position, rank,  
##      rbind, Reduce, rownames, sapply, setdiff, sort, table, tapply,  
##      union, unique, unsplit, which.max, which.min
```

```
##
```

```
## Attaching package: 'S4Vectors'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      expand.grid, I, unname
```

```
## Loading required package: IRanges
```

```
## Loading required package: GenomicRanges
```

```
## Loading required package: GenomeInfoDb
```

```

## Loading required package: SummarizedExperiment

## Loading required package: MatrixGenerics

## Loading required package: matrixStats

##
## Attaching package: 'MatrixGenerics'

## The following objects are masked from 'package:matrixStats':
##
##   colAlls, colAnyNAs, colAnys, colAveragesPerRowSet, colCollapse,
##   colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
##   colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
##   colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
##   colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
##   colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
##   colWeightedMeans, colWeightedMedians, colWeightedSds,
##   colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAveragesPerColSet,
##   rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
##   rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
##   rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
##   rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
##   rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
##   rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
##   rowWeightedSds, rowWeightedVars

## Loading required package: Biobase

## Welcome to Bioconductor
##
##   Vignettes contain introductory material; view with
##   'browseVignettes()'. To cite Bioconductor, see
##   'citation("Biobase")', and for packages 'citation("pkgname)".

##
## Attaching package: 'Biobase'

## The following object is masked from 'package:MatrixGenerics':
##
##   rowMedians

## The following objects are masked from 'package:matrixStats':
##
##   anyMissing, rowMedians

load data files

metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"

# Import metadata and take a peek
colData = read.csv(metaFile, row.names = 1)
head(colData)

```

```
##                condition
## SRR493366 control_sirna
## SRR493367 control_sirna
## SRR493368 control_sirna
## SRR493369     hoxa1_kd
## SRR493370     hoxa1_kd
## SRR493371     hoxa1_kd
```

Import count data

```
countData = read.csv(countFile, row.names=1)
head(countData)
```

```
##                length SRR493366 SRR493367 SRR493368 SRR493369 SRR493370
## ENSG00000186092     918         0         0         0         0         0
## ENSG00000279928     718         0         0         0         0         0
## ENSG00000279457    1982        23        28        29        29        28
## ENSG00000278566     939         0         0         0         0         0
## ENSG00000273547     939         0         0         0         0         0
## ENSG00000187634    3214        124        123        205        207        212
##                SRR493371
## ENSG00000186092         0
## ENSG00000279928         0
## ENSG00000279457        46
## ENSG00000278566         0
## ENSG00000273547         0
## ENSG00000187634       258
```

Q. Complete the code below to remove the troublesome first column from countData

```
# Note we need to remove the odd first $length col
countData <- as.matrix(countData[, -1])
head(countData)
```

```
##                SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000186092         0         0         0         0         0         0
## ENSG00000279928         0         0         0         0         0         0
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000278566         0         0         0         0         0         0
## ENSG00000273547         0         0         0         0         0         0
## ENSG00000187634       124       123       205       207       212       258
```

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

```
# Filter count data where you have 0 read count across all samples.
to.rm <- which(rowMeans(countData) == 0, arr.ind = TRUE)
countData2 = countData[-to.rm, ]
head(countData2)
```

```
##                SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
```

## ENSG00000279457	23	28	29	29	28	46
## ENSG00000187634	124	123	205	207	212	258
## ENSG00000188976	1637	1831	2383	1226	1326	1504
## ENSG00000187961	120	153	180	236	255	357
## ENSG00000187583	24	48	65	44	48	64
## ENSG00000187642	4	9	16	14	16	16

```
##Running DESeq2
```

```
dds = DESeqDataSetFromMatrix(countData=countData2,
                              colData=colData,
                              design=~condition)
```

```
## Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in
## design formula are characters, converting to factors
```

```
dds = DESeq(dds)
```

```
## estimating size factors
```

```
## estimating dispersions
```

```
## gene-wise dispersion estimates
```

```
## mean-dispersion relationship
```

```
## final dispersion estimates
```

```
## fitting model and testing
```

```
dds
```

```
## class: DESeqDataSet
## dim: 15975 6
## metadata(1): version
## assays(4): counts mu H cooks
## rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
## ENSG00000271254
## rowData names(22): baseMean baseVar ... deviance maxCooks
## colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
## colData names(2): condition sizeFactor
```

Get results for the HoxA1 knockdown versus control siRNA (remember that these were labeled as “hoxa1\_kd” and “control\_siRNA” in our original colData metaFile input to DESeq

```
res = results(dds, contrast=c("condition", "hoxa1_kd", "control_siRNA"))
```

Q. Call the summary() function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff.

```
summary(res)
```

```
##
## out of 15975 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up)      : 4349, 27%
## LFC < 0 (down)    : 4396, 28%
## outliers [1]      : 0, 0%
## low counts [2]    : 1237, 7.7%
## (mean count < 0)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```


reset p-value to 0.05

```
res05 <- results(dds, alpha=0.05)
summary(res05)
```

```
##
## out of 15975 with nonzero total read count
## adjusted p-value < 0.05
## LFC > 0 (up)      : 4043, 25%
## LFC < 0 (down)    : 4142, 26%
## outliers [1]      : 0, 0%
## low counts [2]    : 1859, 12%
## (mean count < 1)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

##Volcano plot

```
plot( res$log2FoldChange, -log(res$padj) )
```




Q. Improve this plot by completing the below code, which adds color and axis labels

```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2
inds <- (res$padj < 0.01) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col=mycols, xlab="Log2(FoldChange)", ylab="-Log(P-value)" )
```



## Adding gene annotation > Q. Use the mapIDs() function multiple times to add SYMBOL, ENTREZID and GENENAME annotation to our results by completing the code below.

```
library("AnnotationDbi")
```

## Warning: package 'AnnotationDbi' was built under R version 4.1.2

```
library("org.Hs.eg.db")
```

```
##
```

```
columns(org.Hs.eg.db)
```

```
## [1] "ACCNUM"      "ALIAS"       "ENSEMBL"     "ENSEMBLPROT" "ENSEMBLTRANS"
## [6] "ENTREZID"    "ENZYME"      "EVIDENCE"    "EVIDENCEALL"  "GENENAME"
## [11] "GENETYPE"    "GO"          "GOALL"       "IPI"          "MAP"
## [16] "OMIM"        "ONTOLOGY"    "ONTOLOGYALL" "PATH"         "PFAM"
## [21] "PMID"        "PROSITE"     "REFSEQ"      "SYMBOL"       "UCSCKG"
## [26] "UNIPROT"
```

```
res$symbol = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="SYMBOL",
                    multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
res$entrez = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
res$name = mapIds(org.Hs.eg.db,
                  keys=row.names(res),
                  keytype="ENSEMBL",
                  column="GENENAME",
                  multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
head(res, 10)
```

```
## log2 fold change (MLE): condition hoxa1_kd vs control_sirna
```

```
## Wald test p-value: condition hoxa1 kd vs control sirna
```

```
## DataFrame with 10 rows and 9 columns
```

##	baseMean	log2FoldChange	lfcSE	stat	pvalue
##	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
## ENSG00000279457	29.913579	0.1792571	0.3248216	0.551863	5.81042e-01
## ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03
## ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630158	1.43990e-36
## ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
## ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
## ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01
## ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51282e-25
## ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
## ENSG00000188157	9128.439422	0.3899088	0.0467163	8.346304	7.04321e-17
## ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
##	padj	symbol	entrez	name	
##	<numeric>	<character>	<character>	<character>	
## ENSG00000279457	6.86555e-01	WASH9P	102723897	WAS protein family h..	
## ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif ..	
## ENSG00000188976	1.76549e-35	NOC2L	26155	NOC2 like nucleolar ..	
## ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..	
## ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology ..	
## ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..	
## ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..	
## ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..	
## ENSG00000188157	4.21963e-16	AGRN	375790	agrin	
## ENSG00000237330	NA	RNF223	401934	ring finger protein ..	

Q. Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.



```
res = res[order(res$pvalue),]
write.csv(res, file="deseq_results.csv")
```

##Section 2. Pathway Analysis

#KEGG pathways

```
library(pathview)
```

```
## #####
## Pathview is an open source software package distributed under GNU General
## Public License version 3 (GPLv3). Details of GPLv3 is available at
## http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
## formally cite the original Pathview paper (not just mention it) in publications
## or products. For details, do citation("pathview") within R.
##
## The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG
## license agreement (details at http://www.kegg.jp/kegg/legal.html).
## #####
```

```
library(gage)
```

```
##
```

```
library(gageData)
```

```
data(kegg.sets.hs)
```

```
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
```

```
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways
```

```
head(kegg.sets.hs, 3)
```

```
## $'hsa00232 Caffeine metabolism'
```

```
## [1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
##
```

```
## $'hsa00983 Drug metabolism - other enzymes'
```

```
## [1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
```

```
## [9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
```

```
## [17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
```

```
## [25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
```

```
## [33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
```

```
## [41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
```

```
## [49] "8824" "8833" "9" "978"
```

```
##
```

```
## $'hsa00230 Purine metabolism'
```

```
## [1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"
```

```
## [9] "108" "10846" "109" "111" "11128" "11164" "112" "113"
```

```
## [17] "114" "115" "122481" "122622" "124583" "132" "158" "159"
```

```
## [25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"
## [33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
## [41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"
## [49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"
## [57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"
## [65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"
## [73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"
## [81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"
## [89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"
## [97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"
## [105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
## [113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"
## [121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"
## [129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"
## [137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"
## [145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"
## [153] "9061" "93034" "953" "9533" "954" "955" "956" "957"
## [161] "9583" "9615"
```

The main `gage()` function requires a named vector of fold changes, where the names of the values are the Entrez gene IDs.

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
##      1266      54855      1465      51232      2034      2317
## -2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792
```

run the `gage` pathway analysis.

```
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

look at the object returned from `gage()`.

```
attributes(keggres)
```

```
## $names
## [1] "greater" "less" "stats"
```

look at the first few down (less) pathway results:

```
head(keggres$less)
```

```
##                p.geomean stat.mean          p.val
## hsa04110 Cell cycle      8.995727e-06 -4.378644 8.995727e-06
## hsa03030 DNA replication  9.424076e-05 -3.951803 9.424076e-05
## hsa03013 RNA transport   1.375901e-03 -3.028500 1.375901e-03
## hsa03440 Homologous recombination 3.066756e-03 -2.852899 3.066756e-03
## hsa04114 Oocyte meiosis   3.784520e-03 -2.698128 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 8.961413e-03 -2.405398 8.961413e-03
```

```
##               q.val set.size      exp1
## hsa04110 Cell cycle      0.001448312    121 8.995727e-06
## hsa03030 DNA replication 0.007586381     36 9.424076e-05
## hsa03013 RNA transport  0.073840037    144 1.375901e-03
## hsa03440 Homologous recombination 0.121861535    28 3.066756e-03
## hsa04114 Oocyte meiosis  0.121861535   102 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 0.212222694    53 8.961413e-03
```

use the `pathview()` function to make a pathway plot for the pathway 'Cell Cyle' (hsa04110)

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15
```

```
## Info: Writing image file hsa04110.pathview.png
```

You can play with the other input arguments to `pathview()` to change the display in various ways including generating a PDF graph

```
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15
```

```
## Info: Writing image file hsa04110.pathview.pdf
```

Now, let's process our results a bit more to automagically pull out the top 5 upregulated pathways, then further process that just to get the pathway IDs needed by the `pathview()` function. We'll use these KEGG pathway IDs for `pathview` plotting below

```
## Focus on top 5 upregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$greater)[1:5]
```

```
# Extract the 8 character long IDs part of each string
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
## [1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

Pass these IDs in `keggresids` to the `pathview()` function to draw plots for all the top 5 pathways

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15
```

```
## Info: Writing image file hsa04640.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15

## Info: Writing image file hsa04630.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15

## Info: Writing image file hsa00140.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15

## Info: Writing image file hsa04142.pathview.png

## Info: some node width is different from others, and hence adjusted!

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/kevin/Desktop/BIMM 143/R Studio Project/bimm143_github/Class15

## Info: Writing image file hsa04330.pathview.png
```

### ##Section 3. Gene Ontology (GO)

```
data(go.sets.hs)
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)

lapply(gobpres, head)
```

```
## $greater
##
##          p.geomean stat.mean      p.val
## GO:0007156 homophilic cell adhesion 8.519724e-05 3.824205 8.519724e-05
## GO:0002009 morphogenesis of an epithelium 1.396681e-04 3.653886 1.396681e-04
## GO:0048729 tissue morphogenesis 1.432451e-04 3.643242 1.432451e-04
## GO:0007610 behavior 2.195494e-04 3.530241 2.195494e-04
## GO:0060562 epithelial tube morphogenesis 5.932837e-04 3.261376 5.932837e-04
## GO:0035295 tube development 5.953254e-04 3.253665 5.953254e-04
##          q.val set.size      exp1
## GO:0007156 homophilic cell adhesion 0.1951953      113 8.519724e-05
```

```
## G0:0002009 morphogenesis of an epithelium 0.1951953      339 1.396681e-04
## G0:0048729 tissue morphogenesis          0.1951953      424 1.432451e-04
## G0:0007610 behavior                      0.2243795      427 2.195494e-04
## G0:0060562 epithelial tube morphogenesis 0.3711390      257 5.932837e-04
## G0:0035295 tube development              0.3711390      391 5.953254e-04
##
## $less
##
##                p.geomean stat.mean      p.val
## G0:0048285 organelle fission      1.536227e-15 -8.063910 1.536227e-15
## G0:0000280 nuclear division      4.286961e-15 -7.939217 4.286961e-15
## G0:0007067 mitosis                4.286961e-15 -7.939217 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.169934e-14 -7.797496 1.169934e-14
## G0:0007059 chromosome segregation    2.028624e-11 -6.878340 2.028624e-11
## G0:0000236 mitotic prometaphase     1.729553e-10 -6.695966 1.729553e-10
##
##                q.val set.size      exp1
## G0:0048285 organelle fission      5.841698e-12      376 1.536227e-15
## G0:0000280 nuclear division      5.841698e-12      352 4.286961e-15
## G0:0007067 mitosis                5.841698e-12      352 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.195672e-11      362 1.169934e-14
## G0:0007059 chromosome segregation    1.658603e-08      142 2.028624e-11
## G0:0000236 mitotic prometaphase     1.178402e-07       84 1.729553e-10
##
## $stats
##
##                stat.mean      exp1
## G0:0007156 homophilic cell adhesion    3.824205 3.824205
## G0:0002009 morphogenesis of an epithelium 3.653886 3.653886
## G0:0048729 tissue morphogenesis        3.643242 3.643242
## G0:0007610 behavior                    3.530241 3.530241
## G0:0060562 epithelial tube morphogenesis 3.261376 3.261376
## G0:0035295 tube development            3.253665 3.253665
```

## ##Section 4. Reactome Analysis

Let's now conduct over-representation enrichment analysis and pathway-topology analysis with Reactome using the previous list of significant genes generated from our differential expression results above.

First, Using R, output the list of significant genes at the 0.05 level as a plain text file:

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
## [1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=FALSE)
```

Then, to perform pathway analysis online go to the Reactome website (<https://reactome.org/PathwayBrowser/#TOOL=AT>). Select “choose file” to upload your significant gene list. Then, select the parameters “Project to Humans”, then click “Analyze”.

Q: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?

Endosomal/vacuolar pathway has the most significant “Entities p-value” and this does not match the previous KEGG results. One of the factors that could cause difference between KEGG and Reactome analysis is the fact that these two methods use different databases so the possible, overlapping pathways that can be identified might be different. Another factor is the difference in the way these two methods do the math in overlapping and networking the pathways.