



**Work-based Professional Project in
Bioinformatics (II)**



**Drug-Target interaction prediction via binding
affinity Based on Deep Learning**

التنبؤ بمدى تأثير عقار مع بروتين وفقا لدرجة تفاعلهم اعتمادا على
منهجية التعلم العميق

Salah Gamal Abdelkhabir

4211099

Seham Samy Ezz-Eldeen

4211225

Ahmed Ebrahim Gabr

4211102

Omnia Khamis Khalil

4211028

Ahmed Hamdy Eldakroury

4211126

Sara Ayman Ebrahim

4211272

Ahmed Mohamed Ali

4211095

Level 3

Supervised by:

“Dr. Noha Ezzat Elattar”

Dean:

“Prof.Dr.Hisham Arafat Khalifa”

**Faculty of Artificial Intelligence
Delta University for Science and Tachnology**

Spring 2023/2024

Contributions for each students

no	ID	Student name	دور كل فرد في الفريق واسهاماته
1	4211099	Salah Gamal Abdelkhabir	-Implementing parts from data collection to model evaluation -Participate in documentation(Chapter3) -retrieving names of unknown molecules
2	4211225	Seham Samy Ezz-Eldeen	-Data collection - read articles on DTI principles -project's code -data visualization -chapter 4 in book -designing architecture and framework -work on banner.
3	4211102	Ahmed Ebrahim Gabr	-Implementing Model Deployment
4	4211028	Omnia Khamis Khalil	-Data collection -search in DTI and Binding affinity -chapters 1,2,5 in book -read many research paper on DTI -work on project's research paper
5	4211126	Ahmed Hamdy Eldakroury	Participate in Model Deployment and Data retrieving
6	4211095	Ahmed Mohamed Ali	-searching various database sources -chapter 2 in book -work on project's API -adding the names of missing proteins
7	4211272	Sara Ayman Ibrahim	- Convert drug and target ids into their names - chapter 1 in book - paper - data collecting

عناصر مهمة	نعم	لا	ما زالت في طور الإعداد
هل تمت المشاركة في مسابقات محلية او دولية		✓	
هل تم اعداد او نشر ورقة بحثية من العمل المقدم			✓
هل تم الاتصال بجهات خارجية مستفيدة		✓	
ما هي الخطة المستقبلية لتطوير المشروع	Enhancing model accuracy with advanced deep learning techniques and expanding data sources to include structural and omics data, further improving the predictive capabilities and applicability of our drug-target interaction model in the drug discovery field.		
أضافات			

Dedication:

"Dedicated to all the scientists, researchers, and innovators striving to revolutionize drug discovery. This project is a testament to the power of deep learning in predicting drug-target interactions and advancing the field of personalized medicine. We extend our gratitude to the countless individuals who have contributed to this project, from the collection and curation of data to the development and refinement of the deep learning model. May this work pave the way for novel therapies, accelerate the drug discovery process, and ultimately improve patient outcomes. Together, let us continue pushing the boundaries of scientific knowledge and harnessing the potential of artificial intelligence for the betterment of healthcare."

Contents

List of figure	2
List of Tables	3
1 Chapter 1: Introduction.....	6
1.1 Overview	6
1.2 Why this project ?	7
1.3 Problem Statement	9
1.4 Contribution	10
2 Chapter 2: Background and related work	11
2.1 Background	11
2.2 Related Work	15
2.3 Comprehensive comparison table	16
3 Chapter 3: Proposed Solution	19
3.1 Architecture	19
3.2 Framework	21
4 Chapter 4: Results analysis	35
4.1 Result	35
4.2 Analysis	38
5 Chapter 5: Conclusion.....	48
5.1 Future work.....	48
5.2 conclusion	49
6 REFERENCES.....	50

List of Figures and Tables

1. Figure 3.1(Architecture project).....	20
2. Figure 3.2 (Framework).....	23
3. Figure 3.3 (Binding affinity formula).....	25
4. Figure 3.4 (Data Exploratory Analysis).....	28
5. (Figure 3.5 (architecture of the model).....	32
6. Figure 3.6 (Model Deployment)).....	35
7. Figure 4.1.1 (Training and Validation Loss Over Epochs).....	36
8. Figure 4.1.2 (Mean Squared Error (MSE) on Validation Dataset).....	37
9. Figure 4.1.3 (Pearson Correlation on Validation Dataset).....	37
10. Figure 4.1.4 (Concordance Index on Validation Dataset).....	38
11. Figure 4.1.5 (Mean Squared Error (MSE) on Test Dataset).....	38
12. Figure 4.2.1 (Drug Occurrence Counts).....	39
13. Figure 4.2.2 (Occurrence of Drugs).....	39
14. Figure 4.2.3 (Word Cloud of Drug Occurrence)	40
15. Figure 4.2.4 (Drugs with occurrence).....	41
16. Figure 4.2.5 (Drugs with 362 occurrence)	41
17. Figure 4.2.6(Drugs with 99 occurrence)	41
18. Figure 4.2.7(Drugs with 10 occurrence)	41
19. Figure 4.2.8 (Target Name Occurrence Counts)	42
20. Figure 4.2.9 (Organism Occurrence Counts)	42
21. Figure 4.2.10 (Occurrence of Target Names)	43
22. Figure 4.2.11 (Occurrence of Organisms)	43
23. Figure 4.2.12 (Word Cloud of Target Occurrences)	44
24. Figure 4.2.13 (Word Cloud of Organism Occurrences)	44
25. Figure 4.2.14 (Targets with 6 Occurrences)	45
26. Figure 4.2.15 (Targets with 11 Occurrences)	45

27. Figure 4.2.16 (Targets with 74 Occurrences)	46
28. Figure 4.2.17 (Pie Chart for Drug-Target Pairs)	46
29. Figure 4.2.18 (Pie Chart for Drug-Target Pairs)	47
30. Figure 4.2.19 (Pie Chart for Drug-Target Pairs)	47
Table 1 [Comprehensive comparison table].....	16
Table 2 [Comprehensive comparison table].....	18

Chapter 1: Introduction

1.1 Overview

In this study, the binding affinity that measures the strength of interaction between a protein and ligand was assigned to labeled protein-ligand pairs, while for the unlabeled, they are inferred in drug-target prediction. This task corresponds to the regression problem mostly performed for pairs of proteins. Generally, machine learning techniques for this task are developed with two different goals: to obtain a powerful scoring function in virtual screening problems or to predict real activities of certain targets for the accurate usage of drugs. However, in the area of deep learning, the concept of transfer learning applied to this task integrates the built model with binding affinity predictions to other problems. Our model is expected to predict bioactivity outcomes at the molecular level, thus providing insight into the relationships between the structure of drugs and their molecular activity profile.

The efficacy of a drug is largely determined by the binding affinity of its target protein. The identification of drug-target interactions is a significant and crucial process, which serves to reduce the number of compounds in downstream studies such as pharmacokinetic research, drug mode of action analysis, and the prediction of off-target events. However, the traditional method of drug-target prediction is cumbersome, expensive, and time-consuming. To this end, the application of computational methods has shown utility by complementing experimental methods, and conversely, are capable of significantly reducing their costs

1.2 Why this project:

The drug-target interaction prediction is of critical importance for the advancement of the pharmaceutical industry and the broader field of computational drug discovery. Accurate prediction of drug-target interactions is a crucial step in the drug development pipeline, as it can significantly accelerate the process of identifying and validating potential drug candidates.

1.2.1 The importance of drug target interaction:

- Accurately predicting drug-target binding affinity can significantly expedite the drug discovery process by identifying promising drug candidates and prioritizing targets for further investigation.
- This can lead to substantial cost and time savings, as the development of a new drug typically takes several years and billions of dollars.
- High failure rates are a major challenge in the drug discovery and development pipeline, with only a small fraction of drug candidates successfully reaching the market.

- By improving the prediction of drug-target interactions, this project can help to identify more promising drug candidates, ultimately leading to a higher success rate in drug development.
- Accurate prediction of drug-target interactions can uncover novel therapeutic targets and facilitate the development of new classes of drugs.
- This can expand the available treatment options for various diseases and address unmet medical needs translate to faster access to life-saving and life-improving treatments for patients.
- The predictive model can be used to identify new therapeutic applications for existing drugs, a process known as drug repurposing.
- Drug repurposing can significantly reduce the time and cost associated with the development of new drugs, as existing compounds have already undergone safety and toxicology testing.
- By understanding the specific interactions between drugs and target proteins, the project can contribute to the development of personalized medicine approaches.
- This can lead to the design of more effective and targeted therapies, tailored to the individual patient's genetic profile and disease characteristics.
- The predictive model can be used to identify synergistic drug-target interactions, enabling the design of more effective combination therapies.
- Combination therapies can often provide better treatment outcomes compared to single-drug approaches, especially for complex and multi-factorial diseases.
- The proposed hybrid deep learning model, combining the strengths of CNNs and Transformer networks, represents a novel approach to drug-target interaction prediction.
- The successful development and implementation of this model can contribute to the advancement of computational drug discovery methodologies, inspiring future research and innovation in this field.

- The successful completion of this project can serve as a catalyst for further collaboration and knowledge sharing within the scientific community.
- By publishing the methodology, results, and insights gained, the project can inspire and guide future research efforts in the field of computational drug discovery, leading to a more rapid advancement of the field.

the drug-target interaction prediction project has a wide range of important impacts, including accelerating the drug discovery process, improving drug safety and efficacy, facilitating drug repurposing, enhancing collaboration and knowledge sharing, addressing global health challenges, fostering multidisciplinary collaboration, inspiring the next generation of researchers, and contributing to the Sustainable Development Goals. The successful completion of this project can have far-reaching implications, not only for the pharmaceutical industry but also for the broader fields of computational biology and artificial intelligence.

1.3 Problem statement:

Developing an accurate predictive model for drug-target binding affinity to facilitate the drug discovery process

The drug discovery process is a complex and time-consuming endeavor, often taking several years and substantial financial investments to bring a new drug to market. One of the critical steps in this process is the identification of suitable drug candidates and their corresponding target proteins. Accurately predicting the binding affinity between drugs and target proteins can significantly accelerate this process by prioritizing promising drug-target pairs for further experimental validation.

Traditional approaches to drug-target interaction prediction have relied on various computational methods, such as molecular docking, pharmacophore modeling, and ligand-based virtual screening. While these methods have provided valuable insights, they often require detailed structural information about the drugs and target proteins, which may not always be available. Additionally, these approaches may struggle to capture the complex and nonlinear relationships between the chemical and biological properties of drugs and their target proteins.

- The available data on drug-target interactions, including drug IDs, protein IDs, and their corresponding binding affinities, will be preprocessed. This will involve converting the drug and protein IDs to their respective names to enhance the interpretability of the results.
- Then a hybrid deep learning model will be designed and implemented, combining the capabilities of CNNs and Transformer networks. The CNN component will be responsible for encoding the chemical and structural properties of the drugs, while the Transformer network will capture the sequence-based features of the target proteins.

- This hybrid model will be trained using the preprocessed drug-target interaction data. Appropriate evaluation metrics, such as R-squared, mean squared error, or correlation coefficient, will be used to assess the model's predictive performance.
- The trained model will be analyzed to gain insights into the drug-target interactions. This analysis will include identifying the most influential features, visualizing the learned representations, and highlighting promising drug-target pairs for further experimental validation.

1.4 Contribution

Accurately predicting interactions, between drugs and their targets plays a role in advancing the industry and the realm of computational drug discovery. The following are some contributions

- **Speeding up drug discovery:** Precise predictions of drug target interactions can significantly hasten the identification and validation of drug candidates. By predicting which drugs are likely to interact with targets researchers can prioritize their efforts on the most promising candidates thereby expediting the drug discovery process and cutting down on the time and resources needed for developing new therapeutic agents.
- **Cutting costs and minimizing failures:** Conventional methods of drug discovery often involve time consuming screening procedures. By utilizing methods to forecast drug target interactions researchers can decrease the need for experimental screening and concentrate on a smaller pool of potential candidates. This results in cost reductions. Lowers the chances of failures, during the drug development phase.
- **Expanding the scope of research:** Computational methods allow scientists to investigate interactions, between drugs and targets expanding the possibilities for discovering new drug candidates and uncovering fresh therapeutic opportunities that might have been overlooked through traditional methods.
- **Guiding planning:** Precise prediction of drug target interactions offers insights into how drugs work and their possible side effects. This knowledge can influence the design of experiments helping researchers enhance drug properties like effectiveness, selectivity and safety. By utilizing forecasts researchers can better decide on which experiments to prioritize and develop successful strategies for drug development.
- **Supporting drug repurposing and personalized medicine:** By forecasting drug target interactions it becomes easier to repurpose existing drugs for uses. Identifying targets that a drug may interact with allows researchers to explore therapeutic applications, for current compounds potentially saving time and resources associated with creating entirely new medications. Moreover accurate predictions of these interactions can

advance personalized medicine by assisting in the selection of drugs tailored to an individuals makeup enhancing treatment effectiveness while minimizing reactions.

Chapter 2: Background and related work

2.1 Background

In this chapter, we present the background and related work of our drug-target interaction (DTI) prediction model and challenges in our model and projects similar our project

it is widely recognized that there is a multitude of diseases posing significant threats to human health. Drug discovery, as a crucial area of research, requires urgent exploration. Concurrently, the rapid advancement of computer technology has fostered interdisciplinary collaboration. Particularly, the integration of machine learning and deep learning techniques into bioinformatics has proven effective in enhancing the efficiency of drug discovery. Drug-target interaction (DTI) prediction, which aims to identify the targets of drug molecules, plays a pivotal role in the drug discovery process and has garnered considerable attention in computer-aided drug discovery . Compared to traditional drug discovery models, DTI prediction can significantly reduce the cost associated with drug discovery .

Conventional DTI prediction methods primarily rely on machine learning approaches. Representative methods in recent works include the fuzzy bipartite local model , multi-output prediction method , and superior Bayesian personalized ranking method . Ding et al. developed a fuzzy bipartite local model based on a fuzzy least squares support vector machine and multicore learning to predict DTIs. They employed multicore learning to integrate multiple drugs and targets and utilized fuzzy bipartite local models to infer unknown DTIs. Pliakos et al. [4]proposed DTI prediction as a multi-output prediction problem and addressed it by learning an ensemble of multi-output biclustering trees on a reconfigured network. Ye et al. introduced an Adversarial Bayesian Personalized Ranking model that generated ternary biased-order relations for drug targets. These relations were then used to train a drug and target latent factor matrix, ultimately obtaining score rankings for DTI prediction based on the inner product of latent factors.

With the rapid development of deep learning methods, DTI prediction approaches based on deep learning have emerged, facilitating target identification and advancing the drug repurposing process within heterogeneous drug-gene-disease networks. Sun et al. proposed an auto-encoder-based DTI prediction method that projected drug features into the protein space through a multi-layer encoder and then into the disease space via a decoder. Xuan et al. developed methods to integrate multi-scale adjacent topologies, multiple similarities, associations, and drug- and protein-related interactions. These methods employed a fully connected self-encoder learning framework to acquire low-dimensional feature representations of nodes in heterogeneous networks. Subsequently, a multilayer convolutional neural network was employed to generate

final predictions. However, traditional methods are often limited by small sample sizes and the difficulty in extracting complex graph structure information.

Given that DTIs networks can be modeled as networks themselves, several network-based methods have been proposed to predict DTIs. Manoochehri et al. introduced a network topology-based framework for predicting interacting and non-interacting drug-target pairs, capable of learning complex drug-target topological features. Jin et al. proposed the multi-resolutional collaborative heterogeneous graph convolutional Auto-Encoder method for DTI prediction. This method fused and assigned weights to embeddings of various types of links and continuously added adjacent embeddings using gated recurrent units before combining them to form the final embedding. Yue et al. devised a method for bipartite DTI relations based on heterogeneous network embedding. They decomposed a heterogeneous DTI network into three sub-networks and employed a random forest model to predict new DTIs by combining the features of a bipartite DTI network for drug-target interactions, a drug-based similarity network, and a target-based similarity network. However, current deep learning methods struggle to extract deep-level interaction information and are limited in their applicability to drug-protein interactions.

While existing DTI prediction methods are commendable, certain challenges persist. Researchers often focus solely on drug-protein interactions, overlooking the interactions between two drug-protein pairs.

In recent years, deep learning plays an essential role in computer and other fields. Hinton et al. first introduced the concept of deep learning (DL), with the advancement of DL and the growth of drug-related data, many DL-based methods were applied in various steps of drug discovery. For the drug-target binding affinity (DTA) prediction, DL was used to learn and understand information from both molecules and proteins to determine whether a pair of drug and target could be bound together (classification tasks) or to predict the DTA value (regression tasks). In the DTA prediction task, the first challenge is how to select the appropriate representation of the experimental data. A common molecular representation method is the Simplified Molecular Input Line Entry System (SMILES), and proteins can be represented as amino acid sequences. The recurrent neural network (RNN) is an effective method for extracting protein and molecular features from sequential data. Zheng et al. extracted potential semantic information between protein and molecule through Long Short-Term Memory Network (LSTM), a special recurrent neural network, for drug-target interaction (DTI) prediction. DeepH-DTA used a bidirectional ConvLSTM to model spatial sequence information on SMILES data. GLSTM-DTA combined the graph neural network (GNN) and the LSTM for molecule and protein representation in DTA prediction, respectively. However, the RNN only considers the context of sequences without the original structure of molecules, which will affect the generalization ability of the model on other datasets.

For the molecule, the complete structural information of molecules is contained in the 3D atomic coordinates, but their 3D grid representation has a large number of redundant voxels where no atoms exist, resulting in inefficient computations. In addition, the rotation invariance and scale invariance are both need to be solved in the 3D grid, which could affect the prediction of the binding affinity. In contrast, the 2D graph representation is compact and rotation invariant, which ensures the stability and repeatability of model predictions. The molecule could be

converted to the graph, where atoms and bonds are represented as nodes and edges in the graph. GraphDTA constructs graphs to describe molecules and apply GNN for feature extraction in DTA prediction. MGraphDTA also proposed a multiscale graph neural network for DTA prediction.

Moreover, graph convolutional neural networks (GCN) could be used for molecular representation. For example, Ying et al. combined efficient random walk and graph convolution networks to generate atom embeddings that contain information of graph structure and atom. WGNNDTA proposed a weighted graph neural network to provide more detailed information on the residue interaction for DTA prediction. GanDTI designed a Residual Graph Neural Network to extract the embedding of molecules for DTA and DTI prediction. Shao et al. used GCN to extract features from the drugs and targets, respectively, and the convolutional neural network (CNN) was used to extract and predict potential associations between drugs and targets. For the graph representation, the major challenge is how to update messages between atoms effectively. Message Passing Neural Network (MPNN) was proposed for molecular property prediction, which updated the atom information in the molecular graph while ignoring the information from the bond. To alleviate this problem, CMPNN improved the molecular embedding method considering that the information from chemical bonds to atoms is equally essential.

2.1.1 Binding affinity prediction

The interaction between an active compound and a protein is determined by comprehensive processes that are heavily reflected on the ligand's binding affinity and bioactivity. The magnitude and rank order of the binding pair association is usually presented in terms of three different metrics: dissociation constant (K_d), inhibition constant (K_i) and half maximal inhibitory concentration (IC_{50}). However, K_d is one of the few considered to be unbiased since it is not influenced by the experimental conditions, and expresses a direct measurement of the equilibrium between the receptor-ligand complex and the dissociation components, in which lower values are associated with strong interactions.

Computational drug discovery studies focused in the prediction of binding affinity have been initially driven by the necessity to account for more information in the scoring functions used in structure-based virtual screening. Machine learning methods, including Random Forest, and deep learning architectures, e.g., Feed-Forward Neural Network or 3D CNNs, have been explored as potential replacements for the scoring functions, predicting the binding affinity of protein-ligand complexes either based on different features associated with the 3D structures or 3D single instance learning. Apart from improving the scoring functions, some research studies have been pursuing more realistic methodologies to predict DTIs, exploiting the problem as a binding affinity regression task, and making use of chemogenomic and lower structural data, e.g., 1D or 2D data. On that account, three benchmark datasets associated with the studies of Davis et al., Metz et al. and Tang et al. measured in K_d , K_i and KIBA, respectively, have been exploited to conduct the experiments. In addition to some machine learning algorithms, including the Kronecker-regularized least squares [26] or gradient boosting regression trees, most of the inferring models have been based on the use of 1D CNNs, 2D CNNs or Graph CNNs, where different representations of the proteins and compounds have been explored, including 1D structures, 2D similarity matrices, feature vectors or even graph representations.

In spite of the existing binding affinity prediction methodologies, several of these studies still rely on the use of biased binding affinity metrics, i.e., dependent on the measurement conditions, mechanism of inhibition and concentrations. Furthermore, sequential and structural data are still seldomly used together, which is extremely limiting when inferring new interactions, considering that the features used to characterize the DTIs do not reflect the importance of the structural information, specifically related to binding sites. On that account, these models are unable to assess the magnitude of certain local regions in the prediction score. Moreover, binding affinity prediction models based on deep learning have yet to provide explainability to the predictions, compromising the validity of the results, and limiting the identification and comprehension of the underlying aspects around the interaction.

2.1.2 Explainable deep learning

The interpretability of deep learning architectures have been extremely questioned over the time, especially regarding their intrinsic operations, decisions and results [36]. On that matter, there have been several research advances regarding the explainability of these models and it has been essentially achieved by either adapting the inner architecture (intrinsic interpretability) or performing external evaluations (post-hoc interpretability)

Intrinsic interpretability focus on incorporating explainability directly into the structural units of the architecture (self-interpretable). On that account, attention mechanisms have been explored and incorporated in the architectures to condition the learning process, and provide interpretability through the visualization of the input regions that were given more attention (weight). Apart from attention layers, local modifications on the units of the architectures, e.g., filters of CNNs, have also been presented to get interpretable knowledge representations. On the other hand, post-hoc interpretability establishes a secondary model in order to provide explanations regarding the model behavior and inner operations. On that matter, methods based on local perturbations, including Prediction Difference Analysis or Occlusion Analysis, have been explored to evaluate the model's response based on general local perturbations, e.g., conditional sampling or masking parts of the input. Furthermore, propagation-based methods have also been considered to be efficient, leveraging the model's internal structure for the explanation process. On that account, methods such Deconvolution, Layer Relevance Propagation or Gradient-Weighted Class Activation Mapping, highlight the critical regions in the input for the prediction of the concept, in which the feature activity, the relevance score or the gradients of the model's outcome are backpropagated to the input domain, respectively.

In our project, we apply an end-to-end deep learning methodology to forecast the binding affinity between drugs and targets, quantified by the dissociation constant (K_d). The representation of targets and compounds involves using 1D sequential and structural data, protein sequences, and SMILES (Simplified Molecular Input Line Entry System) strings, respectively. We implement techniques to enhance the interpretability of the convolutional neural networks (CNNs), offering insight into the model's decision-making process by highlighting the regions of input that influenced the predictions the most. Furthermore, we confirm the efficacy of the deep representations. This investigation focuses on three main objectives: a) assessing the efficiency of deep representations in predicting real-valued interaction strength; b) examining the

reliability of CNNs in pinpointing crucial sequential and structural segments for binding; and c) verifying the robustness of the features derived from significant sequential segments.

CNNs have become a critical tool in the field of drug-target interaction prediction due to their powerful feature extraction capabilities and ability to handle complex, structured data. Compared to other projects, CNN-based models often demonstrate superior performance and flexibility, making them an important approach in computational drug discovery. The integration of CNNs with other deep learning techniques continues to push the boundaries of what is possible in predicting drug-target binding affinities

- **Accelerating Drug Discovery:** Predicting drug-target binding affinity can assist in uncovering new drug-target pairs and optimizing drug design by increasing drug binding affinity through structural changes in the molecule's structure¹. This can expedite the early drug discovery process².
- **Cost and Time Efficiency:** Traditional experimental methods such as immunoprecipitation, spectroscopy, calorimetry, and surface plasmon resonance are often dependent on limited structural information from drug-target pairs, specialized domain knowledge, and expensive and time-consuming experimental assays². CNN models provide a new way for DTI prediction to achieve good performance without much knowledge of the biochemical background³.
- **Identifying Relevant Regions for Binding:** CNN models have shown reliability in identifying relevant regions for binding, specifically binding sites and motifs⁴. This can contribute significantly to understanding the binding process and developing new drugs.
- **Explainability:** The deep representations extracted by CNNs provide explanations to the model's decisions based on the identification of the input regions that contributed the most to the prediction⁴. This explainability is crucial for understanding why certain predictions are made and can lead to more trust in the model's predictions.
- **Drug Repurposing:** The prediction of DTI is vital for the development of new drugs, optimizing the whole process chain and leveraging the information available for drug repositioning⁴. This can lead to the discovery of new uses for existing drugs, saving time and resources in the drug development process.

2.2 Related works

Drug-target interactions (DTIs) prediction plays an important role in finding potential therapeutic compounds. Moreover, DTIs prediction is an indispensable step in drug re-positioning and drug discovery. DTIs prediction is also helpful to identify new ligands for new drugs and targets by identifying the interactions between drug compounds and protein targets. DTIs prediction

methods can be roughly divided into traditional methods and deep learning methods. Among a large number of deep learning methods, network-based methods perform well in predicting DTIs. Therefore, the following focuses on the traditional methods and the network-based methods in deep learning.

2.2.1 Traditional DTIs prediction methods

Traditional DTIs prediction methods are mainly divided into two categories: methods based on molecular docking simulation . Ligand-based approaches . Based on basic biophysical principles and the crystal structure of the target binding site, molecular docking methods often yield good prediction of drug ability. In contrast to conventional ligand-protein docking, reverse ligand-protein docking aims to seek potential protein targets by screening an appropriate protein database . Ligand-based approaches are often designed based on the principle of structure-dependent properties. These methods use structural similarity to search similar compounds in terms of activities or treatment mechanisms. Although the above-mentioned methods have shown high prediction accuracy. Those molecular docking methods rely on the three-dimensional structure of the target protein . The results of ligand-based methods may be less than ideal when there are insufficient data on known ligands . However, most current network-based approaches ignore the information relationship between the nodes and the whole heterogeneous graph.

2.2.2 Comprehensive comparison table

Method	Description	Advantages	Limitations
CNN-based models	Utilize convolutional neural networks (CNNs) to extract features from drug and protein representations.	- Can capture local and global dependencies in the data.	- May struggle with capturing long-range dependencies.
Transformer models	Employ transformer-based architectures to model the interactions between drugs and target proteins.	- Effective in capturing long-range dependencies.	- Can be computationally expensive and require large amounts of training data.
Graph neural networks	Utilize graph-based representations to model the structural and functional properties of molecules.	- Can handle complex molecular structures and capture interactions between atoms.	- May require extensive graph preprocessing and feature engineering.
Hybrid models	Combine multiple deep learning techniques (e.g., CNNs and Transformers) to leverage their strengths.	- Can capture both local and global dependencies, as well as long-range interactions.	- Increased model complexity may require more computational resources and longer training times.
Integration of structural and omics data	Incorporate additional data sources such as structural information and omics data (genomics, proteomics, metabolomics) to provide a more comprehensive understanding of drug-target interactions.	- Enables a more holistic representation of drug-target interactions.	- Requires integration and preprocessing of diverse data sources.

Applicability to new drug formats and cross-species analysis	Extend the models to handle different drug formats (e.g., peptides, antibodies) and enable analysis across different species.	- Enables exploration of diverse therapeutics and improves generalizability.	- May require additional data and model adaptations to handle the specific formats and species.
Integration of clinical trial data and personalized medicine applications	Incorporate clinical trial data and consider patient-specific factors for relevance to real-world scenarios and personalized medicine.	- Enhances the practical applicability of the models for personalized treatment decisions.	- Requires access to comprehensive and well-curated clinical trial data, as well as patient-specific information.

Table 1. Comprehensive comparison table

Aspect	Your Project (CNN-DTI)	Similar Project (CNN-DDI) ¹	Similar Project (LDS-CNN) ²
Objective	Predict binding affinity between drugs and targets	Predict drug-drug interactions	Predict DTIs based on large-scale drug screening
Methodology	Utilizes CNN for feature extraction and prediction	Employs CNN to learn feature representations and predict DDIs	Uses unified encoding in CNN for feature abstraction and prediction
Data Source	BindingDB, PDBind, etc.	Drug categories, targets, pathways, enzymes	898,412 interaction data involving 1,683 compounds and 14,350 proteins
Performance Metrics	Concordance index, AUC, etc.	Accuracy, AUC, precision-recall curve	AUC of 0.96, AUPRC of 0.95, accuracy of 90.13%
Validation	Cross-validation, external validation	Cross-validation, comparison with existing algorithms	Tested on large-scale dataset
Explainability	Focus on model interpretability	Not explicitly mentioned	Not explicitly mentioned
Application	Drug discovery, repurposing	Drug development, disease diagnosis	Identifying potential drug targets and candidates
Accessibility	Source code and data available	Not specified	Not specified
Future Directions	Enhancing interpretability, integrating diverse data	Improving feature representation learning	Efficient feature abstraction among different data types

Aspect	Your Project (CNN-DTI)	Similar Project (Graph-Based DTI) ¹	Similar Project (Graph Transformers DTI) ²
Objective	Predict binding affinity between drugs and targets	Predict DTIs using knowledge graph embedding and ProtBERT pretraining	Predict DTIs using graph transformers model
Methodology	Utilizes CNN for feature extraction and prediction	Integrates knowledge graph embedding with ProtBERT for target similarity	Employs graph transformers to model drug-target interaction relationships
Data Source	BindingDB, PDBind, etc.	Enzymes, Ion Channels, G-protein-coupled Receptors datasets	Drug-target interaction network data
Performance Metrics	Concordance index, AUC, etc.	AUC, AUPR, ACC, MCC, F1 score	Not specified
Validation	Cross-validation, external validation	Extensive experimentation and case studies	Peer-reviewed reports
Explainability	Focus on model interpretability	Emphasizes the robustness and accuracy of predictions	Introduces a line graph to model relationships between drugs and targets
Application	Drug discovery, repurposing	Effective computational methodology for drug discovery	Accelerating drug research and drug repositioning
Accessibility	Source code and data available	Not specified	Not specified
Future Directions	Enhancing interpretability, integrating diverse data	Utilizing diverse similarity measures for robust predictions	Exploring different level relationships of drugs and targets

Table 2. Comprehensive comparison table

Chapter 3: Proposed Solution

3.1 Architecture

This section provides a detailed overview of the architecture of our project. The architecture comprises various components and tools essential for processing the project. A systematic architecture is crucial for achieving project success. In our project, we rely on the architecture to meet our targets effectively. The figure below illustrates the overall architecture.




Figure 3.1(Architecture project)

- **Therapeutics Data Commons (TDC)**

Therapeutics Data Commons (TDC) is a coordinated initiative designed to facilitate access to and evaluation of artificial intelligence capabilities across therapeutic modalities and stages of discovery. It supports the development of AI methods, with a strong emphasis on identifying

which AI methods are most suitable for drug discovery applications and understanding the reasons behind their suitability.

Researchers from various disciplines can leverage TDC for multiple applications. TDC serves as a convergence point for biochemical and AI scientists by offering AI-solvable tasks, AI-ready datasets, and curated benchmarks. TDC promotes algorithmic and scientific advancements, accelerates the development of machine learning methods, and aids their validation and transition into biomedical and clinical implementations.

In our project, we utilized TDC to obtain a comprehensive dataset package, which includes experimental Drug-Target Interaction (DTI) data. This dataset specifically comprises Drug SMILES (Simplified Molecular Input Line Entry System) representations and Protein sequences, along with their binding affinity scores. Our objective was to retrieve the maximum affinity scores.

- **Data Cleaning and Exploratory Analysis:**

After acquiring the dataset from TDC, the next step involved data cleaning. We performed Data Exploratory Analysis (DEA) using the RDKit library.

RDKit is a robust collection of cheminformatics and machine-learning software written in C++ and Python. We employed the RDKit library to extract meaningful information from the data, such as the 3D structure of drug molecules and the details of carbon atoms in the Drug SMILES representations.

- **Training Methods**

For the training phase, we utilized DeepPurpose.

DeepPurpose is a deep learning-based drug repurposing and virtual screening toolkit implemented using PyTorch. We used DeepPurpose to access its comprehensive package of encoder methods. Utilizing the built-in models provided by DeepPurpose, we constructed a neural network incorporating CNN (Convolutional Neural Network) and Transformer Encoders for our regression task.

- **Visualization and Metrics**

To visualize various metrics, we employed Scikit-learn.

Scikit-learn is a widely-used machine learning library in Python. We used it to visualize and analyze several metrics, including Mean Square Error (MSE), Pearson Correlation, Concordance Index, and R2 score. These metrics provided valuable insights into the performance of our models.

- **Deployment**

The final phase involved deploying the project via a web application using Flask, HTML, and CSS.

Flask is a lightweight web framework in Python that we used to create the backend of our web application. HTML and CSS were employed for designing and structuring the front end of the application, ensuring a user-friendly interface.

3.2 Framework

We have talked about the architecture and mentioned the modules we used.

Now, Moving to the Framework. Framework is the flowchart and is the backbone of the project.

It determines the full plan of steps for the project. Now we declaring our framework.

The framework including the following:

- Data Collection
- Data Cleaning
- Data Exploratory analysis
- Model Construction and Model evaluation
- Model deployment

These steps are inside the following figure:




Figure 3.2 (Framework)

3.2.1 Data Collection:

Data Collection was the most challenging step because of lack of databases and trusted resources. Our dataset was collected from Binding Database via TDC Library as we mentioned.

This dataset contains 5 columns Drug ID, Drug SMILES (Simplified Molecular Input Line Entry System) , Target ID, Target sequence and finally the experimental binding affinity score.

Let's get a look on Binding database.

BindingDB is a public, web-accessible database of measured binding affinities, focusing chiefly on the interactions of proteins considered to be candidate drug-targets with ligands that are small, drug-like molecules. BindingDB supports medicinal chemistry and drug discovery via literature awareness and development of structure-activity relations (SAR and QSAR); validation of computational chemistry and molecular modeling approaches such as docking, scoring and free energy methods; chemical biology and chemical genomics; and basic studies of the physical chemistry of molecular recognition. BindingDB also includes a small collection of host-guest binding data of interest to chemists studying supramolecular systems.

The data collection derives from a variety of measurement techniques, including enzyme inhibition and kinetics, isothermal titration calorimetry, NMR, and radioligand and competition assays. BindingDB includes data extracted from the literature and patents by the BindingDB project, selected PubChem confirmatory BioAssays, and ChEMBL entries.

- Note that we retrieved the drug names from ChemSpider database according by the SMILES,

And we retrieved the target names from UniProt database according to the sequence of Amino acids.

- Note that else, the most important column is for binding affinity, this must be sensitive and trusted data and we had to study how this score calculated and why he is with this level of sensitivity.

First, let's define the binding affinity score. The Binding affinity score is the strength of the binding interaction between a single biomolecule (e.g., a protein or DNA) to its ligand or binding partner (e.g., a drug or inhibitor). Binding affinity is typically measured and reported by the equilibrium dissociation constant (KD), which is used to evaluate and rank order strengths of bimolecular interactions. The smaller the KD value, the greater the binding affinity of the ligand for its target. The larger the KD value, the more weakly the target molecule and ligand are attracted to and bind to one another.

Binding affinity is calculated through following formula:

$$pK_d = -\log_{10} \left(\frac{K_d}{1e9} \right)$$

Figure 3.3 (Binding affinity formula)

Now we know How data was collected, Let's explore the data.

The data contains table of 42236 rows $\times$ 5 columns. This table represents the samples (Drug-Target pairs).

But there are only 9644 samples for unique drugs and 1082 samples for unique targets.

3.2.2 Data cleaning

Data cleaning is an essential step in the data preprocessing pipeline that involves identifying and correcting errors, inconsistencies, and missing values in the dataset. The main goal is to improve the quality and reliability of the data, which is crucial for accurate analysis and modeling. Clean data ensures that the results of any analysis or model are valid and dependable.

Importance of Data Cleaning:

- **Accuracy:** Ensures that the data accurately reflects the real-world scenario being studied.
- **Consistency:** Standardizes the data format, removing discrepancies and making the dataset uniform.
- **Completeness:** Addresses missing values, ensuring the dataset is as complete as possible.
- **Validity:** Ensures that the data adheres to predefined rules and constraints, making it suitable for further analysis.
- **Enhanced Model Performance:** Improves the performance and accuracy of machine learning models by reducing noise and irrelevant information.

Data Cleaning Steps:

- **Removing Missing Values:**

Rows containing null values were removed to prevent potential issues in subsequent analyses and modeling. This step ensures that the dataset is free from incomplete entries that could skew results or cause errors in the analysis.

- **Extracting and Analyzing the Target Variable:**

The target variable 'Y' was extracted and converted to a format suitable for analysis. The smallest values of 'Y' were examined to understand the distribution and identify any anomalies or unusual data points.

- **Outlier Removal:**

Outliers were identified and removed by filtering 'Y' values within a specified range. This step ensures that the data falls within a reasonable and expected range, which helps improve the robustness and accuracy of subsequent analyses and models.

- **Examining Drug Information:**

The 'Drug' column was extracted to analyze the distribution and characteristics of the drugs in the dataset. This step helps in understanding the dataset's composition and the diversity of drug entries.

- **Verifying Dataset Shape:**

The shape of the dataset was checked to ensure that it retained a substantial number of samples after the cleaning steps. This verification step ensures that the dataset is still sufficiently large for meaningful analysis and modeling.

- **Resetting Index Values:**

The index of the DataFrame was reset to maintain a sequential order after rows had been removed. This step ensures that the dataset remains well-organized and easy to navigate.

- **Scaling the Target Variable:**

The target variable 'Y' was scaled to a specified range (0 to 100) using a scaling technique. This normalization step ensures that the data is within a consistent scale, which improves the performance of machine learning algorithms by making the data more uniform and comparable.

3.2.3 Data exploratory analysis:

Exploratory Data Analysis (EDA) involves examining the dataset to summarize its main characteristics, often with visual methods. EDA helps uncover patterns, spot anomalies, test hypotheses, and check assumptions with the help of summary statistics and graphical representations.

Steps in Exploratory Data Analysis

1. Generating Molecular Structures:

- Molecular structures of the drugs were generated using the RDKit library. RDKit is a collection of cheminformatics and machine learning tools that are used for various computational chemistry tasks.
-
- The molecular structure column was added to the DataFrame, allowing for the visualization and analysis of drug structures.

2. Analyzing the Number of Atoms in Drug Molecules:

- The number of atoms in each drug molecule was calculated to gain insights into the molecular complexity of the drugs in the dataset.
- This information helps in understanding the size and complexity of the drug molecules, which can be critical for modeling and predicting drug-target interactions.

Steps and Insights:

1. Molecular Structure Generation:

- RDKit's `PandasTools.AddMoleculeColumnToFrame` function was utilized to add a molecular structure column to the DataFrame based on the SMILES notation of the drugs.
- This step provided a visual representation of the drug molecules, which is essential for understanding their chemical properties and potential interactions with targets.

2. Atom Count Analysis:

- The number of atoms in each drug molecule was calculated using RDKit's `Chem.MolFromSmiles` function.

- This analysis provided insights into the molecular size and complexity, which are important factors in drug design and efficacy.

The figure below shows the two processes of Data Exploratory Analysis:




Structure	Number_of_Atoms
	10
	10
	6

Figure 3.4 (Data Exploratory Analysis)

3.2.4 Model Construction:

In this section, we describe the construction of our deep learning model designed to predict the binding affinity between drug molecules and target proteins. Our model utilizes both drug sequences and target sequences as inputs, processes them through various layers, and outputs the predicted affinity score. Below, we detail each layer, its function, and the parameters used in the model.

The model consists of two main branches for processing drug sequences and target sequences separately. These branches are then concatenated and passed through fully connected layers to predict the binding affinity score.

Description of Architecture:

Input Layers:

The model has two input layers: one for drug sequences and one for target sequences. These layers accept the raw sequences of the drug molecules and protein targets, respectively.

Embedding Layers:

- Drug Embedding Layer:

This layer converts the input drug sequences into dense vector representations using a Transformer-based embedding approach. This helps in capturing the semantic meaning of the drug sequences in a high-dimensional space.

- Hidden Dimension: 128
- Filters: 32, 64, 96
- Kernel Sizes: 4, 8, 12

- Target Embedding Layer:

This layer converts the input target sequences into dense vector representations using a Convolutional Neural Network (CNN)-based embedding approach. This helps in extracting spatial features from the target sequences.

- Filters: 32, 64, 96
- Kernel Sizes: 4, 8, 12

Positional Embeddings and Convolutional Layers:

- Drug Positional Embedding Layer:

Positional embeddings are added to the drug embeddings to capture the order of elements in the sequences, which is crucial for understanding the sequence structure.

- Target Convolutional Layers:

The target sequences are processed through a series of convolutional layers to extract hierarchical features. These layers progressively capture more complex patterns in the target sequences:

Convolutional Layer 1

- Filters: 32
- Kernel Size: 4

Convolutional Layer 2

- Filters: 64
- Kernel Size: 8

Convolutional Layer 3

- Filters: 96
- Kernel Size: 12
-

Normalization and Dropout:

- Drug Layer Normalization and Dropout:

This step applies layer normalization and dropout to the drug embeddings. Normalization helps stabilize and accelerate training, while dropout prevents overfitting by randomly setting some of the activations to zero during training.

- Dropout Probability: 0.1

- Transformer Encoder Layers:

The drug embeddings are processed through multiple Transformer encoder layers. These layers use self-attention mechanisms to capture dependencies between different parts of the drug sequences, allowing the model to understand the context of each element in the sequence.

- Number of Attention Heads: 8
- Attention Dropout Probability: 0.1
- Hidden Dropout Probability: 0.1
- Intermediate Size: 512

Flatten Layer:

After processing through the convolutional layers, the output of the target branch is flattened into a single vector. This flattening step prepares the data for concatenation with the drug branch.

Concatenation Layer:

The processed outputs from the drug and target branches are concatenated into a single representation. This combined representation incorporates information from both the drug and the target sequences.

Fully Connected Layers:

The concatenated representation is passed through several fully connected layers. These layers transform the combined features into a form suitable for predicting the binding affinity:

- Fully Connected Layer 1
- Output Dimension: 1024
- Fully Connected Layer 2
- Output Dimension: 1024
- Fully Connected Layer 3
- Output Dimension: 512

Output Layer:

The final layer of the model is the output layer, which predicts the binding affinity score. This score indicates the strength of the interaction between the drug and the target protein.

Training Parameters:

The model is trained using the following parameters:

- Training Epochs: 30 epochs.
- Learning Rate: 0.0001.
- Batch Size: 128.

The following figure shows the architecture of the model:




Figure 3.5 (architecture of the model)

3.2.5 Model Deployment:

Model deployment is the process of making a machine learning model available for use by end-users. It involves integrating the model into an environment where it can be accessed via a user interface or an API, allowing predictions to be made based on new data inputs. In our project, model deployment is crucial as it enables biologists and other end-users to make predictions about drug-target interactions.

Importance for Biologists

The ability to predict drug-target interactions (DTIs) is vital for biologists involved in drug discovery and development. Accurate predictions can:

- **Accelerate Research:** By quickly identifying potential drug candidates, researchers can save significant time and resources.
- **Enhance Decision-Making:** Reliable DTI predictions help in making informed decisions regarding the viability of compounds for further testing.
- **Reduce Costs:** Early identification of promising drug candidates reduces the need for costly and time-consuming experimental procedures.
- **Facilitate Personalized Medicine:** Understanding DTIs can aid in developing personalized treatment plans based on individual genetic profiles and specific target interactions.

Technologies and Frameworks

- Flask:

Flask is a lightweight and versatile web framework for Python, ideal for building web applications and APIs. In our project, Flask is used to create the web server that handles requests, processes inputs, and returns predictions. Its simplicity and flexibility make it a perfect choice for our deployment needs.

- HTML:

HTML (HyperText Markup Language) is the standard language for creating web pages. We used HTML to design the structure of the web interface, ensuring it is user-friendly and accessible. The HTML code defines the layout, input forms, and display elements for prediction results.

- CSS:

CSS (Cascading Style Sheets) is used to style the HTML elements, enhancing the visual appeal of the web interface. By using CSS, we ensured that the web application is not only functional but also aesthetically pleasing, providing a better user experience.

- **API Functionality**

The API serves as the backbone of our web application, allowing users to interact with the model efficiently. Here are the key functionalities provided by our API:

- 1. Home Route:**

The home route ("/") serves as the main page of the web application. It displays dropdown menus for selecting drugs and targets and provides a form for users to submit their input. When the page is loaded, the API retrieves and displays the list of available drugs and targets from the dataset.

- 2. Prediction Route:**

The prediction route ("/predict") handles the core functionality of the API. When a user submits the form with their selected drug and target, the API processes this input, retrieves the corresponding SMILES and sequence data, and uses the pre-trained model to predict the binding affinity. The result is then displayed on the web interface, providing immediate feedback to the user.

- 3. Prediction API Endpoint:**

In addition to the web interface, the API includes a dedicated endpoint ("/predict_api") for programmatic access. This allows other systems or applications to send drug SMILES and target sequence data via a POST request and receive the predicted binding affinity in response. This endpoint broadens the usability of our model, enabling integration with other tools and workflows.

- **User Interface Design:**

The user interface is designed to be intuitive and easy to use, ensuring that biologists and researchers can effortlessly interact with the model. Here are some design elements:

- **Dropdown Menus:**

Users can select drugs and targets from dropdown lists, minimizing the risk of input errors and ensuring accurate predictions.

- **Prediction Display:**

The predicted binding affinity is prominently displayed on the interface, providing clear and immediate results.

- **Error Handling:**

The interface includes mechanisms to handle and display errors, such as missing inputs or invalid selections, ensuring users are informed of any issues.

- **Deployment and Accessibility**

The API and web application are deployed on a server, making them accessible to users via a web browser. This deployment ensures that the model can be accessed from anywhere, providing a convenient and scalable solution for predicting drug-target interactions.

The following figure shows the Model Deployment:




Figure 3.6 (Model Deployment)

Chapter 4: Results analysis

4.1 Results:

In this chapter, we present the results and analysis of our drug-target interaction (DTI) prediction model. To evaluate the performance of our model, we used several key metrics: training and validation loss over epochs, mean squared error (MSE), concordance index, and Pearson correlation. These metrics provide a comprehensive assessment of the model's predictive accuracy and reliability.

1) Training and Validation Loss Over Epochs:

Training and validation loss are crucial indicators of a model's learning process. The training loss measures the error on the training dataset, while the validation loss measures the error on the validation dataset. Monitoring these losses over epochs helps us understand how well the model is learning and whether it is overfitting or underfitting. **Figure 4.1.1** illustrates the training and validation loss over the epochs, demonstrating the model's learning trajectory.



Figure 4.1.1 (Training and Validation Loss Over Epochs)

2) Mean Squared Error (MSE) on Validation Dataset:

The mean squared error (MSE) is a widely used metric for regression tasks that calculates the average of the squared differences between predicted and actual values. In the context of our DTI model, MSE validation assesses how closely the predicted binding affinities match the true values on the validation dataset. **Figure 4.1.2** shows the MSE validation results, providing insights into the model's accuracy in predicting binding affinities.




Figure 4.1.2 (Mean Squared Error (MSE) on Validation Dataset)

3) Pearson Correlation:

Pearson correlation validation assesses the linear relationship between the predicted and actual binding affinities. It ranges from -1 to 1, where 1 indicates a perfect positive linear correlation, -1 indicates a perfect negative linear correlation, and 0 indicates no linear correlation. A higher Pearson correlation coefficient suggests that the model's predictions are more accurately aligned with the true binding affinities. **Figure 4.1.3** depicts the Pearson correlation validation results, illustrating the strength of the linear relationship between predicted and actual affinities.




Figure 4.1.3 (Pearson Correlation on Validation Dataset)

4) Concordance Index:

The concordance index (CI) is a metric used to evaluate the predictive accuracy of models, particularly in survival analysis and risk prediction. For our DTI model, the concordance index validation measures the degree to which the predicted binding affinities correctly rank the interactions relative to each other. A CI value closer to 1 signifies a higher concordance between predicted and actual rankings, indicating better model performance. **Figure 4.1.4** presents the concordance index validation results, highlighting the model's effectiveness in ranking interactions.




Figure 4.1.4 (Concordance Index on Validation Dataset)

5) MSE on Test Dataset:

To further evaluate the performance of our model, we calculated the mean squared error (MSE) on the test dataset at every 1000 iterations. This provides a granular view of how the model's predictive accuracy evolves during training. Monitoring the MSE on the test dataset helps us ensure that the model generalizes well to unseen data and does not overfit to the training dataset. **Figure 4.1.5** shows the MSE on the test dataset per 1000 iterations, highlighting the model's performance and stability over time.




Figure 4.1.5 (Mean Squared Error (MSE) on Test Dataset)

4.2 Analysis:

In this part, we delve into the comprehensive analysis of our dataset, visualizing both drug and target data to uncover patterns and insights that can guide our DTI model's development and evaluation. We utilized various visualization techniques to present the data in an informative and engaging manner, leveraging the power of Plotly for interactive plots and tables, word clouds for textual data representation, and pie charts for categorical data distribution.

1) Drug Data Visualization:

- Occurrence of Drugs:

We used Plotly to create interactive tables, As seen in **Figure 4.2.1**. And plots As seen in **Figure 4.2.2** showing the occurrence of different drugs in the dataset. this visualizations help identify the most frequently occurring drugs, providing insights into the dataset's composition.

Figure 4.2.1 (Drug Occurrence Counts)


Drug Occurrence Counts

Drug Number	Drug Name	Occurrence Count
1	staurosporine	378
3	Tandutinib	367
4	Sunitinib	367
5	Sorafenib	367
2	Midostaurin	367
6	Tozasertib	366
7	Lestaurtinib	365
8	Quizartinib	365
29	209410-46-8	363
24	Linifanib	363
25	Vandetanib	363
26	Erlotinib	363
28	722544-51-6	363
33	452105-23-6	363
30	345627-80-7	363
31	Gefitinib	363

Figure 4.2.2 (Occurrence of Drugs)

- Word Cloud for Drugs :

Occurrences of Drugs






Figure 4.2.4 (Drugs with 9 occurrence)




Figure 4.2.5 (Drugs with 362 occurrence)




Figure 4.2.7(Drugs with 10 occurrence)




Figure 4.2.6(Drugs with 99 occurrence)

2) Target Data Visualization:

- Occurrence of Targets and Sequences:

Similar to the drug data, Plotly was used to create tables as shown in **Figure 4.2.8** , **Figure 4.2.9** , and plots showing the occurrence of target proteins and their sequences, illustrated in **Figure 4.2.10**, **Figure 4.2.11**. This helps in identifying the most common targets and understanding the diversity of the target proteins in the dataset.

Target Name Occurrence Counts

Target Number	Target Name	Occurrence Count
1	Tyrosine-protein kinase Fer;	532
2	Eotaxin;	374
3	MAP kinase-interacting serine/threonine-protein kinase 1;	317
4	Serine/threonine-protein kinase B-raf {ECO:0000305};	300
5	5-hydroxytryptamine receptor 2C {ECO:0000305};	274
6	Retinoic acid receptor alpha;	255
7	Ephrin type-A receptor 8;	239
8	Beta-2 adrenergic receptor;	239
9	Cytochrome P450 130;	237
10	Type-1 angiotensin II receptor;	216
11	Regulatory protein E2 {ECO:0000255 HAMAP-Rule:MF_04001};	212
12	Envelope glycoprotein;	211
13	Tyrosine-protein kinase SYK;	192
14	Gamma-aminobutyric acid receptor subunit alpha-1;	184
15	Mitogen-activated protein kinase kinase kinase 10;	177
16	Cyclin-G-associated kinase {ECO:0000305};	172

Figure 4.2.8 (Target Name Occurrence Counts)

Organism Occurrence Counts

Organism Number	Organism	Occurrence Count
1	Homo sapiens (Human).	36715
2	Rattus norvegicus (Rat).	1580
3	Mus musculus (Mouse).	495
4	Cavia porcellus (Guinea pig).	423
5	Bos taurus (Bovine).	368
6	Mycobacterium tuberculosis (strain CDC 1551 / Oshkosh).	349
7	Mycobacterium tuberculosis (strain ATCC 25618 / H37Rv).	267
8	Oryctolagus cuniculus (Rabbit).	219
9	Zaire ebolavirus (strain Mayinga-76) (ZEBOV) (Zaire Ebola virus).	211
10	Escherichia coli (strain K12).	200
11	Gallus gallus (Chicken).	171
12	Human papillomavirus type 16.	157
13	Sus scrofa (Pig).	151
14	Human immunodeficiency virus type 1 group M subtype B (isolate HXB2)	149

Figure 4.2.9 (Organism Occurrence Counts)




Figure 4.2.10 (Occurrence of Target Names)






Figure 4.2.11 (Occurrence of Organisms)

- **Word Cloud for Targets and Organisms:**

Word clouds were generated for both target proteins as shown in **Figure 4.2.12**, and organisms as shown in **Figure 4.2.13** to visualize their frequency. These word clouds provide a quick overview of the most common targets and the organisms they are associated with, highlighting key entities in the dataset.



- Pie Charts for Target Occurrence Groups:

Pie charts were created to display the distribution of target occurrences across different groups. These charts, shown in **Figure 4.2.14**, **Figure 4.2.15**, **Figure 4.2.16** aids in understanding the relative abundance of various targets and identifying potential biases.




Figure 4.2.14 (Targets with 6 Occurrences)




Figure 4.2.15 (Targets with 11 Occurrences)




Figure 4.2.16 (Targets with 74 Occurrences)

3) Drug-Target Pairs Visualization:

- Pie Chart for Drug-Target Pairs :

A pie chart was created to show the Top 100 Drug-Target pairs by Total Y value in the dataset. This visualization helps in understanding the proportion of different pairs, providing insights into the interaction landscape within the dataset. This can be illustrated in **Figure 4.2.17, Figure 4.2.18, and Figure 4.2.19.**




Figure 4.2.17




Figure 4.2.18




Figure 4.2.19

4.3 limitation and challenges:

Developers in the bioinformatics field face several limitations and challenges due to the lack of data, particularly regarding Drug design projects such as drug-target interactions. Here we mention some of these challenges along with potential mitigations for each:

1) Incomplete Data:

- **Challenge:** Incomplete or sparse data can hinder the identification and validation of new drug targets, limiting the development of novel therapeutics.
- **Mitigation:** Encourage collaborative data sharing among research institutions and pharmaceutical companies. Public databases like PubChem and DrugBank can be enriched through community contributions.

2) Limited Diversity in Available Data:

- **Challenge:** Existing datasets may not cover a wide range of biological conditions or diverse genetic backgrounds, leading to biased models that don't generalize well.
- **Mitigation:** Promote and fund research that specifically aims to generate diverse and comprehensive datasets. Implement synthetic data generation techniques and use transfer learning to apply knowledge from well-studied domains to less-studied ones.

3) High Noise Levels and Inaccuracies:

- **Challenge:** Experimental data can be noisy or inaccurate due to technical limitations or human error, affecting the reliability of computational models.
- **Mitigation:** Develop and apply robust statistical methods and machine learning algorithms that can handle noisy data. Cross-validation and ensemble methods can help improve the reliability of predictions. Encourage the use of standardized protocols for data generation and reporting.

4) Ethical and Legal Constraints:

- **Challenge:** Privacy concerns and regulatory issues can limit access to valuable datasets, especially patient data.
- **Mitigation:** Develop privacy-preserving data analysis methods, such as federated learning, which allow model training without exposing raw data. Work within legal frameworks to ensure compliance while advocating for policies that balance data accessibility with privacy concerns.

5) Resource-Intensive Data Generation:

- **Challenge:** Generating high-quality, large-scale biological data is often resource-intensive and costly.
- **Mitigation:** Optimize existing experimental protocols to reduce costs and improve efficiency. Leverage computational techniques like "in silico" modeling and simulations to complement experimental data.

6) Difficulty in Data Integration:

- **Challenge:** Integrating data from various sources (e.g., genomic, proteomic, pharmacological) can be complex and computationally challenging.
- **Mitigation:** Use advanced data integration frameworks and platforms that support multi-omics data analysis. Develop scalable computational infrastructures and algorithms designed for large-scale data integration.

Chapter 5: Conclusion

5.1 Future work

Future work for this DTI (Drug-Target Interaction) project will focus on enhancing the accuracy of our AI models by integrating advanced deep learning techniques, such as transformers and graph neural networks. Additionally, incorporating structural and omics data will provide a more comprehensive understanding of drug-target interactions. We aim to expand the model's applicability to new drug formats and cross-species analysis. Moreover, integrating clinical trial data and exploring personalized medicine applications will ensure the model's relevance to real-world scenarios.

Future research should focus on methods that combine multiple similarities. Ensemble-based models that integrate various types of similarities are likely to yield more accurate results than those using a single similarity. For example, repurposed drugs have been identified via retrospective clinical analysis (e.g., reviewing side effects), pharmacological analysis, or serendipity. Given the successful examples of repurposing minoxidil from hypertension to hair loss, sildenafil from angina to erectile dysfunction, and thalidomide from morning sickness to multiple myeloma, current research aims to adopt a more comprehensive, systematic approach.

Significant efforts are being invested to identify molecular drivers of disease development, progression, and treatment resistance, providing numerous candidate targets for drugs across the spectrum of human diseases. However, many of these molecular drivers have no known drug targets. Thus, a comprehensive, improved methodology for predicting DTIs would be highly beneficial. Due to the challenges discussed in Section 4.1, the current knowledge of which cellular molecules are targeted by drugs is scarce and derived from various, sometimes complementary, sources.

Appropriate representation of datasets is crucial for gaining insights and effectiveness in DTI predictions. In Big Data applications, data is often sparse (mostly zeros) and partially missing.

Missing data imputation, especially in the context of sparse, noisy data, is therefore a central problem. To infer the missing entries from the known ones, reasonable assumptions should be made based on available data.

5.2 conclusion

Our drug-target interaction prediction model has achieved successful results in accurately predicting binding affinity between various drugs and target proteins. The primary objective of our approach is to estimate the interaction activity score by utilizing readily available structural information of compounds and the amino acid sequences of proteins. By leveraging these "in silico" methods, we aim to streamline the drug discovery process and provide valuable insights into drug efficacy and interactions, reducing the reliance on extensive experimental data.

The utilization of structural information and protein sequences allows us to make predictions based on the inherent characteristics of the compounds and target proteins. This approach circumvents the need for time-consuming and costly experimental assays, which are traditionally required to assess drug-target interactions. By leveraging computational techniques, we can expedite the screening and evaluation of potential drug candidates, significantly accelerating the drug discovery timeline.

The ability to estimate interaction activity scores using readily available data is particularly valuable in the early stages of drug development when limited experimental information is available. Our model provides researchers with a tool to prioritize drug candidates based on their predicted binding affinities, guiding further investigations and optimizing resource allocation.

Furthermore, our "in silico" approach offers a cost-effective alternative to experimental methods, potentially reducing the financial burden associated with drug discovery. By minimizing the reliance on extensive experimental data, we can optimize the allocation of research and development resources, increasing the efficiency of the drug discovery process.

By successfully predicting drug-target interactions, our model provides valuable insights into the efficacy and potential interactions of drugs. This information can guide researchers in selecting the most promising candidates for further development, potentially leading to the discovery of novel therapeutic options.

our drug-target interaction prediction model leverages readily available structural information and protein sequences to estimate interaction activity scores. This "in silico" approach streamlines the drug discovery process, reduces the need for extensive experimental data, and

provides valuable insights into drug efficacy and interactions. By enabling more efficient and informed decision-making, our model has the potential to accelerate the development of new drugs and improve patient outcomes.

REFERENCES

- 1) Bagherian, Maryam, et al. "Machine learning approaches and databases for prediction of drug–target interaction: a survey paper." *Briefings in bioinformatics* 22.1 (2021): 247-269.
- 2) Huang, Kexin, et al. "MolTrans: molecular interaction transformer for drug–target interaction prediction." *Bioinformatics* 37.6 (2021): 830-836.
- 3) Huang, Kexin, et al. "DeepPurpose: a deep learning library for drug–target interaction prediction." *Bioinformatics* 36.22-23 (2020): 5545-5547.
- 4) Zhao, Tianyi, et al. "Identifying drug–target interactions based on graph convolutional network and deep neural network." *Briefings in bioinformatics* 22.2 (2021): 2141-2150.
- 5) Li, Yang, et al. "Drug–target interaction predication via multi-channel graph neural networks." *Briefings in Bioinformatics* 23.1 (2022): bbab346.
- 6) Dehghan, Alireza, et al. "TripletMultiDTI: multimodal representation learning in drug-target interaction prediction with triplet loss function." *Expert Systems with Applications* 232 (2023): 120754.
- 7) Yue, Yang, and Shan He. "DTI-HeNE: a novel method for drug-target interaction prediction based on heterogeneous network embedding." *BMC bioinformatics* 22 (2021): 1-20.
- 8) Wang, Shuyu, et al. "GanDTI: A multi-task neural network for drug-target interaction prediction." *Computational Biology and Chemistry* 92 (2021): 107476.
- 9) Chen, Xing, et al. "Drug–target interaction prediction: databases, web servers and computational models." *Briefings in bioinformatics* 17.4 (2016): 696-712.
- 10) Wen, Ming, et al. "Deep-learning-based drug–target interaction prediction." *Journal of proteome research* 16.4 (2017): 1401-1409.
- 11) Luo, Yunan, et al. "A network integration approach for drug-target interaction prediction and computational drug repositioning from heterogeneous information." *Nature communications* 8.1 (2017): 573.
- 12) Wang, Lei, et al. "A computational-based method for predicting drug–target interactions by using stacked autoencoder deep neural network." *Journal of Computational Biology* 25.3 (2018): 361-373.
- 13) Öztürk, Hakime, Arzucan Özgür, and Elif Ozkirimli. "DeepDTA: deep drug–target binding affinity prediction." *Bioinformatics* 34.17 (2018): i821-i829.
- 14) Scott, Duncan E., et al. "Small molecules, big targets: drug discovery faces the protein–protein interaction challenge." *Nature Reviews Drug Discovery* 15.8 (2016): 533-550.
- 15) Sriram, Krishna, and Paul A. Insel. "G protein-coupled receptors as targets for approved drugs: how many targets and how many drugs?." *Molecular pharmacology* 93.4 (2018): 251-258.
- 16) Nguyen, Thin, et al. "GraphDTA: predicting drug–target binding affinity with graph neural networks." *Bioinformatics* 37.8 (2021): 1140-1147.
- 17) Ryu, Jae Yong, Hyun Uk Kim, and Sang Yup Lee. "Deep learning improves prediction of drug–drug and drug–food interactions." *Proceedings of the national academy of sciences* 115.18 (2018): E4304-E4311.
- 18) Bansal A, Srivastava PA, Singh TR. An integrative approach to develop computational pipeline for drug–target interaction network analysis. *Sci Rep* 2018;8(1):10238.
- 19) Santos, Rita, et al. "A comprehensive map of molecular drug targets." *Nature reviews Drug discovery* 16.1 (2017): 19-34.

- 20) Feng, Yanghe, Qi Wang, and Tengjiao Wang. "Drug target protein-protein interaction networks: a systematic perspective." *BioMed research international* 2017 (2017).
- 21) Mukkamala M, Hein M. Variants of RMSProp and Adagrad with logarithmic regret bounds In: Doina P, Yee Whye T, editors. Proceedings of the 34th International Conference on Machine Learning. vol. 70. Sydney: PMLR: 2017. p. 2545–53.
- 22) Chen B, Ding Y, Wild DJ. Assessing drug target association using semantic linked data. *PLoS Comput Biol* 2012;8(7):e1002574.
- 23) Wu Z, Cheng F, Li J, et al. SDTNBI: an integrated network and chemoinformatics tool for systematic prediction of drug–target interactions and drug repositioning. *Brief Bioinform* 2016;18(2):333–47.
- 24) Bansal A, Srivastava PA, Singh TR. An integrative approach to develop computational pipeline for drug–target interaction network analysis. *Sci Rep* 2018;8(1):10238.
- 25) Swann SL, Brown SP, Muchmore SW, et al. A unified, probabilistic framework for structure-and ligand-based virtual screening. *J Med Chem* 2011;54(5):1223–32.
- 26) Cheng T, Li Q, Wang Y, Bryant SH. Identifying compound target associations by combining bioactivity profile similarity search and public databases mining. *J Chem Inf Model* 2011;51(9):2440–8.
- 27) 28. Cheng F, Li W, Wu Z, et al. Prediction of polypharmacological profiles of drugs by the integration of chemical, side effect, and therapeutic space. *J Chem Inf Model* 2013;53(4):753–62.
- 28) van Westen GJ, Wegner JK, IJzerman AP, et al. Proteochemometric modeling as a tool to design selective compounds and for extrapolating to novel targets. *MedChemComm* 2011; 2(1):16–30.
- 29) Paricharak S, Cortés-Ciriano I, IJzerman AP, et al. Proteochemometric modelling coupled to in silico target prediction: an integrated approach for the simultaneous prediction of polypharmacology and binding affinity/potency of small molecules. *J Chem* 2015;7(1):15.
- 30) Yang M, Simm J, Lam CC, et al. Linking drug target and pathway activation for effective therapy using multi-task learning. *Sci Rep* 2018;8:8322.
- 31) Fu G, Ding Y, Seal A, et al. Predicting drug target interactions using meta-path based semantic network analysis. *BMC Bioinformatics* 2016;17(1):160.
- 32) González-Díaz H, Prado-Prado F, García-Mera X, et al. Mind-best: web server for drugs and target discovery; design, synthesis, and assay of MAO-B inhibitors and theoretical-experimental study of G3PDH protein from *Trichomonas gallinae*. *J Proteome Res* 2011;10(4):1698–718.
- 33) . Xie L, Evangelidis T, Xie L, et al. Drug discovery using chemical systems biology: weak inhibition of multiple kinases may contribute to the anti-cancer effect of nelfinavir. *PloS Comput Biol* 2011;7(4):e1002037.
- 34) Yang L, Wang K, Chen J, et al. Exploring off-targets and offsystems for adverse drug reactions via chemical-protein interactome–clozapine-induced agranulocytosis as a case study. *PLoS Comput Biol* 2011;7(3):e1002016.
- 35) . Li YY, Jones SJ. Drug repositioning for personalized medicine. *Genome Med* 2012;4(3):27.
- 36) Li YY, Jones SJ. Drug repositioning for personalized medicine. *Genome Med* 2012;4(3):27.
- 37) . Kinnings SL, Liu N, Buchmeier N, et al. Drug discovery using chemical systems biology: repositioning the safe medicine Comtan to treat multi-drug and extensively drug resistant tuberculosis. *PLoS Comput Biol* 2009;5(7):e1000423.

- 38) Xie L, Bourne PE. Detecting evolutionary relationships across existing fold space, using sequence orderindependent profile–profile alignments. *Proc Natl Acad Sci* 2008;105(14):5441–6.
- 39) Gottlieb A, Stein GY, Ruppin E, et al. Predict: a method for inferring novel drug indications with application to personalized medicine. *Mol Syst Biol* 2011;7(1):496.
- 40) Mahé P, Ueda N, Akutsu T, et al. Graph kernels for molecular structure- activity relationship analysis with support vector machines. *J Chem Inf Model* 2005;45(4):939–51.
- 41) Koutsoukas A, Lowe R, KalantarMotamedi Y, et al. In silico target predictions: defining a benchmarking data set and comparison of performance of the multiclass Naïve Bayes and Parzen–Rosenblatt window. *J Chem Inf Model* 2013; 53(8):1957–66.
- 42) Jamali AA, Ferdousi R, Razzaghi S, et al. Drugminer: comparative analysis of machine learning algorithms for prediction of potential druggable proteins. *Drug Discov Today* 2016;21(5):718–24.
- 43) Peón A, Naulaerts S, Ballester PJ. Predicting the reliability of drug-target interaction predictions with maximum coverage of target space. *Sci Rep* 2017;7(1):3820.
- 44) Fang J, Wu Z, Cai C, et al. Quantitative and systems pharmacology. 1. In silico prediction of drug–target interactions of natural products enables new targeted cancer therapy. *J Chem Inf Model* 2017;57(11):2657–71.
- 45) Liu Y, Qiu S, Zhang P, et al. Computational drug discovery with dyadic positive-unlabeled learning. In: *Proceedings of the 2017 SIAM International Conference on Data Mining University City, Philadelphia, USA. SIAM, 2017, 45–53.*
- 46) Kutalik Z, Beckmann JS, Bergmann S. A modular approach for integrative analysis of large-scale gene-expression and drug-response data. *Nat Biotechnol* 2008;26(5):531.
- 47) Chiang AP, Butte AJ. Systematic evaluation of drug–disease relationships to identify leads for novel drug uses. *Clin Pharmacol Ther* 2009;86(5):507–10.
- 48) Yang K, Bai H, Ouyang Q, et al. Finding multiple target optimal intervention in disease-related molecular network. *Mol Syst Biol* 2008;4(1):228.
- 49) . Emig D, Ivliev A, Pustovalova O, et al. Drug target prediction and repositioning using an integrated network-based approach. *PLoS One* 2013;8(4):e60618.
- 50) Tatonetti NP, Denny J, Murphy S, et al. Detecting drug interactions from adverse-event reports: interaction between paroxetine and pravastatin increases blood glucose levels. *Clin Pharmacol Ther* 2011;90(1):133–42.
- 51) Tatonetti NP, Fernald GH, Altman RB. A novel signal detection algorithm for identifying hidden drug–drug interactions in adverse event reports. *J Am Med Inform Assoc* 19(1): 79–85, 2011.
- 52) Zeng J, Li D, Wu Y, et al. An empirical study of features fusion techniques for protein–protein interaction prediction. *Curr Bioinform* 2016;11(1):4–12.
- 53) . Wei L, Xing P, Zeng J, et al. Improved prediction of protein–protein interactions using novel negative samples, features, and an ensemble classifier. *Artif Intell Med* 2017;83: 67–74.
- 54) . Kim S, Jin D, Lee H. Predicting drug–target interactions using drug–drug interactions. *PloS One* 2013;8(11):e80129.
- 55) Zhu S, Okuno Y, Tsujimoto G, et al. A probabilistic model for mining implicit ‘chemical compound–gene’ relations from literature. *Bioinformatics* 2005;21(suppl_2):ii245–51.
- 56) Lü L, Zhou T. Link prediction in complex networks: a survey. *Physica A* 2011;390(6):1150-70.
- 57) Adomavicius G, Tuzhilin A. Toward the next generation of recommender systems: a survey of the state-of-the-art and possible extensions. *IEEE Trans Knowl Data Eng* 2005;(6):734–49.

- 58)** Su X, Khoshgoftaar TM. A survey of collaborative filtering techniques. *Adv Artif Intell* 2009;2009.
- 59)** Nguyen J, Zhu M. Content-boosted matrix factorization techniques for recommender systems. *Stat Anal Data Min* 2013;6(4):286–301.
- 60)** Bock JR, Gough DA. Virtual screen for ligands of orphan protein-coupled receptors. *J Chem Inf Model* 2005;45(5):1402–14.
- 61)** Kuhn M, Campillos M, González P, et al. Large-scale prediction of drug–target relationships. *FEBS Lett* 2008; 582(8):1283–90.
- 62)** van Laarhoven, T. & Marchiori, E. Predicting drug-target interactions for new drug compounds using a weighted nearest neighbor profile. *PLoS ONE* 8, e66952 (2013).
- 63)** Wang, S. & Peng, J. Network-assisted target identification for haploinsufficiency and homozygous profiling screens. *PLoS Comput. Biol.* 13, e1005553 (2017).
- 64)** Campillos, M., Kuhn, M., Gavin, A.-C., Jensen, L. J. & Bork, P. Drug target identification using side-effect similarity. *Science* 321, 263–266 (2008).
- 65)** Mizutani, S., Pauwels, E., Stoven, V., Goto, S. & Yamanishi, Y. Relating drug–protein interaction network with drug side effects. *Bioinformatics* 28,i522–i528 (2012).
- 66)** Iorio, F. et al. Discovery of drug mode of action and drug repositioning from transcriptional responses. *Proc. Natl Acad. Sci. USA* 107, 14621–14626 (2010).
- 67)** Wang, W., Yang, S., Zhang, X. & Li, J. Drug repositioning by integrating target information through a heterogeneous network model. *Bioinformatics* 30,2923–2930 (2014).
- 68)** Wang, W., Yang, S., Zhang, X. & Li, J. Drug repositioning by integrating target information through a heterogeneous network model. *Bioinformatics* 30,2923–2930 (2014).
- 69)** Sirota, M. et al. Discovery and preclinical validation of drug indications using compendia of public gene expression data. *Sci. Transl. Med.* 3, 96ra77–96ra77(2011).
- 70)** Yang, F., Xu, J. & Zeng, J. in *Pacific Symposium on Biocomputing*. Pacific Symposium on Biocomputing, 148 (NIH Public Access, 2014).