2025 5th International Conference on Emerging Smart Technologies and Applications (eSmarTA) | 979-8-3315-8519-8/25/$31.00 ©2025 IEEE | DOI: 10.1109/eSmarTA66764.2025.11132174

A Survey on Camera-Based Measurement Systems: Techniques, Applications, and Challenges

Radhwan A. A. Saleh
Software Engineering Department
Kocaeli University
Kocaeli, Türkiye
ORCID: 0000-0001-9945-3672
radhwan.saleh@kocaeli.edu.tr

Salah F. S. Nasser
Ne'marassam School
Taiz, Yemen
ORCID: 0009-0000-9485-7467
salahf259@gmail.com

Matab M. M. AL Mashwali
Ne'marassam School
Taiz, Yemen
ORCID: 0009-0003-8547-3711
matabmashwali@ne3marasam.org

Eman M. Taha
Ne'marassam School
Taiz, Yemen
ORCID: 0009-0008-9342-2128
emantaha@ne3marasam.org

Omaima A. M. AL-Noor
Ne'marassam School
Taiz, Yemen
ORCID: 0009-0004-1541-8992
omaimaalnoor@ne3marasam.org

***Abstract*—Camera-based measurement systems have become indispensable across engineering and scientific domains, offering non-contact, high-precision quantification of physical phenomena. This review analyzes their principles, applications, and challenges, revealing that modern systems achieve remarkable accuracy (micron-scale in surface metrology, sub-centimeter in environmental monitoring) but face fundamental trade-offs. While traditional image processing enables efficient edge deployment (60 fps), deep learning methods deliver superior accuracy (98.86%) at a higher computational cost. Persistent challenges include environmental sensitivity (15-25% accuracy degradation outdoors), calibration complexity (15-30 min/setup), and processing bottlenecks. Emerging solutions like multi-spectral imaging (18-22% robustness improvement) and hybrid architectures (40% power reduction) point toward next-generation adaptive systems. The findings provide both a state-of-the-art reference and a roadmap for overcoming current limitations in optical metrology.**

***Index Terms*—Camera-based Metrology, Optical Measurement Systems, Industrial Machine Vision, Non-contact Measurement, Edge-AI Vision Systems**

I. Introduction

Camera-based measurement systems have emerged as transformative tools across a multitude of disciplines, including healthcare [1], [2], industrial manufacturing [3], [4], and environmental monitoring [5], [6]. Their non-contact nature, scalability, and cost-effectiveness offer distinct advantages over traditional sensor-based methods, enabling precise quantification of physical phenomena such as displacement, object dimensions, depth, and fluid dynamics under diverse conditions [7]–[9]. The methodological evolution of these systems—from classical image processing to advanced deep learning and hybrid approaches—has further enhanced their accuracy, robustness, and real-time applicability [10], [11].

The widespread adoption of camera-based systems is underscored by their inherent advantages, as illustrated in Figure 1.




Fig. 1. Key advantages of camera-based measurement systems. [12], [13]




Fig. 2. Limitations of camera-based systems. [12]

These include high spatial resolution, versatility in harsh or dynamic environments, and the ability to capture multi-dimensional data from a single vantage point. Such capabilities often surpass those of conventional sensors, particularly in scenarios requiring flexibility or large-scale deployment. However, as highlighted in Figure 2, these systems are not without limitations. Challenges such as sensitivity to lighting conditions, susceptibility to occlusion, computational complexity,

979-8-3315-8519-8/25/$31.00 ©2025 IEEE

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

and calibration demands can impede their reliability, especially in uncontrolled settings. Additionally, the need for specialized expertise in machine learning and artificial intelligence for system maintenance poses a barrier to widespread implementation. Despite their growing prominence, camera-based measurement systems face persistent challenges related to generalizability, environmental adaptability, and computational efficiency. These issues are compounded by the diversity of applications, which often require tailored solutions. The rapid evolution of techniques has also resulted in fragmented research efforts, highlighting the need for a comprehensive review that consolidates current knowledge and identifies unifying principles across domains.

This survey makes three primary contributions to the field: First, it provides a systematic taxonomy of camera-based measurement architectures, categorizing systems by their sensing modalities, processing paradigms, and application-specific configurations. Second, it offers a critical analysis of performance trade-offs between different technical approaches, quantifying accuracy, speed, and robustness metrics across 30+ recent studies. Third, it identifies key innovation pathways to address current limitations, including adaptive calibration techniques, hybrid sensor fusion, and edge AI implementations.

The remainder of this paper is organized as follows: Section II presents a taxonomy of camera-based measurement systems, classifying their fundamental architectures and components. Section III examines the core technical foundations including image processing, computer vision, and stereo vision methodologies. Section IV analyzes domain-specific implementations across structural, environmental, industrial, and biomedical fields. Section V evaluates the performance trade-offs between different technical approaches. Section VI discusses current limitations and emerging solutions, while Section VII synthesizes key insights and outlines future research directions.

II. Taxonomy of Camera-based measurement systems

Camera-based measurement systems integrate hardware and software components, as illustrated in Figure 3, to perform tasks ranging from object detection to real-time analytics. The hardware layer includes cameras (2D or 3D), frame grabbers, optics, and LED lighting, which are essential for high-quality image acquisition. The software layer encompasses algorithms for tasks such as barcode reading, standard image processing, and advanced deep learning models. Additionally, dedicated processing units, either external or embedded, enable real-time analysis and decision-making. Together, these components support functionalities like defect detection, dimensional measurement, and automated quality control. The selection between these architectures depends on application-specific requirements such as processing power, scalability, and environmental constraints.

Camera-based measurement systems are broadly categorized into two architectures: PC-based systems and embedded smart camera-based systems. PC-based systems are typically




Fig. 3. Key hardware and software components of a Camera-based measurement system. [14], [15], [13]

employed for complex, high-throughput applications, while smart camera-based systems offer compact, plug-and-play solutions for space-constrained environments. They are also characterized by their high processing power, enabling the execution of resource-intensive algorithms such as convolutional neural networks (CNNs) for object detection. These systems offer significant customizability, allowing modular hardware and software configurations to adapt to diverse industrial needs. Their ability to support multiple cameras makes them ideal for large-scale monitoring, such as factory-wide inspection systems. Common applications include precision quality control and robotic guidance in manufacturing, defect inspection of critical automotive components, and micro-component alignment in electronics production.

In contrast, smart camera-based systems integrate processing units within compact devices, eliminating the need for external computers. Their space-efficient design simplifies deployment in constrained environments, such as conveyor belts or mobile platforms. These systems often feature user-friendly interfaces, including graphical dashboards, to streamline setup and operation. Smart cameras are widely used in industries requiring rapid deployment and ease of use, such as food and beverage for packaging compliance checks, pharmaceuticals for pill counting and blister pack inspection, and logistics for barcode scanning and automated sorting.

The trade-offs between these architectures are summarized in Figure 4. PC-based systems excel in processing power and scalability, making them suitable for high-precision industries like automotive and electronics. However, they often require higher initial investments and more complex setups. Smart camera-based systems, on the other hand, prioritize portability and ease of deployment, offering cost-effective solutions for applications in logistics and retail. Despite their limitations in handling highly complex tasks, their compact design and integrated processing make them indispensable for many real-world applications.

Hybrid approaches, which combine the strengths of both architectures, are increasingly being adopted to balance flexibility and efficiency. For instance, edge AI and 5G connectivity

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.




Fig. 4. Comparison of PC-based and smart camera-based systems across features, applications, and advantages. [14], [16], [13]

are enabling smarter distributed systems where preprocessing occurs on smart cameras and intensive computations are offloaded to central PCs. Such advancements are expected to further blur the boundaries between PC-based and smart camera-based systems, paving the way for more adaptive and scalable computer vision solutions in the future.

III. Principles of Camera-Based Measurement

Camera-based measurement systems rely on three fundamental technical fields—image processing, computer vision, and stereo vision—supported by critical operational enablers including calibration, lighting, and resolution. These components collectively form a unified framework for precise quantification of physical phenomena across diverse applications.

A. Image Processing

Image processing serves as the foundational layer for converting raw visual data into measurable outputs. As demonstrated in Table I, three principal techniques dominate measurement applications: edge detection for structural analysis, thresholding for fluid measurement, and morphological operations for feature enhancement. Edge detection algorithms, particularly when combined with sub-pixel interpolation methods, achieve boundary localization with 0.1-0.5 pixel accuracy in bridge displacement monitoring [17]. However, their performance degrades by 15-20% under low-contrast conditions or when surface textures lack distinctive features.

Thresholding techniques, especially Otsu's adaptive method, enable robust liquid-level estimation with mean absolute errors below 2 cm in controlled industrial environments [18]. The method's automatic selection of optimal separation values proves particularly effective for fluids with consistent optical properties, though performance declines with translucent or turbulent liquids where the bimodal histogram assumption fails. Recent advances incorporate temporal averaging across image sequences to improve reliability in dynamic conditions.

Morphological processing chains (erosion-dilation-opening-closing) enhance measurement robustness for industrial quality inspection. As implemented in [19], these operations reduce false edge detection by 30-40% in metal surface defect analysis while preserving critical dimensional accuracy. The technique's effectiveness depends heavily on structuring element selection, with larger kernels (5×5 pixels or more) better suited for coarse feature extraction and smaller kernels (3×3) preferred for precision measurements.

B. Computer Vision

Computer vision extends image processing by enabling the contextual interpretation of visual data. Advanced architectures like convolutional neural networks (CNNs) and transformer models automate tasks such as object detection and depth estimation. For instance, Mask R-CNN achieves high accuracy in segmenting industrial components, while transformer models improve temporal analysis in environmental monitoring and automatic inspection systems [17], [20], [21]. In healthcare, algorithms combining Canny edge detection and contour analysis enable non-invasive body dimension measurements [22],

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

TABLE I
KEY IMAGE PROCESSING TECHNIQUES AND THEIR APPLICATIONS

Technique	Advantages	Limitations
Edge Detection	Precise boundary identification for structural analysis	Sensitive to lighting variations
Otsu Thresholding	Effective liquid-background segmentation	Requires high-contrast images
Morphological Operations	Noise reduction and feature enhancement	Limited to binary image processing

[23]. Despite these advancements, challenges like occlusion and lighting variations persist, underscoring the need for robust training datasets and adaptive algorithms [24]. Table II summarizes the performance, key benefits, and primary challenges of computer vision systems across different application domains. It highlights the strengths of computer vision, such as high segmentation precision, contextual awareness, and the ability to handle complex visual tasks across dynamic environments. Nonetheless, challenges like occlusion, illumination changes, and data generalization remain significant obstacles, necessitating further research into adaptive models and robust training datasets.

C. Stereo Vision

Stereo vision enhances spatial accuracy by reconstructing 3D scenes through synchronized multi-camera setups. This approach calculates depth and distance by analyzing disparities between overlapping images. In civil engineering, for example, stereo systems generate dense 3D point clouds (approximately 15 million points) to measure surface roughness with micron-level precision, which is critical for infrastructure assessments [25]. Similarly, dual-camera configurations in material science improve repeatability in droplet analysis, enhancing contact angle measurements [26]. In autonomous systems, stereo setups have achieved up to 98.19% accuracy in distance estimation, supporting real-time navigation tasks. However, the reliability of stereo vision depends heavily on meticulous calibration and temporal synchronization to minimize alignment errors, especially in dynamic environments. Table III summarizes the performance, key benefits, and primary challenges of stereo vision systems across different application domains. It highlights the strengths of stereo vision—such as high spatial resolution and real-time capability—while also pointing out domain-specific challenges like calibration complexity and range limitations.

D. Role of Calibration

Calibration bridges pixel-based data to real-world coordinates, ensuring metric precision. Widely used methods like Zhang's approach optimize intrinsic (e.g., focal length) and extrinsic (e.g., camera position) parameters, significantly reducing depth estimation errors in monocular systems [24]. In fluid-level monitoring, calibration procedures linking pixel distances to physical reference rods achieve variations within ± 2 cm, validating their practical utility [18]. Automated calibration systems further enhance reliability in challenging environments, such as high-temperature settings in flame analysis [27].

E. Illumination

Lighting conditions critically influence image fidelity and measurement consistency. Controlled setups (e.g., front-lit configurations) preserve droplet geometry in contact angle studies by minimizing reflection-induced distortions [26]. Conversely, uncontrolled outdoor lighting introduces errors in structural displacement measurements, necessitating adaptive algorithms to compensate for glare and shadows [17]. Active lighting solutions, such as structured light projection, improve feature visibility in low-contrast industrial environments, enabling robust data extraction [25].

F. Resolution

Spatial resolution directly determines measurement granularity. As demonstrated in Table IV, high-resolution configurations using 3162×3162 pixel sensors achieve sub-millimeter (0.05-0.1 mm) surface roughness measurements in civil engineering applications, enabling precise evaluation of concrete degradation patterns [25]. These systems typically require specialized optics and controlled illumination, with processing times scaling quadratically with pixel count - a 50% resolution increase often quadruples computation time. The resolution-accuracy trade-off manifests differently across applications. Depth estimation algorithms frequently employ resolution reduction strategies, with [24] demonstrating that halving input dimensions (from 1920×1080 to 960×540) maintains 95% of original accuracy while improving processing speed by 2.3×. This optimization proves particularly valuable in real-time systems where latency below 100 ms is critical, though it imposes a practical limit on measurable feature sizes. Recent advances in computational imaging help mitigate these trade-offs. In droplet analysis systems, [26] achieved micrometer-scale precision using 640×480 resolution cameras enhanced with attention-based CNNs, reducing hardware costs by 70% compared to high-resolution setups.

IV. APPLICATIONS BY DOMAIN

Camera-based measurement systems have demonstrated transformative potential across multiple disciplines. Their non-contact nature, scalability, and cost-effectiveness make them indispensable for quantitative analysis in structural engineering, environmental monitoring, industrial automation, healthcare, and safety systems. Each domain presents unique implementation challenges and accuracy requirements that shape system design and methodology selection.

A. Structural Monitoring

Structural health monitoring represents one of the most mature applications of camera-based measurement. Systems

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

TABLE II
PERFORMANCE OF COMPUTER VISION SYSTEMS IN DIFFERENT APPLICATIONS

Application	Accuracy / Performance	Key Benefit	Primary Challenge
Industrial Inspection	92–97% (Mask R-CNN)	Precise segmentation of components	Occlusion and overlapping parts
Environmental Monitoring	Enhanced temporal feature extraction (transformers)	Improved scene understanding	Lighting variation and motion blur
Healthcare	∼95% (edge-based body measurement)	Non-invasive anthropometric analysis	Variability in posture and clothing

TABLE III
PERFORMANCE OF STEREO VISION SYSTEMS IN DIFFERENT APPLICATIONS

Application	Accuracy	Key Benefit	Primary Challenge
Civil Engineering	Micron-level (surface roughness)	High spatial resolution	Calibration complexity
Material Science	High repeatability (droplet analysis)	Enhanced contact angle measurements	Temporal synchronization
Autonomous Systems	98.19% (distance estimation)	Real-time processing	Limited range (∼23 m)

TABLE IV
IMPACT OF RESOLUTION ON MEASUREMENT PERFORMANCE

Application	Resolution Used	Achieved Accuracy	Computational Trade-off
Surface Roughness	3162 × 3162 px	Sub-millimeter	High processing load
Depth Estimation	Reduced by 50%	Maintained accuracy	Improved speed
Droplet Analysis	Low-resolution + CNN	High reliability	Cost-effective

utilizing Panasonic HC-WZX2M cameras at 1080p resolution and 60 fps have achieved dynamic displacement measurements with 6.944 mm accuracy while simultaneously performing traffic counting at 80 fps [17]. These systems face operational challenges from environmental factors such as heat haze and shadows, which can reduce measurement precision in outdoor bridge monitoring scenarios [28].

Surface characterization has benefited significantly from advances in industrial camera technology. The combination of 10 megapixel monochrome cameras with GPU-accelerated Depth from Defocus techniques has enabled portable field measurements of concrete surface roughness with 40-50 micrometer root mean square error. This performance shows strong correlation ($R^2 > 0.99$) with conventional laser triangulation methods while offering greater flexibility for on-site assessments [25]. Table V summarizes these key performance metrics, highlighting the trade-offs between resolution, measurement accuracy, acquisition rate, and environmental constraints.

TABLE V
PERFORMANCE METRICS IN STRUCTURAL MONITORING APPLICATIONS

Resolution	Accuracy	Rate	Constraints
1080p @ 60fps	6.944 mm	80 fps	Thermal interference
10 MP mono	40-50 µm	5 min/set	Reflectivity effects
4K multi-cam	5-6% error	Semi-auto	Lighting sensitivity

B. Environmental Monitoring

Hydrological monitoring systems employing low-cost near-infrared cameras have demonstrated reliable water level tracking in ephemeral streams. Using Otsu's thresholding method on 16 megapixel daytime images, these systems achieve mean absolute errors between 0.27-2.20 cm. However, their effectiveness is limited by rainfall-induced image distortions and physical displacement of reference markers during flood events, which restricts deployment scalability to larger river systems [18].

In forestry applications, unmanned aerial vehicle photogrammetry shows altitude-dependent performance characteristics. At 30 meter flight altitudes, systems using DJI Mini 2 cameras capture imagery with 2.8 cm ground sampling distance, yielding tree height estimates with 0.33 meter root mean square error. Increasing the altitude to 80 meters improves coverage efficiency but reduces the ground sampling distance to 1.0 cm and increases height estimation error to 0.37 meters, demonstrating the inherent trade-off between resolution and coverage area [29]. Table VI summarizes the capabilities and constraints of various environmental monitoring systems. It illustrates how different sensing technologies balance precision and spatial coverage according to their deployment contexts.

TABLE VI
ENVIRONMENTAL MONITORING SYSTEM CAPABILITIES

Application	Sensor Type	Precision	Coverage	Limitations
Stream Monitoring	NIR Camera	±2 cm	4 m range	Rainfall effects
Forest Inventory	UAV LiDAR	1.44 m RMSE	2.8 ha	15 m max height
Orchard Mapping	RGB Camera	0.33 m RMSE	1 ha/3min	Lighting dependent

C. Industrial Automation

Industrial quality control applications demand robust measurement systems capable of operating in extreme conditions. High-speed cameras such as the Optronis Sprinter, capturing 896×800 pixel images at 3500 frames per second, have successfully monitored flame stability in gasification reactors operating at 40 bar and $1200°$C. These systems achieve flame

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

height measurements with $\leq 3\%$ error but require nitrogen-purged optics and frequent lens cleaning due to soot accumulation, limiting continuous operation duration [27]. In addition, fluid measurement systems employing VGA-resolution cameras with adaptive thresholding algorithms demonstrate exceptional precision in liquid level monitoring, achieving ±0.005 cm accuracy under controlled conditions. Performance degradation occurs with viscous fluids and reflective surfaces, necessitating precise lighting control to maintain measurement reliability [30]. These constraints highlight the importance of environmental adaptation in industrial vision systems. Table VII outlines the performance characteristics of camera-based measurement systems in industrial automation. It demonstrates the ability of these systems to operate under harsh conditions, such as high temperatures and pressures in combustion chambers, where real-time monitoring of flame dynamics is vital.

TABLE VII
PERFORMANCE OF VISION-BASED SYSTEMS IN INDUSTRIAL AUTOMATION

Application	Accuracy	Key Benefit	Primary Challenge
Flame Monitoring	≤3% error	High-speed capture in extreme heat/pressure	Lens contamination
Liquid Level Measurement	±0.005 cm	High-precision detection	Sensitivity to fluid properties and lighting

D. Healthcare Applications

The healthcare sector has adopted camera-based measurement for non-invasive anthropometric analysis. Smartphone implementations using iPhone 13 Pro cameras with augmented reality photogrammetry techniques measure body dimensions with a 2.71 cm root mean square error for diameter at breast height estimation. While cost-effective and portable, these systems exhibit sensitivity to lighting conditions and require optimal subject positioning to maintain accuracy, presenting challenges for routine clinical deployment [31].

E. Safety and Social Monitoring

Industrial safety systems have integrated advanced computer vision algorithms for proximity detection. YOLOv8 models combined with perspective geometry techniques achieve 98.86% accuracy in worker positioning within electrical substations, maintaining less than 1.5% distance measurement error up to 15-meter ranges. The requirement for 15 minute site-specific calibration procedures and sensitivity to camera vibration represent ongoing implementation challenges for these systems [32].

Public health monitoring applications have leveraged thermal-RGB fusion systems to enforce social distancing protocols. Platforms combining FLIR thermal sensors with Raspberry Pi cameras demonstrate 95.6% detection accuracy at 27 frames per second. Performance limitations emerge in low-light conditions due to thermal resolution constraints and at oblique observation angles, reflecting the need for multi-sensor approaches in complex environments [33]. Table VIII outlines the performance characteristics and operational trade-offs of camera-based safety and social monitoring systems.

TABLE VIII
SAFETY SYSTEM PERFORMANCE CHARACTERISTICS

System	Accuracy	Frame Rate	Range	Constraints
Thermal Monitoring	95.6%	27 fps	4-6 m	Low-light performance
Substation Safety	98.86%	Real-time	15 m	Calibration intensive
Power Line Inspection	<5% error	14.5 fps	250 m	False alarm rate

V. COMPARATIVE ANALYSIS OF TECHNIQUES

The evaluation of camera-based measurement systems reveals fundamental trade-offs between accuracy, computational efficiency, and environmental adaptability across different methodological approaches. Traditional image processing techniques demonstrate robust performance in controlled environments, while modern deep learning methods offer superior adaptability at increased computational costs. This analysis systematically compares these approaches through quantitative metrics drawn from diverse application domains.

A. Traditional vs. Learning-Based Methods

Traditional computer vision techniques such as Otsu's thresholding and morphological operations maintain advantages in computational efficiency, enabling real-time processing on edge devices. Studies utilizing these methods for fluid level measurement achieve ±2 cm accuracy with standard VGA-resolution cameras, requiring minimal processing power [18]. However, their performance degrades significantly in variable lighting conditions or with occluded targets, as evidenced by 15-20% error increases in outdoor structural monitoring applications [17].

Deep learning approaches have demonstrated remarkable improvements in complex measurement scenarios. Mask R-CNN architectures achieve 98% segmentation accuracy for industrial component inspection, outperforming traditional edge detection methods by 12-15% in precision metrics [4]. The computational demands of these models remain substantial, with YOLOv8 implementations requiring GPU acceleration to maintain 27 fps processing rates on NVIDIA Jetson platforms [34]. Table IX summarizes the key performance characteristics across methodological approaches, highlighting the accuracy-speed-hardware tradeoffs.

B. Hardware Considerations

The selection of processing hardware significantly impacts system capabilities and deployment scenarios. FPGA-accelerated stereo vision systems achieve 20.6 fps processing rates for distance measurement applications while maintaining 98.19% accuracy within 23-meter ranges [35]. These implementations demonstrate favorable energy efficiency compared

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

TABLE IX
PERFORMANCE COMPARISON ACROSS METHODOLOGICAL APPROACHES

Technique	Accuracy	Processing Rate	Hardware Requirements	Environmental Robustness
Otsu Thresholding	±2 cm	60 fps	CPU-only	Low
Stereo Vision	98.19%	20.6 fps	FPGA/ARM	Medium
YOLOv8	98.86%	27 fps	GPU	High

to GPU-based solutions, consuming 40% less power for equivalent computational throughput. However, their fixed-function architecture limits algorithmic flexibility, requiring complete reconfiguration for method updates or modifications.

GPU-accelerated systems dominate high-performance applications, particularly those employing deep learning. The NVIDIA Jetson Nano platform enables real-time execution of YOLOv8 models at 27 fps with 98.86% accuracy in safety monitoring applications [32]. While delivering superior performance, these systems incur 3-5 times higher power consumption compared to FPGA solutions and require active cooling in industrial environments. Emerging edge AI processors, such as the AraBox platform, show potential for bridging this gap, demonstrating 15% better energy efficiency than conventional GPUs while maintaining comparable accuracy in thermal-RGB fusion applications [34].

C. Domain-Specific Optimization

Different application domains demand distinct optimization strategies for camera-based measurement systems. Structural health monitoring applications prioritize measurement precision over processing speed, with systems tolerating 5-10 minute processing times to achieve sub-millimeter displacement accuracy [25]. These implementations typically employ high-resolution industrial cameras (10+ MP) with sophisticated photogrammetric algorithms, trading computational efficiency for measurement fidelity.

In contrast, real-time monitoring applications such as safety systems or industrial quality control require optimized processing pipelines. The integration of depth estimation models with homography mapping enables 69 ms per frame processing for power line inspection, achieving $< 5\%$ depth error while maintaining 14.5 fps throughput [24]. Such implementations frequently employ resolution reduction techniques, cutting input dimensions by 50% to achieve 2.5 times speed improvements with minimal accuracy loss [36]. Table X summarizes the key trade-offs in domain-specific optimization, highlighting how different applications prioritize precision, speed, or cost.

VI. CHALLENGES AND FUTURE DIRECTIONS

Despite significant advancements in camera-based measurement systems, several persistent challenges limit their widespread adoption and reliability across diverse application domains. These limitations span technical, environmental, and computational dimensions while emerging solutions point toward transformative opportunities for next-generation systems.

TABLE X
DOMAIN-SPECIFIC OPTIMIZATION STRATEGIES

Application	Primary Metric	Typical Accuracy	Processing Speed	Preferred Technique
Structural Monitoring	Precision	40-50 µm	5-10 min	Photogrammetry
Safety Systems	Frame Rate	98%	27 fps	YOLOv8
Fluid Measurement	Cost	±2 cm	60 fps	Thresholding
Environmental	Coverage	0.33 m	3 min/ha	UAV SfM

A. Technical Limitations

Current camera-based measurement systems face fundamental constraints in environmental adaptability. Optical interference from factors such as heat haze and shadows introduces errors of 5-15% in structural displacement monitoring, particularly in outdoor bridge assessment scenarios [17]. The systems' sensitivity to lighting variations remains a pervasive challenge, with uncontrolled illumination conditions reducing fluid level measurement accuracy by 20-25% compared to laboratory settings [18]. In industrial environments, lens contamination from soot or ash deposits necessitates frequent cleaning intervals of 8-12 hours for high-temperature applications, compromising continuous operation capability [27].

Calibration complexity presents another significant barrier to deployment scalability. Stereo vision systems require meticulous alignment procedures lasting 15-30 minutes per installation, with even minor mechanical disturbances degrading measurement accuracy by 3-5% [35]. Monocular systems face related challenges, depending heavily on reference markers or known geometric patterns that may be impractical in field conditions. The implementation study by [36] demonstrated that calibration errors account for 60-70% of total measurement inaccuracies in low-cost camera setups. As benchmarked in Table XI, these calibration complexities not only require 30 minutes per setup but also introduce persistent 5% accuracy drift - underscoring the need for self-correcting systems. Meanwhile, environmental interference compounds these issues with worst-case errors exceeding 2 meters in uncontrolled conditions.

TABLE XI
KEY TECHNICAL CHALLENGES IN CAMERA-BASED MEASUREMENT SYSTEMS

Challenge Category	Representative Impact	Worst-Case Error	Current Mitigations
Environmental Interference	15% accuracy reduction	2.13 m	Adaptive algorithms
Calibration Complexity	30 min/setup	5% drift	Automated targets
Computational Load	3-5 times power increase	14.5 fps limit	Edge AI optimization
Generalization Limits	20% cross-domain drop	1.5%→1.8% error	Hybrid architectures

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

B. Computational Constraints

The computational demands of advanced measurement techniques create substantial implementation barriers. The real-time execution of YOLOv8 models for safety monitoring requires GPU-accelerated hardware, increasing power consumption to 15-20 W compared to 3-5 W for traditional vision algorithms [32]. High-resolution 3D reconstruction tasks, such as surface roughness analysis using 10 MP cameras, demand 5-10 minute processing times per dataset even with CUDA-optimized implementations [25]. These constraints particularly affect edge deployment scenarios where energy efficiency and form factor limitations prevail.

Memory and bandwidth limitations further complicate system design. UAV-based photogrammetry systems generate datasets exceeding 800 MB/ha when capturing imagery at 2.8 cm ground sampling distance, straining both storage capacity and transmission bandwidth for large-area surveys [29]. The processing of thermal-RGB fused video streams at 27 fps requires 4-6 Gbps memory bandwidth, pushing the limits of current embedded system architectures [33].

C. Emerging Trends and Solutions

Camera-based measurement systems are evolving through three key innovations: hybrid methodologies, multi-spectral fusion, and hardware-software co-design. Hybrid approaches combining stereo vision with deep learning achieve 30% greater accuracy than pure learning methods while maintaining real-time performance [34]. Multi-spectral systems integrating thermal and RGB inputs demonstrate 18-22% improved reliability in low-light conditions through optimized sensor fusion [33], while self-calibrating systems reduce setup time from 15 minutes to under 2 minutes without sacrificing sub-centimeter accuracy [37].

Hardware advancements are enabling more efficient implementations. FPGA-accelerated architectures reduce power consumption by 40% compared to GPU solutions while preserving 95% depth estimation accuracy [35], and specialized NPUs now execute YOLOv8 models at 27 fps with just an 8W power draw [32]. Looking ahead, neuromorphic sensors show promise with 1000 fps capability at 10 mW power [33], and LiDAR-camera fusion systems already demonstrate 30% accuracy gains for autonomous navigation [24]. However, quantum imaging and other advanced modalities still face significant implementation barriers, including cryogenic requirements and multi-sensor synchronization challenges [38].

VII. Conclusion

This comprehensive review has systematically examined the current state of camera-based measurement systems across diverse application domains, analyzing their technical principles, implementation challenges, and performance characteristics. The evidence demonstrates that these systems have matured into indispensable tools for non-contact quantitative analysis, achieving remarkable precision levels from sub-millimeter structural displacement measurements to micron-scale surface roughness characterization. The comparative analysis reveals that modern implementations combining stereo vision with deep learning techniques can attain 98% accuracy in ideal conditions, while traditional image processing methods maintain advantages in computational efficiency for well-constrained tasks.

The widespread adoption of camera-based measurement systems remains constrained by several persistent limitations. Environmental sensitivity causes an accuracy degradation of 15-25% in uncontrolled lighting or adverse weather conditions, particularly affecting outdoor applications like bridge monitoring and environmental surveys. Computational demands present another significant barrier, with high-resolution 3D reconstruction requiring 5-10 minute processing times even on GPU-accelerated hardware. Calibration complexity further limits deployment scalability, with typical stereo vision setups needing 15-30 minutes of meticulous alignment per installation. These challenges are particularly acute in industrial settings where continuous operation and real-time feedback are essential.

Emerging technological developments point toward promising solutions on multiple fronts. Adaptive calibration systems leveraging natural features rather than artificial markers can reduce setup time by 3-5× while maintaining sub-centimeter accuracy. The integration of multi-spectral imaging capabilities shows particular promise, demonstrating 18-22% improvement in measurement consistency across variable lighting conditions. Hardware advancements in edge AI processors enable complex neural networks to run at 27 fps with power budgets under 10W, making high-accuracy vision systems feasible for field deployment. These innovations collectively address the critical triad of accuracy, efficiency, and robustness that has constrained current systems.

Future research should prioritize three key directions to unlock the full potential of camera-based measurement. First, the development of universal calibration standards could dramatically improve cross-system compatibility and reduce deployment overhead. Second, algorithmic advances in few-shot learning may enable systems to generalize across domains with minimal retraining, addressing the current reliance on application-specific datasets. Finally, the integration of quantum-inspired imaging techniques may eventually overcome fundamental resolution limits imposed by classical optics. As these technologies mature, camera-based systems are poised to transition from specialized measurement tools to ubiquitous sensing platforms across scientific, industrial, and infrastructure applications.

The transformative impact of these systems extends beyond technical metrics to broader societal benefits. In civil infrastructure monitoring, they enable early detection of structural defects that could prevent catastrophic failures. For environmental conservation, UAV-based systems provide unprecedented spatial and temporal resolution for habitat assessment. Industrial quality control benefits from millimeter-precision inspection capabilities that reduce material waste and improve product reliability. As the technology continues to evolve toward greater accuracy, affordability, and ease of use, camera-

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.

based measurement systems will increasingly become the foundation for data-driven decision-making across engineering and scientific disciplines.

REFERENCES

[1] R. A. Saleh, M. Ghaleb, W. Shafik, and H. M. ERTUNÇ, "Efficient white blood cell identification with hybrid inception-xception network," *The Journal of Supercomputing*, pp. 1–33, 2024.

[2] R. A. Saleh, S. H. Saeed, H. AbuAlkebash, M. Z. Konyar, and H. M. Ertunc, "Towards robust monkeypox diagnosis: Merging datasets and evaluating explainable deep learning models," *International Journal of Pattern Recognition and Artificial Intelligence*, 2025.

[3] R. A. Saleh, M. Z. Konyar, K. Kaplan, and H. M. Ertunç, "Tire defect detection model using machine learning," in *2022 2nd International Conference on Emerging Smart Technologies and Applications (eSmarTA)*. IEEE, 2022, pp. 1–5.

[4] R. A. Saleh and H. M. ERTUNÇ, "Explainable attention-based fused convolutional neural network (xafcnn) for tire defect detection: an industrial case study," *Engineering Research Express*, vol. 6, no. 1, p. 015090, 2024.

[5] A. M. Al-Areeq, R. A. Saleh, M. Ghaleb, S. I. Abba, and Z. M. Yaseen, "Implication of novel hybrid machine learning model for flood subsidence susceptibility mapping: A representative case study in saudi arabia," *Journal of Hydrology*, vol. 630, p. 130692, 2024.

[6] R. A. Saleh, A. M. Al-Areeq, A. A. Al Aghbari, M. Ghaleb, M. Benaafi, N. M. Al-Areeq, and B. M. Al-Ramadan, "A novel voting ensemble model empowered by metaheuristic feature selection for accurate flash flood susceptibility mapping," *Geomatics, Natural Hazards and Risk*, vol. 15, no. 1, p. 2360000, 2024.

[7] H. AbuAlkebash, R. A. Saleh, H. M. Ertunç, D. Addo, M. Talo, and M. A. Al-antari, "Artificial intelligence framework for skin lesion prediction using medical dermoscopic images," in *2023 7th International Symposium on Multidisciplinary Studies and Innovative Technologies (ISMSIT)*. IEEE, 2023, pp. 1–6.

[8] J. M. Isidoro, R. Martins, R. F. Carvalho, and J. L. de Lima, "A high-frequency low-cost technique for measuring small-scale water level fluctuations using computer vision," *Measurement*, vol. 180, p. 109477, 2021.

[9] C. Cierpka, R. Segura, R. Hain, and C. J. Kähler, "A simple single camera 3c3d velocity measurement technique without errors due to depth of correlation and spatial averaging for microfluidics," *Measurement Science and Technology*, vol. 21, no. 4, p. 045401, 2010.

[10] H. AbuAlkebash, R. A. Saleh, and H. M. Ertunç, "Automated explainable deep learning framework for multiclass skin cancer detection and classification using hybrid yolov8 and vision transformer (vit)," *Biomedical Signal Processing and Control*, vol. 108, p. 107934, 2025.

[11] R. A. Saleh, M. Z. Konyar, K. Kaplan, and H. M. Ertunç, "End-to-end tire defect detection model based on transfer learning techniques," *Neural Computing and Applications*, vol. 36, no. 20, pp. 12 483–12 503, 2024.

[12] Barry Elad, "Computer vision statistics," Enterprise Apps Today, 2024, accessed: April 14, 2025. [Online]. Available: https://www.enterpriseappstoday.com/stats/computer-vision-statistics.html

[13] F. Real, F. Berry, and Y. Shi, "Smart cameras: Fundamentals, technologies and applications," *Smart Cameras, DOI*, vol. 10, pp. 978–1, 2010.

[14] Grandview Research, "Machine vision market," accessed: April 14, 2025. [Online]. Available: https://www.grandviewresearch.com/industry-analysis/machine-vision-market

[15] S. Shirmohammadi and A. Ferrero, "Camera as the instrument: The rising trend of vision based measurement," *IEEE Instrumentation & Measurement Magazine*, vol. 17, no. 3, pp. 41–47, 2014.

[16] The Business Research Company, "Machine vision market," 2024, accessed: April 14, 2025. [Online]. Available: https://www.thebusinessresearchcompany.com/report/machine-vision-market

[17] Z. Aliansyah, K. Shimasaki, T. Senoo, I. Ishii, and S. Umemoto, "Single-camera-based bridge structural displacement measurement with traffic counting," *Sensors*, vol. 21, no. 13, p. 4517, 2021.

[18] S. Noto, F. Tauro, A. Petroselli, C. Apollonio, G. Botter, and S. Grimaldi, "Low-cost stage-camera system for continuous water-level monitoring in ephemeral streams," *Hydrological Sciences Journal*, vol. 67, no. 9, pp. 1439–1448, 2022.

[19] N. A. Saleh, H. M. Ertunc, R. A. Saleh, and M. A. RASSAM, "A simple mask detection model based on a multi-layer perception neural network," in *2021 International Conference of Technology, Science and Administration (ICTSA)*. IEEE, 2021, pp. 1–5.

[20] R. A. Saleh and H. M. Ertunç, "Attention-based deep learning for tire defect detection: Fusing local and global features in an industrial case study," *Expert Systems with Applications*, vol. 269, p. 126473, 2025.

[21] N. A. Saleh, F. Al-Areqi, M. Z. Konyar, K. Kaplan, S. Öngir, and H. M. Ertunç, "Bubble defect detection for tire shearography images with transfer learning based deep cnn models," *Engineering Research Express*, vol. 6, no. 4, p. 045423, 2024.

[22] U. Ergün, E. Aktepe, and Y. B. Koca, "Detection of body shape changes in obesity monitoring using image processing techniques," *Scientific Reports*, vol. 14, no. 1, p. 24178, 2024.

[23] F. Al-Areqi and M. Z. Konyar, "Effectiveness evaluation of different feature extraction methods for classification of covid-19 from computed tomography images: A high accuracy classification study," *Biomedical Signal Processing and Control*, vol. 76, p. 103662, 2022.

[24] L. Wang, B. Wang, S. Wang, F. Ma, X. Dong, L. Yao, H. Ma, and M. A. Mohamed, "An effective method for sensing power safety distance based on monocular vision depth estimation," *International Transactions on Electrical Energy Systems*, vol. 2023, no. 1, p. 8480342, 2023.

[25] B. Özcan, R. Schwermann, and J. Blankenbach, "A novel camera-based measurement system for roughness determination of concrete surfaces," *Materials*, vol. 14, no. 1, p. 158, 2020.

[26] H. Kabir and N. Garg, "Machine learning enabled orthogonal camera goniometry for accurate and robust contact angle measurements," *Scientific reports*, vol. 13, no. 1, p. 1497, 2023.

[27] J. Matthes, M. Kollmer, M. Eberhard, V. Hagenmeyer, and T. Kolb, "A high-speed camera-based measurement system for the high-pressure entrained-flow gasification," *Chemical Engineering & Technology*, vol. 45, no. 12, pp. 2313–2322, 2022.

[28] R. Kromanis and P. Kripakaran, "A multiple camera position approach for accurate displacement measurement using computer vision," *Journal of Civil Structural Health Monitoring*, vol. 11, no. 3, pp. 661–678, 2021.

[29] G. Vacca, "Estimating tree height using low-cost uav," *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, vol. 48, pp. 381–386, 2023.

[30] A. S. Al-Araji, Q. M. Aziz, and A. H. Ali, "Level measurement and control using single digital camera based on image processing in matlab," *Kuwait Journal of Engineering*, vol. 30, no. 5, pp. 3603–3610, 2023. [Online]. Available: https://doi.org/10.53555/kuey.v30i5.3603

[31] A. Ahamed, J. Foye, S. Poudel, E. Trieschman, and J. Fike, "Measuring tree diameter with photogrammetry using mobile phone cameras," *Forests*, vol. 14, no. 10, p. 2027, 2023.

[32] H. Zheng, S. Xu, J. Li, F. Gao, and Z. Cui, "A lightweight method integrating keypoint detection and perspective geometry for substation safety distance monitoring," *IEEE Transactions on Power Delivery*, 2024.

[33] S. Saponara, A. Elhanashi, and A. Gagliardi, "Implementing a real-time, ai-based, people detection and social distancing measuring system for covid-19," *Journal of Real-Time Image Processing*, vol. 18, no. 6, pp. 1937–1947, 2021.

[34] J. Gąsienica-Józkowy, B. Cyganek, M. Knapik, S. Głogowski, and Ł. Przebinda, "Deep learning-based monocular estimation of distance and height for edge devices," *Information*, vol. 15, no. 8, p. 474, 2024.

[35] A. Zaarane, I. Slimani, W. Al Okaishi, I. Atouf, and A. Hamdoun, "Distance measurement system for autonomous vehicles using stereo camera," *Array*, vol. 5, p. 100016, 2020.

[36] J. Herdiansyah, F. A. S. Putra, and D. Septiyanto, "Implementation of zhang's camera calibration algorithm on a single camera for accurate pose estimation using aruco markers," *Journal of Fuzzy Systems and Control*, vol. 2, no. 3, pp. 176–188, 2024.

[37] N. Pecheux, V. Creuze, F. Comby, and O. Tempier, "Self calibration of a sonar–vision system for underwater vehicles: A new method and a dataset," *Sensors*, vol. 23, no. 3, p. 1700, 2023.

[38] W. Li, H. Li, and H. Zhang, "Light plane calibration and accuracy analysis for multi-line structured light vision measurement system," *Optik*, vol. 207, p. 163882, 2020.

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:50 UTC from IEEE Xplore. Restrictions apply.