2025 5th International Conference on Emerging Smart Technologies and Applications (eSmarTA) | 979-8-3315-8519-8/25/$31.00 ©2025 IEEE | DOI: 10.1109/eSmarTA66764.2025.11131700

Advances in Error Compensation for Robotic Manipulators: A Systematic Review from Geometric Calibration to AI-Driven Hybrid Control

Radhwan A. A. Saleh
Software Engineering Department
Kocaeli University, Kocaeli, Türkiye
ORCID: 0000-0001-9945-3672
radhwan.saleh@kocaeli.edu.tr

Salah F. S. Nasser
Ne'marassam School
Taiz, Yemen
ORCID: 0009-0000-9485-7467
salahf259@gmail.com

Taiba S. M. Abdullah
Faculty of Engineering and Information Technology
Taiz University, Taiz, Yemen
ORCID: 0009-0004-9525-3939
taibaseddeq24@gmail.com

***Abstract*—This paper presents a comprehensive review of error compensation techniques for robotic manipulators, addressing the critical need for enhanced precision in modern industrial applications. It establishes a systematic taxonomy of error sources that categorizes geometric and non-geometric inaccuracies based on their physical origins and temporal characteristics. The review critically analyzes three dominant compensation paradigms: physics-based modeling approaches that leverage rigorous kinematic formulations, data-driven machine learning techniques capable of capturing complex nonlinear error patterns, and hybrid methodologies that combine their complementary strengths. Through extensive comparative evaluation, it is demonstrated that hybrid physics-ML approaches achieve superior performance in dynamic industrial environments, with certain implementations reducing positioning errors by up to 97%. The analysis reveals fundamental trade-offs between theoretical precision, computational efficiency, and practical implementation across different methodologies. Emerging research directions, including digital twin-enabled adaptive compensation and edge-cloud collaborative architectures, are identified as promising solutions to current limitations. This review provides both a theoretical framework for understanding robotic error phenomena and practical guidelines for implementing compensation systems in industrial settings, serving as a valuable reference for researchers and practitioners advancing the state-of-the-art in robotic precision.**

***Index Terms*—Robotic manipulators error compensation, Robots relocation methods, Real-time error compensation, Self-correcting manipulators**

I. Introduction

The industrial robotics sector has undergone a paradigm shift in recent years, propelled by advancements in automation, artificial intelligence, and cyber-physical systems. As illustrated in Figure 1, the integration of robotic manipulators into smart manufacturing environments has elevated their role from mere automation tools to critical enablers of high-precision, adaptive production systems. With global deployments exceeding 4500 units annually [1], the demand for sub-millimeter accuracy in robotic operations has become a non-negotiable requirement across industries such as aerospace, semiconductor manufacturing, and precision assembly [2], [3]. This escalating demand, however, exposes a fundamental challenge: the inherent discrepancy between idealized kinematic models and the complex, dynamic realities of physical robotic systems. Emerging standards, including ISO 8373 (Figure 2), now explicitly mandate stringent precision thresholds, compelling researchers and practitioners to confront the limitations of conventional error compensation approaches [2]. Precision degradation in robotic manipulators stems from a confluence of interdependent error sources, including geometric misalignments [4], thermal deformation [5], structural deformations [6], and sensor nonlinearities [7]. These errors exhibit complex spatiotemporal behaviors, often manifesting as nonlinear couplings that defy simplistic compensation strategies. For instance, thermally induced joint expansions- deformation may interact unpredictably with payload-induced elastic deformations [6], [8], while sensor quantization effects can obscure high-frequency vibrational modes [6], [8], [9].

The industrial imperative for scalable, maintainable systems further complicates this landscape, as sophisticated compensation algorithms must balance computational tractability with real-time performance under dynamic operating conditions [7], [9], [10]. This tension is particularly acute in data-driven and hybrid methodologies, where model interpretability and industrial robustness remain persistent challenges [2], [11], [12].

This review article makes three significant contributions to the field of robotic error compensation. First, it presents a comprehensive taxonomy that systematically classifies error sources based on their physical origins, temporal characteristics, and propagation mechanisms through the kinematic chain. Second, it provides a critical analysis of contemporary compensation methodologies, evaluating their performance across key metrics, including accuracy improvement, computational efficiency, and industrial applicability. It also reveals fundamental trade-offs between physics-based, data-driven, and hybrid approaches that guide method selection for specific operational scenarios. Third, it identifies emerging research directions at the intersection of digital twin technologies, edge-cloud architectures, and physics-informed machine learning

979-8-3315-8519-8/25/$31.00 ©2025 IEEE

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

that promise to overcome current limitations in adaptive compensation. These insights collectively advance the theoretical understanding of robotic error phenomena while providing practical guidance for implementing compensation systems in industrial settings.

The article is structured to provide both foundational knowledge and cutting-edge insights for researchers and practitioners. Section II establishes a unified classification framework for robotic errors based on their physical origins and temporal characteristics. Section III presents a rigorous comparative analysis of compensation techniques, evaluating their theoretical foundations and industrial applicability. Section IV examines the performance trade-offs between different methodologies, while Section V outlines promising research directions at the intersection of robotics, machine learning, and industrial IoT.




Fig. 1. Integration of robotic manipulators in a smart manufacturing ecosystem, highlighting real-time data flows and adaptive control loops. [13]




Fig. 2. Key precision and performance metrics mandated by ISO 8373 for industrial robotic systems. [13]

II. Taxonomy of Robotic Manipulator Errors

Robotic manipulator errors can be systematically classified into two fundamental categories based on their physical origins and temporal characteristics, as illustrated in Figure 3. Geometric errors stem from inherent imperfections in the mechanical structure, while non-geometric errors arise from dynamic operational conditions and environmental factors. This comprehensive taxonomy provides a framework for understanding how different error sources contribute to overall positioning inaccuracies, where geometric errors typically dominate static performance and non-geometric errors primarily affect dynamic operation. The interaction between these error types often creates complex nonlinear behaviors that challenge traditional compensation approaches, particularly in high-precision applications where sub-millimeter accuracy is required.

A. Geometric Errors

Geometric errors originate from deviations in the physical dimensions and alignment of robotic components, fundamentally affecting the kinematic chain's accuracy. These errors manifest in three primary forms:

Manufacturing defects include dimensional inaccuracies in link lengths, joint offsets, and axis misalignments that occur during component production [6], [14]. Even minor deviations at the manufacturing stage can propagate through the kinematic chain, resulting in significant end-effector positioning errors [6]. For instance, errors in links can accumulate increasing inaccuracies at the tool center point for serial manipulators with long kinematic chains [6], [15].

Assembly and installation errors introduce additional geometric inaccuracies through improper alignment of transmission mechanisms and discrepancies between controller parameters and physical implementations. Common examples include bearing misalignments, improper gear meshing, and incorrect mounting of position sensors. These errors are particularly challenging because they often combine with manufacturing defects to create complex error patterns that vary across the workspace [16].

Wear-induced geometric errors develop progressively over the robot's operational lifetime, including abrasive wear in joints, gear tooth deformation, and bearing clearance growth. The temporal nature of these errors necessitates periodic recalibration, especially in applications involving high loads or repetitive motions [6], [16], [17].

The cumulative effect of geometric errors can be quantified through the positioning accuracy metric defined in ISO 9283 [18]:

$$p_i = \|X_i^m - X_i^t\| \tag{1}$$

where X_i^m represents the measured position and X_i^t denotes the target position. The average positioning error across multiple measurements provides a comprehensive assessment of geometric accuracy [19]:

$$\bar{P} = \frac{1}{n}\sum_{i=1}^{n} \|\mathbf{p}_i^m - \mathbf{p}_i^t\| \tag{2}$$

where $\|.\|$ describes the Euclidean norm, p_i^m denotes the measured end-effector position at pose i, p_i^t refers to the

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.




Fig. 3. Taxonomy of Robotic Manipulator Arm Error Sources

TABLE I
TAXONOMY OF ERROR SOURCES IN ROBOTIC MANIPULATORS

Lifecycle Phase	Error Dynamics	Error Category	Primary Source Description
Manufacturing	Static	Geometric Error	Dimensional deviations introduced during fabrication, such as inaccurate link lengths, joint offsets, and axis misalignments, which directly affect the manipulator's kinematic model.
Assembly & Installation	Dynamic	Geometric Error	Errors resulting from improper alignment of transmission components, mounting inaccuracies, or discrepancies between controller parameters and actual robot configurations.
Operational Wear	Time-Dependent	Geometric Error	Progressive structural degradation due to continuous usage, including joint backlash development, gear tooth deformation, and increasing bearing clearances, requiring periodic recalibration.
In-Motion Operation	Configuration-Dependent	Non-Geometric	Deflections caused by joint flexibility, link deformation, and transmission elasticity, especially under variable payloads or near singular configurations.
Actuation and Control	Dynamic	Non-Geometric	Nonlinear effects including backlash, hysteresis, and gear mesh irregularities, which generate position-dependent dead zones and asymmetric motion behavior.
Environmental Interaction	Time-Varying	Non-Geometric	Expansion or contraction of structural components due to temperature fluctuations, leading to position drift and altered material properties.
High-Speed Motion	Velocity-Dependent	Non-Geometric	Stick-slip motion, varying frictional torques, and wear-induced surface changes that result in inconsistent response across joint trajectories.
Long-Term Operation	Progressive	Non-Geometric	Changes in material stiffness, fatigue behavior, or lubrication properties over time, affecting both geometric precision and dynamic stability.

targeted position and n is the number of measurements taken in a given experiment.

B. Non-Geometric Errors

Non-geometric errors encompass dynamic phenomena that traditional kinematic models typically neglect, presenting complex challenges for error compensation. Structural compliance represents a major category, comprising joint flexibility, link deformation, and transmission system elasticity. These effects become particularly significant under variable payloads, where the combined stiffness of the manipulator structure and drive systems determines the magnitude of compliance-induced errors [16].

The end-effector deflection due to structural compliance can be modeled through the Jacobian matrix [16]:

$$\Delta P_C = J_\theta \Delta\theta_c \tag{3}$$

where J_θ relates joint space deflections $\Delta\theta_c$ to Cartesian space errors ΔP_C.

Transmission system inaccuracies introduce nonlinear effects such as backlash, hysteresis, and gear tooth compliance [6], [19], [20]. Backlash errors create dead zones in joint positioning that vary with motion direction, described by [19]:

$$\hat{q}_i = q_i - \bar{q}_i \varepsilon_i \tag{4}$$

where ε_i quantifies the backlash amount and $\bar{q}_i$ indicates the joint's approach direction.

Thermal effects induce time-varying errors through differential expansion of components, with the thermal drift following [21]:

$$\Delta L = L_0 \cdot \alpha \cdot \Delta T \tag{5}$$

where α is the material's coefficient of thermal expansion and ΔT represents temperature changes.

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.




Fig. 4. Error Escalation in Robotic Manipulator Lifecycles.

Frictional phenomena cause velocity-dependent errors through stick-slip motion and nonlinear torque requirements, while material degradation leads to progressive changes in mechanical properties over time [6], [9].

The comprehensive classification of robotic manipulator errors presented in Table I provides valuable insights into the temporal characteristics and root causes of different error types. The table organizes error sources according to their lifecycle phase, dynamics, and category, revealing important patterns in error manifestation. The table particularly highlights how error characteristics evolve from the manufacturing process to long-term operation. This lifecycle perspective, illsturated in Figure 4, is crucial for developing targeted compensation strategies, as it demonstrates that certain errors (like manufacturing defects) require one-time calibration, while others (such as thermal drift or wear) demand continuous monitoring and adjustment. The clear separation between geometric and non-geometric errors across different operational phases helps identify when model-based compensation may be sufficient versus when data-driven adaptive approaches become necessary.

C. Error Propagation and Coupling Effects

The propagation of errors through a robotic manipulator's kinematic chain follows complex nonlinear relationships that depend on the manipulator's configuration and loading conditions. Geometric errors typically propagate according to the manipulator's forward kinematics, with the sensitivity to individual parameter errors varying significantly across the workspace. For serial manipulators, errors in proximal joints generally have a larger effect on end-effector positioning than distal joint errors due to the multiplicative nature of the transformation chain.

Non-geometric errors often exhibit configuration-dependent behavior where their impact varies nonlinearly with joint positions and velocities. Compliance errors, for instance, become more pronounced in configurations where the manipulator approaches singularities, as the effective stiffness decreases dramatically. Similarly, thermal effects may cause asymmetric errors due to differential heating of components based on their orientation and exposure to heat sources.

The coupling between different error types creates particularly challenging compensation scenarios. A common example is the interaction between backlash and friction, where the dead zone caused by backlash varies with the friction-induced torque requirements. Another significant coupling occurs between thermal effects and structural compliance, as temperature changes alter both geometric parameters and material stiffness properties. These coupled effects often require advanced compensation techniques that go beyond the simple superposition of individual error models.

III. Methodological Approaches to Error Compensation

Modern error compensation techniques can be classified into three distinct methodological paradigms, each addressing different aspects of robotic inaccuracies through specialized theoretical frameworks. As illustrated in Figure 5, these approaches

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

range from purely physics-based formulations to data-driven machine learning techniques and hybrid methodologies that combine both perspectives. The evolution of these methods reflects the growing complexity of robotic applications and the need for increasingly sophisticated compensation strategies in high-precision manufacturing environments.




Fig. 5. Classification of methodological approaches to robotic error compensation showing the three dominant paradigms and their characteristic features

A. Foundations of Robot Calibration

Effective error compensation begins with proper robot calibration, which requires models satisfying four fundamental criteria, as illustrated in Figure 6. These principles collectively ensure that the kinematic model is both mathematically robust and practically adaptable to various industrial scenarios. Each criterion contributes uniquely to model quality, calibration precision, and downstream error compensation performance.




Fig. 6. Robot Model Calibration Criteria [19], [22], [23], [24]

1) Generalization: The calibration model should be capable of representing all possible serial kinematic chains, including varying link arrangements, joint types, and actuation methods. This universality is essential to ensure that the same modeling framework can be applied across different industrial robots, reducing the need for model-specific tuning and enhancing scalability in smart manufacturing environments.

2) Kinematic Mapping: A well-posed mapping from kinematic parameters to task space must be free from singularities and locally stable. This implies that small changes in the robot's physical structure (e.g., due to joint wear or thermal drift) result in only minor deviations in the identified model parameters. Smooth and stable mappings support real-time adaptation and robust inverse kinematics, which are critical for precision tasks.

3) Number of Independent Kinematic Parameters: The model must expose all degrees of freedom and parameters that define the robot's configuration. Including redundant or dependent parameters can lead to ill-posed optimization problems and overfitting during calibration. Instead, a minimal but sufficient parameter set enables efficient identification while preserving interpretability.

4) Differentiability: A differentiable formulation is necessary for gradient-based optimization and parameter identification. This criterion allows for the application of modern machine learning algorithms, such as backpropagation in neural networks or Jacobian-based optimization in nonlinear solvers. Differentiability enhances the integration of the model into hybrid learning-control frameworks.

Together, these criteria serve as design rules for constructing calibration models that are mathematically sound and practically viable. Modern approaches—ranging from screw theory-based kinematics to physics-informed neural networks—are increasingly evaluated against these standards to ensure high accuracy, adaptability, and computational efficiency. In the broader context of this work, satisfying these foundational conditions is a prerequisite for deploying any compensation strategy that involves real-time control, learning-based adaptation, or sensor fusion.

B. Physics-Based Modeling Approaches

Physics-based compensation methods establish deterministic relationships between mechanical parameters and observed errors through rigorous kinematic formulations. These approaches leverage fundamental principles from screw theory, Lie algebra, and parameterized kinematic chains to create differentiable mappings between joint space and operational space inaccuracies [16], [19], [25], [26]. The results in Table II reveal several important trends in physics-based compensation. The modified Denavit-Hartenberg (DH) approach with compliance compensation demonstrates robust performance with 80-90% accuracy improvement across various loading conditions, making it particularly suitable for industrial applications with variable payloads [16]. The POE (Product-of-Exponentials) formulation shows even broader effectiveness with 69-97% error reduction, especially when combined with thermal compensation strategies [19]. The remarkable precision of screw theory formulations (achieving 10^{-13} mm accuracy in controlled conditions) highlights the potential of rigorous mathematical frameworks, though this comes with increased computational demands as indicated by the "High" efficiency rating [26].

The primary strength of physics-based methods lies in their interpretability and guaranteed convergence properties under

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

well-defined conditions. For instance, the work of [26] demonstrates how screw theory-based formulations can achieve sub-nanometer precision in kinematic modeling. However, these approaches often struggle with unmodeled dynamic effects and environmental disturbances that fall outside their theoretical assumptions [9]. The requirement for precise initial parameter identification and their limited adaptability to changing operational conditions represent significant challenges for real-world implementation [19].

TABLE II
PERFORMANCE OF PHYSICS-BASED COMPENSATION METHODS

Methodology	**Accuracy Improvement**	**Computational Efficiency**
Modified DH with compliance compensation	80–90%	Moderate
POE with thermal compensation	69–97%	High
Thermo-geometric model	0.06–0.07 mm	Moderate
Screw theory formulation	10^{-13} mm	High

C. Machine Learning Techniques

Advanced machine learning approaches have emerged as powerful tools for compensating complex, nonlinear error patterns that elude physical modeling. Temporal Convolutional Networks (TCNs) and hybrid metaheuristic neural architectures demonstrate particular efficacy in handling time-varying errors induced by thermal drift, variable payloads, and transmission system nonlinearities [3], [4], [7], [27]. As shown in Table III, these data-driven methods excel at capturing stochastic disturbances and adapting to changing operational conditions.

The machine learning approaches summarized in Table III showcase the diversity of contemporary data-driven compensation techniques. The GPSO-NN (Genetic Particle Swarm Optimization-Neural Network) framework stands out with its 87.9% positioning error reduction, combining evolutionary optimization with deep learning capabilities [3]. The PSO-SVM (Particle Swarm Optimized-Support Vector Machine) method achieves a remarkable 96.95% fault detection accuracy, demonstrating the effectiveness of hybrid optimization-classification approaches [7]. While TCNs (Temporal Convolutional Networks) show slightly lower performance (85% error reduction), their inherent capacity for temporal pattern recognition makes them invaluable for dynamic error prediction [27]. The DRL-PPO (Deep Reinforcement Learning-Proximal Policy Optimization) approach represents the only real-time capable method in this category, achieving a 93.6% success rate in joint failure scenarios [4].

The GPSO-NN framework developed by [3] exemplifies the potential of machine learning approaches, achieving an 87.9% reduction in positioning errors through swarm-optimized neural networks. Similarly, the temporal convolutional network approach of [27] demonstrates how temporal dependencies in dynamic tracking errors can be effectively modeled and compensated. However, the black-box nature of these methods and their dependence on extensive training datasets introduce challenges in industrial deployment, particularly in applications requiring certification or validation of compensation algorithms [28]–[31].

TABLE III
PERFORMANCE OF MACHINE LEARNING COMPENSATION METHODS

ML Approach	Accuracy Improvement	Real-Time Capability
GPSO-NN	87.9%	Offline
PSO-SVM	96.95%	Offline
TCN	85%	Offline
DRL-PPO	93.6%	Real-time

D. Hybrid Physics-ML Integration

The most promising recent developments involve hybrid approaches that combine physical models with machine learning to leverage their complementary strengths. As detailed in Table IV, these methods maintain the interpretability of physics-based models while incorporating data-driven components to handle unmodeled phenomena. Techniques like kinetostatic-GPR (Gaussian Process Regression) fusion and physics-informed DBNs (Deep Belief Networks) demonstrate superior performance by decomposing errors into modeled and residual components [17], [32], [33].

Table IV presents compelling evidence for the effectiveness of hybrid methodologies. The DBNs (Deep Belief Networks) with error similarity analysis achieve 83.99% positional accuracy improvement, combining the pattern recognition capabilities of deep learning with physical error modeling [33]. The Lie algebra optimization approach reaches exceptional absolute accuracy (0.0518 mm mean error) by incorporating rigorous mathematical constraints into the optimization process [32]. The LPOE-GPR (Local Product-of-Exponentials with Gaussian Process Regression) fusion method demonstrates the broadest applicability with 54.8% accuracy improvement across varying load conditions, though at the cost of higher implementation complexity [17].

The work of [17] exemplifies this paradigm, where Gaussian Process Regression enhances a Local POE model to achieve 54.8% accuracy improvement under variable loading conditions. Similarly, [33] demonstrates how deep belief networks can be combined with error-similarity analysis to improve positional and orientation accuracy. These hybrid approaches represent a significant advancement over purely physical or data-driven methods, though challenges remain in optimizing their computational efficiency and ensuring robust performance across diverse operating conditions [17], [33].

TABLE IV
PERFORMANCE OF HYBRID PHYSICS-ML COMPENSATION METHODS

Hybrid Approach	**Accuracy Improvement**	**Implementation Complexity**
DBNs with error similarity	83.99%	High
Lie algebra with optimization	0.0518 mm	Moderate
LPOE-GPR fusion	54.8%	High

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

IV. Comparative Analysis of Compensation Techniques

The systematic evaluation of robotic error compensation methodologies reveals fundamental trade-offs between theoretical precision, computational efficiency, and practical implementation across three dominant paradigms. As demonstrated in Tables V and VI, each approach exhibits distinct performance characteristics that dictate their suitability for specific industrial applications. This analysis integrates quantitative performance metrics with qualitative implementation considerations to establish guidelines for method selection based on operational requirements and error types.

A. Methodological Trade-off Analysis

Physics-based modeling approaches demonstrate medium to high accuracy across various applications. These methods excel in scenarios requiring certifiable precision, as evidenced by the 0.06-0.07 mm accuracy achieved in thermal drift compensation for ABB IRB4600 robots [25]. The thermo-geometrical model implementation showcases both the strengths and limitations of physics-based approaches, delivering exceptional precision but requiring offline calibration that restricts real-time adaptability [25]. Similarly, the Lie algebra optimization method reaches a remarkable 0.0518 mm mean accuracy in geometric error compensation, though its dependence on precise initial calibration limits robustness in field deployments [32].

Machine learning techniques exhibit superior adaptability for complex, nonlinear error patterns [34]–[36]. However, these data-driven methods demand substantial computational resources and extensive training datasets [37]. While offering high accuracy, these methods face challenges in industrial certification due to their black-box nature and sensitivity to environmental variations.

Hybrid methodologies bridge the gap between physical interpretability and data-driven adaptability. These hybrid approaches represent a promising direction for general-purpose applications, though their increased implementation complexity and variable computational costs necessitate careful system design.

B. Error-Specific Performance Evaluation

The detailed error-type analysis presented in Table VI reveals crucial patterns in methodological effectiveness across different error categories. Geometric errors respond most effectively to physics-based approaches, with modified DH models achieving 80-90% error reduction in HIWIN RT-605-710 robot and POE formulations reaching 69-97% improvement in KUKA KR-16/30-3 implementations [16], [19]. The exceptional 0.0518 mm accuracy of Lie algebra optimization in UR5 and KUKA LBR systems demonstrates the potential of rigorous mathematical frameworks, though this precision comes at the cost of calibration complexity [32].

Thermal and compliance errors show superior compensation through hybrid methodologies. The thermo-geometrical model maintains 0.06-0.07 mm accuracy in ABB IRB4600 robots by decoupling thermal effects from mechanical backlash, while TCN-based load decomposition achieves 85% error reduction in UR10 collaborative robots through advanced temporal analysis [25], [27]. These results highlight the importance of combining physical understanding with data-driven adaptation for dynamic error sources.

For system faults and complex operational scenarios, machine learning approaches demonstrate unmatched capabilities. The Support Vector Machine with Particle Swarm Optimization (SVM-PSO) detects 96.95% of sensor faults in SCARA systems, while DRL-PPO maintains 93.6% task success during joint failures in Franka Emika 7-DOF robots [4], [7]. However, these methods require substantial infrastructure, with SVM-PSO needing 63,000 training samples and DRL-PPO demanding GPU acceleration for real-time operation [4], [7].

C. Industrial Implementation Guidelines

The comparative analysis yields several key recommendations for industrial implementation. For high-precision applications in controlled environments, physics-based methods offer reliable performance with moderate computational requirements, as demonstrated by the 0.06-0.07 mm thermal accuracy in aerospace manufacturing [25]. Dynamic production environments with variable conditions benefit more from hybrid approaches, with LPOE-GPR showing 54.8% improvement under load variations while maintaining reasonable computational demands [17].

Applications requiring fault tolerance and adaptive control should prioritize machine learning techniques, particularly for complex robotic systems like 7-DOF manipulators, where DRL-PPO demonstrates 93.6% failure recovery [4]. However, these implementations must account for the substantial infrastructure requirements, including GPU acceleration and extensive training datasets. The choice between methodologies ultimately depends on the specific balance required between precision, adaptability, and implementation cost for each industrial scenario.

V. Future Directions in Error Compensation

The rapid evolution of robotic error compensation techniques is being shaped by several transformative trends that promise to address current limitations while opening new possibilities for precision automation. As hybrid methodologies gain prominence, their integration with emerging technologies is creating novel paradigms for real-time adaptive control in increasingly complex operational environments.

- **Digital Twin-Enabled Adaptive Compensation:** The convergence of hybrid physics-ML approaches with digital twin technologies represents one of the most promising directions for next-generation error compensation. Modern implementations now leverage high-fidelity virtual replicas that continuously synchronize with physical robots through distributed sensor networks, enabling closed-loop compensation with sub-millisecond latency. However, significant challenges remain in reducing

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

TABLE V
COMPARATIVE ANALYSIS OF ERROR COMPENSATION METHODOLOGIES

Methodology	**Core Techniques**	**Accuracy**	**Compute Cost**	**Real-Time**	**Advantages**	**Limitations**
Integrated Physics-Based Modeling	- Screw theory - Newton-Raphson - Modified DH - POE formula	Medium–High	Medium	Limited	- Fast convergence - Multi-error handling - Load-adaptive - Industrial XCT	- Simulation-only - Thermal sensitivity - Static payload - Workspace limits
Advanced ML for Error Prediction	- GPSO-NN - SVM-PSO - TCN-PDLD - POMDP (PPO)	High	Moderate	Yes	- Fault detection - Adaptive control - Minimal hardware - Complex tasks	- Optimization needed - Data dependency - Modeling complexity - Environment challenges
Hybrid Physics-ML Approach	- DBNs - Lie algebra - GPR + Mechanics	High	Variable	Good	- Robust calibration - Noise immunity - Load-aware - Simple procedures	- Data sensitivity - Camera exclusion - Model complexity - Limited validation

TABLE VI
ERROR COMPENSATION TECHNIQUES ANALYSIS

Error Type	**Study**	**Compensation Methods**	**Accuracy Gains**	**Key Challenges**	**Innovative Solutions**	**Case Study**
Geometric	[16]	- Modified DH model - Taylor expansions - Gauss-Newton	80–90% positioning	Static payload dependency	Laser tracker (FARO Vantage-E)	HIWIN RT-605-710
Geometric	[19]	- POE formulation - Distributed sensors	69–97% error reduction	Cross-model generalization	Unified calibration framework	KUKA KR-16/30-3
Geometric	[32]	- Lie algebra matrices - Single-camera calib.	0.0518 mm	Initial calibration sensitivity	Multi-error calibration	UR5 KUKA LBR
Thermal Drift	[19]	- Thermal mapping - Photogrammetry	0.1 mm thermal error	Costly sensors	Combined compensation	KUKA KR-16/30-3
Thermal Drift	[25]	- Thermo-geometrical model - Laser+IR fusion	0.06–0.07 mm	Offline limitations	Decoupling thermal effects	ABB IRB4600
Compliance	[16]	- Stiffness matrix - Payload ID	80–90%	Dynamic payloads	Iterative refinement	HIWIN RT-605-710
Compliance	[27]	- TCN - Load decomposition	85% error reduction	Structural deformation	Temporal data segmentation	UR10
Sensor Faults	[7]	- SVM-PSO - Gaussian kernel	96.95%	Large datasets	Hybrid PSO-SVM	SCARA
Joint Failures	[4]	- DRL-POMDP (PPO) - 24k episodes	93.6%	Real-world transition	Adaptive control	Franka 7-DOF
Positioning	[3]	- GPSO-NN	77.6–87.9%	Partial compensation	Lightweight architecture	KUKA KR500-3
Multi-Source	[17]	- GPR + Kinetostatic	8.1–54.8%	Limited load coverage	Heavy-load calibration	ABB IRB4400
Multi-Source	[33]	- DBNs - Cross-contrast	83.99/54.88%	Environmental factors	Model-agnostic approach	KUKA KR500-3
Kinematic modeling	[26]	- Screw theory - Newton-Raphson	$< 10^{-3}$ mm	High-DOF complexity	Simplified modeling	ABB IRB14000

the computational overhead of maintaining millimeter-accurate digital twins across large-scale industrial deployments.

- **Edge-Cloud Collaborative Architectures:** Emerging distributed computing frameworks are addressing the computational bottlenecks of advanced compensation algorithms through innovative edge-cloud partitioning. Future developments in federated learning and edge AI accelerators are expected to further enhance the real-time capabilities of these distributed systems.
- **Physics-Informed Machine Learning:** The integration of physical constraints into neural network architectures is yielding a new generation of interpretable, data-efficient hybrid models. Current research focuses on extending this paradigm to include multi-physics constraints encompassing mechanical, thermal, and electromagnetic interactions in complex robotic systems.
- **Self-Calibrating Robotic Systems:** Autonomous calibration represents another significant frontier, where reinforcement learning agents continuously optimize compensation parameters during normal operation. Such systems demonstrate particular value in field applications

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

where traditional calibration procedures prove impractical, though challenges persist in ensuring stability during the learning process.

VI. Challenges and Research Priorities

While these emerging directions show considerable promise, several critical challenges must be addressed to enable widespread industrial adoption. The computational complexity of high-fidelity digital twins remains prohibitive for many applications, necessitating research into reduced-order modeling techniques that preserve essential dynamics while minimizing resource requirements. The development of standardized interfaces between physical robots and their virtual counterparts would significantly accelerate deployment timelines. Additionally, the verification and certification of adaptive learning systems in safety-critical applications require new methodologies that can guarantee performance bounds under uncertain operating conditions.

Energy efficiency represents another crucial research frontier, particularly for mobile and collaborative robotic systems where power constraints limit computational capabilities. Recent work on neuromorphic computing for error prediction shows potential for 10-100x improvements in energy efficiency compared to conventional GPU implementations. The integration of quantum computing principles for high-dimensional optimization problems in calibration procedures may further revolutionize the field in coming years.

The continued expansion of robotic applications into extreme environments - from deep-sea exploration to space operations - will drive demand for compensation systems that maintain precision across unprecedented temperature ranges, radiation levels, and mechanical stresses. These challenges will require fundamentally new approaches to error modeling and compensation that go beyond current technological paradigms, potentially incorporating bio-inspired adaptive mechanisms and novel materials with self-correcting properties.

As the field progresses, the convergence of these technological vectors promises to enable a new era of autonomous precision robotics, where self-optimizing systems maintain sub-micron accuracy across years of continuous operation in dynamic, unpredictable environments. The realization of this vision will depend on sustained interdisciplinary collaboration across robotics, materials science, computer engineering, and applied mathematics.

VII. Conclusion

This comprehensive review has systematically examined the state-of-the-art in robotic manipulator error compensation, revealing critical insights into both current capabilities and future research directions. The developed taxonomy of error sources establishes a fundamental framework for understanding how geometric and non-geometric inaccuracies propagate through robotic systems, while the comparative analysis of compensation methodologies provides concrete evidence of their respective strengths and limitations. Physics-based approaches demonstrate exceptional precision in controlled conditions, with screw theory formulations achieving sub-nanometer accuracy in simulation environments. Machine learning techniques show remarkable adaptability to complex nonlinear errors, with hybrid PSO-SVM models attaining 96.95% fault detection accuracy. However, hybrid methodologies combining physical models with data-driven components emerge as the most promising direction, evidenced by LPOE-GPR implementations achieving 54.8% accuracy improvement under variable loading conditions.

The review identifies several critical challenges that must be addressed to advance the field. Computational complexity remains a fundamental constraint for high-fidelity digital twin implementations, while the certification of adaptive learning systems in safety-critical applications requires new verification methodologies. Energy efficiency poses another significant barrier, particularly for mobile and collaborative robotic systems where power constraints limit computational capabilities. Future research should prioritize the development of reduced-order modeling techniques for digital twins, standardized interfaces between physical and virtual systems, and neuromorphic computing architectures for energy-efficient error prediction. The integration of quantum computing principles for high-dimensional optimization problems in calibration procedures may offer transformative potential in coming years.

As robotic applications expand into extreme environments and increasingly complex operational scenarios, the field must develop fundamentally new approaches to error compensation that transcend current technological paradigms. The convergence of digital twin technologies, edge-cloud architectures, and physics-informed machine learning presents a particularly promising pathway toward autonomous robotic systems capable of maintaining sub-micron accuracy in dynamic, unpredictable environments. Realizing this vision will require sustained interdisciplinary collaboration across robotics, materials science, computer engineering, and applied mathematics. This review serves both to consolidate current knowledge and to stimulate innovative research that addresses the pressing challenges in robotic error compensation for next-generation industrial applications.

References

[1] A. Dzedzickis, J. Subačiūtė-Žemaitienė, E. Šutinys, U. Samukaitė-Bubnienė, and V. Bučinskas, "Advanced applications of industrial robotics: New trends and possibilities," *Applied Sciences*, vol. 12, no. 1, p. 135, 2021.

[2] A. F. Pedroso, N. P. Sebbe, F. J. Silva, R. D. Campilho, R. C. Sales-Contini, R. D. Costa, and I. I. Sánchez, "An overview on the recent advances in robot-assisted compensation methods used in machining lightweight materials," *Robotics and Computer-Integrated Manufacturing*, vol. 91, p. 102844, 2025.

[3] L. Bo, T. Wei, C. Zhang, H. Fangfang, C. Guangyu, and L. Yufei, "Positioning error compensation of an industrial robot using neural networks and experimental study," *Chinese Journal of Aeronautics*, vol. 35, no. 2, pp. 346–360, 2022.

[4] T.-H. Pham, G. Aikins, T. Truong, and K.-D. Nguyen, "Adaptive compensation for robotic joint failures using partially observable reinforcement learning," *Algorithms*, vol. 17, no. 10, p. 436, 2024.

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.

[5] R. Kluz, A. Kubit, and T. Trzepiecinski, "Investigations of temperature-induced errors in positioning of an industrial robot arm," *Journal of Mechanical Science and Technology*, vol. 32, pp. 5421–5432, 2018.

[6] S. Kana, J. Gurnani, V. Ramanathan, S. H. Turlapati, M. Z. Ariffin, and D. Campolo, "Fast kinematic re-calibration for industrial robot arms," *Sensors*, vol. 22, no. 6, p. 2295, 2022.

[7] D. Maincer, Y. Bennahamed, M. Mansour, M. Alharthi, and S. S. Ghonein, "Fault diagnosis in robot manipulators using svm and knn," *Intelligent Automation & Soft Computing*, vol. 35, no. 2, pp. 1957–1969, 2023.

[8] S. Cao, Q. Cheng, Y. Guo, W. Zhu, H. Wang, and Y. Ke, "Pose error compensation based on joint space division for 6-dof robot manipulators," *Precision Engineering*, vol. 74, pp. 195–204, 2022.

[9] R. Kermenov, G. Nabissi, S. Longhi, and A. Bonci, "Anomaly detection and concept drift adaptation for dynamic systems: a general method with practical implementation using an industrial collaborative robot," *Sensors*, vol. 23, no. 6, p. 3260, 2023.

[10] P. Carbone, G. E. Gévay, G. Hermann, A. Katsifodimos, J. Soto, V. Markl, and S. Haridi, "Large-scale data stream processing systems," *Handbook of big data technologies*, pp. 219–260, 2017.

[11] S. Tripathi, D. Muhr, M. Brunner, H. Jodlbauer, M. Dehmer, and F. Emmert-Streib, "Ensuring the robustness and reliability of data-driven knowledge discovery models in production and manufacturing," *Frontiers in artificial intelligence*, vol. 4, p. 576892, 2021.

[12] M. Alizadeh and Z. H. Zhu, "A comprehensive survey of space robotic manipulators for on-orbit servicing," *Frontiers in Robotics and AI*, vol. 11, p. 1470950, 2024.

[13] International Federation of Robotics, "Industrial robots," IFR, 2021, accessed: April 12, 2025. [Online]. Available: https://ifr.org/industrial-robots

[14] J. M. S. Motta, C. H. Llanos-Quintero, and R. Coral Sampaio, "Inverse kinematics and model calibration optimization of a five-dof robot for repairing the surface profiles of hydraulic turbine blades," *International Journal of Advanced Robotic Systems*, vol. 13, no. 3, p. 114, 2016.

[15] Y. Wang and G. S. Chirikjian, "Large kinematic error propagation in revolute manipulators," in *Advances in Robot Kinematics: Mechanisms and Motion*. Springer, 2006, pp. 95–102.

[16] H.-M. Li, C.-K. Liu, Y.-C. Yang, and M.-S. Tsai, "Simultaneous compensation of geometric and compliance errors for robotics with consideration of variable payload effects," *Mechatronics*, vol. 102, p. 103228, 2024.

[17] Y. Zhou, C.-Y. Chen, Y. Tang, H. Wan, J. Luo, G. Yang, and C. Zhang, "A comprehensive on-load calibration method for industrial robots based on a unified kinetostatic error model and gaussian process regression," *IEEE Transactions on Instrumentation and Measurement*, 2024.

[18] "Manipulating industrial robots – performance criteria and related test methods," 1998, available at: https://webstore.ansi.org/standards/ISO/iso92831998.

[19] P. Sigron, I. Aschwanden, and M. Bambach, "Compensation of geometric, backlash, and thermal drift errors using a universal industrial robot model," *IEEE Transactions on Automation Science and Engineering*, 2023.

[20] M. Slamani, A. Nubiola, and I. A. Bonev, "Modeling and assessment of the backlash error of an industrial robot," *Robotica*, vol. 30, no. 7, pp. 1167–1175, 2012.

[21] N. Slobodzyan, "Evaluation of open-loop linear drive accuracy achieved by calibration and linear thermal expansion compensation," *Radio industry (Russia)*, vol. 29, p. 54, 2019.

[22] B. W. Mooring, Z. S. Roth, and M. R. Driels, *Fundamentals of manipulator calibration*. Wiley-interscience, 1991.

[23] F. C. Park and K. Okamura, "Kinematic calibration and the product of exponentials formula," in *Advances in robot kinematics and computational geometry*. Springer, 1994, pp. 119–128.

[24] L. Wu, R. Crawford, and J. Roberts, "Geometric interpretation of the general poe model for a serial-link robot via conversion into dh parameterization," in *2019 International Conference on Robotics and Automation (ICRA)*. IEEE, 2019, pp. 7360–7366.

[25] A. Le Reun, K. Subrin, A. Dubois, and S. Garnier, "Thermal drift and backlash issues for industrial robots positioning performance," *Robotica*, vol. 40, no. 9, pp. 2933–2952, 2022.

[26] D. Ge, "Kinematics modeling of redundant manipulator based on screw theory and newton-raphson method," in *Journal of Physics: Conference Series*, vol. 2246, no. 1. IOP Publishing, 2022, p. 012068.

[27] S. Tan, J. Yang, and H. Ding, "A prediction and compensation method of robot tracking error considering pose-dependent load decomposition," *Robotics and Computer-Integrated Manufacturing*, vol. 80, p. 102476, 2023.

[28] R. A. Saleh and H. M. Ertunç, "Attention-based deep learning for tire defect detection: Fusing local and global features in an industrial case study," *Expert Systems with Applications*, vol. 269, p. 126473, 2025.

[29] R. A. Saleh and H. M. ERTUNÇ, "Explainable attention-based fused convolutional neural network (xafcnn) for tire defect detection: an industrial case study," *Engineering Research Express*, vol. 6, no. 1, p. 015090, 2024.

[30] R. A. Saleh, M. Z. Konyar, K. Kaplan, and H. M. Ertunç, "End-to-end tire defect detection model based on transfer learning techniques," *Neural Computing and Applications*, pp. 1–21, 2024.

[31] R. Saleh, F. Al-Areqi, M. Z. Konyar, K. Kaplan, S. Öngir, and H. Ertunç, "Advancing tire safety: Xai-powered foreign object defect detection with xception networks and grad-cam interpretation," *APPLIED SCIENCES*, vol. 14, no. 10, 2024.

[32] Z. Liu, X. Liu, Z. Cao, X. Gong, M. Tan, and J. Yu, "High precision calibration for three-dimensional vision-guided robot system," *IEEE Transactions on Industrial Electronics*, vol. 70, no. 1, pp. 624–634, 2022.

[33] W. Wang, W. Tian, W. Liao, B. Li, and J. Hu, "Error compensation of industrial robot based on deep belief network and error similarity," *Robotics and Computer-Integrated Manufacturing*, vol. 73, p. 102220, 2022.

[34] R. A. Saleh, M. Z. Konyar, K. Kaplan, and H. M. Ertunç, "Tire defect detection model using machine learning," in *2022 2nd International Conference on Emerging Smart Technologies and Applications (eSmarTA)*. IEEE, 2022, pp. 1–5.

[35] N. A. Saleh, H. M. Ertunc, R. A. Saleh, and M. A. RASSAM, "A simple mask detection model based on a multi-layer perception neural network," in *2021 International Conference of Technology, Science and Administration (ICTSA)*. IEEE, 2021, pp. 1–5.

[36] H. AbuAlkebash, R. A. Saleh, and H. M. Ertunç, "Automated explainable deep learning framework for multiclass skin cancer detection and classification using hybrid yolov8 and vision transformer (vit)," *Biomedical Signal Processing and Control*, vol. 108, p. 107934, 2025.

[37] R. A. Saleh, M. Ghaleb, W. Shafik, and H. M. ERTUNÇ, "Efficient white blood cell identification with hybrid inception-xception network," *The Journal of Supercomputing*, vol. 80, no. 17, pp. 25 155–25 187, 2024.

Authorized licensed use limited to: King Fahd University of Petroleum and Minerals. Downloaded on June 06,2026 at 14:22:59 UTC from IEEE Xplore. Restrictions apply.