IN THE NAME OF ALLAH

SENSITIVITY ANALYSIS OF CONCRETE FRAME BY CHANGING COLUMN REBAR DIAMETER AND COLUMN SECTION DEPTH. ANALYZING CREEP AND SHRINKAGE OF A CONCRETE FRAME. EVALUATING STRAIN HARDENING USING OPENSEES AND CALCULATE STRUCTURAL BEHAVIOR COEFFICIENT

WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)





CORE AND COVER CONCRETE REALTION



WITHOUT HARDENING AND ULTIMATE STRAIN



WITH HARDENING AND ULTIMATE STRAIN



COLUMN SECTION



BEAM SECTION


Correlation Heatmap
DIAc
Hc
RO_COL
RO_BE
DISP_X
DISP_Y
ROTATION
AXIAL_FORCE
SHEAR_FORCE
MOMENT_WO
AXIAL_RIGIDITY
ROTATIONAL_ST
LATERAL_ST_Y
LATERAL_ST_X
R_MAX
Elastic_ST_MAX
Plastic_ST_MAX
Tangent_ST_MAX
Ductility_Rito_MAX
Over_Strength_Factor_MAX
Structural_Behavior_Coefficient_MAX
Variable
Variable
1.00
0.75
0.50
0.25
0.00
−0.25
−0.50
−0.75

3D Contour Plot of Structure Shear Reaction in X Dir. [N]




3D Contour Plot of Structure Axial Reaction in Y Dir. [N]
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600
Structure Axial Reaction in Y Dir. [N]
1e+6
1.995
1.997
0.998
0.000
−0.998
−2.004
3.706e7
1.997
0.998
0.000
−0.998
−2.004

3D Contour Plot of Structure Moment Reaction in Y Dir. [N.mm]




3D Contour Plot of Structure Displacement in X Dir. [mm]
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600
Structure Displacement in X Dir. [mm]
1.4
1.6
1.8
2.0
2.2
2.4

3D Contour Plot of Structure Displacement in Y Dir. [mm]




3D Contour Plot of Structure Elastic Stiffness [N/mm]
Structure Elastic Stiffness [N/mm]
850
800
750
700
650
600
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600


3D Contour Plot of Structure Plastic Stiffness [N/mm]
Structure Plastic Stiffness [N/mm]
2800
2600
2400
2200
2000
1800
1600
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600


3D Contour Plot of Ductility Rito [mm/mm]
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600
Ductility Rito [mm/mm]
1.8
2.0
2.2
2.4
2.6
2.8
3.0


3D Contour Plot of Over Strength Factor [N/N]
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600
Over Strength Factor [N/N]
5.5
6.0
6.5
7.0
7.5


3D Contour Plot of Structural Behavior Coefficient
Rebar Diameter [mm]
18
20
22
24
26
28
30
32
Column Section Depth [mm]
500
520
540
560
580
600
Structural Behavior Coefficient
10
12
14
16
18
20
22
24


P-M Interaction
1e7
3.5
3.0
2.5
2.0
1.5
1.0
0.5
0.0
Axial Force [N]
0.00
0.25
0.50
0.75
1.00
1.25
1.50
1.75
Bending Moment [N.mm]
1e7


SHEAR FORCE-DISPLACEMENT DIAGRAM
Shear Force [N]
0
−500
−1000
−1500
−2000
−2500
−3000
−3500
0.0
0.2
0.4
0.6
0.8
1.0
1.2
Displacement in X [mm]


AXIAL FORCE-DISPLACEMENT DIAGRAM
1e7
3.5
3.0
2.5
2.0
1.5
1.0
0.5
0.0
Axial Force [N]
−25
−20
−15
−10
−5
0
Displacement in Y [mm]


MOMENT-ROTATION DIAGRAM
1e7
1.75
1.50
1.25
1.00
0.75
0.50
0.25
0.00
Moment [kN.mm]
−0.005
−0.004
−0.003
−0.002
−0.001
0.000
Rotation [rad]


ROTATIONAL STIFFNESS-LATERAL STIFFNESS DIAGRAM (X Dir)
Rotational Stiffness [N.mm/Rad]
10^4
10^3
2×10^9
3×10^9
4×10^9
6×10^9
Lateral Stiffness in X Dir. [N/mm]


ROTATIONAL STIFFNESS-LATERAL STIFFNESS DIAGRAM (Y Dir)
Rotational Stiffness [N.mm/Rad]
4×10^6
3×10^6
2×10^6
10^6
2×10^9
3×10^9
4×10^9
6×10^9
Lateral Stiffness in Y Dir. [N/mm]


Axial Force During the Analysis
1e7
3.5
3.0
2.5
2.0
1.5
1.0
0.5
0.0
Axial Force [N]
0
10
20
30
40
50
60
70
Steps


Moment During the Analysis
1e7
1.75
1.50
1.25
1.00
0.75
0.50
0.25
0.00
Moment [kN.mm]
0
10
20
30
40
50
60
70
Steps


Displacement During the Analysis (X)
Displacement - X [mm]
0.0
0.2
0.4
0.6
0.8
1.0
1.2
0
10
20
30
40
50
60
70
Steps


Displacement During the Analysis (Y)
Displacement - Y [mm]
0
−5
−10
−15
−20
−25
0
10
20
30
40
50
60
70
Steps


Last Data of BaseShear-Displacement Analysis - Ductility Ratio: 1.7708 - Over Strength Factor: 5.7132
Base-Shear [N]
3500
3000
2500
2000
1500
1000
500
0
0.0
0.2
0.4
0.6
0.8
1.0
1.2
Displacement in X [mm]
Curve
Bilinear Fitted


Last Data of BaseAxial-Displacement Analysis - Ductility Ratio: 2.1813 - Over Strength Factor: 2.0433
1e7
3.5
3.0
2.5
2.0
1.5
1.0
0.5
0.0
Base-Axial [N]
0
5
10
15
20
25
Displacement in Y [mm]
Curve
Bilinear Fitted


Undeformed and Deformed Shapes - DEFORMED SCALE: 10.00
3
5
4
3
5
4
1
2
Undeformed
Deformed
Z [mm]
X [mm]
0
500
1000
1500
2000
2500
3000
0
1000
2000
3000
4000
5000
6000
7000