IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL

FREE-VIBRATION ANALYSIS OF CONCRETE FRAME. EVALUATING STRAIN HARDENING AND ULTIMATE STRAIN CRITERIA USING OPENSEES

WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)


Initial Lateral Displacement
m
m
8
9
7
11
12
10
3
3
4
1
2
COLUMN LENGTH
2
3
1
1
2
5
6
4
BEAM LENGTH



CORE AND COVER CONCRETE REALTION



WITHOUT HARDENING AND ULTIMATE STRAIN



WITH HARDENING AND ULTIMATE STRAIN



COLUMN SECTION



BEAM SECTION


Spyder (Python 3.12)
File Edit Search Source Run Debug Consoles Projects Tools View Help
C:\Users\Dell\Desktop\OPENSEES_FILES\CONCRETE_FRA...S\FREE-VIBRATION\CONCRETE_FRAME_FREE-VIBRATION.py
CONCRETE_FRAME_FREE-VIBRATION.py
IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL
FREE-VIBRATION ANALYSIS OF CONCRETE FRAME. EVALUATING STRAIN HARDENING AND ULTIMATE STRAIN CRITERIA
THIS PROGRAM WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)
EMAIL: salar.d.ghashghaei@gmail.com
1. Objective: The study evaluates the dynamic response of a concrete frame under
free-vibration conditions, comparing two steel material models:
- Steel01: Bilinear elastic-perfectly plastic (*no hardening/ultimate strain*).
- Hysteretic: Tri-linear with strain hardening, pinching, and stiffness degradation (*includes ulti
2. Model Setup:
- Geometry: 2D frame with columns (500×500 mm) and beam (500×300 mm), subjected to
an initial displacement (1.1 mm).
- Materials: Confined/unconfined concrete (`Concrete01`) and steel rebars (either `Steel01` or `Hys
- Damping: Rayleigh damping (5% initial guess) calibrated via eigenvalue analysis.
3. Dynamic Response:
- Period: Natural period (`T`) calculated from eigenanalysis (~0.28 s for fundamental mode).
- Displacement Decay: Logarithmic decrement used to compute damping ratios (`ξ`).
The *Hysteretic* model showed higher energy dissipation due to degradation.
4. Force-Displacement Behavior:
- Shear (X-direction): The *Hysteretic* model exhibited pinching and reduced
stiffness in hysteresis loops, while *Steel01* maintained symmetric, undegraded cycles.
- Axial (Y-direction): Both models showed nonlinear coupling, but *Hysteretic*
introduced residual displacements from cumulative damage.
- Moment-Rotation: *Hysteretic* displayed strength decay under cyclic rotations,
unlike *Steel01*'s stable post-yield plateau.
5. Stiffness Evolution:
- Lateral Stiffness (X/Y): Degraded faster in the *Hysteretic* model due to rebar buckling/concrete
...esktop\OPENSEES_FILES\CONCRETE_FRAME_EXAMPLES\FREE-VIBRATION
Name Type Size Value
AsB float 1 254.46900494077323
AsC float 1 490.8738521234052
Bb int 1 500
Bc int 1 500
Bs float 1 0.00245013477088948 7
coverB int 1 50
coverC int 1 50
DIAb int 1 18
Help Variable Explorer Debugger Plots Files
Console 1/A
0.13841000000006803 3.086405113291763 -34085.59603590437
0.13841500000006804 3.0864041349884626 -34085.5830094339
0.13842000000006804 3.0864031566503174 -34085.56998250897
0.13842500000006805 3.0864021782773277 -34085.55695515409
0.13843000000006805 3.086401199869494 -34085.54392733015
0.13843500000006806 3.0864002214268154 -34085.530899095815
0.13844000000006806 3.086399242949293 -34085.51787039726
0.13844500000006807 3.086398264436926 -34085.5048416393
0.13845000000006807 3.086397285889715 -34085.49181168097
0.13845500000006808 3.0863963073076595 -34085.47878165837
IPython Console History
Inline Conda: anaconda3 (Python 3.12.7) LSP: Python Line 124, Col 13 UTF-8 CRLF RW Mem 42%

Free Vibration Analysis


Undeformed and Deformed Shapes - DEFORMED SCALE: 1.00
Z [mm]
X [mm]
0
500
1000
1500
2000
2500
3000
0
1000
2000
3000
4000
5000
6000
7000
1
2
3
3
4
4
Undeformed
Deformed


P-M Interaction
Steel01: WITHOUT HARDENING AND ULTIMATE STRAIN
Hysteretic: WITH HARDENING AND ULTIMATE STRAIN
Axial Force [N]
25000
20000
15000
10000
5000
0
−5000
−1.0
−0.5
0.0
0.5
1.0
1.5
Bending Moment [N.mm]
1e8


SHEAR FORCE-DISPLACEMENT DIAGRAM
Steel01: WITHOUT HARDENING AND ULTIMATE STRAIN
Hysteretic: WITH HARDENING AND ULTIMATE STRAIN
Shear Force [N]
40000
20000
0
−20000
−40000
−60000
−4
−2
0
2
4
Displacement in X [mm]


AXIAL FORCE-DISPLACEMENT DIAGRAM
Steel01: WITHOUT HARDENING AND ULTIMATE STRAIN
Hysteretic: WITH HARDENING AND ULTIMATE STRAIN
Axial Force [N]
25000
20000
15000
10000
5000
0
−5000
0.00
0.05
0.10
0.15
0.20
0.25
Displacement in Y [mm]


MOMENT-ROTATION DIAGRAM
1e8
1.5
1.0
0.5
0.0
−0.5
−1.0
Moment [kN.mm]
−0.0020
−0.0015
−0.0010
−0.0005
0.0000
0.0005
0.0010
0.0015
Rotation [rad]
Steel01: WITHOUT HARDENING AND ULTIMATE STRAIN
Hysteretic: WITH HARDENING AND ULTIMATE STRAIN


ROTATIONAL STIFFNESS-LATERAL STIFFNESS DIAGRAM
Steel01: WITHOUT HARDENING AND ULTIMATE STRAIN
Hysteretic: WITH HARDENING AND ULTIMATE STRAIN
Rotational Stiffness [N.mm/Rad]
Lateral Stiffness in X Dir. [N/mm]
10^{1}
10^{2}
10^{3}
10^{4}
10^{5}
10^{6}
10^{7}
10^{7}
10^{8}
10^{9}
10^{10}
10^{11}
10^{12}
10^{13}
10^{14}


ROTATIONAL STIFFNESS-LATERAL STIFFNESS DIAGRAM
Steel01: WITHOUT HARDENING AND ULTIMATE STRAIN
Hysteretic: WITH HARDENING AND ULTIMATE STRAIN
Rotational Stiffness [N.mm/Rad]
Lateral Stiffness in Y Dir. [N/mm]
10^{11}
10^{9}
10^{7}
10^{5}
10^{3}
10^{1}
10^{-1}
10^{-3}
10^{7}
10^{8}
10^{9}
10^{10}
10^{11}
10^{12}
10^{13}
10^{14}


Time vs Displacement - MAX. ABS: 5.099999998535088 | ξ (Calculated): 1.30407e+01 %
Displacement in X [mm]
Time [s]
4
2
0
−2
−4
0
20
40
60
80
100
120
140


Time vs Displacement - MAX. ABS: 0.2687453914087112
Displacement in Y [mm]
0.25
0.20
0.15
0.10
0.05
0.00
0
20
40
60
80
100
120
140
Time [s]


Time vs Velocity - MAX. ABS: 2.8073353678597948
Velocity in X [mm/s]
Time [s]
3
2
1
0
−1
−2
−3
0
20
40
60
80
100
120
140


Time vs Acceleration - MAX. ABS: 2.343859740639072
Acceleration in X [mm/s^2]
Time [s]
2
1
0
−1
−2
0
20
40
60
80
100
120
140


Time vs Base-reaction - MAX. ABS: 56253.06847358722
60000
40000
20000
0
−20000
−40000
−60000
Base-reaction [N]
0
20
40
60
80
100
120
140
Time [s]