IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL

OPTIMIZATION OF STRUCTURAL BEHAVIOR COEFFICIENT USING PUSHOVER ANALYSIS OF CONCRETE FRAME SECTIONS: EVALUATING STRAIN HARDENING AND ULTIMATE STRAIN EFFECTS IN OPENSEES. DETERMINING OPTIMAL COLUMN SECTION DEPTH FOR A TARGET STRUCTURAL BEHAVIOR COEFFICIENT VIA THE NEWTON-RAPHSON METHOD.

WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)


8
9
7
m
m
11
12
10
3
3
4
INCREMENTAL
DISPLACEMENT
1
2
COLUMN
LENGTH
2
3
1
1
2
5
6
4
BEAM
LENGTH



CORE AND COVER CONCRETE RELATION



WITHOUT HARDENING AND ULTIMATE STRAIN



WITH HARDENING AND ULTIMATE STRAIN



COLUMN SECTION



BEAM SECTION

Spyder (Python 3.12)

File Edit Search Source Run Debug Consoles Projects Tools View Help

...E_FRAME_EXAMPLES\OPTIMIZATION\PUSHOVER_Cdepth_OPTIMIZATION

C:\Users\Dell\Desktop\OPENSEES_FILES\CONCRETE_FRA...USHOVER_STRUCTURAL_BEHAVIOR_COEFFICIENT_Cdepth.py

CONCRETE_FRAME_PUS...FFICIENT_Cdepth.py

```
#####################################################################################################
#                    >> IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL <<               #
# OPTIMIZATION OF STRUCTURAL BEHAVIOR COEFFICIENT USING PUSHOVER ANALYSIS OF CONCRETE FRAME SECTIONS:  #
# EVALUATING STRAIN HARDENING AND ULTIMATE STRAIN EFFECTS IN OPENSEES. DETERMINING OPTIMAL COLUMN SECTION #
# DEPTH FOR A TARGET STRUCTURAL BEHAVIOR COEFFICIENT VIA THE NEWTON-RAPHSON METHOD.                 #
#---------------------------------------------------------------------------------------------------#
#                            OPTIMIZATION ALGORITHM: NEWTON-RAPHSON METHOD                          #
#---------------------------------------------------------------------------------------------------#
#                          THIS PROGRAM WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)               #
#                                  EMAIL: salar.d.ghashghaei@gmail.com                              #
#####################################################################################################
"""
1. The script performs pushover analysis on a concrete frame using OpenSees
 to optimize the column rebar diameter for a target ductility ratio.
2. Two steel material models (*Steel01* and *Hysteretic*) and two concrete
 models (*Concrete01* and *Concrete02*) are supported.
3. A frame with beam and column elements is created, and nonlinear beam-column
 elements are used for realistic simulation.
4. Rebar areas are calculated based on input diameters, and sectional properties
 are defined using confined and unconfined concrete.
5. The *PUSHOVER\_ANALYSIS* function incrementally applies lateral displacement
 and records force, displacement, and stiffness data.
6. The response is processed to compute the bilinear approximation and extract
 ductility and strength parameters.
7. A Newton-Raphson root-finding algorithm adjusts the column section depth to
 match the target structural ductility ratio.
8. Finite difference approximation is used to estimate the derivative of the
 ductility function with respect to rebar diameter.
9. Each iteration updates the column section depth until convergence is achieved or the
 maximum number of iterations is reached.
10. Convergence is based on the residual of the diameter update (DX) relative
 to a tolerance threshold.
11. The optimal column section depth is printed upon successful convergence.
12. This method allows automated column section depth design optimization
```

23 %



Help Variable Explorer Debugger Plots Files

Console 1/A

```
800.1591306200913

        Optimum Column Section Depth :          800.159131
        Iteration Counts:                       14
        Convergence Residual:
8.0085464881e-08

Total time (s): 311.6406


+==========================+
```

IPython Console History

Inline Conda: anaconda3 (Python 3.12.7) LSP: Python Line 14, Col 29 UTF-8 CRLF RW Mem 40%

NONLINEAR STATIC ANALYSIS (PUSHOVER)


Undeformed and Deformed Shapes - DEFORMED SCALE: 1.00
Undeformed
Deformed
Optimum Column Section Depth : 800.159131
Iteration Counts: 14
Convergence Residual: 8.0085464881e-08
Total time (s): 311.6406
Z [mm]
X [mm]
0
500
1000
1500
2000
2500
3000
0
1000
2000
3000
4000
5000
6000
7000
8000
1
2
3
4


Last Data of BaseShear-Displacement Analysis - Ductility Ratio: 7.3653 - Over Strength Factor: 1.0183
1e6
Base-Shear [N]
Displacement in X [mm]
+==========================+
= Analysis curve fitted =
Disp Base Shear

[[0.00000000e+00 0.00000000e+00]
[8.99441255e+01 2.90071530e+06]
[6.62462079e+02 2.95377982e+06]]
+==========+
+----------+
Structure Elastic Stiffness : 32250.19
Structure Plastic Stiffness : 4458.79
Structure Tangent Stiffness : 92.69
Structure Ductility Ratio : 7.37
Structure Over Strength Factor: 1.02
+----------+
Over Strength Coefficient (Ω0): 1.0183
Displacement Ductility Ratio (μ):7.3653
Ductility Coefficient (Rμ): 7.3653
Structural Behavior Coefficient (R): 7.5000
Curve
Bilinear Fitted


P-M Interaction
1e7
6
5
4
3
2
1
0
Axial Force [N]
0.0
0.2
0.4
0.6
0.8
1.0
1.2
1.4
1.6
1e11
Bending Moment [N.mm]


SHEAR FORCE-DISPLACEMENT DIAGRAM
1e7
0
−1
−2
−3
−4
−5
−6
Shear Force [N]
0
50
100
150
200
250
300
350
400
Displacement in X [mm]


AXIAL FORCE-DISPLACEMENT DIAGRAM
1e7
6
5
4
3
2
1
0
Axial Force [N]
−40
−35
−30
−25
−20
−15
−10
−5
0
Displacement in Y [mm]


MOMENT-ROTATION DIAGRAM
1e11
1.6
1.4
1.2
1.0
0.8
0.6
0.4
0.2
0.0
Moment [kN.mm]
−0.14
−0.12
−0.10
−0.08
−0.06
−0.04
−0.02
0.00
Rotation [rad]


ROTATIONAL STIFFNESS-LATERAL STIFFNESS DIAGRAM
Rotational Stiffness [N.mm/Rad]
2.6 × 10^5
2.4 × 10^5
2.2 × 10^5
2 × 10^5
1.8 × 10^5
1.6 × 10^5
1.1 × 10^12
1.2 × 10^12
1.3 × 10^12
1.4 × 10^12
1.5 × 10^12
Lateral Stiffness in X Dir. [N/mm]


ROTATIONAL STIFFNESS-LATERAL STIFFNESS DIAGRAM
Rotational Stiffness [N.mm/Rad]
10^7
1.1×10^{12}
1.2×10^{12}
1.3×10^{12}
1.4×10^{12}
1.5×10^{12}
Lateral Stiffness in Y Dir. [N/mm]