


>> IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL <<

DETERMINATION OF OPTIMUM STRUCTURAL YIELD STRENGTH FROM ENERGY DISSIPATION CAPACITY INDEX USING FINITE-DIFFERENCE NEWTON ITERATION AND OPENSEES

THIS PROGRAM WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)



$$\text{Structural Ductility Damage Index} = \frac{\Delta_d - \Delta_y}{\Delta_u - \Delta_y}$$


Δ_d = Lateral Displaement from Dynamic Analysis

Δ_y = Lateral Yield Displaement from Pushover Analysis


Δ_u = Lateral Ultimate Displaement from Pushover Analysis

$$P(t) = P_0 e^{-0.05\bar{\omega}t} \sin(\bar{\omega}t)$$


$$m\ddot{u} + c\dot{u} + ku = P(t)$$



ELASTIC MATERIAL



INELASTIC MATERIAL



File Edit Search Source Run Debug Consoles Projects Tools View Help


C:\Users\Dell\Desktop\OPENSEES_FILES\+EIGHT_ANALY...TIMIZATION_DEC...FY_OPTIMIZATION_DEC...SOF.py

FY_OPTIMIZATION_DEC...SOF.py x DISSIPATED_ENERGY_WITH_PLOT_FUN.py x

```
1 #####
2 # >> IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL <<
3 # DETERMINATION OF OPTIMUM YIELD STRENGTH FROM ENERGY DISSIPATION CAPACITY INDEX U
4 # FINITE-DIFFERENCE NEWTON ITERATION
5 #
6 # COMPREHENSIVE NONLINEAR SEISMIC ASSESSMENT OF A SINGLE-DEGREE-FREEDOM STRUCTURE : AN OPEN
7 # FOR STATIC PUSHOVER, CYCLIC DEGRADATION, STATIC TIME-HISTORY AND DYNAMIC TIME-HISTORY
8 #
9 # P(t) = P0 sin(wt)
10 # P(t) = P0 exp(-0.05wt) sin(wt)
11 #
12 # ASSESSMENT OF DUCTILITY DAMAGE INDICES FOR STRUCTURAL ELEMENTS AND SYSTEMS AND EV
13 # OF ENERGY DISSIPATION CAPACITY INDEX
14 #
15 # THIS PYTHON SCRIPT WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)
16 # EMAIL: salar.d.ghashghaei@gmail.com
17 #####
18 """
19 Nonlinear Seismic Performance Assessment of a SDOF:
20 An OpenSeesPy Framework for Material and Geometric Nonlinearity Under Static, Cyclic, and E
21
22 This OpenSeesPy script performs rigorous nonlinear static and dynamic analysis of a SDOF
23 for performance-based earthquake engineering. The 2D model incorporates both material nonl
24 (elastic-perfectly plastic or hysteretic steel with strain hardening)
25 and geometric nonlinearity (corotational truss formulation) to capture P-delta effects
26 and large displacements-essential for collapse assessment.
27
28 Eight analysis protocols are implemented:
29 (1) [PERIOD] : Structural Period
30 (2) [STATIC] : Gravity load analysis establishing dead load state
31 (3) [PUSHOVER] : Displacement-controlled pushover generating full capacity curves
32 and plastic mechanism identification
33 (4) [CYCLIC_DISPLACEMENT] : Symmetric cyclic displacement protocol capturing hysteresis,
34 pinching behavior, and energy dissipation degradation
```

34 %

Force-Displacement Curve



Displacement [m]	Force [N]	Path Type
-0.4	-100000	Loading
-0.2	-50000	Loading
0.0	0	Loading
0.2	100000	Loading
0.4	100000	Loading
0.4	25000	Unloading
0.2	0	Unloading
0.0	0	Unloading
-0.2	-50000	Unloading
-0.4	-100000	Unloading

IPython Console Files Help Variable Explorer Debugger Plots History

OPTIMIZATION PROBLEM FOR ENERGY DISSIPATION CAPACITY INDEX (EDCI)

Spyder (Python 3.12)

File Edit Search Source Run Debug Consoles Projects Tools View Help

C:\Users\ DELL\Desktop\OPENSEES_FILES\+HEIGHT_ANALY...TIMIZATION_DEC1_SDOF\FY_OPTIMIZATION_DEC1_SDOF.py

FY_OPTIMIZATION_DEC1_SDOF.py x DISSIPATED_ENERGY_WITH_PLOT_FUN.py x

```
1 #####
2 # >> IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL <<
3 # DETERMINATION OF OPTIMUM YIELD STRENGTH FROM ENERGY DISSIPATION CAPACITY INDEX I
4 # FINITE-DIFFERENCE NEWTON ITERATION
5 #
6 # COMPREHENSIVE NONLINEAR SEISMIC ASSESSMENT OF A SINGLE-DEGREE-FREEDOM STRUCTURE : AN OPEN
7 # FOR STATIC PUSHOVER, CYCLIC DEGRADATION, STATIC TIME-HISTORY AND DYNAMIC TIME-HISTORY
8 #
9 # P(t) = P0 sin(wt)
10 # P(t) = P0 exp(-0.05wt) sin(wt)
11 #
12 # ASSESSMENT OF DUCTILITY DAMAGE INDICES FOR STRUCTURAL ELEMENTS AND SYSTEMS AND EV
13 # OF ENERGY DISSIPATION CAPACITY INDEX
14 #
15 # THIS PYTHON SCRIPT WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)
16 # EMAIL: salar.d.ghashghaei@gmail.com
17 #####
18 """
19 Nonlinear Seismic Performance Assessment of a SDOF:
20 An OpenSeesPy Framework for Material and Geometric Nonlinearity Under Static, Cyclic, and E
21
22 This OpenSeesPy script performs rigorous nonlinear static and dynamic analysis of a SDOF
23 for performance-based earthquake engineering. The 2D model incorporates both material nonl
24 (elastic-perfectly plastic or hysteretic steel with strain hardening)
25 and geometric nonlinearity (corotational truss formulation) to capture P-delta effects
26 and large displacements-essential for collapse assessment.
27
28 Eight analysis protocols are implemented:
29 (1) [PERIOD] : Structural Period
30 (2) [STATIC] : Gravity load analysis establishing dead load state
31 (3) [PUSHOVER] : Displacement-controlled pushover generating full capacity curves
32 and plastic mechanism identification
33 (4) [CYCLIC_DISPLACEMENT] : Symmetric cyclic displacement protocol capturing hysteresis,
34 pinching behavior, and energy dissipation degradation
```

Console 1/A x

```
+-----+
| lambda | omega | period | frequency |
+-----+
| 9.000e+02 | 30.0000 | 0.2094 | 4.7746 |
+-----+

Time: 20.0000, Displacement: 0.0120 mm, Reaction: -20.00 N

SEISMIC ANALYSIS DONE.

Xmax: 166719.0593285352
Dissipated Energy from Earthquake= 32412.64 N·mm
Dissipated Energy from Cyclic Displacement= 162063.22 N·mm

DISSIPATED ENERGY CAPACITY INDEX: 20.000 [%]

ZONE 2: MINOR DAMAGE

Fmax: -3.704793840597631e-07
DF: -0.0003704793556380537
DX: 2.876851536854367e-11
IT: 7 - RESIDUAL: 2.876851536854367e-11 X: 166719.0583285352

Optimum X: 166719.0583
Iteration Counts: 7
Convergence Residual: 2.8768515369e-11

Total time (s): 60.9844
```

IPython Console Files Help Variable Explorer Debugger Plots History

Inline Conda: anaconda3 (Python 3.12.7) ✓ LSP: Python Line 73, Col 1 UTF-8 CRLF RW Mem 38%

Dissipated Energy from Earthquake= 32412.64 N·m

Dissipated Energy from Cyclic Displacement= 162063.22 N·m

DISSIPATED ENERGY CAPACITY INDEX: 20.000 [%]

ZONE 2: MINOR DAMAGE

Fmax: -3.704793840597631e-07

DF: -0.0003704793556380537

DX: 2.876851536854367e-11


IT: 7 - RESIDUAL: 2.876851536854367e-11 X: 166719.0583285352

Optimum X (YIELD STRENGTH): 166719.0583

Iteration Counts: 7

Convergence Residual: 2.8768515369e-11

Earthquake Response - Dissipated Energy (Convex Hull)



Cyclic Loading - Dissipated Energy (Convex Hull)

