



>> IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL <<

**DETERMINATION OF OPTIMUM
STRUCTURAL ULTIMATE
DISPLACEMENT FROM ENERGY
DISSIPATION CAPACITY INDEX USING
FINITE-DIFFERENCE NEWTON
ITERATION AND OPENSEES**

THIS PROGRAM WRITTEN BY SALAR DELAVAR GHASHGHAEE (QASHQAI)



$$\text{Structural Ductility Damage Index} = \frac{\Delta_d - \Delta_y}{\Delta_u - \Delta_y}$$



Δ_d = Lateral Displacement from Dynamic Analysis

Δ_y = Lateral Yield Displacement from Pushover Analysis


Δ_u = Lateral Ultimate Displacement from Pushover Analysis

$$P(t) = P_0 e^{-0.05\bar{\omega}t} \sin(\bar{\omega}t)$$


$$m\ddot{u} + c\dot{u} + ku = P(t)$$




ELASTIC MATERIAL



INELASTIC MATERIAL





Displacement-based seismic analysis transformation, converting a multi-degree-of-freedom (MDOF) system into an equivalent single-degree-of-freedom (SDOF) system for seismic assessment




$$\Delta_d = \frac{\sum_{i=1}^n m_i \Delta_i^2}{\sum_{i=1}^n m_i \Delta_i} \quad m_{eff} = \frac{\sum_{i=1}^n m_i \Delta_i}{\Delta_d}$$

$$k_{eff} = \frac{\sum_{i=1}^n k_i \Delta_i}{\Delta_d} \quad T_{eff} = \frac{2\pi}{\sqrt{\frac{k_{eff}}{m_{eff}}}}$$





FORCE-DISPLACEMENT CURVE FOR SHEAR-WALL



Spyder (Python 3.12)

File Edit Search Source Run Debug Consoles Projects Tools View Help

C:\Users\De\l\Desktop\OPENSEES_FILES\+EIGHT_ANALY...ANA+P(t)_MDOF_TWO_DSU_OPTIMIZATION_DECI_8_ANA.py

P(t)_MDOF_TWO_DSU...TION_DECI_8_ANA.py

DISSIPATED_ENERGY_WITH_PLOT_FUN.py

```
1 #####
2 # >> IN THE NAME OF ALLAH, THE MOST GRACIOUS, THE MOST MERCIFUL <<
3 # DETERMINATION OF OPTIMUM STRUCTURAL ULTIMATE DISPLACEMENT FROM ENERGY DISSIPATION CAPACIT
4 # FINITE-DIFFERENCE NEWTON ITERATION AND OPENSEES
5 #
6 # COMPREHENSIVE NONLINEAR SEISMIC ASSESSMENT OF A MULTI-DEGREE-FREEDOM STRUCTURE : AN OPENS
7 # FOR STATIC PUSHOVER, CYCLIC DEGRADATION, STATIC TIME-HISTORY AND DYNAMIC TIME-HISTORY
8 #
9 # EACH STORY HAS FRAME AND SHEAR-WALL (OR BRACE) INTERACTION
10 #
11 # EQUIVALENT SDOF SYSTEM DERIVATION VIA DISPLACEMENT-BASED SEISMIC DESIGN PROCEDURE WITH PL
12 #
13 # P(t) = P0 sin(wt)
14 # P(t) = P0 exp(-0.05wt) sin(wt)
15 #
16 # ASSESSMENT OF DUCTILITY DAMAGE INDICES FOR STRUCTURAL ELEMENTS AND SYSTEMS AND EV
17 # OF ENERGY DISSIPATION CAPACITY INDEX
18 #
19 # THIS PYTHON SCRIPT WRITTEN BY SALAR DELAVAR GHASHGHAEI (QASHQAI)
20 # EMAIL: salar.d.ghashghaei@gmail.com
21 #####
22 """
23 Nonlinear Seismic Performance Assessment of a MDOF:
24 An OpenSeesPy Framework for Material and Geometric Nonlinearity Under Static, Cyclic, and E
25
26 This OpenSeesPy script performs rigorous nonlinear static and dynamic analysis of a MDOF
27 for performance-based earthquake engineering. The 2D model incorporates both material nonl
28 (elastic-perfectly plastic or hysteretic steel with strain hardening)
29 and geometric nonlinearity (corotational truss formulation) to capture P-delta effects
30 and large displacements-essential for collapse assessment.
31
32 Eight analysis protocols are implemented:
33 (1) [PERIOD] : Structural Period
34 (2) [STATIC] : Gravity load analysis establishing dead load state
```

...CAPACITY_INDEX\52_MDOF_TWO_DSU_OPTIMIZATION_DECI_8_ANA+

47 %

Cyclic Loading - Dissipated Energy (Convex Hull)

IPython Console

Files

Help

Variable Explorer

Debugger

Plots

History

Inline Conda: anaconda3 (Python 3.12.7) ✓ LSP: Python Line 167, Col 30 UTF-8 CRLF RW Mem 50 %

OPTIMIZATION PROBLEM FOR ENERGY DISSIPATION CAPACITY INDEX (EDCI)

Spyder (Python 3.12)

File Edit Search Source Run Debug Consoles Projects Tools View Help

C:\Users\Dell\Desktop\OPENSEES_FILES\+HEIGHT_ANALY...ANA+P(t)_MDOF_TWO_DSU_OPTIMIZATION_DEC1_8_ANA.py

P(t)_MDOF_TWO_DSU...TION_DEC1_8_ANA.py x DISSIPATED_ENERGY_WITH_PLOT_FUN.py x

```
996 TOTAL MASS = 5000.0 # [kg] Total Mass of Structure
997 #%%
998 # CYCLIC DISPLACEMENT ANALYSIS (STATIC TIME-HISTORY ANALYSIS)
999 MAT_TYPE = 'INELASTIC' # 'ELASTIC' OR 'INELASTIC'
1000
1001 # -----
1002 # FIND THE OPTIMUM VALUE (NEWTON-RAPHSON SOLVER FOR OPTIMAL ULTIMATE DISPLACEMENT)
1003 # -----
1004 import time as TI
1005 import numpy as np
1006
1007 X = 0.1 # Intial Guess for X -> Ultimate Displacement of Structure
1008 ESP = 1e-3 # Finite difference derivative Convergence Tolerance
1009 TOLERANCE = 1e-6 # Convergence Tolerance
1010 RESIDUAL = 100 # Convergence Residual
1011 IT = 0 # Intial Iteration
1012 ITMAX = 100000 # Max. Iteration
1013 DEMAND = 20.0 # [%] Target Value -> ENERGY DISSIPATION CAPACITY INDEX
1014
1015 # Analysis Durations:
1016 starttime = TI.process_time()
1017
1018 while (RESIDUAL > TOLERANCE):
1019     # X -----
1020     ANAL_TYPE = 'CYCLIC_DISPLACEMENT'
1021     DATA = MDOF_TWO(X, MAT_TYPE, TOTAL_MASS, ANAL_TYPE)
1022
1023     (reaction_CP, disp_CP, DI_CP, __, __,
1024      PERIOD_MIN_CP, PERIOD_MAX_CP) = DATA
1025
1026     ANAL_TYPE = 'SEISMIC'
1027     DATA = MDOF_TWO(X, MAT_TYPE, TOTAL_MASS, ANAL_TYPE)
1028     (time_SEI, reaction_SEI, disp_SEI, velo_SEI, acc_SEI, DI_SEI, __, __,
```

Console 1/A x

```
+-----+
| lambda | omega | period | frequency |
+-----+
| 1.463e+04 | 120.9375 | 0.0520 | 19.2478 |
| 7.177e+04 | 267.9069 | 0.0235 | 42.6387 |
+-----+
```

Time: 20.0000, Displacement: 0.0001 mm, Reaction: -136.94 N

SEISMIC ANALYSIS DONE.

Dissipated Energy from Earthquake= 107144.43 N·m
Dissipated Energy from Cyclic Displacement= 537039.39 N·m

DISSIPATED ENERGY CAPACITY INDEX: 19.951 [%]

ZONE 2: MINOR DAMAGE

Fmax: -0.04905571378935747
DF: -48.50787233662501
DX: -6.163404080723617e-07
IT: 10 - RESIDUAL: 6.163404080723617e-07 X: 0.4854119294851071

Optimum X (ULTIMATE DISPLACEMENT): 0.4854
Iteration Counts: 10
Convergence Residual: 6.1634040807e-07

Total time (s): 84.4688

IPython Console Files Help Variable Explorer Debugger Plots History

Inline Conda: anaconda3 (Python 3.12.7) ✓ LSP: Python Line 167, Col 30 UTF-8 CRLF RW Mem 50%

Dissipated Energy from Earthquake= 107144.43 N·m

Dissipated Energy from Cyclic Displacement= 537039.39 N·m

DISSIPATED ENERGY CAPACITY INDEX: 19.951 [%]

ZONE 2: MINOR DAMAGE

Fmax: -0.04905571378935747

DF: -48.50787233662501

DX: -6.163404080723617e-07


IT: 10 - RESIDUAL: 6.163404080723617e-07 X: 0.4854119294851071

Optimum X (ULTIMATE DISPLACEMENT): 0.4854

Iteration Counts: 10

Convergence Residual: 6.1634040807e-07

Total time (s): 84.4688



Cyclic Loading - Dissipated Energy (Convex Hull)

