

# HW2\_096411

May 15, 2022

```
[ ]: import numpy as np
import matplotlib.pyplot as plt
from scipy import stats
import pandas as pd

from sklearn.model_selection import train_test_split
# use seaborn plotting defaults
import seaborn as sns; sns.set()


[ ]: from sklearn.datasets import load_wine
# Read the wine dataset
dataset = load_wine()
df = pd.DataFrame(data=dataset['data'], columns=dataset['feature_names'])
df = df.assign(target=pd.Series(dataset['target']).values)

[ ]: # Filter the irrelevant columns
df = df[['alcohol', 'magnesium', 'target']]
# Filter the irrelevant label
df = df[df.target != 0]


[ ]: from sklearn.svm import SVC

[ ]: train_df, val_df = train_test_split(df, test_size=30, random_state=3)

[ ]: #1.1
sns.scatterplot(data=train_df, x='alcohol', y='magnesium',
               hue='target', palette=['c', 'm'])
plt.title("train set")
plt.show()
```



```
[ ]: #1.2
sns.scatterplot(data=val_df, x='alcohol', y='magnesium',
               hue='target', palette=['c', 'm'])
plt.title("val set")
plt.show()
```



#1-

hard-SVM

```
[ ]: #2
from sklearn.svm import SVC

def plot_svc_decision_function(model, ax=None, plot_support=True):
    """Plot the decision function for a 2D SVC"""
    if ax is None:
        ax = plt.gca()
    xlim = ax.get_xlim()
    ylim = ax.get_ylim()

    # create grid to evaluate model
    x = np.linspace(xlim[0], xlim[1], 30)
    y = np.linspace(ylim[0], ylim[1], 30)
    Y, X = np.meshgrid(y, x)
    xy = np.vstack([X.ravel(), Y.ravel()]).T
    P = model.decision_function(xy).reshape(X.shape)

    # plot decision boundary and margins
    ax.contour(X, Y, P, colors='k',
               levels=[-1, 0, 1], alpha=0.5,
               linestyles=['--', '-', '--'])
```

```

# plot support vectors
if plot_support:
    ax.scatter(model.support_vectors_[0],
               model.support_vectors_[1],
               s=50, linewidth=1, facecolors='none', edgecolor='black');
ax.set_xlim(xlim)
ax.set_ylim(ylim)

```



```


[ ]: #2.1
C=[0.1, 0.05, 0.01]
for c in C:
    model = SVC(kernel='linear',C=c)

    sns.scatterplot(data=train_df, x="alcohol", y="magnesium",
                    hue="target",palette=['c','m'])
    X_t=train_df.to_numpy()
    y_t=X_t[:,-1]
    X_t=np.delete(X_t,2,1)
    model.fit(X_t,y_t)

    plot_svc_decision_function(model)
    plt.legend()
    s1= "train_set for C=%.2f"
    plt.title(s1%c)
    plt.grid()
    plt.show()

```








```
[ ]: #2.2
C=[0.1, 0.05, 0.01]
for c in C:
    model = SVC(kernel='linear',C=c)

    sns.scatterplot(data=val_df, x="alcohol", y="magnesium", hue="target", palette=['c', 'm'])
    X_V=val_df.to_numpy()
    y_V=X_V[:, -1]
    X_V=np.delete(X_V, 2, 1)
    model.fit(X_V, y_V)

    plot_svc_decision_function(model)
    plt.legend()
    s1= "Val_set for C=%.2f"
    plt.title(s1%c)
    plt.grid()
    plt.show()
```






```
[ ]: #4
C=[0.1, 0.05, 0.01]
train=[]
val=[]
margin=[]
for c in C:
    model=SVC(kernel='linear',C=c)
    model.fit(train_df[['alcohol','magnesium']],train_df['target'])
    train.append(model.score(train_df[['alcohol','magnesium']],train_df['target']))
    margin.append(1/(np.linalg.norm(model.coef_)))
fig,ax=plt.subplots()

plt.title('margin(C)')
plt.xlabel('C')
plt.ylabel('margin')
ax.plot(C,margin,c='m')
plt.grid
plt.show()
```






```
[ ]: #5


train_error=[]
val_error=[]
for c in C:
    model=SVC(kernel='linear',C=c)
    model.fit(train_df[['alcohol','magnesium']],train_df['target'])
    train_error.append(1-model.
    ↪score(train_df[['alcohol','magnesium']],train_df['target']))
    val_error.append(1-model.
    ↪score(val_df[['alcohol','magnesium']],val_df['target']))
fig,ax=plt.subplots()
plt.title('Error(C)')
plt.xlabel('C')
plt.ylabel("Error")
ax.plot(C,train_error,c='m',label='train error')
ax.plot(C,val_error,c='c',label='val error')
plt.grid()
plt.legend()
plt.plot()
```

```
[ ]: [ ]
```



```
[ ]: #6
degree=[2,3,4,5,6,7,8]
train_error=[]
val_error=[]
for d in degree:
    model=SVC(kernel='poly',C=1,degree=d)
    model.fit(train_df[['alcohol','magnesium']],train_df['target'])
    train_error.append(1-model.
    ↪score(train_df[['alcohol','magnesium']],train_df['target']))
    val_error.append(1-model.
    ↪score(val_df[['alcohol','magnesium']],val_df['target']))
fig,ax=plt.subplots()
plt.title('Error(degree)')
plt.xlabel('degree')
plt.ylabel("Error")
ax.plot(degree,train_error,c='m',label='train error')
ax.plot(degree,val_error,c='c',label='val error')
plt.grid()
plt.legend()
plt.plot()
```

```
[ ]: []
```



```
[ ]: #7.1
model = SVC(kernel='poly',degree=3,C=1)

sns.scatterplot(data=train_df, x="alcohol", y="magnesium",
    hue="target",palette=['c','m'])
X_t=train_df.to_numpy()
y_t=X_t[:,-1]
X_t=np.delete(X_t,2,1)
model.fit(X_t,y_t)

plot_svc_decision_function(model)
plt.legend()

plt.title('train_set for argmax_degree=3')
plt.grid()
plt.show()

#7
model = SVC(kernel='poly',degree=4,C=1)

sns.scatterplot(data=train_df, x="alcohol", y="magnesium",
    hue="target",palette=['c','m'])
X_t=train_df.to_numpy()
```


```


y_t=X_t[:,-1]
X_t=np.delete(X_t,2,1)
model.fit(X_t,y_t)

plot_svc_decision_function(model)
plt.legend()

plt.title('train_set for argmin_degree=4')
plt.grid()
plt.show()

```





```
[ ]: #7.2
#7
model = SVC(kernel='poly',degree=3,C=1)

sns.scatterplot(data=val_df, x="alcohol", y="magnesium",
                hue="target",palette=['c','m'])
X_V=val_df.to_numpy()
y_V=X_V[:,-1]
X_V=np.delete(X_V,2,1)
model.fit(X_V,y_V)

plot_svc_decision_function(model)
plt.legend()

plt.title('Val_set for argmax_degree=3')
plt.grid()
plt.show()

model2 = SVC(kernel='poly',degree=5,C=1)

sns.scatterplot(data=val_df, x="alcohol", y="magnesium",
                hue="target",palette=['c','m'])
X_V=val_df.to_numpy()
```

```

y_V=X_V[:,-1]
X_V=np.delete(X_V,2,1)
model2.fit(X_V,y_V)

plot_svc_decision_function(model2)
plt.legend()

plt.title('Val_set for argmin_degree=5')
plt.grid()
plt.show()

```

