

Parallel and Distributed Computing

CS3006 (BCS-6C/6D)

Lecture 19

Instructor: Dr. Syed Mohammad Irteza

Assistant Professor, Department of Computer Science, FAST

04 April, 2023

Previous Lecture

- Basic Communication Operations
 - Scatter
 - Gather
- All-to-all Personalized Communication
 - Total exchange
- MPI
 - Introduction
 - Basic routines/procedures

Message Passing Interface (MPI)

- The minimal set of MPI routines:

<code>MPI_Init</code>	Initializes MPI.
<code>MPI_Finalize</code>	Terminates MPI.
<code>MPI_Comm_size</code>	Determines the number of processes.
<code>MPI_Comm_rank</code>	Determines the label of calling process.
<code>MPI_Send</code>	Sends a message.
<code>MPI_Recv</code>	Receives a message.

Starting and Terminating the MPI Library

- `MPI_Init` is called prior to any calls to other MPI routines. Its purpose is to *initialize the MPI environment*.
- `MPI_Finalize` is called at the end of the computation, and it performs various *clean-up tasks to terminate the MPI environment*.
- The prototypes of these two functions are:

```
int MPI_Init(int *argc, char ***argv)
```

```
int MPI_Finalize()
```

- `MPI_Init` also strips off any MPI related *command-line arguments*.
- All MPI routines, data-types, and constants are prefixed by “`MPI_`”. The *return code for successful completion* is `MPI_SUCCESS`.

Communicators

- A communicator defines a *communication domain*
 - a set of processes that can communicate with each other.
- Information about communication domains is stored in variables of type `MPI_Comm`.
- Communicators are used as arguments to all message transfer MPI routines.
- A *process can belong to many different* (possibly overlapping) communication domains.
- MPI defines a default communicator called `MPI_COMM_WORLD` which *includes all the processes*.

Querying Information

- The `MPI_Comm_size` and `MPI_Comm_rank` functions are used to determine the *number of processes* and the *label of the calling process*, respectively.
- The calling sequences of these routines are as follows:

```
int MPI_Comm_size(MPI_Comm comm, int *size)
int MPI_Comm_rank(MPI_Comm comm, int *rank)
```
- The rank of a process is an integer that ranges from zero up to the size of the communicator minus one.

Hello World Program

```
#include <mpi.h>
main(int argc, char *argv[])
{
    int np, myrank;
    MPI_Init(&argc, &argv);
    MPI_Comm_size(MPI_COMM_WORLD, &np);
    MPI_Comm_rank(MPI_COMM_WORLD, &myrank);
    printf("From process %d out of %d, HelloWorld!\n",
myrank, np);
    MPI_Finalize();
}
```

MPI Setup with Windows & Visual Studio

- <https://medium.com/geekculture/configuring-mpi-on-windows-10-and-executing-the-hello-world-program-in-visual-studio-code-2019-879776f6493f>

Sending and Receiving Messages

- The basic functions for *sending* and *receiving* messages in MPI are the `MPI_Send` and `MPI_Recv`, respectively.

- The calling sequences of these routines are as follows:

```
int MPI_Send(void *buf, int count, MPI_Datatype datatype, int
dest, int tag, MPI_Comm comm)
```

```
int MPI_Recv(void *buf, int count, MPI_Datatype datatype, int
source, int tag, MPI_Comm comm, MPI_Status *status)
```

- MPI provides *equivalent datatypes for all C datatypes*. This is done for *portability* reasons.
- The *message-tag* can take values ranging from zero up to the MPI defined constant `MPI_TAG_UB`.

MPI Datatypes

MPI Datatype	C Datatype
MPI_CHAR	signed char
MPI_SHORT	signed short int
MPI_INT	signed int
MPI_LONG	signed long int
MPI_UNSIGNED_CHAR	unsigned char
MPI_UNSIGNED_SHORT	unsigned short int
MPI_UNSIGNED	unsigned int
MPI_UNSIGNED_LONG	unsigned long int
MPI_FLOAT	float
MPI_DOUBLE	double
MPI_LONG_DOUBLE	long double
MPI_BYTE	

Sending and Receiving Messages

- MPI allows specification of **wildcard** arguments for both source and tag.
- If source is set to `MPI_ANY_SOURCE`, then any process of the communication domain can be the source of the message.
- If tag is set to `MPI_ANY_TAG`, then messages with any tag are accepted.
- On the receive side, the message must be of length equal to or less than the length field specified.

Sending and Receiving Messages

- On the receiving end, the status variable can be used to get information about the `MPI_Recv` operation.

- The corresponding data structure contains:

```
typedef struct MPI_Status {  
    int MPI_SOURCE;  
    int MPI_TAG;  
    int MPI_ERROR; };
```

- `MPI_Status` is usually used to take source and tag information in a 'receive' with wildcard entries on the corresponding positions.

Send/Receive Messages: Example Program

```
if (my_rank==0) {
    int sendBuff=10, tag=1, dest=1;
    printf("Process:%d is sending \'%d\' to process:%d \n", my_rank, sendBuff, dest);

    MPI_Send(&sendBuff, 1, MPI_INT, dest, tag, MPI_COMM_WORLD);

} else if (my_rank==1) {
    int recvBuff;
    int source=0, tag=1;

    MPI_Recv(&recvBuff, 1, MPI_INT, source, tag, MPI_COMM_WORLD, &status);
    printf("Process:%d is has received \'%d\' from process:%d\n",my_rank, recvBuff,
source);

} else {
}
```

Ensuring Operation Semantics

- Consider the following code segments:

P0

```
a = 100;  
send(&a, 1, 1);  
a = 0;
```

P1

```
receive(&a, 1, 0)  
printf("%d\n", a);
```

- The semantics of the send operation require that the value received by process P1 must be 100 as opposed to 0.
- There may be an issue if infrastructure has **network interface hardware** for asynchronous send/receive without the involvement of CPU.
- After programming the network hardware, the control may return immediately to the next instruction, causing changes in the buffer before it is communicated to P1.
- Solutions?

Blocking and non-blocking Operations

Solutions (Assigned Reading 6.2)

1. *Blocking without Buffering*

- Simple and easy to enforce
- Suffers idling and deadlocks

2. *Blocking with Buffering*


- Reduces process idling at the cost of buffer management overheads
- In **presence** of communication hardware, it stores message in a buffer at sender, and communication is done asynchronously when receiver approaches to corresponding receive.
- In **absence** of communication hardware, sender interrupts the receiver and deposits data in buffer at receiver.
- **Issues:** (bounded buffer and unexpected delays + blocking receives)

3. *Non-blocking with and without buffers*

- Difficult to ensure semantics
- Almost entirely masks the communication overheads
- Recommended not to use


Blocking and non-blocking Operations

Figure 6.1. Handshake for a blocking non-buffered send/receive operation. It is easy to see that in cases where sender and receiver do not reach communication point at similar times, there can be considerable idling overheads.




Blocking and non-blocking Operations

Figure 6.2. Blocking buffered transfer protocols: (a) in the presence of communication hardware with buffers at send and receive ends; and (b) in the absence of communication hardware, sender interrupts receiver and deposits data in buffer at receiver end.



Blocking and non-blocking Operations

- Non-blocking without a buffer



Blocking and non-blocking Operations

- **Space of possible protocols for send and receive operations**

	Blocking Operations	Non-Blocking Operations
Buffered	<p>Sending process returns after data has been copied into communication buffer</p>	<p>Sending process returns after initiating DMA transfer to buffer. This operation may not be completed on return</p>
Non-Buffered	<p>Sending process blocks until matching receive operation has been encountered</p> <p>Send and Receive semantics assured by corresponding operation</p>	<p>Programmer must explicitly ensure semantics by polling to verify completion</p>

MPI Rules for Send/Receive

- MPI usually uses blocking buffered Send only if there is enough buffer space to store whole message
- Otherwise, it uses blocking send
- Receive is always blocking

Deadlocks and Avoidance

- Let's see an example: **deadlocks.c**

Deadlocks (Circular)

- Consider the following piece of code, in which process i sends a message to process $i + 1$ (modulo the number of processes) and receives a message from process $i - 1$ (modulo the number of processes).

```
int a[10], b[10], npes, myrank;  
MPI_Status status;  
...  
MPI_Comm_size(MPI_COMM_WORLD, &npes);  
MPI_Comm_rank(MPI_COMM_WORLD, &myrank);  
  
MPI_Send(a, 10, MPI_INT, (myrank+1) % npes, 1, MPI_COMM_WORLD);  
MPI_Recv(b, 10, MPI_INT, (myrank-1+npes) % npes, 1, MPI_COMM_WORLD, &status);
```

Once again, we have a deadlock if MPI_Send is blocking

Deadlocks (Solution)

- We can break the circular wait to avoid deadlocks as follows:

```
int a[10], b[10], npes, myrank;
MPI_Status status;
...
MPI_Comm_size(MPI_COMM_WORLD, &npes);
MPI_Comm_rank(MPI_COMM_WORLD, &myrank);
if (myrank%2 == 1) {
    MPI_Send(a, 10, MPI_INT, (myrank+1)%npes, 1, MPI_COMM_WORLD);
    MPI_Recv(b, 10, MPI_INT, (myrank-1+npes)%npes, 1, MPI_COMM_WORLD, &status);
} else {
    MPI_Recv(b, 10, MPI_INT, (myrank-1+npes)%npes, 1, MPI_COMM_WORLD, &status);
    MPI_Send(a, 10, MPI_INT, (myrank+1)%npes, 1, MPI_COMM_WORLD);
}
...
```

Avoiding deadlocks using Simultaneous sendReceive operation

- To avoid earlier deadlocks, MPI provides **MPI_Sendrecv** function
 - It can both send and receive message
 - Does not suffer from the circular deadlock problem
 - One can think of MPI_Sendrecv as allowing data to travel for both send and receive simultaneously.

```
int MPI_Sendrecv(void *sendbuf, int sendcount,  
    MPI_Datatype senddatatype, int dest, int sendtag, void  
    *recvbuf, int recvcount, MPI_Datatype recvdatatype, int  
    source, int recvtag, MPI_Comm comm, MPI_Status *status)
```

- **Programming example:** sendReceive_simult.c

Avoiding deadlocks using Simultaneous sendReceive operation

- **MPI_Sendrecv_replace** function
 - If we wish to use the same buffer for both send and receive
 - First sends value[s] of current buffer and then overwrites them with received ones
- **Syntax**

```
int MPI_Sendrecv_replace(void *buf, int count,  
    MPI_Datatype datatype, int dest, int sendtag, int  
    source, int recvtag, MPI_Comm comm, MPI_Status  
    *status)
```


Sorting in the Parallel Era.....

- Can we efficiently apply a Bubble-Sort type of sorting algorithm when the individual values are dispersed across different machines (processes)?

References

1. Slides of Dr. Rana Asif Rehman & Dr. Haroon Mahmood
2. Kumar, V., Grama, A., Gupta, A., & Karypis, G. (1994). *Introduction to parallel computing* (Vol. 110). Redwood City, CA: Benjamin/Cummings.
3. Quinn, M. J. *Parallel Programming in C with MPI and OpenMP*, (2003).

Helpful Links:

1. <https://mpitutorial.com/tutorials/mpi-send-and-receive/>
2. <https://medium.com/geekculture/configuring-mpi-on-windows-10-and-executing-the-hello-world-program-in-visual-studio-code-2019-879776f6493f>