

Satisfiability Checking

Propositional Logic

Prof. Dr. Erika Ábrahám

RWTH Aachen University
Informatik 2
LuFG Theory of Hybrid Systems

WS 16/17

The slides are partly taken from:

www.decision-procedures.org/slides/

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$.
We write ***APForm*** for the set of all propositional logic formulae.

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$.
We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

$$\perp \quad :=$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

$$\perp := (a \wedge \neg a)$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{array}{ll} \perp & := (a \wedge \neg a) \\ \top & := \end{array}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned}\perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a)\end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write ***APForm*** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$.
We write **APForm** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= \end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$.
We write **APForm** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write **APForm** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= \end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$.
We write **APForm** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned}\perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= ((\varphi_1 \rightarrow \varphi_2) \wedge (\varphi_2 \rightarrow \varphi_1))\end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$. We write **APForm** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= ((\varphi_1 \rightarrow \varphi_2) \wedge (\varphi_2 \rightarrow \varphi_1)) \\ (\varphi_1 \oplus \varphi_2) &:= \end{aligned}$$

Syntax of propositional logic

Abstract syntax of well-formed propositional formulae:

$$\varphi := a \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

where AP is a set of (atomic) **propositions** (Boolean variables) and $a \in AP$.
We write **APForm** for the set of all propositional logic formulae.

Syntactic sugar:

$$\begin{aligned} \perp &:= (a \wedge \neg a) \\ \top &:= (a \vee \neg a) \\ (\varphi_1 \vee \varphi_2) &:= \neg((\neg\varphi_1) \wedge (\neg\varphi_2)) \\ (\varphi_1 \rightarrow \varphi_2) &:= ((\neg\varphi_1) \vee \varphi_2) \\ (\varphi_1 \leftrightarrow \varphi_2) &:= ((\varphi_1 \rightarrow \varphi_2) \wedge (\varphi_2 \rightarrow \varphi_1)) \\ (\varphi_1 \oplus \varphi_2) &:= (\varphi_1 \leftrightarrow (\neg\varphi_2)) \end{aligned}$$

- Examples of **well-formed** formulae:

- $(\neg a)$
- $(\neg(\neg a))$
- $(a \wedge (b \wedge c))$
- $(a \rightarrow (b \rightarrow c))$

- Examples of **well-formed** formulae:

- $(\neg a)$
- $(\neg(\neg a))$
- $(a \wedge (b \wedge c))$
- $(a \rightarrow (b \rightarrow c))$

- We omit parentheses whenever we may restore them through operator precedence:

binds stronger



$\neg \quad \wedge \quad \vee \quad \rightarrow \quad \leftrightarrow$

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

Structures for predicate logic:

- The **domain** is $\mathbb{B} = \{0, 1\}$.
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

Structures for predicate logic:

- The **domain** is $\mathbb{B} = \{0, 1\}$.
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

Example: $AP = \{a, b\}, \alpha(a) = 0, \alpha(b) = 1$

Structures for predicate logic:

- The **domain** is $\mathbb{B} = \{0, 1\}$.
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

Example: $AP = \{a, b\}, \alpha(a) = 0, \alpha(b) = 1$

Equivalently, we can see an assignment α as a set of variables ($\alpha \in 2^{AP}$), defining the variables from the set to be true and the others false.

Semantics: Assignments

Structures for predicate logic:

- The **domain** is $\mathbb{B} = \{0, 1\}$.
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

Example: $AP = \{a, b\}, \alpha(a) = 0, \alpha(b) = 1$

Equivalently, we can see an assignment α as a set of variables ($\alpha \in 2^{AP}$), defining the variables from the set to be true and the others false.

Example: $AP = \{a, b\}, \alpha = \{b\}$

Structures for predicate logic:

- The **domain** is $\mathbb{B} = \{0, 1\}$.
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

Example: $AP = \{a, b\}, \alpha(a) = 0, \alpha(b) = 1$

Equivalently, we can see an assignment α as a set of variables ($\alpha \in 2^{AP}$), defining the variables from the set to be true and the others false.

Example: $AP = \{a, b\}, \alpha = \{b\}$

An assignment can also be seen as being of type $\alpha \in \{0, 1\}^{AP}$, if we have an order on the propositions.

Semantics: Assignments

Structures for predicate logic:

- The **domain** is $\mathbb{B} = \{0, 1\}$.
- The **interpretation** assigns Boolean values to the variables:

$$\alpha : AP \rightarrow \{0, 1\}$$

We call these special interpretations **assignments** and use *Assign* to denote the set of all assignments.

Example: $AP = \{a, b\}, \alpha(a) = 0, \alpha(b) = 1$

Equivalently, we can see an assignment α as a set of variables ($\alpha \in 2^{AP}$), defining the variables from the set to be true and the others false.

Example: $AP = \{a, b\}, \alpha = \{b\}$

An assignment can also be seen as being of type $\alpha \in \{0, 1\}^{AP}$, if we have an order on the propositions.

Example: $AP = \{a, b\}, \alpha = 01$

Only the projected assignment matters...

- Let $\alpha_1, \alpha_2 \in \text{Assign}$ and $\varphi \in \text{APForm}$.
- Let $AP(\varphi)$ be the atomic propositions in φ .
- Clearly $AP(\varphi) \subseteq AP$.
- **Lemma:** if $\alpha_1|_{AP(\varphi)} = \alpha_2|_{AP(\varphi)}$, then



Projection

$$(\alpha_1 \text{ satisfies } \varphi) \quad \text{iff} \quad (\alpha_2 \text{ satisfies } \varphi)$$

- We will assume, for simplicity, that $AP = AP(\varphi)$.

Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.

Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators.
They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators.
They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

p	q	$\neg p$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$p \oplus q$
0	0	1	0	0	1	1	0
0	1	1	0	1	1	0	1
1	0	0	0	1	0	0	1
1	1	0	1	1	1	1	0

Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

p	q	$\neg p$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$p \oplus q$
0	0	1	0	0	1	1	0
0	1	1	0	1	1	0	1
1	0	0	0	1	0	0	1
1	1	0	1	1	1	1	0

Each possible assignment is covered by a line of the truth table.

α **satisfies** φ iff in the line for α and the column for φ the entry is 1.

Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

p	q	$\neg p$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$p \oplus q$
0	0	1	0	0	1	1	0
0	1	1	0	1	1	0	1
1	0	0	0	1	0	0	1
1	1	0	1	1	1	1	0

Each possible assignment is covered by a line of the truth table.

α **satisfies** φ iff in the line for α and the column for φ the entry is 1.

Q: How many binary operators can we define that have different semantics?

Semantics I: Truth tables

- **Truth tables** define the semantics (=meaning) of the operators. They can be used to define the semantics of formulae inductively over their structure.
- Convention: 0 = false, 1 = true

p	q	$\neg p$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$p \oplus q$
0	0	1	0	0	1	1	0
0	1	1	0	1	1	0	1
1	0	0	0	1	0	0	1
1	1	0	1	1	1	1	0

Each possible assignment is covered by a line of the truth table.

α **satisfies** φ iff in the line for α and the column for φ the entry is 1.

Q: How many binary operators can we define that have different semantics?

A: 16

Semantics I: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.

Semantics I: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.
- Let $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ be an assignment with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

Semantics I: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.
- Let $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ be an assignment with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.
- Q: Does α satisfy φ ?

Semantics I: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.
- Let $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ be an assignment with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.
- Q: Does α satisfy φ ?
- A1: Compute with truth table:

a	b	c	$b \rightarrow c$	$a \vee (b \rightarrow c)$
0	0	0	1	1
0	0	1	1	1
0	1	0	0	0
0	1	1	1	1
1	0	0	1	1
1	0	1	1	1
1	1	0	0	1
1	1	1	1	1

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \textit{Assign} \times \textit{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$$\alpha \models p$$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$$\alpha \models p \quad \text{iff} \quad \alpha(p) = \text{true}$$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$$\begin{array}{ll} \alpha \models p & \text{iff } \alpha(p) = \text{true} \\ \alpha \models \neg\varphi & \end{array}$$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$$\begin{array}{ll} \alpha \models p & \text{iff } \alpha(p) = \text{true} \\ \alpha \models \neg\varphi & \text{iff } \alpha \not\models \varphi \end{array}$$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$ iff $\alpha(p) = \text{true}$

$\alpha \models \neg\varphi$ iff $\alpha \not\models \varphi$

$\alpha \models \varphi_1 \wedge \varphi_2$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	iff	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	iff	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	iff	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg\varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1 \text{ and } \alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$		

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg\varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	iff	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	iff	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	iff	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	iff	$\alpha \models \varphi_1$ or $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$		

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	iff	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	iff	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	iff	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	iff	$\alpha \models \varphi_1$ or $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	iff	$\alpha \models \varphi_1$ implies $\alpha \models \varphi_2$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>implies</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \leftrightarrow \varphi_2$		

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	<i>iff</i>	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	<i>iff</i>	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>and</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>or</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>implies</i> $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \leftrightarrow \varphi_2$	<i>iff</i>	$\alpha \models \varphi_1$ <i>iff</i> $\alpha \models \varphi_2$

Semantics II: Satisfaction relation

Satisfaction relation: $\models \subseteq \text{Assign} \times \text{APForm}$

Instead of $(\alpha, \varphi) \in \models$ we write $\alpha \models \varphi$ and say that

- α satisfies φ or
- φ holds for α or
- α is a model of φ .

\models is defined recursively:

$\alpha \models p$	iff	$\alpha(p) = \text{true}$
$\alpha \models \neg \varphi$	iff	$\alpha \not\models \varphi$
$\alpha \models \varphi_1 \wedge \varphi_2$	iff	$\alpha \models \varphi_1$ and $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \vee \varphi_2$	iff	$\alpha \models \varphi_1$ or $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \rightarrow \varphi_2$	iff	$\alpha \models \varphi_1$ implies $\alpha \models \varphi_2$
$\alpha \models \varphi_1 \leftrightarrow \varphi_2$	iff	$\alpha \models \varphi_1$ iff $\alpha \models \varphi_2$

Note: More elegant but semantically equivalent to truth tables.

Semantics II: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.

Semantics II: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.
- Let $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ be an assignment with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

Semantics II: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.
- Let $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ be an assignment with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.
- Q: Does α satisfy φ ?

Semantics II: Example

- Let φ be defined as $(a \vee (b \rightarrow c))$.
- Let $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ be an assignment with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.
- Q: Does α satisfy φ ?

A2: Compute with the satisfaction relation:

$$\alpha \models (a \vee (b \rightarrow c))$$

$$\text{iff } \alpha \models a \text{ or } \alpha \models (b \rightarrow c)$$

$$\text{iff } \alpha \models a \text{ or } (\alpha \models b \text{ implies } \alpha \models c)$$

$$\text{iff } 0 \text{ or } (0 \text{ implies } 1)$$

$$\text{iff } 0 \text{ or } 1$$

$$\text{iff } 1$$

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment $\alpha : AP \rightarrow \{0, 1\}$ is a model of a propositional logic formula $\varphi \in APForm$:

Semantics III: The algorithmic view

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment $\alpha : AP \rightarrow \{0, 1\}$ is a model of a propositional logic formula $\varphi \in APForm$:

```
Eval( $\alpha, \varphi$ ) {  
  if  $\varphi \equiv a$  return  $\alpha(a)$ ;  
  if  $\varphi \equiv (\neg\varphi_1)$  return not Eval( $\alpha, \varphi_1$ );  
  if  $\varphi \equiv (\varphi_1 \text{ op } \varphi_2)$   
    return Eval( $\alpha, \varphi_1$ ) [op] Eval( $\alpha, \varphi_2$ );  
}
```

Semantics III: The algorithmic view

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment $\alpha : AP \rightarrow \{0, 1\}$ is a model of a propositional logic formula $\varphi \in APForm$:

```
Eval( $\alpha, \varphi$ ) {  
    if  $\varphi \equiv a$  return  $\alpha(a)$ ;  
    if  $\varphi \equiv (\neg\varphi_1)$  return not Eval( $\alpha, \varphi_1$ );  
    if  $\varphi \equiv (\varphi_1 \text{ op } \varphi_2)$   
        return Eval( $\alpha, \varphi_1$ ) [op] Eval( $\alpha, \varphi_2$ );  
}
```

- Equivalent to the \models relation, but from the algorithmic view.

Semantics III: The algorithmic view

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment $\alpha : AP \rightarrow \{0, 1\}$ is a model of a propositional logic formula $\varphi \in APForm$:

```
Eval( $\alpha, \varphi$ ) {  
    if  $\varphi \equiv a$  return  $\alpha(a)$ ;  
    if  $\varphi \equiv (\neg\varphi_1)$  return not Eval( $\alpha, \varphi_1$ );  
    if  $\varphi \equiv (\varphi_1 \text{ op } \varphi_2)$   
        return Eval( $\alpha, \varphi_1$ ) [op] Eval( $\alpha, \varphi_2$ );  
}
```

- Equivalent to the \models relation, but from the algorithmic view.
- Q: Complexity?

Semantics III: The algorithmic view

- Using the satisfaction relation we can define an **algorithm** for the problem to decide whether an assignment $\alpha : AP \rightarrow \{0, 1\}$ is a model of a propositional logic formula $\varphi \in APForm$:

```
Eval( $\alpha, \varphi$ ) {  
    if  $\varphi \equiv a$  return  $\alpha(a)$ ;  
    if  $\varphi \equiv (\neg\varphi_1)$  return not Eval( $\alpha, \varphi_1$ );  
    if  $\varphi \equiv (\varphi_1 \text{ op } \varphi_2)$   
        return Eval( $\alpha, \varphi_1$ ) [op] Eval( $\alpha, \varphi_2$ );  
}
```

- Equivalent to the \models relation, but from the algorithmic view.
- Q: Complexity? A: **Polynomial** (time and space).

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$
- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

Semantics III: Example

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $Eval(\alpha, \varphi) =$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $Eval(\alpha, \varphi) = Eval(\alpha, a) \text{ or } Eval(\alpha, b \rightarrow c) =$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $Eval(\alpha, \varphi) = Eval(\alpha, a) \text{ or } Eval(\alpha, b \rightarrow c) =$
 $0 \text{ or } (Eval(\alpha, b) \text{ implies } Eval(\alpha, c)) =$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \end{aligned}$$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \\ &0 \text{ or } 1 = \end{aligned}$$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \\ &0 \text{ or } 1 = \\ &1 \end{aligned}$$

- Recall our example

- $\varphi = (a \vee (b \rightarrow c))$

- $\alpha : \{a, b, c\} \rightarrow \{0, 1\}$ with $\alpha(a) = 0$, $\alpha(b) = 0$, and $\alpha(c) = 1$.

- $$\begin{aligned} \text{Eval}(\alpha, \varphi) &= \text{Eval}(\alpha, a) \text{ or } \text{Eval}(\alpha, b \rightarrow c) = \\ &0 \text{ or } (\text{Eval}(\alpha, b) \text{ implies } \text{Eval}(\alpha, c)) = \\ &0 \text{ or } (0 \text{ implies } 1) = \\ &0 \text{ or } 1 = \\ &1 \end{aligned}$$

- Hence, $\alpha \models \varphi$.

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{\text{Assign}}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$sat(a) \quad =$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{\text{Assign}}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\text{sat}(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} sat(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ sat(\neg\varphi_1) &= \end{aligned}$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} sat(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ sat(\neg\varphi_1) &= Assign \setminus sat(\varphi_1) \end{aligned}$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} \text{sat}(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ \text{sat}(\neg\varphi_1) &= \text{Assign} \setminus \text{sat}(\varphi_1) \\ \text{sat}(\varphi_1 \wedge \varphi_2) &= \end{aligned}$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$sat(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$sat(\neg\varphi_1) = Assign \setminus sat(\varphi_1)$$

$$sat(\varphi_1 \wedge \varphi_2) = sat(\varphi_1) \cap sat(\varphi_2)$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} \text{sat}(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ \text{sat}(\neg\varphi_1) &= \text{Assign} \setminus \text{sat}(\varphi_1) \\ \text{sat}(\varphi_1 \wedge \varphi_2) &= \text{sat}(\varphi_1) \cap \text{sat}(\varphi_2) \\ \text{sat}(\varphi_1 \vee \varphi_2) &= \end{aligned}$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function **$sat : APForm \rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$sat(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$sat(\neg\varphi_1) = Assign \setminus sat(\varphi_1)$$

$$sat(\varphi_1 \wedge \varphi_2) = sat(\varphi_1) \cap sat(\varphi_2)$$

$$sat(\varphi_1 \vee \varphi_2) = sat(\varphi_1) \cup sat(\varphi_2)$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{Assign}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} \text{sat}(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ \text{sat}(\neg\varphi_1) &= \text{Assign} \setminus \text{sat}(\varphi_1) \\ \text{sat}(\varphi_1 \wedge \varphi_2) &= \text{sat}(\varphi_1) \cap \text{sat}(\varphi_2) \\ \text{sat}(\varphi_1 \vee \varphi_2) &= \text{sat}(\varphi_1) \cup \text{sat}(\varphi_2) \\ \text{sat}(\varphi_1 \rightarrow \varphi_2) &= \end{aligned}$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : APForm \rightarrow 2^{Assign}**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\text{sat}(a) = \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP$$

$$\text{sat}(\neg\varphi_1) = \text{Assign} \setminus \text{sat}(\varphi_1)$$

$$\text{sat}(\varphi_1 \wedge \varphi_2) = \text{sat}(\varphi_1) \cap \text{sat}(\varphi_2)$$

$$\text{sat}(\varphi_1 \vee \varphi_2) = \text{sat}(\varphi_1) \cup \text{sat}(\varphi_2)$$

$$\text{sat}(\varphi_1 \rightarrow \varphi_2) = (\text{Assign} \setminus \text{sat}(\varphi_1)) \cup \text{sat}(\varphi_2)$$

Satisfying assignments

- Intuition: each formula specifies a **set of assignments** satisfying it.
- Remember: *Assign* denotes the set of all assignments.
- Function ***sat* : *APForm* $\rightarrow 2^{\text{Assign}}$**
(a formula \rightarrow set of its satisfying assignments)
- Recursive definition:

$$\begin{aligned} \text{sat}(a) &= \{\alpha \mid \alpha(a) = 1\}, \quad a \in AP \\ \text{sat}(\neg\varphi_1) &= \text{Assign} \setminus \text{sat}(\varphi_1) \\ \text{sat}(\varphi_1 \wedge \varphi_2) &= \text{sat}(\varphi_1) \cap \text{sat}(\varphi_2) \\ \text{sat}(\varphi_1 \vee \varphi_2) &= \text{sat}(\varphi_1) \cup \text{sat}(\varphi_2) \\ \text{sat}(\varphi_1 \rightarrow \varphi_2) &= (\text{Assign} \setminus \text{sat}(\varphi_1)) \cup \text{sat}(\varphi_2) \end{aligned}$$

- For $\varphi \in APForm$ and $\alpha \in Assign$ it holds that

$$\alpha \models \varphi \quad \text{iff} \quad \alpha \in \text{sat}(\varphi)$$

Satisfying assignments: Example

$$\text{sat}(\textcolor{red}{a} \vee (\textcolor{blue}{b} \rightarrow \textcolor{green}{c})) =$$

Satisfying assignments: Example

$$\begin{aligned} \text{sat}(\textcolor{red}{a} \vee (\textcolor{blue}{b} \rightarrow \textcolor{green}{c})) &= \\ \textcolor{red}{\text{sat}(\textcolor{red}{a})} \cup \text{sat}(\textcolor{blue}{b} \rightarrow \textcolor{green}{c}) \end{aligned}$$

Satisfying assignments: Example

$$\text{sat}(a \vee (b \rightarrow c)) =$$

$$\text{sat}(a) \cup \text{sat}(b \rightarrow c) =$$

$$\text{sat}(a) \cup ((\text{Assign} \setminus \text{sat}(b)) \cup \text{sat}(c))$$

Satisfying assignments: Example

$$\text{sat}(\textcolor{red}{a} \vee (\textcolor{blue}{b} \rightarrow \textcolor{green}{c})) \quad =$$

$$\textcolor{red}{\text{sat}(\textcolor{red}{a})} \cup \text{sat}(\textcolor{blue}{b} \rightarrow \textcolor{green}{c}) \quad =$$

$$\textcolor{red}{\text{sat}(\textcolor{red}{a})} \cup ((\textcolor{blue}{Assign} \setminus \textcolor{blue}{\text{sat}(\textcolor{blue}{b})}) \cup \textcolor{green}{\text{sat}(\textcolor{green}{c})}) \quad =$$

$$\{\alpha \in \textcolor{red}{Assign} \mid \alpha(\textcolor{red}{a}) = 1\} \cup$$

$$\{\alpha \in \textcolor{blue}{Assign} \mid \alpha(\textcolor{blue}{b}) = 0\} \cup$$

$$\{\alpha \in \textcolor{green}{Assign} \mid \alpha(\textcolor{green}{c}) = 1\}$$

Satisfying assignments: Example

$$\text{sat}(a \vee (b \rightarrow c)) =$$

$$\text{sat}(a) \cup \text{sat}(b \rightarrow c) =$$

$$\text{sat}(a) \cup ((\text{Assign} \setminus \text{sat}(b)) \cup \text{sat}(c)) =$$

$$\{\alpha \in \text{Assign} \mid \alpha(a) = 1\} \cup$$

$$\{\alpha \in \text{Assign} \mid \alpha(b) = 0\} \cup$$

$$\{\alpha \in \text{Assign} \mid \alpha(c) = 1\} =$$

$$\{\alpha \in \text{Assign} \mid \alpha(a) = 1 \text{ or } \alpha(b) = 0 \text{ or } \alpha(c) = 1\}$$

Extensions of \models

- We define $\models \subseteq 2^{Assign} \times APForm$ by

$$T \models \varphi \text{ iff } T \subseteq sat(\varphi)$$

for formulae $\varphi \in APForm$ and assignment sets $T \subseteq 2^{Assign}$.

Extensions of \models

- We define $\models \subseteq 2^{Assign} \times APForm$ by

$$T \models \varphi \text{ iff } T \subseteq sat(\varphi)$$

for formulae $\varphi \in APForm$ and assignment sets $T \subseteq 2^{Assign}$.

Examples: $\{\alpha \in Assign \mid \alpha(a) = \alpha(c) = 1\} \models a \vee (b \rightarrow c)$
 $\{\alpha \in Assign \mid \alpha(x_1) = 1\} \models x_1 \vee x_2$

Extensions of \models

- We define $\models \subseteq 2^{Assign} \times APForm$ by

$$T \models \varphi \text{ iff } T \subseteq sat(\varphi)$$

for formulae $\varphi \in APForm$ and assignment sets $T \subseteq 2^{Assign}$.

Examples: $\{\alpha \in Assign \mid \alpha(a) = \alpha(c) = 1\} \models a \vee (b \rightarrow c)$
 $\{\alpha \in Assign \mid \alpha(x_1) = 1\} \models x_1 \vee x_2$

- We define $\models \subseteq 2^{APForm} \times 2^{APForm}$ by

$$\varphi_1 \models \varphi_2 \text{ iff } sat(\varphi_1) \subseteq sat(\varphi_2)$$

for formulae $\varphi_1, \varphi_2 \in APForm$.

Extensions of \models

- We define $\models \subseteq 2^{Assign} \times APForm$ by

$$T \models \varphi \text{ iff } T \subseteq sat(\varphi)$$

for formulae $\varphi \in APForm$ and assignment sets $T \subseteq 2^{Assign}$.

Examples: $\{\alpha \in Assign \mid \alpha(a) = \alpha(c) = 1\} \models a \vee (b \rightarrow c)$
 $\{\alpha \in Assign \mid \alpha(x_1) = 1\} \models x_1 \vee x_2$

- We define $\models \subseteq 2^{APForm} \times 2^{APForm}$ by

$$\varphi_1 \models \varphi_2 \text{ iff } sat(\varphi_1) \subseteq sat(\varphi_2)$$

for formulae $\varphi_1, \varphi_2 \in APForm$.

Examples: $a \wedge c \models a \vee (b \rightarrow c)$
 $x_1 \models x_1 \vee x_2$

Short summary for propositional logic

- **Syntax** of propositional formulae $\varphi \in APForm$:

$$\varphi := AP \mid (\neg\varphi) \mid (\varphi \wedge \varphi)$$

- **Semantics:**

- **Assignments** $\alpha \in Assign$:

$$\alpha : AP \rightarrow \{0, 1\}$$

$$\alpha \in 2^{AP}$$

$$\alpha \in \{0, 1\}^{AP}$$

- **Satisfaction relation:**

$$\models \subseteq Assign \times APForm \quad , \quad (\text{e.g., } \alpha \models \varphi)$$

$$\models \subseteq 2^{Assign} \times APForm \quad , \quad (\text{e.g., } \{\alpha_1, \dots, \alpha_n\} \models \varphi)$$

$$\models \subseteq APForm \times APForm \quad , \quad (\text{e.g., } \varphi_1 \models \varphi_2)$$

$$sat : APForm \rightarrow 2^{Assign} \quad , \quad (\text{e.g., } sat(\varphi))$$

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

Semantic classification of formulae

- A formula φ is called **valid** if $\text{sat}(\varphi) = \text{Assign}$.
(Also called a **tautology**).

Semantic classification of formulae


- A formula φ is called **valid** if $\text{sat}(\varphi) = \text{Assign}$.
(Also called a **tautology**).
- A formula φ is called **satisfiable** if $\text{sat}(\varphi) \neq \emptyset$.

Semantic classification of formulae

- A formula φ is called **valid** if $\text{sat}(\varphi) = \text{Assign}$.
(Also called a **tautology**).
- A formula φ is called **satisfiable** if $\text{sat}(\varphi) \neq \emptyset$.
- A formula φ is called **unsatisfiable** if $\text{sat}(\varphi) = \emptyset$.
(Also called a **contradiction**).

Semantic classification of formulae

- A formula φ is called **valid** if $\text{sat}(\varphi) = \text{Assign.}$
(Also called a **tautology**).
- A formula φ is called **satisfiable** if $\text{sat}(\varphi) \neq \emptyset$.
- A formula φ is called **unsatisfiable** if $\text{sat}(\varphi) = \emptyset$.
(Also called a **contradiction**).



Some notations

Some notations

- We can write:

- $\models \varphi$ when φ is valid

- We can write:
 - $\models \varphi$ when φ is valid
 - $\not\models \varphi$ when φ is not valid

- We can write:
 - $\models \varphi$ when φ is valid
 - $\not\models \varphi$ when φ is not valid
 - $\not\models \neg\varphi$ when φ is

- We can write:
 - $\models \varphi$ when φ is **valid**
 - $\not\models \varphi$ when φ is **not valid**
 - $\not\models \neg\varphi$ when φ is **satisfiable**

- We can write:
 - $\models \varphi$ when φ is **valid**
 - $\not\models \varphi$ when φ is **not valid**
 - $\not\models \neg\varphi$ when φ is **satisfiable**
 - $\models \neg\varphi$ when φ is

- We can write:
 - $\models \varphi$ when φ is **valid**
 - $\not\models \varphi$ when φ is **not valid**
 - $\models \neg\varphi$ when φ is **satisfiable**
 - $\models \neg\varphi$ when φ is **unsatisfiable**

Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

Examples

■ $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

- $(x_1 \vee x_2) \rightarrow x_1$

Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is valid

- $(x_1 \vee x_2) \rightarrow x_1$

is satisfiable

Examples

- $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is **valid**

- $(x_1 \vee x_2) \rightarrow x_1$

is **satisfiable**

- $(x_1 \wedge x_2) \wedge \neg x_1$

Examples

■ $(x_1 \wedge x_2) \rightarrow (x_1 \vee x_2)$

is **valid**

■ $(x_1 \vee x_2) \rightarrow x_1$

is **satisfiable**

■ $(x_1 \wedge x_2) \wedge \neg x_1$

is **unsatisfiable**

■ Here are some valid formulae:

■ $\models a \wedge 1 \leftrightarrow a$

■ $\models a \wedge 0 \leftrightarrow 0$

- Here are some valid formulae:
 - $\models a \wedge 1 \leftrightarrow a$
 - $\models a \wedge 0 \leftrightarrow 0$
 - $\models \neg\neg a \leftrightarrow a$ (double-negation rule)

- Here are some valid formulae:
 - $\models a \wedge 1 \leftrightarrow a$
 - $\models a \wedge 0 \leftrightarrow 0$
 - $\models \neg\neg a \leftrightarrow a$ (double-negation rule)
 - $\models a \wedge (b \vee c) \leftrightarrow (a \wedge b) \vee (a \wedge c)$

- Here are some valid formulae:

- $\models a \wedge 1 \leftrightarrow a$
- $\models a \wedge 0 \leftrightarrow 0$
- $\models \neg\neg a \leftrightarrow a$ (double-negation rule)
- $\models a \wedge (b \vee c) \leftrightarrow (a \wedge b) \vee (a \wedge c)$

- Some more (De Morgan rules):

- $\models \neg(a \wedge b) \leftrightarrow (\neg a \vee \neg b)$
- $\models \neg(a \vee b) \leftrightarrow (\neg a \wedge \neg b)$

The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

Given an input propositional formula φ , decide whether φ is satisfiable.

The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

Given an input propositional formula φ , decide whether φ is satisfiable.

- This problem is decidable but **NP-complete**.

The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

Given an input propositional formula φ , decide whether φ is satisfiable.

- This problem is decidable but **NP-complete**.
- An algorithm that always terminates for each propositional logic formula with the correct answer is called a **decision procedure** for propositional logic.


The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

Given an input propositional formula φ , decide whether φ is satisfiable.

- This problem is decidable but **NP-complete**.
- An algorithm that always terminates for each propositional logic formula with the correct answer is called a **decision procedure** for propositional logic.

Goal: Design and implement such a decision procedure:




The satisfiability problem for propositional logic

- The **satisfiability problem** for propositional logic is as follows:

Given an input propositional formula φ , decide whether φ is satisfiable.

- This problem is decidable but **NP-complete**.
- An algorithm that always terminates for each propositional logic formula with the correct answer is called a **decision procedure** for propositional logic.

Goal: Design and implement such a decision procedure:



Note: A formula φ is valid iff $\neg\varphi$ is unsatisfiable.

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

Before we solve this problem...

- Suppose we can solve the satisfiability problem... how can this help us?

Before we solve this problem...

- Suppose we can solve the satisfiability problem... how can this help us?
- There are numerous problems in the industry that are solved via the satisfiability problem of propositional logic
 - Logistics
 - Planning
 - Electronic Design Automation industry
 - Cryptography
 - ...

Example 1: Placement of wedding guests

- Three chairs in a row: 1, 2, 3
- We need to place Aunt, Sister and Father.
- Constraints:
 - Aunt doesn't want to sit near Father
 - Aunt doesn't want to sit in the left chair
 - Sister doesn't want to sit to the right of Father

Example 1: Placement of wedding guests

- Three chairs in a row: 1, 2, 3
- We need to place Aunt, Sister and Father.
- Constraints:
 - Aunt doesn't want to sit near Father
 - Aunt doesn't want to sit in the left chair
 - Sister doesn't want to sit to the right of Father
- Q: Can we satisfy these constraints?

Example 1 (continued)

Example 1 (continued)

- Notation:

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = "person p is sited in chair c " for $1 \leq p, c \leq 3$

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = "person p is sited in chair c " for $1 \leq p, c \leq 3$

- **Constraints:**

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = “person p is sited in chair c ” for $1 \leq p, c \leq 3$

- **Constraints:**

Aunt doesn't want to sit near Father:

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = "person p is sited in chair c " for $1 \leq p, c \leq 3$

- **Constraints:**

Aunt doesn't want to sit near Father:

$$((x_{1,1} \vee x_{1,3}) \rightarrow \neg x_{3,2}) \wedge (x_{1,2} \rightarrow (\neg x_{3,1} \wedge \neg x_{3,3}))$$

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = “person p is sited in chair c ” for $1 \leq p, c \leq 3$

- **Constraints:**

Aunt doesn't want to sit near Father:

$$((x_{1,1} \vee x_{1,3}) \rightarrow \neg x_{3,2}) \wedge (x_{1,2} \rightarrow (\neg x_{3,1} \wedge \neg x_{3,3}))$$

Aunt doesn't want to sit in the left chair:

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = “person p is sited in chair c ” for $1 \leq p, c \leq 3$

- **Constraints:**

Aunt doesn't want to sit near Father:

$$((x_{1,1} \vee x_{1,3}) \rightarrow \neg x_{3,2}) \wedge (x_{1,2} \rightarrow (\neg x_{3,1} \wedge \neg x_{3,3}))$$

Aunt doesn't want to sit in the left chair:

$$\neg x_{1,1}$$

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = "person p is sited in chair c " for $1 \leq p, c \leq 3$

- **Constraints:**

Aunt doesn't want to sit near Father:

$$((x_{1,1} \vee x_{1,3}) \rightarrow \neg x_{3,2}) \wedge (x_{1,2} \rightarrow (\neg x_{3,1} \wedge \neg x_{3,3}))$$

Aunt doesn't want to sit in the left chair:

$$\neg x_{1,1}$$

Sister doesn't want to sit to the right of Father:

Example 1 (continued)

- **Notation:** Aunt = 1, Sister = 2, Father = 3

Left chair = 1, Middle chair = 2, Right chair = 3

Introduce a propositional variable for each pair (person, chair):

$x_{p,c}$ = “person p is sited in chair c ” for $1 \leq p, c \leq 3$

- **Constraints:**

Aunt doesn't want to sit near Father:

$$((x_{1,1} \vee x_{1,3}) \rightarrow \neg x_{3,2}) \wedge (x_{1,2} \rightarrow (\neg x_{3,1} \wedge \neg x_{3,3}))$$

Aunt doesn't want to sit in the left chair:

$$\neg x_{1,1}$$

Sister doesn't want to sit to the right of Father:

$$(x_{3,1} \rightarrow \neg x_{2,2}) \wedge (x_{3,2} \rightarrow \neg x_{2,3})$$

Example 1 (continued)

Example 1 (continued)

Each person is placed:

Example 1 (continued)

Each person is placed:

$$(x_{1,1} \vee x_{1,2} \vee x_{1,3}) \wedge (x_{2,1} \vee x_{2,2} \vee x_{2,3}) \wedge (x_{3,1} \vee x_{3,2} \vee x_{3,3})$$

$$\bigwedge_{p=1}^3 \bigvee_{c=1}^3 x_{p,c}$$

Example 1 (continued)

Each person is placed:

$$(x_{1,1} \vee x_{1,2} \vee x_{1,3}) \wedge (x_{2,1} \vee x_{2,2} \vee x_{2,3}) \wedge (x_{3,1} \vee x_{3,2} \vee x_{3,3})$$

$$\bigwedge_{p=1}^3 \bigvee_{c=1}^3 x_{p,c}$$

No person is placed in more than one chair:

Example 1 (continued)

Each person is placed:

$$(x_{1,1} \vee x_{1,2} \vee x_{1,3}) \wedge (x_{2,1} \vee x_{2,2} \vee x_{2,3}) \wedge (x_{3,1} \vee x_{3,2} \vee x_{3,3})$$

$$\bigwedge_{p=1}^3 \bigvee_{c=1}^3 x_{p,c}$$

No person is placed in more than one chair:

$$\bigwedge_{p=1}^3 \bigwedge_{c1=1}^3 \bigwedge_{c2=c1+1}^3 (\neg x_{p,c1} \vee \neg x_{p,c2})$$

Example 1 (continued)

Each person is placed:

$$(x_{1,1} \vee x_{1,2} \vee x_{1,3}) \wedge (x_{2,1} \vee x_{2,2} \vee x_{2,3}) \wedge (x_{3,1} \vee x_{3,2} \vee x_{3,3})$$

$$\bigwedge_{p=1}^3 \bigvee_{c=1}^3 x_{p,c}$$

No person is placed in more than one chair:

$$\bigwedge_{p=1}^3 \bigwedge_{c1=1}^3 \bigwedge_{c2=c1+1}^3 (\neg x_{p,c1} \vee \neg x_{p,c2})$$

At most one person per chair:

Example 1 (continued)

Each person is placed:

$$(x_{1,1} \vee x_{1,2} \vee x_{1,3}) \wedge (x_{2,1} \vee x_{2,2} \vee x_{2,3}) \wedge (x_{3,1} \vee x_{3,2} \vee x_{3,3})$$

$$\bigwedge_{p=1}^3 \bigvee_{c=1}^3 x_{p,c}$$

No person is placed in more than one chair:

$$\bigwedge_{p=1}^3 \bigwedge_{c1=1}^3 \bigwedge_{c2=c1+1}^3 (\neg x_{p,c1} \vee \neg x_{p,c2})$$

At most one person per chair:

$$\bigwedge_{p1=1}^3 \bigwedge_{p2=p1+1}^3 \bigwedge_{c=1}^3 (\neg x_{p1,c} \vee \neg x_{p2,c})$$

Example 2: Assignment of frequencies

- n radio stations
- For each station assign one of k transmission frequencies, $k < n$.
- E – set of pairs of stations, that are too close to have the same frequency.

Example 2: Assignment of frequencies

- n radio stations
- For each station assign one of k transmission frequencies, $k < n$.
- E – set of pairs of stations, that are too close to have the same frequency.
- **Q:** Can we assign to each station a frequency, such that no station pairs from E have the same frequency?

Example 2 (continued)

- Notation:

Example 2 (continued)

- Notation:

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

Example 2 (continued)

- **Notation:**

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

- **Constraints:**

Example 2 (continued)

- **Notation:**

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

- **Constraints:**

Every station is assigned at least one frequency:

Example 2 (continued)

- **Notation:**

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

- **Constraints:**

Every station is assigned at least one frequency:

$$\bigwedge_{s=1}^n \left(\bigvee_{f=1}^k x_{s,f} \right)$$

Example 2 (continued)

- **Notation:**

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

- **Constraints:**

Every station is assigned at least one frequency:

$$\bigwedge_{s=1}^n \left(\bigvee_{f=1}^k x_{s,f} \right)$$

Every station is assigned at most one frequency:

Example 2 (continued)

■ Notation:

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

■ Constraints:

Every station is assigned at least one frequency:

$$\bigwedge_{s=1}^n \left(\bigvee_{f=1}^k x_{s,f} \right)$$

Every station is assigned at most one frequency:

$$\bigwedge_{s=1}^n \bigwedge_{f1=1}^{k-1} \bigwedge_{f2=f1+1}^k (\neg x_{s,f1} \vee \neg x_{s,f2})$$

Example 2 (continued)

- **Notation:**

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

- **Constraints:**

Every station is assigned at least one frequency:

$$\bigwedge_{s=1}^n \left(\bigvee_{f=1}^k x_{s,f} \right)$$

Every station is assigned at most one frequency:

$$\bigwedge_{s=1}^n \bigwedge_{f1=1}^{k-1} \bigwedge_{f2=f1+1}^k (\neg x_{s,f1} \vee \neg x_{s,f2})$$

Close stations are not assigned the same frequency:

Example 2 (continued)

- **Notation:**

$x_{s,f}$ = “station s is assigned frequency f ” for $1 \leq s \leq n$, $1 \leq f \leq k$

- **Constraints:**

Every station is assigned at least one frequency:

$$\bigwedge_{s=1}^n \left(\bigvee_{f=1}^k x_{s,f} \right)$$

Every station is assigned at most one frequency:

$$\bigwedge_{s=1}^n \bigwedge_{f1=1}^{k-1} \bigwedge_{f2=f1+1}^k (\neg x_{s,f1} \vee \neg x_{s,f2})$$

Close stations are not assigned the same frequency:

For each $(s1, s2) \in E$,

$$\bigwedge_{f=1}^k (\neg x_{s1,f} \vee \neg x_{s2,f})$$

Example 3: Seminar topic assignment

- n participants
- n topics
- Set of preferences $E \subseteq \{1, \dots, n\} \times \{1, \dots, n\}$
 $(p, t) \in E$ means: participant p would take topic t

Example 3: Seminar topic assignment

- n participants
- n topics
- Set of preferences $E \subseteq \{1, \dots, n\} \times \{1, \dots, n\}$
 $(p, t) \in E$ means: participant p would take topic t
- **Q:** Can we assign to each participant a topic which he/she is willing to take?

Example 3 (continued)

- Notation:

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**
 - Each participant is assigned at least one topic:

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**

Each participant is assigned at least one topic:

$$\bigwedge_{p=1}^n \left(\bigvee_{t=1}^n x_{p,t} \right)$$

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**

Each participant is assigned at least one topic:

$$\bigwedge_{p=1}^n \left(\bigvee_{t=1}^n x_{p,t} \right)$$

Each participant is assigned at most one topic:

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**

Each participant is assigned at least one topic:

$$\bigwedge_{p=1}^n \left(\bigvee_{t=1}^n x_{p,t} \right)$$

Each participant is assigned at most one topic:

$$\bigwedge_{p=1}^n \bigwedge_{t1=1}^{n-1} \bigwedge_{t2=t1+1}^n (\neg x_{p,t1} \vee \neg x_{p,t2})$$

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**

Each participant is assigned at least one topic:

$$\bigwedge_{p=1}^n \left(\bigvee_{t=1}^n x_{p,t} \right)$$

Each participant is assigned at most one topic:

$$\bigwedge_{p=1}^n \bigwedge_{t1=1}^{n-1} \bigwedge_{t2=t1+1}^n (\neg x_{p,t1} \vee \neg x_{p,t2})$$

Each participant is willing to take his/her assigned topic:

Example 3 (continued)

- **Notation:** $x_{p,t}$ = “participant p is assigned topic t ”
- **Constraints:**

Each participant is assigned at least one topic:

$$\bigwedge_{p=1}^n \left(\bigvee_{t=1}^n x_{p,t} \right)$$

Each participant is assigned at most one topic:

$$\bigwedge_{p=1}^n \bigwedge_{t1=1}^{n-1} \bigwedge_{t2=t1+1}^n (\neg x_{p,t1} \vee \neg x_{p,t2})$$

Each participant is willing to take his/her assigned topic:

$$\bigwedge_{p=1}^n \bigwedge_{(p,t) \notin E} \neg x_{p,t}$$

Example 3 (continued)

Example 3 (continued)

Each topic is assigned to at most one participant:

Example 3 (continued)

Each topic is assigned to at most one participant:

$$\bigwedge_{t=1}^n \bigwedge_{p1=1}^n \bigwedge_{p2=p1+1}^n (\neg x_{p1,t} \vee \neg x_{p2,t})$$

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

- Definition: A **literal** is either a variable or a negation of a variable.

- Definition: A **literal** is either a variable or a negation of a variable.
- **Example:** $\varphi = \neg(a \vee \neg b)$
Variables: $AP(\varphi) = \{a, b\}$
Literals: $lit(\varphi) = \{a, \neg b\}$

- Definition: A **literal** is either a variable or a negation of a variable.
- **Example:** $\varphi = \neg(a \vee \neg b)$
Variables: $AP(\varphi) = \{a, b\}$
Literals: $lit(\varphi) = \{a, \neg b\}$
- **Note:** Equivalent formulae can have different literals.

- Definition: A **literal** is either a variable or a negation of a variable.

- Example: $\varphi = \neg(a \vee \neg b)$

Variables: $AP(\varphi) = \{a, b\}$

Literals: $lit(\varphi) = \{a, \neg b\}$

- Note: Equivalent formulae can have different literals.

Example: $\varphi' = \neg a \wedge b$

Literals: $lit(\varphi') = \{\neg a, b\}$

- Definition: a **term** is a conjunction of literals
 - **Example:** $(a \wedge \neg b \wedge c)$

- Definition: a **term** is a conjunction of literals
 - Example: $(a \wedge \neg b \wedge c)$
- Definition: a **clause** is a disjunction of literals
 - Example: $(a \vee \neg b \vee c)$

Negation Normal Form (NNF)

- Definition: A formula is in **Negation Normal Form (NNF)** iff
 - (1) it contains only \neg , \wedge and \vee as connectives and
 - (2) only variables are negated.

Negation Normal Form (NNF)

- Definition: A formula is in **Negation Normal Form (NNF)** iff
 - (1) it contains only \neg , \wedge and \vee as connectives and
 - (2) only variables are negated.
- **Examples:**
 - $\varphi_1 = \neg(a \vee \neg b)$ is **not** in NNF
 - $\varphi_2 = \neg a \wedge b$ is **in** NNF

- Every formula can be converted to NNF in linear time:
 - Eliminate all connectives other than \wedge , \vee , \neg
 - Use De Morgan and double-negation rules to push negations to operands

- Every formula can be converted to NNF in linear time:
 - Eliminate all connectives other than \wedge , \vee , \neg
 - Use De Morgan and double-negation rules to push negations to operands
- **Example:** $\varphi = \neg(a \rightarrow \neg b)$
 - Eliminate ' \rightarrow ': $\varphi = \neg(\neg a \vee \neg b)$

- Every formula can be converted to NNF in linear time:
 - Eliminate all connectives other than \wedge , \vee , \neg
 - Use De Morgan and double-negation rules to push negations to operands
- **Example:** $\varphi = \neg(a \rightarrow \neg b)$
 - Eliminate ' \rightarrow ': $\varphi = \neg(\neg a \vee \neg b)$
 - Push negation using De Morgan: $\varphi = (\neg\neg a \wedge \neg\neg b)$

- Every formula can be converted to NNF in linear time:
 - Eliminate all connectives other than \wedge , \vee , \neg
 - Use De Morgan and double-negation rules to push negations to operands
- **Example:** $\varphi = \neg(a \rightarrow \neg b)$
 - Eliminate ' \rightarrow ': $\varphi = \neg(\neg a \vee \neg b)$
 - Push negation using De Morgan: $\varphi = (\neg\neg a \wedge \neg\neg b)$
 - Use double-negation rule: $\varphi = (a \wedge b)$

Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.

Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.
- In other words, it is a formula of the form

$$\bigvee_i \left(\bigwedge_j l_{i,j} \right)$$

where $l_{i,j}$ is the j -th literal in the i -th term.

Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.
- In other words, it is a formula of the form

$$\bigvee_i \left(\bigwedge_j l_{i,j} \right)$$

where $l_{i,j}$ is the j -th literal in the i -th term.

- Example:

$$\varphi = (a \wedge \neg b \wedge c) \vee (\neg a \wedge d) \vee (b) \text{ is in DNF}$$

Disjunctive Normal Form (DNF)

- Definition: A formula is said to be in **Disjunctive Normal Form (DNF)** iff it is a disjunction of terms.
- In other words, it is a formula of the form

$$\bigvee_i \left(\bigwedge_j l_{i,j} \right)$$

where $l_{i,j}$ is the j -th literal in the i -th term.

- Example:

$$\varphi = (a \wedge \neg b \wedge c) \vee (\neg a \wedge d) \vee (b) \text{ is in DNF}$$

- DNF is a special case of NNF.

Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

- **Example:**

$$\begin{aligned}\varphi &= (a \vee b) \wedge (\neg c \vee d) \\ &= ((a \vee b) \wedge (\neg c)) \vee ((a \vee b) \wedge d) \\ &= (a \wedge \neg c) \vee (b \wedge \neg c) \vee (a \wedge d) \vee (b \wedge d)\end{aligned}$$

Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

- **Example:**

$$\begin{aligned}\varphi &= (a \vee b) \wedge (\neg c \vee d) \\ &= ((a \vee b) \wedge (\neg c)) \vee ((a \vee b) \wedge d) \\ &= (a \wedge \neg c) \vee (b \wedge \neg c) \vee (a \wedge d) \vee (b \wedge d)\end{aligned}$$

- Now consider $\varphi_n = (a_1 \vee b_1) \wedge (a_2 \vee b_2) \wedge \dots \wedge (a_n \vee b_n)$.
- **Q:** How many clauses will the DNF have?

Converting to DNF

- Every formula can be converted to DNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \wedge (\varphi_2 \vee \varphi_3) \leftrightarrow (\varphi_1 \wedge \varphi_2) \vee (\varphi_1 \wedge \varphi_3)$$

- **Example:**

$$\begin{aligned}\varphi &= (a \vee b) \wedge (\neg c \vee d) \\ &= ((a \vee b) \wedge (\neg c)) \vee ((a \vee b) \wedge d) \\ &= (a \wedge \neg c) \vee (b \wedge \neg c) \vee (a \wedge d) \vee (b \wedge d)\end{aligned}$$

- Now consider $\varphi_n = (a_1 \vee b_1) \wedge (a_2 \vee b_2) \wedge \dots \wedge (a_n \vee b_n)$.

- **Q:** How many clauses will the DNF have?

A: 2^n

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term $a_2 \wedge a_1$ is satisfiable.

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term $a_2 \wedge a_1$ is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term $a_2 \wedge a_1$ is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

A: Linear (time and space).

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term $a_2 \wedge a_1$ is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

A: Linear (time and space).

- Q: Can there be any polynomial transformation into DNF?

- Q: Is the following DNF formula satisfiable?

$$(a_1 \wedge a_2 \wedge \neg a_1) \vee (a_2 \wedge a_1) \vee (a_2 \wedge \neg a_3 \wedge a_3)$$

A: Yes, because the term $a_2 \wedge a_1$ is satisfiable.

- Q: What is the complexity of the satisfiability check of DNF formulae?

A: Linear (time and space).

- Q: Can there be any polynomial transformation into DNF?

- A: No, it would violate the NP-completeness of the problem.

Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.

Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.
- In other words, it is a formula of the form

$$\bigwedge_i \left(\bigvee_j l_{i,j} \right)$$

where $l_{i,j}$ is the j -th literal in the i -th clause.

Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.
- In other words, it is a formula of the form

$$\bigwedge_i \left(\bigvee_j l_{i,j} \right)$$

where $l_{i,j}$ is the j -th literal in the i -th clause.

- Example:

$$\varphi = (a \vee \neg b \vee c) \wedge (\neg a \vee d) \wedge (b) \text{ is in CNF}$$

Conjunctive Normal Form (CNF)

- Definition: A formula is said to be in **Conjunctive Normal Form (CNF)** iff it is a conjunction of clauses.
- In other words, it is a formula of the form

$$\bigwedge_i \left(\bigvee_j l_{i,j} \right)$$

where $l_{i,j}$ is the j -th literal in the i -th clause.

- **Example:**

$$\varphi = (a \vee \neg b \vee c) \wedge (\neg a \vee d) \wedge (b) \text{ is in CNF}$$

- Also CNF is a special case of NNF.

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Consider the formula $\varphi = (a_1 \wedge b_1) \vee (a_2 \wedge b_2)$.

Transformation: $(a_1 \vee a_2) \wedge (a_1 \vee b_2) \wedge (b_1 \vee a_2) \wedge (b_1 \vee b_2)$

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Consider the formula $\varphi = (a_1 \wedge b_1) \vee (a_2 \wedge b_2)$.

Transformation: $(a_1 \vee a_2) \wedge (a_1 \vee b_2) \wedge (b_1 \vee a_2) \wedge (b_1 \vee b_2)$

- Now consider $\varphi_n = (a_1 \wedge b_1) \vee (a_2 \wedge b_2) \vee \dots \vee (a_n \wedge b_n)$.

Q: How many clauses does the resulting CNF have?

- Every formula can be converted to CNF in **exponential** time and space:

- 1 Convert to NNF

- 2 Distribute disjunctions following the rule:

$$\models \varphi_1 \vee (\varphi_2 \wedge \varphi_3) \leftrightarrow (\varphi_1 \vee \varphi_2) \wedge (\varphi_1 \vee \varphi_3)$$

- Consider the formula $\varphi = (a_1 \wedge b_1) \vee (a_2 \wedge b_2)$.

Transformation: $(a_1 \vee a_2) \wedge (a_1 \vee b_2) \wedge (b_1 \vee a_2) \wedge (b_1 \vee b_2)$

- Now consider $\varphi_n = (a_1 \wedge b_1) \vee (a_2 \wedge b_2) \vee \dots \vee (a_n \wedge b_n)$.

Q: How many clauses does the resulting CNF have?

A: 2^n

Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equi-satisfiable**.

Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equi-satisfiable**.

- Consider the formula


$$\varphi = (a \rightarrow (b \wedge c))$$

Converting to CNF: Tseitin's encoding

- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equi-satisfiable**.

- Consider the formula
 $\varphi = (a \rightarrow (b \wedge c))$

Parse tree:



Converting to CNF: Tseitin's encoding


- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equi-satisfiable**.

- Consider the formula

$$\varphi = (a \rightarrow (b \wedge c))$$

- Associate a new auxiliary variable with each gate.

Parse tree:



Converting to CNF: Tseitin's encoding


- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equi-satisfiable**.

- Consider the formula

$$\varphi = (a \rightarrow (b \wedge c))$$

- Associate a new auxiliary variable with each gate.
- Add constraints that define these new variables.

Parse tree:



Converting to CNF: Tseitin's encoding


- Every formula can be converted to CNF in **linear** time and space if new variables are added.
- The original and the converted formulae are **not equivalent** but **equi-satisfiable**.

- Consider the formula

$$\varphi = (a \rightarrow (b \wedge c))$$

- Associate a new auxiliary variable with each gate.
- Add constraints that define these new variables.
- Finally, enforce the root node.

Parse tree:




Converting to CNF: Tseitin's encoding

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge$$

$$(h_2 \leftrightarrow (b \wedge c)) \wedge$$

$$(h_1)$$



- Each gate encoding has a CNF representation with 3 or 4 clauses.

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge (h_2 \leftrightarrow (b \wedge c)) \wedge (h_1)$$

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge (h_2 \leftrightarrow (b \wedge c)) \wedge (h_1)$$

- First: $(h_1 \vee a) \wedge (h_1 \vee \neg h_2) \wedge (\neg h_1 \vee \neg a \vee h_2)$

- Need to satisfy:

$$(h_1 \leftrightarrow (a \rightarrow h_2)) \wedge (h_2 \leftrightarrow (b \wedge c)) \wedge (h_1)$$

- First: $(h_1 \vee a) \wedge (h_1 \vee \neg h_2) \wedge (\neg h_1 \vee \neg a \vee h_2)$
- Second: $(\neg h_2 \vee b) \wedge (\neg h_2 \vee c) \wedge (h_2 \vee \neg b \vee \neg c)$

- Let's go back to

$$\varphi_n = (x_1 \wedge y_1) \vee (x_2 \wedge y_2) \vee \cdots \vee (x_n \wedge y_n)$$

- Let's go back to

$$\varphi_n = (x_1 \wedge y_1) \vee (x_2 \wedge y_2) \vee \cdots \vee (x_n \wedge y_n)$$

- With Tseitin's encoding we need:

- n auxiliary variables h_1, \dots, h_n .
- Each adds 3 constraints.
- Top clause: $(h_1 \vee \cdots \vee h_n)$

Converting to CNF: Tseitin's encoding

- Let's go back to

$$\varphi_n = (x_1 \wedge y_1) \vee (x_2 \wedge y_2) \vee \cdots \vee (x_n \wedge y_n)$$

- With Tseitin's encoding we need:

- n auxiliary variables h_1, \dots, h_n .
- Each adds 3 constraints.
- Top clause: $(h_1 \vee \cdots \vee h_n)$

- Hence, we have

- $3n + 1$ clauses, instead of 2^n .
- $3n$ variables rather than $2n$.

Propositional logic - Outline

- Syntax of propositional logic
- Semantics of propositional logic
- Satisfiability and validity
- Modeling with propositional logic
- Normal forms
- Enumeration and deduction

Two classes of algorithms for validity

Two classes of algorithms for validity

- Q: Is φ satisfiable? (Is $\neg\varphi$ valid?)

Two classes of algorithms for validity

- Q: Is φ satisfiable? (Is $\neg\varphi$ valid?)
- Complexity: **NP-Complete** (Cook's theorem)

Two classes of algorithms for validity

- **Q:** Is φ satisfiable? (Is $\neg\varphi$ valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:

Two classes of algorithms for validity

- Q: Is φ satisfiable? (Is $\neg\varphi$ valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:
 - Enumeration of possible solutions (Truth tables etc.)
 - Deduction

Two classes of algorithms for validity

- **Q:** Is φ satisfiable? (Is $\neg\varphi$ valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:
 - Enumeration of possible solutions (Truth tables etc.)
 - Deduction
- More generally (beyond propositional logic):

Two classes of algorithms for validity

- **Q:** Is φ satisfiable? (Is $\neg\varphi$ valid?)
- Complexity: **NP-Complete** (Cook's theorem)
- Two classes of algorithms for finding out:
 - Enumeration of possible solutions (Truth tables etc.)
 - Deduction
- More generally (beyond propositional logic):
 - **Enumeration** is possible only in some logics.
 - **Deduction** cannot necessarily be fully automated.

The satisfiability problem

- Given a formula φ , is φ satisfiable?

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ){  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ){  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ) {  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ) {  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

$$\varphi \quad \text{iff} \quad \varphi[0/a] \vee \varphi[1/a]$$

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ) {  
    for all  $\alpha \in Assign$   
        if Eval( $\alpha, \varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

$$\varphi \quad \text{iff} \quad \varphi[0/a] \vee \varphi[1/a]$$

- Q: What is the difference?

The satisfiability problem

- Given a formula φ , is φ satisfiable?

Enumeration the first:

```
Boolean SAT( $\varphi$ ) {  
    for all  $\alpha \in \text{Assign}$   
        if Eval( $\alpha$ ,  $\varphi$ ) return true;  
    return false;  
}
```

Enumeration the second:

Use substitution to eliminate all variables one by one:

$$\varphi \quad \text{iff} \quad \varphi[0/a] \vee \varphi[1/a]$$

- Q: What is the difference?
A: Branching on complete vs. partial assignments.

Deduction requires axioms and inference rules

■ Inference rules:

$$\frac{\textit{Antecedents}}{\textit{Consequents}} \quad (\textit{rule name})$$

Meaning: If all antecedents hold then at least one of the consequents can be derived.

Deduction requires axioms and inference rules

■ Inference rules:

$$\frac{\textit{Antecedents}}{\textit{Consequents}} \quad (\textit{rule name})$$

Meaning: If all antecedents hold then at least one of the consequents can be derived.

■ Examples:

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (\textit{Trans})$$

$$\frac{a \rightarrow b \quad a}{b} \quad (\textit{M.P.})$$

- **Axioms** are inference rules with no antecedents, e.g.,

$$\frac{}{a \rightarrow (b \rightarrow a)} \quad (H1)$$

- **Axioms** are inference rules with no antecedents, e.g.,

$$\frac{}{a \rightarrow (b \rightarrow a)} \quad (H1)$$

- A **proof system** consists of a set of axioms and inference rules.

- Let \mathcal{H} be a proof system.
- $\Gamma \vdash_{\mathcal{H}} \varphi$ means: There is a proof of φ in system \mathcal{H} whose premises are included in Γ
- $\vdash_{\mathcal{H}}$ is called the **provability (derivability) relation**.

Example

- Let \mathcal{H} be the proof system comprised of the rules **Trans** and **M.P.** that we saw earlier:

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (\text{Trans})$$

$$\frac{a \rightarrow b \quad a}{b} \quad (\text{M.P.})$$

- Does the following relation hold?

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

1. $a \rightarrow b$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

1. $a \rightarrow b$ *premise*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*
7. $a \rightarrow e$

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*
7. $a \rightarrow e$ 3, 6, *Trans*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*
7. $a \rightarrow e$ 3, 6, *Trans*
8. a

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*
7. $a \rightarrow e$ 3, 6, *Trans*
8. a *premise*

Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*
7. $a \rightarrow e$ 3, 6, *Trans*
8. a *premise*
9. e


Deductive proof: Example

$$\frac{a \rightarrow b \quad b \rightarrow c}{a \rightarrow c} \quad (Trans) \quad \frac{a \rightarrow b \quad a}{b} \quad (M.P.)$$

$a \rightarrow b, b \rightarrow c, c \rightarrow d, d \rightarrow e, a \vdash_{\mathcal{H}} e$

1. $a \rightarrow b$ *premise*
2. $b \rightarrow c$ *premise*
3. $a \rightarrow c$ 1, 2, *Trans*
4. $c \rightarrow d$ *premise*
5. $d \rightarrow e$ *premise*
6. $c \rightarrow e$ 4, 5, *Trans*
7. $a \rightarrow e$ 3, 6, *Trans*
8. a *premise*
9. e 7, 8, *M.P.*

Proof graph



- For a given proof system \mathcal{H} ,

- For a given proof system \mathcal{H} ,
 - **Soundness:** Does \vdash conclude “correct” conclusions from premises?

- For a given proof system \mathcal{H} ,
 - **Soundness:** Does \vdash conclude “correct” conclusions from premises?
 - **Completeness:** Can we conclude all true statements with \mathcal{H} ?

- For a given proof system \mathcal{H} ,
 - **Soundness:** Does \vdash conclude “correct” conclusions from premises?
 - **Completeness:** Can we conclude all true statements with \mathcal{H} ?
- **Correct with respect to what?**

- For a given proof system \mathcal{H} ,
 - **Soundness:** Does \vdash conclude “correct” conclusions from premises?
 - **Completeness:** Can we conclude all true statements with \mathcal{H} ?
- **Correct with respect to what?**

With respect to the semantic definition of the logic. In the case of propositional logic truth tables give us this.

- Let \mathcal{H} be a proof system

Soundness of \mathcal{H} :

Soundness and completeness

- Let \mathcal{H} be a proof system

Soundness of \mathcal{H} : if $\vdash_{\mathcal{H}} \varphi$ then $\models \varphi$

Soundness and completeness

- Let \mathcal{H} be a proof system

Soundness of \mathcal{H} : if $\vdash_{\mathcal{H}} \varphi$ then $\models \varphi$

Completeness of \mathcal{H} :

Soundness and completeness

- Let \mathcal{H} be a proof system

Soundness of \mathcal{H} : if $\vdash_{\mathcal{H}} \varphi$ then $\models \varphi$

Completeness of \mathcal{H} : if $\models \varphi$ then $\vdash_{\mathcal{H}} \varphi$

Soundness and completeness

- Let \mathcal{H} be a proof system

Soundness of \mathcal{H} : if $\vdash_{\mathcal{H}} \varphi$ then $\models \varphi$

Completeness of \mathcal{H} : if $\models \varphi$ then $\vdash_{\mathcal{H}} \varphi$

- How to prove soundness and completeness?

Example: Hilbert axiom system (H)

- Let H be (M.P.) together with the following axiom schemes:

$$\overline{a \rightarrow (b \rightarrow a)} \quad (H1)$$

$$\overline{((a \rightarrow (b \rightarrow c)) \rightarrow ((a \rightarrow b) \rightarrow (a \rightarrow c)))} \quad (H2)$$

$$\overline{(\neg b \rightarrow \neg a) \rightarrow (a \rightarrow b)} \quad (H3)$$

- H is **sound and complete** for propositional logic.

- To prove soundness of H , prove the soundness of its axioms and inference rules (easy with truth-tables).

- To prove soundness of H, prove the soundness of its axioms and inference rules (easy with truth-tables).

For example:

a	b	$a \rightarrow (b \rightarrow a)$
0	0	1
0	1	1
1	0	1
1	1	1

- To prove soundness of H, prove the soundness of its axioms and inference rules (easy with truth-tables).

For example:

a	b	$a \rightarrow (b \rightarrow a)$
0	0	1
0	1	1
1	0	1
1	1	1

- Completeness: harder, but possible.

The resolution proof system

The resolution proof system

- The **resolution** inference rule for CNF:

$$\frac{(I \vee l_1 \vee l_2 \vee \dots \vee l_n) \quad (\neg I \vee l'_1 \vee \dots \vee l'_m)}{(l_1 \vee \dots \vee l_n \vee l'_1 \vee \dots \vee l'_m)} \text{ Resolution}$$

- **Example:**

$$\frac{(a \vee b) \quad (\neg a \vee c)}{(b \vee c)}$$


- We first see some example proofs, before proving soundness and completeness.

Proof by resolution

- Let $\varphi = (a_1 \vee a_3) \wedge (\neg a_1 \vee a_2 \vee a_5) \wedge (\neg a_1 \vee a_4) \wedge (\neg a_1 \vee \neg a_4)$
- We want to prove $\varphi \rightarrow (a_3)$

Proof by resolution


- Let $\varphi = (a_1 \vee a_3) \wedge (\neg a_1 \vee a_2 \vee a_5) \wedge (\neg a_1 \vee a_4) \wedge (\neg a_1 \vee \neg a_4)$
- We want to prove $\varphi \rightarrow (a_3)$



- Resolution is a sound and complete proof system for CNF.
- If the input formula is unsatisfiable, there exists a proof of the empty clause.

Example

Let $\varphi = (a_1 \vee a_3) \wedge (\neg a_1 \vee a_2) \wedge (\neg a_1 \vee a_4) \wedge (\neg a_1 \vee \neg a_4) \wedge (\neg a_3)$.



Soundness and completeness of resolution

- Soundness

Soundness and completeness of resolution

- **Soundness** is straightforward. Just prove by truth table that

$$\models ((\varphi_1 \vee a) \wedge (\varphi_2 \vee \neg a)) \rightarrow (\varphi_1 \vee \varphi_2).$$

Soundness and completeness of resolution

- **Soundness** is straightforward. Just prove by truth table that

$$\models ((\varphi_1 \vee a) \wedge (\varphi_2 \vee \neg a)) \rightarrow (\varphi_1 \vee \varphi_2).$$

- **Completeness** is a bit more involved.

Soundness and completeness of resolution

- **Soundness** is straightforward. Just prove by truth table that

$$\models ((\varphi_1 \vee a) \wedge (\varphi_2 \vee \neg a)) \rightarrow (\varphi_1 \vee \varphi_2).$$

- **Completeness** is a bit more involved.

Basic idea: Use resolution for **variable elimination**.

$$\begin{aligned} & (a \vee \varphi_1) \wedge \dots \wedge (a \vee \varphi_n) \wedge \\ & (\neg a \vee \psi_1) \wedge \dots \wedge (\neg a \vee \psi_m) \wedge \\ & \quad R \\ & \Leftrightarrow \\ & (\varphi_1 \vee \psi_1) \wedge \dots \wedge (\varphi_1 \vee \psi_m) \wedge \\ & \quad \dots \\ & (\varphi_n \vee \psi_1) \wedge \dots \wedge (\varphi_n \vee \psi_m) \wedge \\ & \quad R \end{aligned}$$

where φ_i ($i = 1, \dots, n$), ψ_j ($j = 1, \dots, m$), and R contains neither a nor $\neg a$.