

Satisfiability Checking - WS 2016/2017

Series 2

gereon.kremer@cs.rwth-aachen.de
<https://ths.rwth-aachen.de/teaching/>

Exercise 1

We define the famous *Pigeon Hole Problem (PHP)* over $\mathbb{N} = \mathbb{N} \setminus \{0\}$:

Given: $n \in \mathbb{N}$.

Question: Do $n + 1$ pigeons fit into n holes, if no two pigeons fit into one hole?

- What is the solution to the pigeon hole problems for all $n \in \mathbb{N}$?
- Formulate the pigeon hole problem for $n = 2$ holes (and thus 3 pigeons) in propositional logic.
- If your formula is not already in CNF, convert it into CNF. Use resolution to deduce the empty clause.
- Specify a preferably small unsatisfiable core of the problem, that is a subset of the clause set that is already unsatisfiable.
- The pigeon hole problems are a “worst-case” for many SAT-solvers. Can you guess why? Substantiate your claims!

1 + 2 + 2 + 1 + 1 points

Exercise 2

- Transfer the formula you created in Exercise 1 b) into the standard SAT input format (DIMACS¹). Also store your result as a text file and check it for satisfiability by using MiniSat². Verify the result and give the running time of the computation.
- Download additional pigeon whole problems for $n = 6, 7, \dots$ from the L²P room. They are already in the DIMACS format. Use MiniSat to check for satisfiability. Note the running times of each computation in a table. What do you think is the largest n whose corresponding formula can be solved within one hour? Give a reason!
- Download the modified versions of the pigeon hole problems having n holes and $n + 2$ pigeons. How are the running times compared to the original problems?

1 + 2 + 2 points

¹See for example <http://www.satcompetition.org/2009/format-benchmarks2009.html>

²Download from <http://minisat.se/MiniSat.html>