


Bit-Vectors

Chapter 6



Decision Procedures An Algorithmic Point of View

- 1 Introduction to Bit-Vector Logic
- 2 Syntax
- 3 Semantics
- 4 Decision procedures for Bit-Vector Logic
 - Flattening Bit-Vector Logic
 - Incremental Flattening

What kind of logic do we need for **system-level software**?

```
State { int created = 0; }

IoCreateDevice.exit {
  if ($return==STATUS_SUCCESS)
    created = 1;
}

IoDeleteDevice.exit { created = 0; }

fun_AddDevice.exit {
  if (created && (pdevobj->Flags & DO_DEVICE_INITIALIZING) != 0) {
    abort "AddDevice routine failed to set "
      "~DO_DEVICE_INITIALIZING flag";
  }
}
```

An Invariant of Microsoft Windows Device Drivers

What kind of logic do we need for **system-level software**?

```
State { int created = 0; }

IoCreateDevice.exit {
  if ($return==STATUS_SUCCESS)
    created = 1;
}

IoDeleteDevice.exit { created = 0; }

fun_AddDevice.exit {
  if (created && (pdevobj->Flags & DO_DEVICE_INITIALIZING) != 0) {
    abort "AddDevice routine failed to set "
      "~DO_DEVICE_INITIALIZING flag";
  }
}
```

An Invariant of Microsoft Windows Device Drivers


What kind of logic do we need for **system-level software**?

```
State { int created = 0; }

IoCreateDevice.exit {
    if ($return==STATUS_SUCCESS)
        created = 1;
}

IoDeleteDevice.exit { created = 0; }

fun_AddDevice.exit {
    if (created && (pdevobj->Flags & DO_DEVICE_INITIALIZING) != 0) {
        abort "AddDevice routine failed to set "
            "~DO_DEVICE_INITIALIZING flag";
    }
}
```



An Invariant of Microsoft Windows Device Drivers

What kind of logic do we need for system-level software?

- We need **bit-vector logic** – with bit-wise operators, arithmetic overflow
- We want to scale to large programs – must verify **large formulas**

What kind of logic do we need for system-level software?

- We need **bit-vector logic** – with bit-wise operators, arithmetic overflow
- We want to scale to large programs – must verify **large formulas**
- Examples of program analysis tools that generate bit-vector formulas:
 - CBMC
 - SATABS
 - F-Soft (NEC)
 - SATURN (Stanford, Alex Aiken)
 - EXE (Stanford, Dawson Engler, David Dill)
 - Variants of those developed at IBM, Microsoft

$formula$: $formula \vee formula \mid \neg formula \mid atom$
 $atom$: $term \ rel \ term \mid Boolean-Identifier \mid term[constant]$
 rel : $= \mid <$
 $term$: $term \ op \ term \mid identifier \mid \sim term \mid constant \mid$
 $atom?term:term \mid$
 $term[constant:constant] \mid ext(term)$
 op : $+ \mid - \mid \cdot \mid / \mid << \mid >> \mid \& \mid \mid \mid \oplus \mid \circ$

$formula : formula \vee formula \mid \neg formula \mid atom$
 $atom : term \ rel \ term \mid Boolean-Identifier \mid term[constant]$
 $rel : = \mid <$
 $term : term \ op \ term \mid identifier \mid \sim term \mid constant \mid$
 $atom?term:term \mid$
 $term[constant:constant] \mid ext(term)$
 $op : + \mid - \mid \cdot \mid / \mid << \mid >> \mid \& \mid \mid \mid \oplus \mid \circ$

- $\sim x$: bit-wise negation of x
- $ext(x)$: sign- or zero-extension of x
- $x << d$: left shift with distance d
- $x \circ y$: concatenation of x and y

Danger!

$$(x - y > 0) \iff (x > y)$$

Valid over \mathbb{R}/\mathbb{N} , but not over the bit-vectors.
(Many compilers have this sort of bug)



- The meaning depends on the **width** and **encoding** of the variables.

- The meaning depends on the **width** and **encoding** of the variables.
- Typical encodings:

- **Binary encoding**

$$\langle x \rangle_U := \sum_{i=0}^{l-1} a_i \cdot 2^i$$

- **Two's complement**

$$\langle x \rangle_S := -2^{\frac{l-1}{2}} \cdot a_{\frac{l-1}{2}} + \sum_{i=0}^{l-2} a_i \cdot 2^i$$

- But maybe also fixed-point, floating-point, ...

$$\langle 11001000 \rangle_U = 200$$


$$\langle 11001000 \rangle_S = -128 + 64 + 8 = -56$$

$$\langle 01100100 \rangle_S = 100$$

Notation to clarify width and encoding:

$$\mathcal{X}_{[32]}S$$

Notation to clarify width and encoding:



Definition (Bit-Vector)

A *bit-vector* is a vector of Boolean values with a given length l :


$$b : \{0, \dots, l - 1\} \longrightarrow \{0, 1\}$$

Definition (Bit-Vector)

A *bit-vector* is a vector of Boolean values with a given length l :

$$b : \{0, \dots, l-1\} \longrightarrow \{0, 1\}$$

The value of bit number i of x is $x(i)$.



We also write x_i for $x(i)$.

λ expressions are functions without a name

λ expressions are functions without a name

Examples:

- The vector of length l that consists of zeros:

$$\lambda i \in \{0, \dots, l-1\}. 0$$

- A function that inverts (flips all bits in) a bit-vector:

$$bv\text{-}invert(x) := \lambda i \in \{0, \dots, l-1\}. \neg x_i$$

- A bit-wise OR:

$$bv\text{-}or(x, y) := \lambda i \in \{0, \dots, l-1\}. (x_i \vee y_i)$$

\implies we now have semantics for the bit-wise operators.

Example

$$(x_{[10]} \circ y_{[5]})[14] \iff x[9]$$

$$(x_{[10]} \circ y_{[5]})[14] \iff x[9]$$

- This is translated as follows:

$$x[9] = x_9$$

$$(x_{[10]} \circ y_{[5]})[14] \iff x[9]$$

- This is translated as follows:

$$x[9] = x_9$$

$$(x \circ y) = \lambda i. (i < 5) ? y_i : x_{i-5}$$

$$(x_{[10]} \circ y_{[5]})[14] \iff x[9]$$

- This is translated as follows:

$$x[9] = x_9$$

$$(x \circ y) = \lambda i.(i < 5)?y_i : x_{i-5}$$

$$(x \circ y)[14] = (\lambda i.(i < 5)?y_i : x_{i-5})(14)$$

$$(x_{[10]} \circ y_{[5]})[14] \iff x[9]$$

- This is translated as follows:

$$x[9] = x_9$$

$$(x \circ y) = \lambda i.(i < 5)?y_i : x_{i-5}$$

$$(x \circ y)[14] = (\lambda i.(i < 5)?y_i : x_{i-5})(14)$$

- Final result:

$$(\lambda i.(i < 5)?y_i : x_{i-5})(14) \iff x_9$$

What is the output of the following program?

```
unsigned char number = 200;  
number = number + 100;  
printf("Sum: %d\n", number);
```



What is the output of the following program?

```
unsigned char number = 200;  
number = number + 100;  
printf("Sum: %d\n", number);
```



On most architectures, this is 44!

$$\begin{array}{rcl} & 11001000 & = 200 \\ + & 01100100 & = 100 \\ \hline = & 00101100 & = 44 \end{array}$$

What is the output of the following program?

```
unsigned char number = 200;  
number = number + 100;  
printf("Sum: %d\n", number);
```



On most architectures, this is 44!

$$\begin{array}{rcl} & 11001000 & = 200 \\ + & 01100100 & = 100 \\ \hline = & 00101100 & = 44 \end{array}$$

⇒ Bit-vector arithmetic uses modular arithmetic!

Semantics for addition, subtraction:

$$a[l] +_U b[l] = c[l] \quad \Longleftrightarrow \quad \langle a \rangle_U + \langle b \rangle_U = \langle c \rangle_U \pmod{2^l}$$

$$a[l] -_U b[l] = c[l] \quad \Longleftrightarrow \quad \langle a \rangle_U - \langle b \rangle_U = \langle c \rangle_U \pmod{2^l}$$

Semantics for addition, subtraction:

$$a[l] +_U b[l] = c[l] \iff \langle a \rangle_U + \langle b \rangle_U = \langle c \rangle_U \pmod{2^l}$$

$$a[l] -_U b[l] = c[l] \iff \langle a \rangle_U - \langle b \rangle_U = \langle c \rangle_U \pmod{2^l}$$

$$a[l] +_S b[l] = c[l] \iff \langle a \rangle_S + \langle b \rangle_S = \langle c \rangle_S \pmod{2^l}$$

$$a[l] -_S b[l] = c[l] \iff \langle a \rangle_S - \langle b \rangle_S = \langle c \rangle_S \pmod{2^l}$$

Semantics for addition, subtraction:

$$a[l] +_U b[l] = c[l] \iff \langle a \rangle_U + \langle b \rangle_U = \langle c \rangle_U \pmod{2^l}$$

$$a[l] -_U b[l] = c[l] \iff \langle a \rangle_U - \langle b \rangle_U = \langle c \rangle_U \pmod{2^l}$$

$$a[l] +_S b[l] = c[l] \iff \langle a \rangle_S + \langle b \rangle_S = \langle c \rangle_S \pmod{2^l}$$

$$a[l] -_S b[l] = c[l] \iff \langle a \rangle_S - \langle b \rangle_S = \langle c \rangle_S \pmod{2^l}$$

We can even mix the encodings:

$$a[l]_U +_U b[l]_S = c[l]_U \iff \langle a \rangle_U + \langle b \rangle_S = \langle c \rangle_U \pmod{2^l}$$

Semantics for $<$, \leq , \geq , and so on:

$$a[l]_U < b[l]_U \iff \langle a \rangle_U < \langle b \rangle_U$$

$$a[l]_S < b[l]_S \iff \langle a \rangle_S < \langle b \rangle_S$$

Semantics for $<$, \leq , \geq , and so on:

$$\begin{aligned}a_{[l]U} < b_{[l]U} &\iff \langle a \rangle_U < \langle b \rangle_U \\a_{[l]S} < b_{[l]S} &\iff \langle a \rangle_S < \langle b \rangle_S\end{aligned}$$

Mixed encodings:

$$\begin{aligned}a_{[l]U} < b_{[l]S} &\iff \langle a \rangle_U < \langle b \rangle_S \\a_{[l]S} < b_{[l]U} &\iff \langle a \rangle_S < \langle b \rangle_U\end{aligned}$$

Note that most compilers don't support comparisons with mixed encodings.

- Satisfiability is **undecidable** for an unbounded width, even without arithmetic.

- Satisfiability is **undecidable** for an unbounded width, even without arithmetic.
- It is **NP-complete** otherwise.

A Simple Decision Procedure

- Transform Bit-Vector Logic to **Propositional Logic**
- Most commonly used decision procedure
- Also called '*bit-blasting*'

- Transform Bit-Vector Logic to **Propositional Logic**
- Most commonly used decision procedure
- Also called '*bit-blasting*'

Bit-Vector Flattening

- 1 Convert propositional part as before
- 2 Add a *Boolean variable for each bit* of each sub-expression (term)
- 3 Add *constraint* for each sub-expression

We denote the new Boolean variable for bit i of term t by $\mu(t)_i$.

What constraints do we generate for a given term?

What constraints do we generate for a given term?

- This is easy for the bit-wise operators.
- Example for $a|_l b$:

$$\bigwedge_{i=0}^{l-1} (\mu(t)_i = (a_i \vee b_i))$$

(read $x = y$ over bits as $x \iff y$)

What constraints do we generate for a given term?

- This is easy for the bit-wise operators.
- Example for $a|_l b$:

$$\bigwedge_{i=0}^{l-1} (\mu(t)_i = (a_i \vee b_i))$$

(read $x = y$ over bits as $x \iff y$)


- We can transform this into CNF using Tseitin's method.

How to flatten $a + b$?

Flattening Bit-Vector Arithmetic

How to flatten $a + b$? (a, b are bits)

→ we can build a *circuit* that adds them!



Full Adder

$$s \equiv (a + b + i) \bmod 2 \equiv a \oplus b \oplus i$$

$$o \equiv (a + b + i) \div 2 \equiv \boxed{a \cdot b \vee a \cdot i \vee b \cdot i}$$

The full adder in CNF:

$$\sigma: (a \vee b \vee \neg o) \wedge (a \vee \neg b \vee i \vee \neg o) \wedge (a \vee \neg b \vee \neg i \vee o) \wedge \\ (\neg a \vee b \vee i \vee \neg o) \wedge (\neg a \vee b \vee \neg i \vee o) \wedge (\neg a \vee \neg b \vee o)$$

6 clauses

$$\Delta: (a \vee b \vee i \vee \neg s) \wedge (a \vee b \vee \neg i \vee s) \wedge (a \vee \neg b \vee i \vee s) \wedge \\ (a \vee \neg b \vee \neg i \vee \neg s) \wedge (\neg a \vee b \vee i \vee s) \wedge (\neg a \vee b \vee \neg i \vee \neg s) \wedge \\ (\neg a \vee \neg b \vee i \vee \neg s) \wedge (\neg a \vee \neg b \vee \neg i \vee s)$$

8 clauses


14 clauses

Ok, this is good for one bit! How about more?

Flattening Bit-Vector Arithmetic

Ok, this is good for one bit! How about more?

8-Bit ripple carry adder (RCA) $a_{[8]u} + a_{[8]u} = s_{[8]u}$



- Also called *carry chain adder*
- Adds $2l$ variables
- Adds $8 \cdot l$ clauses
14

- **Multipliers** result in very hard formulas
- Example:

$$a \cdot b = c \wedge b \cdot a \neq c \wedge x < y \wedge x > y$$

CNF: About 11000 variables, **unsolvable** for current SAT solvers


- Similar problems with division, modulo
- Q: Why is this hard?

- **Multipliers** result in very hard formulas
- Example:

$$a \cdot b = c \wedge b \cdot a \neq c \wedge x < y \wedge x > y$$


CNF: About 11000 variables, **unsolvable** for current SAT solvers

- Similar problems with division, modulo
- Q: Why is this hard?
- Q: How do we fix this?




φ_{sk} : Boolean part of φ

F : set of terms that are in the encoding




φ_{sk} : Boolean part of φ

F : set of terms that are in the encoding



φ_{sk} : Boolean part of φ


F : set of terms that are in the encoding



φ_{sk} : Boolean part of φ

F : set of terms that are in the encoding

I : set of terms that are inconsistent with the current assignment




φ_{sk} : Boolean part of φ

F : set of terms that are in the encoding

I : set of terms that are inconsistent with the current assignment

Incremental Flattening

CEGAR : Counterexample- guided abstraction refinement



φ_{sk} : Boolean part of φ

F : set of terms that are in the encoding

I : set of terms that are inconsistent with the current assignment

- Idea: add 'easy' parts of the formula first
- Only add hard parts when needed
- φ_f only gets stronger – use an incremental SAT solver

- Hey: initially, we only have the skeleton!
How do we know what terms are inconsistent with the current assignment if the variables aren't even in φ_f ?

- Hey: initially, we only have the skeleton!
How do we know what terms are inconsistent with the current assignment if the variables aren't even in φ_f ?
- Solution: **guess** some values for the missing variables.
If you guess right, it's good.

- Hey: initially, we only have the skeleton!
How do we know what terms are inconsistent with the current assignment if the variables aren't even in φ_f ?
- Solution: **guess** some values for the missing variables.
If you guess right, it's good.
- Ideas:
 - All zeros
 - Sign extension for signed bit-vectors
 - Try to propagate constants ($a = b + 1$)