

Satisfiability Checking

Branch and Bound

Prof. Dr. Erika Ábrahám

RWTH Aachen University
Informatik 2
LuFG Theory of Hybrid Systems

WS ~~14~~/15

15/16


Definition

An **integer linear system** S is a linear system $Ax = 0$, $\bigwedge_{i=1}^m l_i \leq s_i \leq u_i$, with the additional **integrality requirement** that all variables are of type integer.

Definition (relaxed system)


Given an integer linear system S , its **relaxation** $\text{relaxed}(S)$ is S without the integrality requirement.

Geometric interpretation




Remember: no
strict inequalities!


Geometric interpretation




Geometric interpretation



Geometric interpretation



Geometric interpretation



Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

procedure Branch-and-Bound(S) {

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
    res = LP(relaxed( $S$ ));
```

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
    res = LP(relaxed( $S$ ));  
    if (res==UNSAT) return UNSAT;
```

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
    res = LP(relaxed( $S$ ));  
    if (res==UNSAT) return UNSAT;  
    else if (res is integral) return SAT;  
    else {
```

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
    res = LP(relaxed( $S$ ));  
    if (res==UNSAT) return UNSAT;  
    else if (res is integral) return SAT;  
    else {  
        Select a variable  $v$  that is assigned a non-integral value  $r$ ;
```

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
  res = LP(relaxed( $S$ ));  
  if (res==UNSAT) return UNSAT;  
  else if (res is integral) return SAT;  
  else {  
    Select a variable  $v$  that is assigned a non-integral value  $r$ ;  
    if (Branch-and-Bound( $S \cup (v \leq \lfloor r \rfloor)$ ))==SAT) return SAT;  
  }
```

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
    res = LP(relaxed( $S$ ));  
    if (res==UNSAT) return UNSAT;  
    else if (res is integral) return SAT;  
    else {  
        Select a variable  $v$  that is assigned a non-integral value  $r$ ;  
        if (Branch-and-Bound( $S \cup (v \leq \lfloor r \rfloor)$ ))==SAT) return SAT;  
        else if (Branch-and-Bound( $S \cup (v \geq \lceil r \rceil)$ ))==SAT) return SAT;
```

Branch and bound algorithm

Input: An integer linear system S

Output: SAT if S is satisfiable, UNSAT otherwise

```
procedure Branch-and-Bound( $S$ ) {  
    res = LP(relaxed( $S$ ));  
    if (res==UNSAT) return UNSAT;  
    else if (res is integral) return SAT;  
    else {  
        Select a variable  $v$  that is assigned a non-integral value  $r$ ;  
        if (Branch-and-Bound( $S \cup (v \leq \lfloor r \rfloor)$ ))==SAT) return SAT;  
        else if (Branch-and-Bound( $S \cup (v \geq \lceil r \rceil)$ ))==SAT) return SAT;  
        else return UNSAT;  
    }  
}
```

Branch and bound

- The algorithm is **incomplete**.
- Example: $1 \leq 3x - 3y \leq 2$ has unbounded real solutions but no integer solutions \rightarrow the algorithm loops forever.
- The algorithm can be made complete for formulae with the small-model property: if there is a solution, then there is also a solution within a (computable) finite bound.
- The algorithm can be extended to **mixed integer linear programming**, where some of the variables are integer-valued while the others are real-valued.



- Branch: Split the search space
- Bound: Exclude unsatisfiable sub-spaces
- We have seen: Depth-first search
- Also possible: Breadth-first search

Optimizations:

- Constraints can be removed: $x_1 + x_2 \leq 2$, $x_1 \leq 1$, $x_2 \leq 1$.

Optimizations:

- Constraints can be removed: $x_1 + x_2 \leq 2$, $x_1 \leq 1$, $x_2 \leq 1$.
First constraint is redundant.

Optimizations:

- Constraints can be removed: $x_1 + x_2 \leq 2$, $x_1 \leq 1$, $x_2 \leq 1$.
First constraint is redundant.
- Bounds can be tightened: $2x_1 + x_2 \leq 2$, $x_2 \geq 4$, $x_1 \leq 3$

Optimizations:

- Constraints can be removed: $x_1 + x_2 \leq 2$, $x_1 \leq 1$, $x_2 \leq 1$.
First constraint is redundant.
- Bounds can be tightened: $2x_1 + x_2 \leq 2$, $x_2 \geq 4$, $x_1 \leq 3$
From the first two constraints we get $x_1 \leq -1$

Optimizations:

- Constraints can be removed: $x_1 + x_2 \leq 2$, $x_1 \leq 1$, $x_2 \leq 1$.
First constraint is redundant.
- Bounds can be tightened: $2x_1 + x_2 \leq 2$, $x_2 \geq 4$, $x_1 \leq 3$
From the first two constraints we get $x_1 \leq -1$
- Assume a constraint $\sum_i a_i x_i \leq b$ with $l_i \leq x_i \leq u_i$.
If $a_k > 0$, we have $x_k \leq (b - \sum_{i \neq k} a_i l_i) / a_k$.
If $a_k < 0$, we have $x_k \geq (b - \sum_{i \neq k} a_i u_i) / a_k$.