

PulseSync Medical – Clinical Follow-up Note

Patient Name	Mark Smith	DOB	1976-05-22
Hospital	PulseSync Medical Specialty Hospital	Document Date	2026-03-12

S: Subjective

Patient reports mild incisional discomfort improving over the last 48 hours. No chest pain, syncope, or palpitations. No fever or wound drainage. Patient able to perform light activities without dyspnea.

O: Objective

Vital Signs: BP 126/78 mmHg, HR 62 bpm, SpO₂ 98% RA

Wound Check: Incision clean, dry, intact; no erythema or discharge

Device Model/Serial: Dual Chamber MRI SureScan Pacemaker / PSM482917

Implant Date/Side: 2025-06-20 / Right pectoral

Leads: Atrial PS-ALD 4574 (ALD4574-219384), Ventricular PS-VLD 5076 (VLD5076-773512)

Telemetry Snapshot: Battery 100%, Est. longevity 8.8 yrs, A-paced 12%, V-paced 8%, AF burden 0%

A: Assessment

Status post dual-chamber pacemaker implantation for symptomatic bradycardia. Wound healing appropriately with no signs of infection. Device parameters stable with appropriate sensing and thresholds. No arrhythmia episodes detected since implant.

P: Plan

- Continue routine wound care; avoid lifting >5 kg on the right side for 2 weeks.
- Remote transmission in 7 days, then every 3 months or as directed.
- In-person device check at 10-14 days post-implant.
- Reinforce MRI-conditional status under institutional protocol.
- Provide patient education materials for activity, travel, and device ID card.

This note is generated for demo workflows (Data 360/Agentforce) and is not a substitute for clinical judgment.

Discharge Summary

Patient Name	Mark Smith	DOB	1976-05-22
Hospital	PulseSync Medical Specialty Hospital	Document Date	2026-03-12

Admission & Discharge

Admission Date/Time	2025-06-20 08:15
Discharge Date/Time	2025-06-21 11:40
Attending Physician	On-duty EP, PulseSync Medical
Procedure Performed	Dual Chamber Pacemaker Implantation

Diagnoses

Primary	Symptomatic bradycardia (suspected sinus node dysfunction)
Secondary	No structural heart disease documented

Procedure Summary

Uneventful pacemaker implantation via right subclavian approach. Leads positioned in RA appendage and RV apex with excellent thresholds. No complications.

Device & Leads

Generator Model	Dual Chamber MRI SureScan Pacemaker
Generator Serial	PSM482917
Implant Side	Right pectoral
Atrial Lead Model/Serial	PS-ALD 4574 / ALD4574-219384
Ventricular Lead Model/Serial	PS-VLD 5076 / VLD5076-773512

Discharge Instructions

- Keep incision clean and dry for 48 hours; avoid submerging until cleared.
- No lifting >5 kg or raising right arm above shoulder for 1-2 weeks.
- Monitor for signs of infection: redness, warmth, drainage, fever; call if present.
- Carry device ID card. Airport security: inform TSA; pacemaker is MRI-conditional under specific conditions.
- Remote transmission check in 7 days; clinic wound check in 10-14 days.

Follow-up Plan

Remote Monitoring	In 7 days post-implant, then every 3 months
Clinic Visit	In-person wound check at 10-14 days

Condition on Discharge

Stable. Pain controlled with oral analgesics. Ambulating independently. Wound clean, dry, intact.

Emergency & Safety Guidance

If chest pain, shortness of breath, syncope, or palpitations occur, seek urgent medical attention. For general concerns, contact the clinic line listed on your discharge paperwork.

For demo only. Not for clinical use.

Patient Information

Patient Name	Mark Smith	DOB	1976-05-22
Hospital	PulseSync Medical Specialty Hospital	Patient ID	PSM491002

Interrogation Details

Interrogation Date	2026-03-10
Device Model	Dual Chamber MRI SureScan Pacemaker
Device Serial	PSM482917
Implant Date	2025-06-20
Implant Side	Right pectoral

Device Interrogation Summary

Parameter	Value
Battery Status	100%
Estimated Longevity	8.6 years
Atrial Pacing Percentage	13%
Ventricular Pacing Percentage	9%
Atrial Fibrillation Burden	0%
Lead Integrity	Normal
Sensing Values	Stable
Pacing Thresholds	Within normal limits

Lead Measurements

Measurement	Value
RA Sensing (P-wave)	3.9 mV
RA Threshold	0.8 V @ 0.4 ms
RA Lead Impedance	515 Ω
RV Sensing (R-wave)	9.8 mV
RV Threshold	0.7 V @ 0.4 ms
RV Lead Impedance	605 Ω
RA Sensing (P-wave)	3.9 mV
RA Threshold	0.8 V @ 0.4 ms