

- The metrics that are tracked depend on whether settings such as participant tracking or presenter tracking are enabled.
- When sales reps present content during a visit, records are synced to Salesforce after the visit is saved or submitted.
- When you cancel a presentation, metrics aren't tracked.
- When session tracking is paused, metrics aren't tracked or associated with the related visit. Users see a reminder on each presentation and page so that they can start or resume tracking when it's appropriate.

What Metrics Are Tracked

Each page in the presentation can contain multiple slides, and one record is created for each slide presented. Metrics are tracked when users spend at least 3 seconds on a slide.

Tracked metrics for each slide can include:

- Presentation details, including pages and content versions.
- Products, messages, and guidance related to presentation pages.
- Information about the related healthcare professional (HCP) account and the visit or remote engagement during which metrics were captured.
- Details about how the participant accessed the presentation, including their browser, device type, and operating system.
- Timestamps for when the user opened and left a page, and the total time spent on the page.
- Content feedback from the participant during or after the presentation.

For details about all metrics collected, see [PresentationClickStrmEntry](#) in the Life Sciences Cloud Developer Guide.

See Also

[Reports and Dashboards](#)

Intelligent Content Reference

Create the content and source files for Life Sciences Customer Engagement presentations and email templates.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

[Guidelines for Life Sciences Email Templates](#)

Create predefined email templates with dynamic variables, rich text, content fragments, and advanced

queries so that field users can send personalized emails to healthcare professionals (HCPs). In the email template ZIP file, include structured layouts, images, text, fragments, and attachments. Then, admins can upload the ZIP files to Life Sciences Customer Engagement and create email templates.

Guidelines for Life Sciences Presentations

Create presentation source files that admins can upload to Life Sciences Customer Engagement and distribute to sales reps. To personalize content for healthcare professionals (HCPs) and healthcare organizations (HCOs), include dynamic content in presentation files. Life Sciences Customer Engagement supports two types of source files for presentations: ZIP files and PDFs.

Guidelines for Life Sciences Email Templates

Create predefined email templates with dynamic variables, rich text, content fragments, and advanced queries so that field users can send personalized emails to healthcare professionals (HCPs). In the email template ZIP file, include structured layouts, images, text, fragments, and attachments. Then, admins can upload the ZIP files to Life Sciences Customer Engagement and create email templates.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Email Template ZIP Files

Create a ZIP file that contains email template data. In Life Sciences Customer Engagement, admins upload these ZIP files to create and share email templates with field users.

Dynamic Capabilities for Email Templates

Life Sciences Customer Engagement uses a Mustache template processor to process and display dynamic content in email templates. Before a page loads, data is collected as a JSON string and fed into the Mustache template processor, which uses it to fill in the content placeholders in the email template. In the Send Email window, users see the populated email template.

Email Template ZIP Files

Create a ZIP file that contains email template data. In Life Sciences Customer Engagement, admins upload these ZIP files to create and share email templates with field users.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

In each email template ZIP file, include these content types.

Content	Required	Description
Index HTML File	Required	An HTML file that contains the HTML code for the email template. Salesforce inserts the HTML file content into email bodies. The file name must be <code>index.html</code>. To use several languages within a single email template so that users can send emails based on the recipient's language, include 1 additional <code>index.html</code> file for each language in the ZIP file. In the file name, include a language suffix to match the ISO code, for example, <code>index_en_US.html</code> or <code>index_fr.html</code>. ISO codes are case-sensitive.
Thumbnail File	Required	A JPG file to use as the preview image for the email template. The file name must be <code>thumbnail.jpg</code>. • The thumbnail file size limit is 2.97MB. • The optimal image resolution is 220x280 pixels.
Attachments Folder	Optional	A folder that contains email attachments. The folder name must be <code>attachments</code>. • These attachment formats are supported: - Documents - Images - Audio

Content	Required	Description
		- Video - Archives • To mark attachments as required, include a required__ prefix in the file name. Users can't deselect, modify, or remove these attachments. • Attachment file names can't include semicolons. • For emails to process correctly, attachments must be under 6 MB.
Fragments Folder	Optional	A folder of fragments, which are HTML content blocks that users can combine in the email body text to customize the email. The folder name must be fragments.

This example email template shows the customer's name and the sales rep's name. For information about the attributes that you can include in the template, see [Supported Attributes in Email Templates](#).

```
<!DOCTYPE html>
<html>
  <body>
    <p>
      Hi {{recipient.name}}, this is an email from a {{sender.firstname}}
      {{sender.lastname}}
    </p>
  </body>
</html>
```

Dynamic Capabilities for Email Templates

Life Sciences Customer Engagement uses a Mustache template processor to process and display dynamic content in email templates. Before a page loads, data is collected as a JSON string and fed into the Mustache template processor, which uses it to fill in the content placeholders in the email template. In the Send Email window, users see the populated email template.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Supported Attributes in Email Templates

Using Mustache variables, you can access Life Sciences Customer Engagement attributes dynamically from an email template.

Supported Content in Email Templates

Add additional content into email template HTML and ZIP files.

JSON Structure for Email Templates

Understand the hierarchy and structure of the JSON properties that are available to the Mustache template processor in Life Sciences Customer Engagement email templates.

Querying Data in Email Templates

Query Life Sciences Customer Engagement data in email templates and show results in emails.

Supported Attributes in Email Templates

Using Mustache variables, you can access Life Sciences Customer Engagement attributes dynamically from an email template.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

These attributes are supported only for email templates in the Life Sciences Cloud mobile app. When users send emails on desktop, only attributes on the user and account objects, which represent the email sender and recipient, are supported.

Supported Formula Fields

Formula fields are supported as variables in Life Sciences email templates only for the user and account objects, which represent the email sender and recipient.

All [standard formula operators and functions](#) are supported in the Life Sciences Customer Engagement mobile app except for these.

- CURRENCYRATE

- DISTANCE
- GETRECORDIDS
- GETSESSIONID
- HTMLENCODE
- HYPERLINK
- IMAGEPROXYURL
- INCLUDE
- ISCLONE
- JSENCODE
- JSINHTMLENCODE
- JUNCTIONIDLIST
- LINKTO
- REQUIRESRIPT
- URLENCODE
- URLFOR
- VLOOKUP

Supported Object Attributes

All populated fields on these objects and their associated objects are supported as variables in Life Sciences email templates. If you use lookup or relationship fields as variables, the ID of the related record shows in the email body. Enter all field names in lowercase.

Object	Description	Format
sender	Fields on the User object, which represents the email sender.	<code>{{sender.fieldname}}</code>
sender.userAdditionalInfo	Fields on the associated UserAdditionalInfo object.	<code>{{sender.useradditionalinfo.fieldname}}</code>
sender.lifeScienceMobileApp	Fields on the associated LifeScienceMobileApp record.	<code>{{sender.lifescimobileapp.fieldname}}</code>
recipient	Fields on the Account object, which represents the email recipient.	<code>{{recipient.fieldname}}</code>
recipient.healthcareProvider	Fields on the associated HealthcareProvider object.	<code>{{recipient.healthcareprovider.fieldname}}</code>
recipient.healthcareProviderSpecialty	Fields on the associated HealthcareProviderSpecialty object.	<code>{{recipient.healthcareproviderspecialty.fieldname}}</code>

Object	Description	Format
	Returns a single primary specialty. Returns only active records that are set to isPrimary, ordered by preference rank.	
recipient.contactPointAddress	Fields on the associated ContactPointAddress object. Addresses are used in this order. • If the preferred address is set on the related ProviderAcctTerritoryInfo, that address is used. • If the preferred address isn't set but a related ContactPointAddress record is set to primary, that address is used. • Otherwise, the primary address that was created most recently is used. • If there's no recent primary address, the address that was created most recently is used.	<code>{{recipient.contactpointaddress.fieldname}}</code>
recipient.contactPointEmails	Fields on the associated ContactPointEmail object. Returns only records that are set to isPrimary, ordered by preference rank.	<code>{{recipient.contactpointemails.0.fieldname}}</code>
recipient.contactPointPhones	Fields on the associated ContactPointPhone object. Returns only records that are set to isPrimary, ordered by preference rank.	<code>{{recipient.contactpointphones.0.fieldname}}</code>
recipient.contactPointSocials	Fields on the associated	<code>{{recipient.contactpointsocials.0.fieldname}}</code>

Object	Description	Format
	ContactPointSocial object. Returns the records that were updated most recently first.	
visit	Fields on the Visit object. Supported in email templates for remote engagement invitations.	<code>{{visit.fieldname}}</code>
visit.providerVisit	Fields on the associated ProviderVisit object.	<code>{{visit.providervisit.fieldname}}</code>

Supported Variables

These variables are supported in email templates.

Variable	Description
<i>surveyDeveloperName</i>	The developer name of a survey. To reference this variable, include <code>{{surveyDeveloperName}}</code> in the email template.
<i>surveyInvitationLink</i>	A link to a survey. To reference this variable, include <code>{{surveyInvitationLink}}</code> in the email template.
<i>remotesession.url</i>	The URL that's generated for a remote session with a specific account. This variable is supported in email templates for remote engagement invitations.

Supported Content in Email Templates

Add additional content into email template HTML and ZIP files.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

DateTime Picker

Add a date, time, or date and time picker to an email template.

Add a date picker without a predefined date so that the current date is prepopulated. Use a `span` element with the `LSC_DateTimeInput` class, for example:

```
<span class="LSC_DateTimeInput">
</span>
```

Add a time picker without a predefined time so that the current time is prepopulated. Use a `span` element with the `LSC_DateTimeInput` class and a `time` attribute, for example:

```
<span class="LSC_DateTimeInput" time>
</span>
```

Add a time picker without a predefined time and with a time zone stamp so that the current time is prepopulated with the time zone. Use a `span` element with `LSC_DateTimeInput` class and a `time` `timezone` attribute, for example:

```
<span class="LSC_DateTimeInput" time timezone>
</span>
```

Add a date or time picker with a predefined value. Use a `span` element with `LSC_DateTimeInput` class, and include the predefined date or time value inside the class, for example:

```
<span class="LSC_DateTimeInput">
30/07/2025
</span>
```

Deep Link Tokens

Add the ability to use a token and a link within an email template so that healthcare professionals (HCPs) can easily open and log into their company site. A Salesforce admin must first add a custom field to the account object to store the required tokens. For example, a Salesforce admin adds these custom fields to the account object.

- `orchestrationlogintokenlong__c`
- `orchestrationlogintokenshort__c`

In the email template, you can use these Mustache variables to insert the token into the link.

- `{{recipient.orchestrationlogintokenlong__c}}`
- `{{recipient.orchestrationlogintokenshort__c}}`

For example, this link uses a token.

```
https://examplesite.com/portal?token={{recipient.orchestrationlogintokenlong__c}}
```

Dropdown Fields and Values

Add dropdown fields with predefined text or URL values to an email template. Users can select these sections or tags in the template and preview the content before they send the email.

To add a dropdown and values, use a `span` element with the `LSC_DropDownInput` class. These attributes are supported.

Attribute	Description
option	The predefined values for the dropdown. You can configure several options, but users can select only one.
default	The default value for the dropdown.
link	A dropdown value that's a URL link. Include the URL address and link text.
subject	Dropdown values with this parameter can override the email template subject so that users can select from predefined email subjects. The subject parameter supports recipient attributes, for example, "Hello, dear <code>{{recipient.fieldname}}</code>."

See this example.

```
<span class="LSC_DropDownInput">
  <span>option1</span>
  <span link="https://www.google.com">option2</span>
  <span default>option3</span>
</span>
<span class="LSC_DropDownInput" subject>
  <span>option1 subject</span>
```

```
<span default link="https://www.google.com">option2 subject</span>
<span>option3 subject</span>
</span>
```

Fragments

Email fragments are pieces of HTML code that users can select and combine in the body of an email to customize the content. In the email template ZIP file, add the email fragments in the `fragments` folder. Fragment file names are mapped to fragment record names in Salesforce.

To enable users to select fragments in the email body, add the `LSC_EmailFragments` class to the template's `index.html` file. These attributes are supported.

Attribute	Description
min	The minimum number of fragments that users can select for the template. - To make fragment selection optional, set <code>min="0"</code>. - To make fragment selection mandatory, enter any number that's greater than 0.
max	The maximum number of fragments that users can select for the template.

See this example.

```
<table class = "LSC_EmailFragments" min="1" max="3">
</table>
```

When you include fragments in your email template, keep these considerations in mind.

- Enclose fragments in a `<table>` tag.
- To render fragments correctly, enclose fragments in `<tr><td>` tags.
- To include images or links, use the `<a href>` tag.
- You can include other attributes supported for Life Sciences Customer Engagement.
- You can't include HTML start and end tags, such as `<HTML>` or `<BODY>`.

See this fragment example.

```
<tr>
```

```

        <td>
        <table>
        <tr>
        <td>
        <a href="https://www.google.com/">Link</a>
        </td>
        </tr>
        </table>
        </td>
    </tr>

```

Presentation Links

Add a placeholder for presentation links where you want links to appear in the email content. In the Send Email window, users can see the presentation names and links, reorder them, and delete them. When users share presentations, links are generated automatically and inserted in the email. See [Send Presentations as Email Links](#).

To add a rich text section in an email template, add an element with the `LSC_PresentationLinks` class, for example:

```

<div class="LSC_PresentationLinks">
</div>

```

Rich Text Section

Add a rich text section to the email template. When users preview email content, they can select these sections to enter and format text before they send the email.

To add a rich text section in an email template, add an element with the `LSC_RichTextInput` class, for example:

```

<div class="LSC_RichTextInput">
</div>

```

When you include a rich text section in your email template, keep these considerations in mind.

- To make the rich text field mandatory, add the `required="true"` attribute.
- To use the `LSC_RichTextInput` class with predefined text, include only the text, text tags, such as `<p>` and `<span>`, and text formatting tags, such as `<i>` and `<b>`.
- The template styling controls the text size in the rich text section.

When users send emails, the text editor supports these options.

- Bold text
- Italic text
- Underlined text
- Strikethrough text
- Align left
- Align center
- Align right
- Numbered list
- Bulleted list
- Indent formatting
- Outdent formatting

User Pictures

To add a user picture in the email template, include this code in the template's HTML where you want the picture to appear. These attributes are supported.

Attribute	Description
height	The picture's height, in pixels.
width	The picture's width, in pixels.
alt	The text that users see when they hover over the image.

See this example.

```
{{#sender.useradditionalinfo.userpictureurl}}  
  
{{/sender.useradditionalinfo.userpictureurl}}
```

JSON Structure for Email Templates

Understand the hierarchy and structure of the JSON properties that are available to the Mustache template processor in Life Sciences Customer Engagement email templates.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

In the Life Sciences Cloud mobile app, all populated account and user fields, along with the associated objects, are available in lowercase within the JSON. Formula fields aren't included.

```
{
  "sender" : {
    "firstname" : "John",
    "lastname" : "Doe",
    "username" : "john.doe@company.com",
    "email" : "john.doe@company.com",
    ...,
    "useradditionalinfo" : {
      "userpictureurl" : "https://publicurltopicture.com/user-picture",
      "secondaryphone" : "555-5555",
      ...,
      "secondaryemail" : "jdoe@anotheremail.com"
    },
    "lifesciencemobileapp" : {
      "devicemetadaversion" : ""
      ...,
      "isdownloadsynchronysuccessful" : true
    }
  },
  "recipient" : {
    "firstname" : "Jane",
    "lastname" : "Smith",
    "personemail" : "jane.smith@recipient.com",
    ...
    "healthcareprovider" : {
      "providertype" : "Medical Doctor",
      ...,
      "phoneticname" : "Jayn Doe"
    },
    "healthcareproviderspecialty" : {
      "specialtycode" : "1234567",
      ...,
      "specialtytype" : "Oncology"
    }
  },
  "contactpointaddress" : {
    "addresstype" : "Business",
    ...,
    "address" : "123 Main St, San Francisco, CA, 94115"
  },
  "contactpointemail" : [
```

```
{
  "emailaddress" : "jsmith@companyemail.com",
  ...,
  "preferencerank" : "1"
},
{
  "emailaddress" : "jsmith2@companyemail.com"
  ...
}
],
contactpointphones : [
{
  "telephonenumber" : "555-5550",
  ...,
  "isprimary" : true
},
{
  "telephonenumber" : "555-5551",
  ...
}
],
contactpointsocials : [
{
  "socialplatformprovider" : "Facebook",
  ...,
  "socialhandlename" : "Jane Doe"
},
{
  "socialplatformprovider" : "Twitter"
  ...
}
],
},
"visit" : {
  "status" : "Planned",
  ...,
  "visitpriority" : "High",
  "providervisit" : {
    "isadhocprovidervisit" : true,
    ...,
    "isconfirmed" : true
  }
}
},
```

```
"surveyinvitationlink" : "https://invitationtosurvey.com/link",
"surveydevelopername" : "Survey Developer Name",
"remotesession.url" : "https://urltosession.com/session-id"
}
```

This code enables you to use the raw JSON that's supplied to the Mustache template processor as a JavaScript object variable.

```
<script type="text/javascript">
<script type="text/javascript">
    var allData = {{{.}}};
</script>
```

Querying Data in Email Templates

Query Life Sciences Customer Engagement data in email templates and show results in emails.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

doLoad Function

Executes code automatically as soon as the Life Sciences email loads.

fetchWithParams Function

Queries Life Sciences Customer Engagement data and returns results to the specified callback method.

fetchValidationFailed Function

Prevent sending emails with empty or invalid query data in Life Sciences Customer Engagement.

doLoad Function

doLoad Function

Executes code automatically as soon as the Life Sciences email loads.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Syntax

```
doLoad()
```

Usage

Include any code that you want to execute automatically when the template loads inside of this method.

Example

```
function doLoad() {  
    EmailTemplate.fetchWithParams(  
        'SELECT Id, Name FROM Account WHERE Id = \''{{recipient.id}}\'',  
        {'batchSize' : 20},  
        'getAccountRecordsCallback'  
    )  
}
```

fetchWithParams Function

fetchWithParams Function

Queries Life Sciences Customer Engagement data and returns results to the specified callback method.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Syntax

```
EmailTemplate.fetchWithParams (query, params, callbackMethod)
```

Arguments

Argument	Description
query	The query as a string.
params	Optional. The ability to specify the batch size. In the params argument, use the <code>batchSize</code> attribute to set the number of records to return. A maximum of 100 records can be returned in each call. This example returns 75 records. <pre>EmailTemplate.fetchWithParams('SELECT Id FROM Account',{ 'batchSize': 75}, 'processFetch');</pre>
callbackMethod	The name of the JavaScript method that represents the queried results in the email and handles errors. Enclose the callback method in single or double quotes.

Usage

- You can fetch 100 records at once.
- To fetch related records, use a separate query.
- You can use aggregated and relationship queries.

JavaScript Support

In the email template HTML, place JavaScript scripts inside the `<script type="text/javascript">` tag.

To make sure that JavaScript scripts execute in order, avoid using asynchronous functions such as `setTimeout`, `setInterval`, and `promises`. Otherwise, Life Sciences Customer Engagement doesn't know when the template body is complete and ready for users to preview content or send emails.

Limitations

- You can't query Long Text Area-type fields with a `WHERE` clause.

- Child relationship queries such as `SELECT Id, (SELECT Id FROM Contacts) FROM Account` aren't supported.
- Avoid using global CSS styles, for example `div {background: red}`, as global styles are applied to the whole page. Instead, use parent based styles such as `.some-custom-container-class div {background: red}`.

Results

In the Life Sciences Cloud mobile app, these events are logged so that you can identify how many times the function executes in the email.

- Delete
- Upsert
- Fetch
- Target isn't specified

Example

This example email template uses the `doLoad` and `EmailTemplate.fetchWithParams` functions.

```
<!DOCTYPE html>
<html>
  <script type="text/javascript">
    function doLoad() {
      EmailTemplate.fetchWithParams('SELECT Id, Name FROM Account', {'batchSize': 100}, 'getAccountRecordsCallback2');
      EmailTemplate.fetchWithParams('SELECT Id, Name FROM Account', {'batchSize': 1}, 'getAccountRecordsCallback3');
    }

    function getAccountRecordsCallback2(data) {
      if(data.state === 'success') {
        const mustacheTarget = document.querySelector('#mainDiv2');
        const html = data.records.map((el)=>{
          if(el.Name){
            return '<div class="renderedData">' +
              '<span>' + el.Name + '</span>' +
              '</div>'
          }
          EmailTemplate.fetchValidationFailed('No Name');
        }).join('');
        const div = document.createElement('div');
        div.innerHTML = html;
        mustacheTarget.append(div);
      }
    }
  </script>
</html>
```

```

    }
  }

  function getAccountRecordsCallback3(data) {
    if(data.state === 'success') {
      const mustacheTarget = document.querySelector('#mainDiv3');
      const html = data.records.map((el)=>{
        if(el.Name){
          return '<div class="renderedData">' +
            '<span>' + el.Name + '</span>' +
            '</div>'
        }
        EmailTemplate.fetchValidationFailed('No Name');
      }).join('');
      const div = document.createElement('div');
      div.innerHTML = html;
      mustacheTarget.append(div);
    }
  }
</script>
<body>
<title>Email query example with batch</title>

<h1>Email query example with batch</h1>
<h2>Account object (batch = 100):</h2>

    <p>EmailTemplate.fetchWithParams will pass the Names from Account ob
ject (batch = 100):</p>
    <div id="mainDiv2"></div>

<h2>Account object (batch = 1): </h2>
    <p>EmailTemplate.fetchWithParams will pass the Names from Account ob
ject (batch = 1):</p>
    <div id="mainDiv3"></div>
  </body>
</html>

```

fetchValidationFailed Function

fetchValidationFailed Function

Prevent sending emails with empty or invalid query data in Life Sciences Customer Engagement.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Syntax

```
EmailTemplate.fetchValidationFailed (string)
```

Arguments

Argument	Description
string	Optional. Contains a specific error message that users see when the query fails for a specific recipient. If left blank, users see the default error message. After users remove the account from the list of recipients, they can send the email.

Usage

Add the `EmailTemplate.fetchValidationFailed (string)` function in addition to `EmailTemplate.fetchWithParams (query, CallbackMethod)`.

Example

This example uses the `EmailTemplate.fetchValidationFailed` function with the `doLoad()` and `EmailTemplate.fetchWithParams` functions.

```
<html>
  <script type="text/javascript">

    function doLoad() {
      EmailTemplate.fetchWithParams('SELECT Id, Name FROM Account WHERE Id =
\'{{recipient.id}}\'', {'batchSize': 100}, 'getAccountRecordsCallback');
    }
  </script>
</html>
```

```

function getAccountRecordsCallback(data) {
  if(data.state === 'success') {
    const mustacheTarget = document.querySelector('#mainDiv');
    const html = data.records.map((el)=>{
      //Validates that the name field isn't empty.
      if(el.Name){
        return '<div class="renderedData">' +
          '<span>' + el.Name + '</span>' +
          '</div>'
      } else {
        //Marks the email invalid.
        EmailTemplate.fetchValidationFailed('Type is missing');
      }
    }).join('');
    const div = document.createElement('div');
    div.innerHTML = html;
    mustacheTarget.append(div);
  }
}
</script>
<body>
  <p>Account Name:</p>
  <div id="mainDiv"></div>
</body>
</html>

```

Guidelines for Life Sciences Presentations

Create presentation source files that admins can upload to Life Sciences Customer Engagement and distribute to sales reps. To personalize content for healthcare professionals (HCPs) and healthcare organizations (HCOs), include dynamic content in presentation files. Life Sciences Customer Engagement supports two types of source files for presentations: ZIP files and PDFs.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

When you create source files for Intelligent Content presentations, design content to be responsive for different iOS devices.

ZIP Files as Sources for Presentations

To use ZIP files as the source for Intelligent Content presentations, create a separate ZIP file for each page in the presentation. In each individual ZIP file, include the HTML content for the presentation page. In Life Sciences Customer Engagement, pages are grouped into presentations, and each page shows separately in the presentation player. Admins can also associate each presentation page with a product and a key message, and Salesforce tracks presentation metrics for each page so that you can analyze and improve performance over time.

PDFs as Sources for Presentations

To create PDF source files for Intelligent Content presentations, include all presentation content in a single PDF. Each page of the PDF source file shows as a separate presentation page in the presentation player.

Best Practices to Send Presentations in Emails

Follow this guidance when you create presentation source files to send in emails in Life Sciences Customer Engagement.

Dynamic Capabilities for Presentations

Life Sciences Customer Engagement uses a presentation player that's powered by a Mustache template processor to display dynamic content. Before a page loads, data is collected as a JSON string and fed into the template processor, which uses it to fill in the content placeholders on the presentation page. In the presentation player, users see the fully populated presentation page.

ZIP Files as Sources for Presentations

To use ZIP files as the source for Intelligent Content presentations, create a separate ZIP file for each page in the presentation. In each individual ZIP file, include the HTML content for the presentation page. In Life Sciences Customer Engagement, pages are grouped into presentations, and each page shows separately in the presentation player. Admins can also associate each presentation page with a product and a key message, and Salesforce tracks presentation metrics for each page so that you can analyze and improve performance over time.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Life Sciences Customer Engagement downloads presentations and pages, and the presentation player runs the HTML, CSS, and JavaScript code to show each page.

Presentation Page Contents

In the ZIP file for each presentation page, include these items.

Content	Required	Description
HTML files	Required	HTML files contain the code for each slide. For each HTML file name, use the format <code>XX_name.html</code>, where XX is the slide number. Start at page 01, and increment sequentially for each additional page. In the HTML files, refer to CSS and JavaScript files for styles and actions.
A JPEG file	Required	JPEGs represent each page's thumbnail. For each JPEG file name, use the format <code>XX_thumbnail.jpg</code>, where XX is the page number. Limit the thumbnail size to less than 3050 KB or 2.97 MB. The optimal resolution for each image is 328 by 232 pixels. For other resolutions, the image uses the Aspect Fill method.
CSS and JavaScript files	Optional	Static resources that the HTML files reference.

File Name Recommendations for ZIP Source Files

Follow these guidelines for PDF file names. When admins upload presentation ZIP files to Life Sciences Customer Engagement, presentation pages are sorted alphabetically.

- Use the format `XX_name.zip` for each page's ZIP file name, where XX is the page number and name is a descriptive title. The page number can't be longer than 2 characters. The descriptive title must contain at least 2 characters.
- Limit the file name size to 960 bytes or fewer.
- Valid characters are A-Z, a-z, and 0-9.
- HTML file names can't include spaces.
- For presentations that admins upload in Life Sciences Customer Engagement:
 - These special characters are supported: -, ., _, !, *, ', (,)
 - These special characters aren't supported: /, \, and combinations `` and ``.
 - We recommend avoiding any other special characters.

- For presentations uploaded via the content management Connect API, special characters aren't supported.
- File extensions are case-sensitive and must be in lowercase, for example, .jpg.
- Double-byte kana, katakana, and numbers are supported, but different operating systems can cause mutations.

Content Recommendations for ZIP Source Files



Note If you create ZIP files on MacOS, the ZIP file can include a system folder. Make sure that you remove any system folders before admins upload ZIP files to Life Sciences Customer Engagement.

Follow these guidelines for presentation content in ZIP source files.

- Each ZIP file must contain at least one HTML file and its corresponding thumbnail JPEG file. For example, 02_secondSlide.html and 02_thumbnail.jpg.
- Each HTML file must include a corresponding thumbnail.
- Thumbnails must be in JPEG format. PNG and GIF files aren't supported.
- If one presentation page ZIP file contains more than 100 slides, we recommend creating separate page ZIP files for every set of 100 slides.
- Each presentation page ZIP file must be 1 GB or smaller.
- CSS and JavaScript files aren't required in presentation page ZIP files.
- In each presentation page ZIP file, you can include multiple HTML, JPEG, CSS, and JavaScript files.
- HTML and JPEG files must be at the top level in each presentation page ZIP file. If you include multiple CSS and JavaScript files, you can create folders for these.
- If you create a presentation as one HTML file and use `<div>` elements to represent each page, the content appears as a single presentation page in the presentation player.

Adding PDFs to Presentations

You can include video files in presentation page ZIP files and refer to the videos in a presentation page's HTML code. This example presentation page HTML code includes a reference to a PDF.

```
<a href="dam/iselling/pdf/example.pdf">EXAMPLE PDF FILE</a>
```

Adding Videos to Presentations

You can include video files in presentation page ZIP files and refer to the videos in a presentation page's HTML code. The video appears on that page in the presentation. The presentation player supports these video formats. In the HTML code, include the `type` attribute.

Video Format	HTML Type Attribute
MP4	"video/mp4"

Video Format	HTML Type Attribute
MOV	"video/quicktime"
M4V	"video/x-m4v"

This example presentation page HTML code includes a reference to an MP4 video file.

```
<video width="320" height="240" controls> <source src="./assets/movie.mp4" type="video/mp4"> Your browser does not support the video tag. </video>
```

Using Videos for Remote Engagement

Videos are supported for remote sessions when your Salesforce org uses Twilio as the service provider. Embedded videos and animation can behave differently in the presentation player during remote sessions. To include animations, we recommend using HTML or JavaScript code instead.

Linking to External Content in Presentations

You can link to external web pages from the presentation page HTML code. Links to PDFs or external content always open in a separate window. To link to an external web page, use this format.

```
<a href="https://www.google.com/">Google.com</a>
```

For details about the characters that you can include in URLs, see the RFC 3986 standard.

Adding Additional Content to Presentations

In presentation ZIP files, you can add additional content as PDF files and use links to reference those files from any page in the presentation. To mark a PDF as additional context, add `isadditionalcontent_` as a prefix in the file name. To link to an additional content PDF file, use the `gotoSlide()` function.

When admins upload additional content as part of a ZIP file presentation in Life Sciences Customer Engagement, the Additional Content checkbox is selected automatically on the presentation page record. Admins can also upload additional content PDFs as presentation source files when they upload or update presentations in bulk.

Using iFrame in Presentations

You can use iFrames in the presentation page HTML code. Scrolling is supported within the iFrame. These attributes are supported.

- `allow`

- `height`
- `name`
- `sandbox`
- `src`
- `srcdoc`
- `width`

Optimizing ZIP File Performance on iPad

To make sure that presentations load quickly and perform well on iPads, follow these guidelines when you build presentation page ZIP files.

- Compress images before you add them to presentations.
- Avoid adding extensive JavaScript logic to each page, such as navigation bars, tabs, tooltips, and dropdown menus.
- Don't use a content management system (CMS) to generate pages, as the CMS can add unnecessary code and slow down page load times.
- Divide complex pages into multiple simple pages. For example, if you have one page with horizontal or vertical tabs, create a separate page for each tab instead.
- Add a background, a simple image, or a color to the body tag that shows when the page is loading.
- Make sure that users are using supported mobile devices.

Example HTML Page in ZIP File Presentations

This example HTML page lists all customers and prints their names.

```
<!DOCTYPE html>
<html>
  <head>
    <link type="text/css" rel="stylesheet" href="media/css/style.css">
  </head>
  <body>
    <div id="screen-container">
      HELLO
      {{#customers}} <!--this is a mustache loop -->
        <span id="doc_name" class="template">{{firstName }} {{ lastName
e }}</span>
      {{/customers}}
      ,<br/>DO YOU WANT TO START THE VISIT?</span>
    </div>
  </body>
</html>
```

PDFs as Sources for Presentations

To create PDF source files for Intelligent Content presentations, include all presentation content in a single PDF. Each page of the PDF source file shows as a separate presentation page in the presentation player.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

File Name Recommendations for PDF Source Files

Follow these guidelines for PDF file names.

- Limit the file name size to 960 bytes or fewer.
- Valid characters are A-Z, a-z, and 0-9.
- For presentations that admins upload from Life Sciences Customer Engagement:
 - These special characters are supported: -, ., _, !, *, ', (,)
 - These special characters aren't supported: /, \, and combinations `“` and `”`.
 - We recommend avoiding any other special characters.
- For presentations uploaded via the content management Connect API, special characters aren't supported.
- Format file extensions in lowercase.
- Double-byte kana, katakana, and numbers are supported, but different operating systems can cause mutations.

Content Recommendations for PDF Source Files

Follow these guidelines for presentation content in PDF source files.

- Upload landscape versions of the PDF files.
- Create PDF presentations that are less than 1 GB or 200 pages.
- To make sure that PDF content displays correctly on iOS, test PDFs in the Preview app on an Apple device.
- To avoid performance issues and make sure that PDFs render correctly on devices with low memory, optimize the PDF file structure. For example, use the print production tools in Adobe Acrobat to flatten the PDF. We recommend these parameters:
 - Raster/Vector Balance: 0
 - Line Art and Text resolution: 160 pixels per inch (PPI), or up to 192 PPI for newer iPad Pros
 - Gradient and Mesh resolution: 160 PPI, or up to 192 PPI for newer iPad Pros
 - Color: JPEG

- Apply to PDF: All pages in document
- To create thumbnail images, PDF pages are cropped based on the first page's crop box. To show full images, remove the crop marks, or set the crop box to fit the part of the page that you want to show.
- To enable navigation between pages in the presentation player, add navigation links to specific pages in the PDF presentation source file.

Limitations for PDF Source Files

Videos aren't supported in PDF source files for presentations.

Best Practices to Send Presentations in Emails

Follow this guidance when you create presentation source files to send in emails in Life Sciences Customer Engagement.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

- In ZIP source files for presentations, also include a PDF file of the presentation. The PDF file is sent as the email attachment.
- To make the page or presentation file mandatory, add the **required__** prefix to the file name in the email template ZIP file. If the presentation is marked as required, users can't deselect the attachment when they send an email that uses the template.
- When an admin user uploads a PDF or ZIP file, the files are uploaded to Salesforce. When the PDF is less than 3 MB, it's attached to the presentation page record by default. For files that are larger than 3 MB, add the PDF file to the presentation page's files manually.

Dynamic Capabilities for Presentations

Life Sciences Customer Engagement uses a presentation player that's powered by a Mustache template processor to display dynamic content. Before a page loads, data is collected as a JSON string and fed into the template processor, which uses it to fill in the content placeholders on the presentation page. In the presentation player, users see the fully populated presentation page.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

package.

Before each page loads in the presentation player, data for each presentation and the associated visit are collected and provided as a JSON string so that the Mustache template processor can populate placeholders on the presentation page. The JSON data can also be stored as a JavaScript variable, allowing for direct access in presentation ZIP files.

Supported Attributes in Presentations

Using Mustache variables, you can access Life Sciences Customer Engagement attributes dynamically from presentation ZIP files.

JSON Structure for Presentations

Understand the hierarchy and structure of the JSON properties that are available to the Mustache template processor for Intelligent Content presentations.

Presentation Player Functions

You can include JavaScript code in the presentation ZIP file for Life Sciences Customer Engagement. When the JavaScript function is called during presentations, the action is performed in the presentation player.

Callback Event Function

When an event occurs in the Life Sciences Cloud mobile app, you can use a callback event function to notify the page's JavaScript, HTML, or template. For example, events can be triggered when users pause or resume tracking presentation metrics.

Supported Attributes in Presentations

Using Mustache variables, you can access Life Sciences Customer Engagement attributes dynamically from presentation ZIP files.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Keep these considerations in mind when you reference Salesforce objects and fields as variables in presentation ZIP files.

- Formula and lookup fields aren't supported.
- When you reference a standard Salesforce field, don't use a prefix or suffix.
- When you reference a custom field in your Salesforce org, use the custom suffix `__c`.
- Format mustache variables in lowercase, for example, `accounttype`.
- Users must have access to the Salesforce objects and fields that the presentation template references.

Account Objects and Fields

In the JSON structure, account fields appear in the `customers` node.

Object	Fields	Additional Details
Account	All standard and custom Account object fields.	• <code>accountType</code> returns HCP for Person Accounts and HCO for Business Accounts. • <code>recordType</code> returns the name and ID of the account's record type.
ContactPointAddress	An array of the account's associated ContactPointAddress records and fields. Only active records are returned.	Addresses are used in this order. • If the preferred address is set on the related provider account territory info, that address is used. • If the preferred address isn't set but a related contact point address record is set to primary, that address is used. • If the account has more than one primary address, the primary address that was created most recently is used. • If there's no recent primary address, the address that was created most recently is used.
HealthcareProviderSpecialties	An array of the account's associated HealthcareProviderSpecialties.	To access the first specialty in the array, use this code. <pre> {{#customers}} Customer Name: {{name}} Specialty: {{healthcareProviderSpecialties.0.name}} {/customers} </pre>

Object	Fields	Additional Details
		Returns only active records that are set to primary, ordered by most recently modified.
ContactPointEmail	An array of the account's associated ContactPointAddress records and fields.	Returns only records that are set to primary, ordered by preference rank.
ContactPointPhone	An array of the account's associated ContactPointPhone records and fields.	Returns only records that are set to primary, ordered by preference rank.
ContactPointSocials	An array of the account's associated ContactPointSocial records and fields.	Returned records are ordered by the social platform provider.
HealthCareProvider	All fields on the account's related HealthcareProviderRecord.	None

Presentation Fields

Field	Description
id	The presentation ID.
name	The presentation name.
sourceSystemIdentifier	A user-provided unique, external identifier for the presentation.
Pages	A predefined list of page fields. • id • sourceSystemIdentifier • contentDocumentId • name • slides: - name
isCustom	Identifies whether the presentation is a custom presentation created by a field user (<code>true</code>) or not (<code>false</code>). Depending on the variable's value in the

Field	Description
	variable, you can apply custom logic. See this HTML code example. <pre> <dl> {{#presentations}} <dt>Name: {{name}}</dt> <dt>Is Custom: {{#isCustom}} This is a custom presentat ion. {{/isCustom}} {{^isCustom}} This is a standard present ation. {{/isCustom}} </dt>
 {{/presentations}} </dl> </pre>

User Objects and Fields

Object	Fields	Additional Details
User	All standard and custom fields.	None
UserAdditionalInfo	All standard and custom fields on the associated UserAdditionalInfo record.	None
LifeScienceMobileApp	On the associated LifeScienceMobileApp record, all fields that contain data about the user's device, such as location and last download sync date.	Available only for the Life Sciences Cloud Mobile app.

Visit Fields

Field	Description
id	The visit ID.
accountId	The account ID.
isParent	Returns <code>true</code> when the Parent Visit field is blank.
sourceSystemIdentifier	A user-provided unique, external identifier for the visit.

Top-Level JSON Fields

These fields are at the top level of the JSON hierarchy, before Life Sciences Customer Engagement data.

Field	Description
currentMode	The current mode of the presentation player.
currentTerritoryId	The current territory ID.
currentTerritoryName	The current territory name.
emailTemplateId	The ID of the email template associated with the current presentation page.
state	The saved state of the presentation on the Life Sciences Cloud Mobile app.
presentationIndex	The presentation index in the presentations array.
pageIndex	The page index in the pages array.
slideIndex	The slide index in the slides array.

JSON Structure for Presentations

Understand the hierarchy and structure of the JSON properties that are available to the Mustache template processor for Intelligent Content presentations.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

```

currentMode: The current mode of the presentation player.
currentTerritoryId: The ID of the current territory.
currentTerritoryName: The name of the current territory.
emailTemplateId: The ID of the email template that's associated with the current page.
state: The saved state of the presentation on the Life Sciences Cloud Mobile app.
presentationIndex: The presentation index in the presentations array.
pageIndex: The page index in the pages array.
slideIndex: The slide index in the slides array.
customers: An array of account records.
    id: The account ID.
    isPrimary: Indicates the account of the primary visit.
    Type: The account type (Account.Type).
    PersonEmail: The account email on account. Emails are also captured in contact point email records.
    firstName: The first name of the account.
    lastName: The last name of the account.
    middleName: The middle name of the account.
    nationality: The nationality of the account.
    salutation: The salutation of the account.
    healthcareProviderSpecialties: An array of specialties.
        isPrimarySpecialty: Returns only primary specialties.
        isActive: Returns only active specialties.
        name: The specialty name.
    name: The name of the account.
    accountType: Returns HCP for a person account. Otherwise, returns HCO.
    sourceSystemIdentifier: The user-provided unique external identifier for the account.
    contactPointAddresses: An array of the account's contact point address records.
        id: The ID of the contact point address.
        street: The street component of the address.
        city: The city component of the address.
        state: The state component of the address.
        postalCode: The postal code for the address.
presentations: An array of presentation records.
    id: The presentation ID.
    name: The presentation name.
    isCustom: Identifies whether the presentation is a custom presentation created by a field user.
    Pages: An array of page records.
        id: The page ID.
        sourceSystemIdentifier: The user-provided unique external identifier f

```

```

or the page.
    slides: An array of slides.
    name: The name of slide, for example, 01_index.html.
user: User fields.
    name: The user's full name.
    firstName: The user's first name.
    lastName: The user's last name.
    userAdditionalInfo: Additional user fields on the associated user addition
al info record.
    availableCountries: The countries that are available for the user in t
he context of a search.
    preferredCountry: The user's preferred country.
visits: An array of visits.
    id: The visit ID.
    accountId: The account ID.
    isParent: Returns true when the Parent Visit field is blank.
    sourceSystemIdentifier: A user-provided unique, external identifier for th
e visit.

```

This template code example shows how to retrieve data from the JSON structure.

```

<div id="screen-container">
  HELLO
  {{#customers}}  <!--This is a Mustache loop -->
    <span id="doc_name" class="template">{{firstName }} {{ lastName }}</sp
an>
  {{/customers}}
  ,<br/>DO YOU WANT TO START THE VISIT?</span>
</div>

```

This code enables you to use the raw JSON that's supplied to the Mustache template processor as a JavaScript object variable.

```

var configData;
document.addEventListener('PresentationDOMContentLoaded', function(event) => {
  configData = event.data;
});

```

Presentation Player Functions

You can include JavaScript code in the presentation ZIP file for Life Sciences Customer Engagement. When the JavaScript function is called during presentations, the action is performed in the presentation player.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

All of the functions listed are available in the Life Sciences Cloud mobile app. Only these functions are available on desktop.

- `gotoSlide`
- `goPreviousPage`
- `goNextPage`

alert Function

Opens an alert on the user's mobile device with the specified message.

createVisit Function

Creates a visit for the selected attendees and returns the result to the specified callback method. When visits are created, Salesforce applies all configured visit validations.

defineNoSwipeRegion Function

Defines an area of the screen where the presentation player ignores the swipe gesture.

destroyNoSwipeRegion Function

Removes the region ID of an area of the screen where the presentation player ignores the swipe gesture.

disableDismiss and enableDismiss Functions

Dismiss functions control how the presentation player is closed and handled when users select the Visit button. These functions execute long-term operations in the 'returntovisitbuttonpress' event handler.

fetchWithParams Function

Queries data that's not already returned in Mustache variables, and returns results to the specified callback method.

getSurveyFlowJson Function

Searches for a survey and returns it in JSON format. Then, the presentation HTML can parse the survey and show it in the presentation player.

goNextPage Function

Goes to the next page in the presentation. If the current page is the last page in the presentation, nothing happens.

goPreviousPage Function

Goes to the previous page in the presentation. If the current page is the first page in the presentation, nothing happens.

goToSlide Function

Goes to the specified pages and assets within a presentation.

launchApprovedEmail Function

Opens the Send Email window with the email template that's linked to the presentation page, if the presentation page specifies a template. If there's no email template ID specified on the presentation page, the page isn't linked to a template.

launchEmails Function

Opens the Send Email window with the email templates that are available to the user.

logError Function

Logs error messages within the presentation player.

saveState Function

Saves data about the presentation's state to the state property in the JSON that's supplied to the presentation's Mustache template. Stores the state on the user's mobile device so that users can resume a presentation and continue where they left off in the same session or a future session.

setSurveyFlowJson Function

Saves survey results to the database for the current presentation and visit when the related visit is saved or submitted.

startTrackingPage Function

Starts tracking presentation metrics in a new presentation click stream entry record for the specified presentation page.

stopTrackingPage Function

Stops tracking presentation metrics for the current slide.

updateFeedback Function

Sets the feedback from the healthcare professional (HCP) to the specified type during presentations.

upsert Function

Creates and updates records for the specified objects and returns results to the specified callback method.

alert Function

alert Function

Opens an alert on the user's mobile device with the specified message.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.alert(message)
```

Arguments

Argument	Description
<code>message</code>	The message to show to the user.

createVisit Function

createVisit Function

Creates a visit for the selected attendees and returns the result to the specified callback method. When visits are created, Salesforce applies all configured visit validations.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.



Tip We recommend invoking this function only once per presentation session.

Syntax

```
PresentationPlayer.createVisit(callbackMethod)
```

Arguments

Argument	Description
<code>callbackMethod</code>	The name of the JavaScript method that receives the results of the operation.

Returns

This method returns JSON that contains the ID of the parent visit, for example:

```
{"state": "success", "id": "<parent_visit_uid>"}
```

Usage

When this function is called during a presentation and a visit is created successfully:

- Users can select the Visit button in the presentation player menu to open the visit. All presentation metrics that are tracked during the session are linked to the visit.
- If no attendees were selected before the visit was created, the account field on the visit is blank.
- Product restrictions and presentation targeting apply to the new visit.
- These records are related to the new visit.
 - Provider visit
 - Provider visit product detailing
 - Provider visit detailing product message
 - Presentation forum
 - Presentation click stream entry

Limitations

- The `createVisit` function doesn't populate the new visit's details into Mustache variables that reference visits.
- Don't use the `upsert` function to create visits.

Example

```
<body>
    <input id="name" style="color: black;">
    <input id="customField" style="color: black;">
    <a href="javascript:createVisit();">Create Visit</a>
</body>
<script type="text/javascript">
    function createVisit() {
        PresentationPlayer.createVisit('callbackMethod');
    }
    function callbackMethod(data) {
        console.log(data);
        PresentationPlayer.alert(JSON.stringify(data));
    }
}
```



```
</script>
```

Errors

This function returns errors when:

- Validation rules fail.
- A visit was already created during the presentation session. In this case, the function returns the ID of the visit that was created previously in JSON format.
- The presentation player is opened for an existing visit. In this case, the function returns the ID of the visit that was created previously in JSON format.
- The presentation player is opened in a context that's unrelated to the visit.

This example is an error result in JSON format.

```
{ "state": "error", "errorMessage": "<error>", "id": "<optional_id_of_previousl  
y_created_visit>" }
```

defineNoSwipeRegion Function

defineNoSwipeRegion Function

Defines an area of the screen where the presentation player ignores the swipe gesture.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.defineNoSwipeRegion(regionId, x, y, width, height)
```

Arguments

Argument	Description
<code>regionId</code>	The ID of the region where you don't want users to be able to swipe.
<code>x</code>	The horizontal coordinate of the top-left corner of the area where users can't swipe as an absolute position, in points.
<code>y</code>	The vertical coordinate of the top-left corner where users can't swipe as an absolute position, in points.
<code>width</code>	The width of the area where users can't swipe, in points.
<code>height</code>	The height of the area where users can't swipe, in points.

Example

In this example, the ID is region.

```
IntelligentContentPlayer.defineNoSwipeRegion("region", 50, 50, 100, 100);
```

destroyNoSwipeRegion Function

destroyNoSwipeRegion Function

Removes the region ID of an area of the screen where the presentation player ignores the swipe gesture.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.destroyNoSwipeRegion(regionId)
```

Arguments

Argument	Description
<code>regionId</code>	The ID of the region where the presentation player ignores the swipe gesture.

disableDismiss and enableDismiss Functions

Dismiss functions control how the presentation player is closed and handled when users select the Visit button. These functions execute long-term operations in the 'returntovisitbuttonpress' event handler.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

PresentationPlayer.disableDismiss()

To prevent the presentation player from being dismissed immediately after the users select the Visit button, call the `PresentationPlayer.disableDismiss()` function before executing long-term database operations such as queries or upserts.

PresentationPlayer.enableDismiss()

To notify and dismiss the presentation player, call the `PresentationPlayer.enableDismiss()` function after long-term operations are finished. If `PresentationPlayer.enableDismiss()` isn't called within 30 seconds, the presentation player is dismissed automatically.

Usage

The `PresentationPlayer.disableDismiss()` and `PresentationPlayer.enableDismiss()` functions control only the presentation that's open in the presentation player. The `'returntovisitbuttonpress'` event is also sent only to the presentation that's currently open when users select the Visit button.

To save data from multiple presentations during one presentation session, users can select the Visit button after presenting a custom presentation. The `'returntovisitbuttonpress'` event is triggered for the current presentation, and any upsert requests are executed. After opening the visit, users can use the Return to Presentation link to return to the same presentation session.

Example

For example, a user opens a custom presentation in the presentation player. When a page is opened, the `PresentationPlayer.disableDismiss()` function is called during the `'viewappearing'` event to prevent the player from being dismissed while long-running operations are in progress.

After the user finishes the presentation and selects the Visit button, the `'returntovisitbuttonpress'` event is triggered, and the presentation executes its long-running database operations, such as fetching or upserting data. Once these operations are complete, the `PresentationPlayer.enableDismiss()` function is called to close the presentation player.

fetchWithParams Function

fetchWithParams Function

Queries data that's not already returned in Mustache variables, and returns results to the specified callback method.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

You can query the User, Account, Record Type, Territory2, UserTerritory2Association, Life Sciences Cloud objects, and custom objects. To query records:

- The user must have Read permissions on the queried objects and fields.
- Active object metadata cache configurations must exist for each object and must be synced to the Life

Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.fetchWithParams(query, params, callbackMethod)
```

Arguments

Argument	Description
<code>query</code>	The SOQL query as a string, or the query locator value for subsequent fetches. You can include Mustache variables within queries. In the <code>query</code> parameter, specify these values. <code>object</code>: The API name of the object. <code>fields</code>: A comma-separated list of field API names. <code>where</code>: Optional. A WHERE condition that references field API names. <code>order by</code>: Optional. The field to order the query by. <code>limit</code>: Optional. The maximum number of records to return. The WHERE clause supports: - These logical operators: <code>AND</code>, <code>OR</code>, <code>NOT</code> - These comparison operators: <code>IN</code>, <code>LIKE</code>, <code>=</code>, <code><</code>, <code>></code> To use the IN operator, surround values in brackets, for example, <code>"Id IN {\"val1\", \"val2\"}"</code>. - These SOQL keywords. <code>SELECT</code> statements with column names, relations, and aggregate functions, but without subqueries <code>FROM</code> statements with only one object name <code>GROUP BY</code> columns or aggregate functions <code>HAVING</code> statements <code>WHERE</code> statements that support subqueries

Argument	Description
	and literal sets - <code>LIMIT</code> and <code>OFFSET</code> functions - <code>ORDER BY</code> functions • These literals. - <code>INT</code> - <code>FLOAT</code> - <code>STRING</code> - <code>NULL</code> - <code>BOOLEAN</code>
<code>params</code>	Optional. The ability to specify the batch size. In the <code>params</code> argument, use the <code>batchSize</code> attribute to set the number of records to return in each call. A maximum of 100 records can be returned in each call.
<code>callbackMethod</code>	The name of the JavaScript method that receives the query results.

Returns

This function returns a JSON result.

Field Name	Type	Description
<code>records</code>	Array<Object>	The result data.
<code>done</code>	Boolean	Indicates whether all data has been queried (<code>true</code>) or not (<code>false</code>).
<code>totalSize</code>	Integer	The total number of records that were processed in the query.
<code>queryLocator</code>	String	A unique SQL identifier that can be used in future requests.
<code>state</code>	String	The request status, such as success or error.

Usage

Regardless of batch size, queries are limited to a maximum of 100 records. This example sets the batch size to 75 records.

```
PresentationPlayer.fetchWithParams('SELECT FirstName, LastName, Name, Email, Phone, Username FROM User WHERE Id = ' + userId, {'batchSize': 75}, getCurrentUserRecordCallback');
```

If the batch size isn't specified, the `fetchWithParams` function queries 15 records by default. To query additional records when using smaller batch sizes, use the `queryLocator` variable.

This example uses the `queryLocator` variable.

```
function getAccounts() {
    PresentationPlayer.fetchWithParams('SELECT Id FROM Account', {'batchSize': 15}, 'getAccountsCallback');
    // Return 15 records
}

function getAccountsCallback(data) {
    // Process records
    PresentationPlayer.fetchWithParams(data.queryLocator, 'getAccountsCallback');
}
```

Example

```
<script type="text/javascript">
    var configData;
    document.addEventListener('PresentationDOMContentLoaded', function(event)
=> {
        configData = event.data;

        function getCurrentUserRecord() {
            let userId = ' \' ' + configData.parameters.id + ' \' ';
            PresentationPlayer.fetchWithParams('SELECT FirstName, LastName, Name, Email, Phone, Username FROM User WHERE Id = ' + userId, {'batchSize': 75},
                'getCurrentUserRecordCallback');
        }
        function getCurrentUserRecordCallback(data) {
```

```
    if (data.state === 'success') {
      const html = data.records.map((el)=>{
        console.log('User Name: ', el.Name);
        console.log('User Email: ', el.Email);
      });
    } else {
      PresentationPlayer.alert(data.message + '\n' + data.code);
    }
  }
</script>
```

Errors

This function returns an error when:

- The query can't access or find a record.
- A SQL error occurs.

getSurveyFlowJson Function

getSurveyFlowJson Function

Searches for a survey and returns it in JSON format. Then, the presentation HTML can parse the survey and show it in the presentation player.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

When called, this function:

- Validates input parameters and returns an error if the survey's developer name is missing.
- Loads the survey based on the developer name and the user's access.
- If there's a saved survey for the current presentation and visit, loads the saved responses. If no survey response is found, loads a new survey.
- Once the survey's JSON data loads, triggers the `"surveyflowjsonloaded"` event.
- Shows an error for invalid requests or missing survey data.

Parameters

```
PresentationPlayer.getSurveyFlowJson(Object)
```

Arguments

Argument	Description
<code>Object</code>	A JSON string in this format. <pre>{ "developerName": "name of the survey" }</pre>

Usage

When survey data is loaded, this function triggers the `"surveyflowjsonloaded"` event automatically. To handle the response, register an event listener.

Example

```
PresentationPlayer.registerEventListener("surveyflowjsonloaded", function(surveyJson)
    ){ // Handle the survey JSON data
      console.log("Survey loaded:", surveyJson);
    });

// Call the function
PresentationPlayer.getSurveyFlowJson({ "developerName": "test_survey" });
```

goNextPage Function

goNextPage Function

Goes to the next page in the presentation. If the current page is the last page in the presentation, nothing happens.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Syntax

```
PresentationPlayer.goPreviousPage()
```

goPreviousPage Function

goPreviousPage Function

Goes to the previous page in the presentation. If the current page is the first page in the presentation, nothing happens.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Syntax

```
PresentationPlayer.goPreviousPage()
```

goToSlide Function

goToSlide Function

Goes to the specified pages and assets within a presentation.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

To make sure that this function opens the correct page or asset, use unique names or IDs for pages and

assets within the presentation.

Syntax

```
PresentationPlayer.gotoSlide([PageId|PageName|SourceSystemIdentifier], slideName, animation)
```

Arguments

Argument	Description
<code>PageId</code>	The ID of a page in the presentation. If left blank, the current page is used. You can use the <code>PageId</code> argument only to navigate to presentation pages. Use this format. <pre>PresentationPage.Id</pre>
<code>PageName</code>	The name of a presentation page or asset. Use this format. <pre>PresentationPage.Name</pre>
<code>SourceSystemIdentifier</code>	An optional external ID for the presentation content, typically provided when users upload presentations via the content API. Use this format. <pre>PresentationPage.SourceSystemIdentifier</pre>
<code>slideName</code>	The name of the slide.
<code>animation</code>	The animation to use to open the slide. These values are supported. <code>noanimation</code> undefined null: Opens the slide immediately with no animation.

Argument	Description
	<code>swipeleft</code>: Opens the slide with a left swipe. <code>swiperight</code>: Opens the slide with a right swipe. Swipe animations can affect performance in the presentation player.

Usage

To reference another page in a presentation, first retrieve its page ID from the JSON.

Before you use the `goToSlide` function, include this code at the top of the HTML or other JavaScript code. The first line of code references the entire JSON file, while the second row gets the page ID, which is stored in a zero-based array.

```
var configData;
document.addEventListener('PresentationDOMContentLoaded', (event) => {
  configData = event.data;
  var PageId =
    configData.presentations[configData.presentationIndex].Pages[1].id;
});
```

Or, you can use this code.

```
var configData = {{{.}}};

var PageId = configData.presentations[configData.presentationIndex].Pages[3].id;
```

Then, use the `goToSlide` function with that ID. For example, this code is attached to an HTML button on the presentation page.

```
<button onclick="PresentationPlayer.goToSlide(PageId, '01_slide.html',null)"
  class="class" type="button">Next</button>
```

launchApprovedEmail Function

launchApprovedEmail Function

Opens the Send Email window with the email template that's linked to the presentation page, if the

presentation page specifies a template. If there's no email template ID specified on the presentation page, the page isn't linked to a template.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.launchApprovedEmail()
```

launchEmails Function

launchEmails Function

Opens the Send Email window with the email templates that are available to the user.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.launchEmails(templates)
```

Arguments

Argument	Description
<code>templates</code>	A comma-separated list of email template names to include in the Send Email window. If left blank, users see all of the templates that are available for the selected territory.

logError Function

logError Function

Logs error messages within the presentation player.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

To log errors efficiently and prevent excess entries:

- Error messages are tracked and logged for each individual presentation page.
- Only 10 error messages are logged for each presentation page.

Syntax

```
PresentationPlayer.logError(errorMessage)
```

Arguments

Argument	Description
<code>errorMessage</code>	The specific error message to include in the log.

saveState Function

saveState Function

Saves data about the presentation's state to the state property in the JSON that's supplied to the presentation's Mustache template. Stores the state on the user's mobile device so that users can resume a presentation and continue where they left off in the same session or a future session.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.saveState(state)
```

Arguments

Argument	Description
<code>state</code>	Any string that represents the state of the presentation, typically in JSON format. For example, the presentation state, such as the current slide position, user preferences, or progress tracking. The state can be retrieved and used by the presentation. State values are stored and saved for each presentation and visit. When users resume a presentation from a visit, they return to their previous state.

setSurveyFlowJson Function

setSurveyFlowJson Function

Saves survey results to the database for the current presentation and visit when the related visit is saved or submitted.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

When called, this function:

- Validates that the response object contains a `fullName` property, or returns an error for invalid response data.
- Processes the stored survey data, and saves it to the database when the related visit is saved or submitted.
- Creates related survey records.

The `surveyflowjsonpassedtovisit` event is triggered when the user selects the Visit button to return to the visit page, not when a user finishes the survey response.

Syntax

```
PresentationPlayer.setSurveyFlowJson(Object, state)
```

Parameters

Argument	Description
<code>Object</code>	Required. A survey response JSON object that includes the <code>fullName</code> , which is the full developer name of the survey, and additional survey response data and answers.
<code>state</code>	Optional. The submission state of the survey response. Supported values are: • <code>save</code> • <code>submit</code> The default value is <code>save</code>.

Usage

Calling the function with the `save` state creates these survey records.

- A survey invitation record for the responded survey.
- A survey subject record.
 - The subject ID is set to the current context, such as the visit ID.
 - The parent ID is set to the new survey invitation record's ID.
- A survey engagement context record.
 - The context type is set to Presentation.
 - The context value is set to the presentation ID.
 - The survey invitation ID is set to the new survey invitation record's ID.
- A survey response offline record.
 - The response is set to the survey response JSON data.
 - The survey invitation ID is set to the new survey invitation record's ID.

Calling the function with the `submit` state creates these survey records.

- All of the records that are created by the `save` state.
- Survey question response records for each question response.

startTrackingPage Function

startTrackingPage Function

Starts tracking presentation metrics in a new presentation click stream entry record for the specified presentation page.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.startTrackingPage(pageid)
```

Arguments

Argument	Description
<code>pageid</code>	The ID of the page to start a new presentation click stream entry record for. Accepts any string as the ID for the current slide.

stopTrackingPage Function

stopTrackingPage Function

Stops tracking presentation metrics for the current slide.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.stopTrackingPage()
```

updateFeedback Function

updateFeedback Function

Sets the feedback from the healthcare professional (HCP) to the specified type during presentations.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.updateFeedback(type)
```

Arguments

Argument	Description
<code>type</code>	The type of feedback. Supported values are: • <code>Positive</code> • <code>Negative</code> • <code>Neutral</code> • <code>null</code>

Example

This example sets the reaction type to Positive on the related provider visit detailing product message record.

```
<a href="javascript:PresentationPlayer.updateFeedback('Positive');">I like the presentation</a>
```

upsert Function

upsert Function

Creates and updates records for the specified objects and returns results to the specified callback method.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

This function is supported only in the Life Sciences Cloud mobile app.

You can create or update custom objects and supported Life Sciences Customer Engagement objects. To

create or update records:

- The user must have Read permissions on the specified objects and fields.
- Active object metadata cache configurations must be created for each object and synced to the Life Sciences Cloud mobile app.

Syntax

```
PresentationPlayer.upsert(objects, callbackMethod)
```

Arguments

Argument	Description
<code>objects</code>	An array of objects to create or update records for. • To create records, specify the object name. • To update records, specify the ID field that contains the ID or the offline ID.
<code>callbackMethod</code>	The name of the JavaScript method that receives the result of the operation.

Returns

This function returns an array of IDs of the new or updated records.

Limitations

This function can't create or update User, Record Type, Territory, Territory2, and UserTerritory2Association records.

You can't use this function to create or update related records. To update related records, such as records in a parent-child relationship, use two function calls.

Example

This example creates records using the object name.

```
<body>  
    <input id="name" style="color: black;">
```

```

        <input id="customField" style="color: black;">
        <a href="javascript:save();">Save Record</a>
    </body>
    <script type="text/javascript">
        function save() {
            let name = document.getElementById("name").value;
            let customField= document.getElementById("customFiel
d").value;

            PresentationPlayer.upsert([
                {
                    'subject': 'Account',
                    'name': name,
                    'customField__c': customField
                }, 'upsertCallbackMethod');
        }
        function upsertCallbackMethod(data) {
            console.log(data);
            PresentationPlayer.alert(JSON.stringify(data));
        }
    </script>

```

This example updates records using record IDs.

```

<script type="text/javascript">
    function save() {
        let name = document.getElementById("name").value;
        let customField= document.getElementById("customFiel
d").value;

        let accountId = allData.customers[0].Id;
        PresentationPlayer.upsert([
            {
                'subject': 'Account',
                'id': accountId,
                'name': name,
                'customField__c': customField
            }, 'upsertCallbackMethod');
    }
    function upsertCallbackMethod(data) {
        if (data.state === 'success') {
            console.log(data);
            PresentationPlayer.alert(JSON.stringify(data));
        } else {
            PresentationPlayer.alert(data.message + '\n' + d
ata.code);
        }
    }

```

```
</script>
```

Errors

This function processes up to 15 records at a time. If you submit more than 15 records, an error occurs.

This function can also return errors if there are failures creating or updating records. For example, errors can occur when:

- Validation rules fail.
- The user doesn't have Read or Edit access to the object or field.
- The object or field isn't supported.
- SQLite database query errors occur.

Callback Event Function

When an event occurs in the Life Sciences Cloud mobile app, you can use a callback event function to notify the page's JavaScript, HTML, or template. For example, events can be triggered when users pause or resume tracking presentation metrics.

REQUIRED EDITIONS

Available in: Lightning Experience

Available in: **Enterprise** and **Unlimited** Editions with Life Sciences Cloud, Life Sciences Cloud for Customer Engagement Add-on license, and the Life Sciences Customer Engagement managed package.

Syntax

```
PresentationPlayer.registerEventListener(iOS_event, myCustomPlayerHandler)
```

Arguments

Argument	Description
<code>iOS_event</code>	The event that occurs on iOS. These events are supported. • <code>'cancelbuttonpress'</code>: The event is triggered when users select the Cancel button.

Argument	Description
	'pausebuttonpress' : The event is triggered when users select the Pause button to stop tracking presentation metrics. 'playbuttonpress' : The event is triggered when users select the Play button to resume tracking presentation metrics. 'returntovisitbuttonpress' : The event is triggered when users select the Visit button. 'viewappearing' : The event is triggered when a page is opened. 'viewdisappearing' : The event is triggered when a page is closed. 'surveyflowjsonloaded' : The event is triggered when the <code>PresentationPlayer.getSurveyFlowJson()</code> function is called. 'surveyflowjsonpassedtovisit' : The event is triggered just before a visit is opened.
<code>myCustomPlayerHandler</code>	Your custom JavaScript function.

Product Management

In the Life Sciences industry, delivering value to customers—healthcare professionals, organizations, and patients—depends on making sure that the right products are available, accessible, and aligned with regulatory requirements. In Life Sciences Cloud, Product Management supports this goal by making it easier to configure, classify, and manage the products that your organization discusses, markets, sells, and distributes. The product hierarchy view helps teams structure portfolios according to SKU-level organization, while product territory alignments make sure that users access only the products approved for their designated regions and purpose, supporting compliance and reducing risk. Product messages and objectives enable personalized and effective engagement by equipping users with targeted guidance tailored to the needs of the customer.

Get Your Org Ready for Product Management

Help product management admins and users quickly search for available products, check territory assignments, and view specific marketing tips to effectively sell the products. Configure all types of products that your company markets, sells, and discusses, including brands, therapeutic areas, and indications.

Product Hierarchy Settings

Product hierarchy provides a centralized view of all the products developed, marketed, and distributed by a life sciences company. It helps product management admins and users drill down into each