

23:01 Welcome TotoNovanta
23:08 hon3stus has logged in
23:20 -Geisi- has logged in



Panormus 2024 VII.755 Italia

10 417 online, week 13 28/06/2026 23

My Clubs World Community ³ Forum

Help Shop TotoNovi

Community

- Overview
- Hattrick Press
- Mentoring
- Testimonials
- Football teams
- Officials
- Match kit search
- Logo rating
- CHPP products
- Hattrick Creators Club

Social

- Federations
- Chat Portal
- Network
- Local Circles

Recruitment

- Recruitment centre
- Recruitment status
- Top recruiters

External

- Twitch
- Wiki
- Blog
- Links
- Stage

Community » CHPP » CHPP Files help » Live

Live

Get (live) match ticker

Changelog [\(show\)](#)

Input

The following input parameters exist:

Simple Detailed

Only available inputs in this file version are shown.

required file = live

optional version = 2.3 ▼

optional actionTypes = view {default} ▼

Indicates what type of action the page should perform.

view {default}

Show the latest event(s) for all tracked matches. If matchID is supplied, that match will be shown with all events since the start of the game ('expanded' view).

optional matchID : [unsigned Integer](#)

The globally unique matchID.

optional sourceSystem : [sourceSystem](#) {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

optional includeStartingLineup : [Boolean](#) {Default:false}

Should <StartingLineup> and <Substitutions> be included in the response?

optional useLiveEventsAndTexts : [Boolean](#) {Default:false}

Should the events and texts be as on the live page on the site?

viewNew

Show those matches where new events have occurred since last request of the page. You'll need to send the which was your last event according to LastShownIndexes

optional includeStartingLineup : [Boolean](#) {Default:false}

Should <Substitutions> be included in the response?

(Note that <StartingLineup> is never provided for viewNew)

optional useLiveEventsAndTexts : [Boolean](#) {Default:false}

Should the events and texts be as on the live page on the site?

optional lastShownIndexes : [String](#)

JSON formatted array of last shown indexes for each match.

See reference: [#LastShownIndexes](#).

viewAll

Show all the events for all matches.

optional includeStartingLineup : [Boolean](#) {Default:false}

Should <StartingLineup> and <Substitutions> be included in the response?

optional useLiveEventsAndTexts : [Boolean](#) {Default:false}

Should the events and texts be as on the live page on the site?

clearAll

Remove all tracked matches from the tracking session.

addMatch

Add a new match to be tracked.

required matchID : [unsigned Integer](#)

The globally unique matchID.

optional sourceSystem : [sourceSystem](#) {Default:hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param



optional includeStartingLineup : Boolean <i>(Default:false)</i> Should <StartingLineup> and <Substitutions> be included in the response?
optional useLiveEventsAndTexts : Boolean <i>(Default:false)</i> Should the events and texts be as on the live page on the site?
deleteMatch Remove a particular match from the session.
required matchID : unsigned Integer The globally unique matchID.
optional sourceSystem : sourceSystem <i>(Default:hattrick)</i> Specifies which source system the match belongs to, this replace the old isYouth param

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple	Detailed	XML	Example
All containers/elements for the selected version and action type are shown. <pre><?xml version="1.0" encoding="utf-8"?> - <HattrickData> - <MatchList> - <Match> <MatchID> : unsigned Integer The globally unique identifier of the match. </MatchID> <MatchType> : MatchTypeID Integer defining the type of match. </MatchType> <SourceSystem> : sourceSystem Specifies which source system the match belongs to, this replace the old isYouth param </SourceSystem> <MatchDate> : DateTime The start date (kick-off) of the match. </MatchDate> - <HomeTeam> <HomeTeamID> : Integer The teamID of the Home team in the match. (Negative for street teams) </HomeTeamID> <HomeTeamName> : String The team name of the Home team in the match. </HomeTeamName> <HomeTeamShortName> : String The short team name of the Home team in the match. </HomeTeamShortName> - <StartingLineup> - <Player> <PlayerID> : unsigned Integer Globally unique ID of the player. </PlayerID> <RoleID> : MatchRoleID An integer indicating which formal 'slot' (Role) the player has filled in the match. </RoleID> <PlayerName> : String The full name of the player. </PlayerName> <Behaviour> : MatchBehaviourID An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker. </Behaviour> </Player> </StartingLineup> </HomeTeam> - <AwayTeam> <AwayTeamID> : Integer The teamID of the Away team in the match. (Negative for street teams) </AwayTeamID> <AwayTeamName> : String The team name of the Away team in the match. </AwayTeamName> <AwayTeamShortName> : String The short team name of the Away team in the match. </AwayTeamShortName> - <StartingLineup> - <Player> <PlayerID> : unsigned Integer Globally unique ID of the player. </PlayerID></pre>			

```

<RoleID> : MatchRoleID
    An integer indicating which formal 'slot' (Role) the player has filled in the match.
</RoleID>
<PlayerName> : String
    The full name of the player.
</PlayerName>
<Behaviour> : MatchBehaviourID
    An integer indicating the individual order or repositioning that the player has played with. Not provided for Captain and Set Pieces taker.
</Behaviour>
</Player>
</StartingLineup>
</AwayTeam>
<-Substitutions>
  <-Substitution>
    <TeamID> : unsigned Integer
        The globally unique TeamID for which the orders were sent.
    </TeamID>
    <SubjectPlayerID> : unsigned Integer
        If a/ substitution: The player leaving. If b/ behaviour change: The player changing his behaviour. Or c/ position swap: the first player that will
        change his position.
    </SubjectPlayerID>
    <ObjectPlayerID> : unsigned Integer
        The player entering (or once more the player changing behaviour). Or if position swap, the player to swap with.
    </ObjectPlayerID>
    <OrderType> : matchOrderTypeID
        The type of the order.
    </OrderType>
    <NewPositionId> : MatchRoleID
        An integer representing the new position for the (entering or staying) player.
    </NewPositionId>
    <NewPositionBehaviour> : MatchBehaviourID
        An integer representing the new behaviour for the (entering or staying) player.
    </NewPositionBehaviour>
    <MatchMinute> : unsigned Integer
        An integer indicating in which minute the order was executed.
    </MatchMinute>
    <MatchPart> : matchPart
        Which part of the match the order was executed.
    </MatchPart>
  </Substitution>
</Substitutions>
<-EventList>
  <-Event Index='unsigned Integer'>
    <Minute> : unsigned Integer
        The match minute when the event happened.
    </Minute>
    <MatchPart> : matchPart
        Which part of the match the event happened.
    </MatchPart>
    <EventKey> : String
        A unique key defining what type of event it was.
    </EventKey>
    <EventText> : String
        String describing the event as it would appear in the match report.
    </EventText>
    <SubjectTeamID> : unsigned Integer
        Integer that, for goals and chances, is indicating the attacking team. For other event, this field usually indicates the team that is doing
        something. It may indicate other things for other events - exactly what is not documented here and the SubjectTeamID information, while fre
        use for CHPPs is 'unsupported' and used 'at your own risk'.
    </SubjectTeamID>
    <SubjectPlayerID> : unsigned Integer
        Integer that, for goals and chances, is indicating the scorer or the player failing to score. For other events, this field usually indicates the
        primarily active player. It may indicate other things for other events and like SubjectTeamID is 'unsupported' and used 'at your own risk'.
    </SubjectPlayerID>
    <ObjectPlayerID> : unsigned Integer
        Integer that, for regular goals and chances, is indicating the defending team's goal keeper. For special event chances/goals, the ObjectPlayer
        often the assisting player of the attacking team, but can be any other player that is involved in the event. For other events, this field is used v
        freely and can indicate any kind of relevant integer data. Like SubjectPlayerID and SubjectTeamID, it is 'unsupported' and used at 'your own ri
    </ObjectPlayerID>
  </Event>
</EventList>
<HomeGoals> : unsigned Integer
    The current number of goals in the match for the home team.
</HomeGoals>
<AwayGoals> : unsigned Integer
    The current number of goals in the match for the away team.
</AwayGoals>
<LastShownEventIndex> : unsigned Integer
    The last shown event. Use this as LastShownIndexes for actionType=viewNew.
</LastShownEventIndex>

```

```
<NextEventMinute> : unsigned Integer
    The minute that the next matchevent will happen, this allows you to only ask for new events when needed. Only available while the match is
    ongoing. It should only be used by the application, it should NOT be shown to the users.
</NextEventMinute>
<NextEventMatchPart> : matchPart
    The matchPart in which the next matchevent will happen, this allows you to only ask for new events when needed. Only available while the match
    ongoing. It should only be used by the application, it should NOT be shown to the users.
</NextEventMatchPart>
</Match>
</MatchList>
</HattrickData>
```

References

#MatchEventTypes

Documentation of the match events in Hattrick [here!](#)

#Note

The viewAll and viewNew actionTypes are intended as the primary CHPP use of HT Live, in the following manner, which is the behaviour we recommend. appreciate all developers who seek to minimize server load by using this recommended way:

Upon first access per session, use viewAll. Then store the events locally in your application, user disk or similar. Then use viewNew for the repeating requests.

#LastShownIndexes

Value	Description
{	This is a JSON-formatted string.
"matches": [	
{ "matchId": "52383954", "sourceSystem": "youth", "index": "4" },	matches
{ "matchId": "341643388", "sourceSystem": "hattrick", "index": "-1" },	An array of all matches.
{ "matchId": "341643388", "sourceSystem": "htointegrated", "index": "-1" },	
{ "matchId": "345947495", "index": "-1" }	matchId
]	The globally unique matchID.
}	
	sourceSystem
	Specifies which source system the match belongs to. Defaults to "Hattrick" if not provided.
	index
	The EventIndex, you should pick this from the <LastShownIndex>-element. You can provide -1 to get all the events if you like, but you might just as well not send that match at all and it will default to -1 anyway.

[Rate this page](#) S

