

Community

- Overview
- Hattrick Press
- Mentoring
- Testimonials
- Football teams
- Officials
- Match kit search
- Logo rating
- CHPP products
- Hattrick Creators
- Club

Social

- Federations
- Chat Portal
- Network
- Local Circles

Recruitment

- Recruitment centre
- Recruitment status
- Top recruiters

External

- Twitch
- Wiki
- Blog
- Links
- Stage

Community » CHPP » CHPP Files help » Match Orders

Match Orders

Match orders for upcoming matches

Changelog [\(show\)](#)

Input

The following input parameters exist:

Simple	Detailed
--------	----------

Only available inputs in this file version are shown.

required

file = matchorders

optional

version = 3.1

optional

actionType = view {default}

Indicates what type of action the page should perform.

view {default}

Returns data on the matchorder for the match requested.

setmatchorder

Sets a matchorder for the match specified. Requests to set matchorder must be sent using POST method. All parameters except lineup (see below) should still be sent in querystring. (Requires "set_matchorder" scope.)

predictratings

Predicts the sector and tactic ratings for the match specified, according to the sent lineup (using POST method). If no lineup is sent the predictions will be for the saved match orders.

required

matchID : unsigned Integer

Specifies which particular match data is requested for.

optional

teamId : unsigned Integer {Default:Your primary club senior teamId}

Team id to get/set orders for. Must refer to a senior or youth team managed by requesting user.

optional

sourceSystem : sourceSystem {Default:Hattrick}

Specifies which source system the match belongs to, this replace the old isYouth param

optional

lineup : String

JSON formatted match orders to set for the match specified or to predict ratings. Must be specified as request body for POST. Required for actionType=setmatchorder and optional for actionType=predictratings, otherwise not used.

See reference: [#Lineup_30](#)

Output

Here you can see the output, based on the values of the input parameters and selected action type.

Simple	Detailed	XML	Example
--------	----------	-----	---------

All containers/elements for the selected version and action type are shown.

```
<?xml version="1.0" encoding="utf-8"?>
- <HattrickData>
  <MatchID> : unsigned Integer
    The globally unique identifier of the match.
  </MatchID>
  <sourceSystem> : sourceSystem
    Specifies which source system the match belongs to, this replace the old isYouth param
  </sourceSystem>
  - <MatchData Available='Boolean'>
    - <HomeTeam>
      <HomeTeamID> : Integer
        The teamID of the Home team in the match. (Negative for street teams)
      </HomeTeamID>
      <HomeTeamName> : String
        The team name of the Home team in the match.
      </HomeTeamName>
    </HomeTeam>
  </MatchData>
</HattrickData>
```

```

- <AwayTeam>
  <AwayTeamID> : Integer
    The teamID of the Away team in the match. (Negative for street teams)
  </AwayTeamID>
  <AwayTeamName> : String
    The team name of the Away team in the match.
  </AwayTeamName>
</AwayTeam>
- <Arena>
  <ArenaID> : unsigned Integer
    The globally unique arenaID.
  </ArenaID>
  <ArenaName> : String
    The name of the arena.
  </ArenaName>
</Arena>
  <MatchDate> : DateTime
    The kick-off date and time of the match.
  </MatchDate>
  <MatchType> : MatchTypeID
    Integer defining the type of match.
  </MatchType>
  <Attitude> : MatchTeamAttitude
    Integer value representing the the team attitude specified for the match. Only shown to the owner of the team - otherwise omitted.
  </Attitude>
  <TacticType> : MatchTacticType
    Integer value representing the team tactic type specified for the match.
  </TacticType>
  <CoachModifier> : coachModifier
    Integer value representing the style of play the team will use in the match. The value ranges from -10 (100% defensive) to 10 (100% offensive). The
    attribute Available specifies if the value has been set or not.
  </CoachModifier>
- <Lineup>
  - <Positions>
    - <Player>
      <PlayerID> : unsigned Integer
        The globally unique playerID.
      </PlayerID>
      <RoleID> : MatchRoleID
        An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be o
        (or zero) player with a particular RoleID (contrary to how PositionCode works).
      </RoleID>
      <FirstName> : String
        First name of the player.
      </FirstName>
      <NickName> : String
        Nick name of the player.
      </NickName>
      <LastName> : String
        Last name of the player.
      </LastName>
      <Behaviour> : MatchBehaviourID
        An integer indicating the individual order or repositioning that the player has played with.
      </Behaviour>
    </Player>
  </Positions>
  - <Bench>
    - <Player>
      <PlayerID> : unsigned Integer
        The globally unique playerID.
      </PlayerID>
      <RoleID> : MatchRoleID
        An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be o
        (or zero) player with a particular RoleID (contrary to how PositionCode works).
      </RoleID>
      <FirstName> : String
        First name of the player.
      </FirstName>
      <NickName> : String
        Nick name of the player.
      </NickName>
      <LastName> : String
        Last name of the player.
      </LastName>
    </Player>
  </Bench>
- <Kickers>
  - <Player>
    <PlayerID> : unsigned Integer
      The globally unique playerID.
  </Player>

```

```

</PlayerID>
<RoleID> : MatchRoleID
    An integer indicating which formal 'slot' (Role) the player has filled in the match, before the repositionings take effect. So, there can only be o
    (or zero) player with a particular RoleID (contrary to how PositionCode works).
</RoleID>
<FirstName> : String
    First name of the player.
</FirstName>
<NickName> : String
    Nick name of the player.
</NickName>
<LastName> : String
    Last name of the player.
</LastName>
</Player>
</Kickers>
- <SetPieces>
    <PlayerID> : unsigned Integer
        The globally unique playerID.
    </PlayerID>
    <FirstName> : String
        First name of the player.
    </FirstName>
    <NickName> : String
        Nick name of the player.
    </NickName>
    <LastName> : String
        Last name of the player.
    </LastName>
</SetPieces>
- <Captain>
    <PlayerID> : unsigned Integer
        The globally unique playerID.
    </PlayerID>
    <FirstName> : String
        First name of the player.
    </FirstName>
    <NickName> : String
        Nick name of the player.
    </NickName>
    <LastName> : String
        Last name of the player.
    </LastName>
</Captain>
</Lineup>
- <PlayerOrders>
    - <PlayerOrder>
        <PlayerOrderID> : unsigned Integer
            The globally unique PlayerOrderID.
        </PlayerOrderID>
        <MatchMinuteCriteria> : unsigned Integer
            An integer indicating in which minute the order should be executed at the earliest.
        </MatchMinuteCriteria>
        <GoalDiffCriteria> : unsigned Integer
            An integer representing different standings also required to trigger the order.
        </GoalDiffCriteria>
        <RedCardCriteria> : unsigned Integer
            An integer representing different red card events also required to trigger the order.
        </RedCardCriteria>
        <SubjectPlayerID> : unsigned Integer
            If a/ substitution: The player leaving. If b/ behaviour change: The player changing his behaviour. Or c/ position swap: the first player that will
            change his position.
        </SubjectPlayerID>
        <ObjectPlayerID> : unsigned Integer
            The player entering (or once more the player changing behaviour). Or if position swap, the player to swap with.
        </ObjectPlayerID>
        <OrderType> : matchOrderTypeID
            The type of the order.
        </OrderType>
        <NewPositionId> : MatchRoleID
            An integer representing the new position for the (entering or staying) player.
        </NewPositionId>
        <NewPositionBehaviour> : MatchBehaviourID
            An integer representing the new behaviour for the (entering or staying) player.
        </NewPositionBehaviour>
        <PlayerOrderExtraInteger> : MatchBehaviourID
            An integer representing the new behaviour for the (entering or staying) player. (It will always have the value 0, as it is not used by the new matc
            engine.)
        </PlayerOrderExtraInteger>
    </PlayerOrder>

```

```
</PlayerOrders>
</MatchData>
</HattrickData>
```

References

#Note	
With version 1.6: Corrected the ID for Substitute (Winger) to 117 (from 118) and corrected the ID for Substitute (Forward) to 118 (from 117).	
#MatchMinuteCriteria	
MatchMinuteCriteria	Description
-1	Anytime
0 ... 119	After x minutes
46	Halftime
91	Before extratime
#GoalDiffCriteria	
GoalDiffCriteria	Description
-1	Any standing
0	Match is tied
1	In the lead
2	Down
3	In the lead by more than one
4	Down by more than one
5	Not down
6	Not in the lead
7	In the lead by more than two
8	Down by more than two
9	Match is not tied
#RedCardCriteria	
RedCardCriteria	Description
-1	Ignore red card status
1	My player red-carded
2	Opponent red-carded
11	My central defender red-carded
12	My midfielder red-carded
13	My forward red-carded
14	My wing back red-carded
15	My winger red-carded
21	Opponent central defender red-carded
22	Opponent midfielder red-carded
23	Opponent forward red-carded
24	Opponent wing back red-carded
25	Opponent winger red-carded
#Lineup_18	
Value	Description
{	This is a JSON-formatted string.
"positions": [	
{ "id": "283974499", "behaviour": "0" },	positions
{ "id": "227622136", "behaviour": "1" },	An array of all positions.
{ "id": "0", "behaviour": "0" },	
{ "id": "226747085", "behaviour": "0" },	
{ "id": "0", "behaviour": "0" },	First 14 positionslots (0-13) represent the players on the field, starting with the goalkeeper (0), followed by right
{ "id": "285319569", "behaviour": "2" },	defender (1), right central defender (2) and so on up to left forward (13).
{ "id": "234525976", "behaviour": "1" },	
{ "id": "190611685", "behaviour": "0" },	The next 5 slots are substitutes in the following order: goalkeeper, defender, midfielder, forward, winger.
{ "id": "255908009", "behaviour": "0" },	
{ "id": "98722167", "behaviour": "0" },	Line 20 and 21 is captain and set pieces taker.
{ "id": "0", "behaviour": "0" },	
{ "id": "327345682", "behaviour": "4" },	The last 11 slots are penalty takers. All 11 of these should always be provided, sending { "id": "0", "behaviour": "0" } wh
{ "id": "312263029", "behaviour": "0" },	not provided by the user. In this example only 5 kickers were set by the user.
{ "id": "327875363", "behaviour": "0" },	
	The id is the PlayerId of the player you want.
	The behaviour is the matchBehaviourID
	The order is very important and concequently its very important that you send id:0 on slots where no player is placed!
{ "id": "319107771", "behaviour": "0" },	
{ "id": "224242073", "behaviour": "0" },	
{ "id": "266402745", "behaviour": "0" },	
{ "id": "304433518", "behaviour": "0" },	settings
{ "id": "214058496", "behaviour": "0" },	tactic is matchTacticType .
{ "id": "190611685", "behaviour": "0" },	speechLevel is the matchTeamAttitude .
{ "id": "226747085", "behaviour": "0" },	

newLineup should always be empty.

coachModifier is the style of play and is a value between -10 (100% defensive) and 10 (100% offensive). The available values depend on the level of the team's tactical assistant. If the coach is offensive you can go 2 steps, or 20%, per level towards defensive, and vice versa. If you have a neutral coach you can go 1 step, or 10%, per level in either direction. This value is optional and is recommended to not include if the user doesn't have a tactical assistant. Ignored for youth matches.

An array of all Subs / Orders. You can have 0-5 of subs/orders, plus an additional one per level of the teams tactical assistant. Send an empty array for 0 substitutions.

playerin is the playerId of the player in the "in" box.

orderType: 1 = substitution or behaviour change, 3 = position swap.

min: MatchMinuteCriteria

beh: see [matchBehaviourID](#). -1 means no change.

card: RedCardCriteria

standing: GoalDiffCriteria

kickers

<pre> {"id":226747085,"behaviour":0}, {"id":190611685,"behaviour":0}, {"id":98722167,"behaviour":0}, {"id":283974499,"behaviour":0}, {"id":227622136,"behaviour":0}, {"id":0,"behaviour":0}, {"id":0,"behaviour":0}, {"id":0,"behaviour":0}, {"id":0,"behaviour":0}, {"id":0,"behaviour":0}, {"id":0,"behaviour":0},], "captain": "190611685", "setPieces": "226747085", "settings": { "tactic": "0", "speechLevel": "0", "newLineup": "", "coachModifier": "0", "manMarkerPlayerId": "0", "manMarkingPlayerId": "0" }, "substitutions": [{ "playerin": "304433518", "playerout": "327875363", "orderType": "1", "min": "80", "pos": "-1", "beh": "-1", "card": "-1", "standing": "0" }, { "playerin": "319107771", "playerout": "283974499", "orderType": "1", "min": "89", "pos": "-1", "beh": "-1", "card": "-1", "standing": "3" }] } </pre>	captain The PlayerId of the player you want as captain. "0" if not set. setPieces The PlayerId of the player you want as set pieces taker. "0" if not set. settings <i>tactic</i> is matchTacticType. <i>speechLevel</i> is the matchTeamAttitude. <i>newLineup</i> should always be empty. <i>coachModifier</i> is the style of play and is a value between -10 (100% defensive) and 10 (100% offensive). The available values depends on the level of the teams tactical assistant. If the coach is offensive you can go 2 steps, or 20%, per level towards defensive, and vice versa. If you have a neutral coach you can go 1 step, or 10%, per level in either direction. This value is optional and is recommended to not include if the user doesn't have a tactical assistant. Ignor for youth matches. substitutions An array of all Subs / Orders. You can have 0-5 of subs/orders, plus an additional one per level of the teams tactical assistant. Send an empty array for 0 substitutions. <i>playerin</i> is the playerId of the player in the "in" box. <i>playerout</i> is consequently the playerId of the player in the "out" box, this should be same as playerin if its a behaviour change. <i>orderType</i>: 1 = substitution or behaviour change, 3 = position swap. <i>min</i>: MatchMinuteCriteria <i>pos</i>: the position the player should take after the substitution, 0-13, see positions above for the order. -1 means no change. <i>beh</i>: see matchBehaviourID. -1 means no change. <i>card</i>: RedCardCriteria <i>standing</i>: GoalDiffCriteria
---	---

[Rate this page](#) S
[About Hatrick](#)
[Fantasy football games](#)
[Hattrick Supporter](#)
[Help](#)
[Contact Us](#)
[Privacy](#)
[Hattrick Wiki](#)
