

Executing an SQL Server stored procedure from events

Calling the procedure without parameters.

If stored procedure doesn't return the recordset:

```
DB::Exec("EXEC StoredProcNameHere");
```

If stored procedure returns the recordset:

```
DB::Query("EXEC StoredProcNameHere");
```

Passing one of the field values as a parameter:

```
$sql = DB::PrepareSQL( "EXEC StoredProcNameHere ':1'", $values["FieldName"] );  
DB::Exec( $sql );
```

Executing MySQL stored procedure from the event

Calling the procedure without parameters.

If stored procedure doesn't return the recordset:

```
DB::Exec("CALL StoredProcNameHere");
```

If stored procedure returns the recordset:

```
DB::Query("CALL StoredProcNameHere");
```

Passing one of the field values as a parameter:

```
$sql = DB::PrepareSQL( "CALL StoredProcNameHere ':1'", $values["FieldName"] );  
DB::Exec( $sql );
```

Executing ORACLE stored procedure from the event

Calling the procedure without parameters.

If stored procedure doesn't return the recordset:

```
DB::Exec("BEGIN STOREDPROCNAME(); END;");
```

If stored procedure returns the recordset:

```
DB::Query("BEGIN STOREDPROCNAME(); END;");
```

Passing one of the field values as a parameter:

```
$sql = DB::PrepareSQL("BEGIN STOREDPROCNAME(':1'); END;", $values["FieldName"]);  
DB::Query($sql);
```

See also:

- [Connecting to the database](#)
- [Connecting to Oracle database](#)
- [Table events](#)
- [Global events](#)