




STATE OF ISRAEL
MINISTRY OF TRANSPORT



17/2/2014

Subject: Enhanced Security Procedures for All Commercial
Passengers Flights Overflying or Arriving to Israel FIR- Waiver.

1. Introduction

The Security Department of the Ministry Of Transport threat perspective is that commercial flights to Israel FIR are under an increased risk. The situation necessitates taking additional "Protective Measures" to further reduce vulnerability and increase response capability during the period of heightened alert.

2. The Enhanced Protective Measures.

2.1. Flight deck door security procedures

- a. The Pilot-In-Command (PIC) of an airplane must ensure that the door is closed and locked from the moment the passenger entry doors are closed in preparation for departure until they are opened on arrival.
- b. The flight deck door may be unlocked and opened when authorized crew members are required to exit or enter the flight deck in the performance of their duties, for physiological needs or for overriding concerns related to the safety of flight. The above waiver is subjected to the implementation of well established reliable procedures to protect the cockpit entrance during flight deck door transition avoiding hijacker form piggy-bag forced entry e.g. flight attendant blocker, galley cart.
- c. The flight deck door should not be unlocked and opened even for authorized crew members from before reaching the identification reporting point (from the West Nicosia FIR – at 180 NM; from the South Cairo FIR – 10 min before Passing Sharm El-Sheikh) and until after landing. For over-flight flights from the East Amman FIR; the



(X) flight deck door should not be unlocked and opened even for authorized crew members from takeoff and until after the aircraft exits the Israel FIR.

d. Overriding Safety of Flight Considerations Ultimately, the PIC will determine at his discretion when an overriding safety of flight consideration warrants opening the flight deck door. Circumstances which may be considered overriding safety of flight concerns include but are not limited to the following:

- 1) visual inspections to confirm such things as a potential fuel leak, engine condition, visual gear/flap configuration, inspection of contaminated surfaces;
- 2) safety/emergency procedures, such as pilot incapacitation or fire fighting;
- 3) abnormal or emergency landings where safety procedures requires that the door be open for landing; and
- 4) To communicate essential information where there is no appropriate alternative under the circumstances.

2.2. Advance cabin landing preparation

(X) All passengers must be seated and belts fastened, at least 30 minutes before landing in Israel and until landing.

Over flights:

Flights to Jordan: All passengers must be seated and belts fastened, at least 30 minutes before landing in Jordan and until landing.

Flights from Jordan: All passengers must be seated and belts fastened, at least 15 minutes after takeoff from Jordan.

2.3. Enhanced security procedures for access an aircraft operating to Israel:

a. Aircraft Security Search

After the designation of the aircraft for the flight to Israel and before the loading of catering, supplies and luggage, law enforcement officers or security staff shall deploy an 'aircraft security Search'.

'Aircraft Security Search': A thorough inspection of the interior and the exterior of the aircraft for the purpose of discovering prohibited articles.

b. Access Control for an aircraft designated for operating to Israel

Security measures should be deployed for controlling access to the parked aircraft from its designation for the flight to Israel and until its departure as follows:

- (a) Security guards or law enforcement officers should be posted to continuously guard the aircraft and the adjacent ramp area to prevent unauthorized access and to prevent introduction of threat articles on board of the aircraft.
- (b) All staff requiring access to the aircraft area shall be subjected to a security background check.
- (c) Security identification cards shall be issued to all requiring access to the aircraft area. The security identification card shall carry the name and photograph of the bearer and card shall be worn in a visible place, at all times while its holder is on duty at the aircraft area.
- (d) ALL persons (including employees) and their accessible property should be screened immediately prior to accessing the aircraft.

2.4. Security Staff Authorization:

People who are deployed to undertake security duties either as all or part of their employment, airport employees or certified private contractors, shall be approved or certified by the national appropriate authority as to their background check, selection, training and qualification.

Dani Shenar

Head of Security Department
Ministry of Transport
Government of Israel

1. General

...ing and approach procedures in use
... on the values and factors contained
... of Vol. I of the PANS-OPS. The listing
... at speeds as indicated below.

Flight Level (FL)	Altitude (ft)	Turbulence conditions
Up to FL 140 (4 250 M) inclusive	Up to 140 KT	280 KT (520 KMH) or Mach 0.8, whichever is less
Above FL 140 (4 250 M) to FL 200 (6 100 M) inclusive	140 KT	
Above FL 200 (6 100 M) to FL 340 (10 350 M) inclusive	175 KMH	
Above FL 340 (10 350 M)	175 KMH	Mach 0.8

2.4 IfR flights enroute, the mission, with the Tel-Aviv Ben-Gurion TMA, TWR, SRT & MZ, shall be cleared to a specified holding point until authorized by contact approach control (within the MZ) to descend to a specified time level or position. The aircraft shall remain at the specified time level or position until further clearance is received from TWR, TMA or APP. If the clearance is issued in minutes, before further instructions have been received, holding procedures shall be carried out at the level last authorized.

2.2 Due to the limited amount of available data, it is of importance that the approaches to the pattern and the holding procedures, are carried out as precisely as possible. Pilots are strongly requested to inform ATIS of the approach and the approach and/or holding pattern used. In pilot procedures required it is pilot's discretion to maintain the recommended frequency until reaching point to change position to the next frequency used.

3.3. Flights entering Tbilisi will be required to make first contact with the appropriate authorities for identification purposes.

- [illegible]

From the South contact South Identification FREQ
FRI 127.000 MHz, SRY 127.750 MHz not later than
8 am 4-8-68 along Route R 650. Level
of operation is the same.

RFQ PRI 118.800 MHZ SRV 121.000
180 NM from BGN AOR DMZ

A pilot shall establish contact before entering. 141
A pilot shall select mode A 3, code 6100

Submittal No. _____ Submittal Date _____ Submittal By _____	Submittal No. _____ Submittal Date _____ Submittal By _____
--	--

Flights entering Tel-Aviv ER, shall arrive at one of the following connecting points:

SALAM or TALAM

 NaAlSO_4

Labels from Cairo FIR along G18 are not permitted
on any FabaAvis FIR from the south.

found at west and northwest GULLA, SOLIN,
ADRIAN DAVAR.

Flights involving the FTR from points other than those shown on the "off-airways" direct from point to point route are prohibited. ATN routes are strictly prohibited, unless otherwise authorized by ATC.

+972-3-9774569
X: +972-3-9774599
MAIL: aip@mot.gov.il

STATE OF ISRAEL
MINISTRY OF TRANSPORT
CIVIL AVIATION AUTHORITY
AERONAUTICAL INFORMATION
SERVICES UNIT
GOLAN BUILDING, GOLAN STREET,
P O B 1101, AIRPORT CITY, 70100

AIC 2\16
Series A
11 May 2016

Security Identification procedure for Traffic entering "Tel-Aviv" FIR

This AIC is meant to amend the Security Identification procedure, published in the Israeli AIP ENR 1.5, and is in force with immediate effect & permanently.

Flights entering Tel-Aviv FIR shall contact the appropriate ACC unit for identification purposes.

All flights shall report squawk number and flight level on first contact.

a. From Amman FIR:

- 1) Departing traffic from Amman/Queen Alia, Amman/Marka, Al-Azraq AB and King Abdullah AB: contact "Tel-Aviv Control" freq: PRI 121.400 MHz, SRY 122.150 MHz, as soon as practical after takeoff, and not later than 10 NM east of position "TALMI"/ "SALAM" (for traffic VIA Ben Gurion TMA).
- 2) All other traffic not specified in 1: contact "Tel-Aviv Identification" freq: PRI 124.300 MHz, SRY 118.800 MHz, as soon as practical, and not later than 25 NM east of position TALMI.

b. From the Arab Republic of Egypt:

- 1) Contact "South Identification" freq: PRI 122.750 MHz SRY 132.000 MHz, not later than 10 minutes before position "Sharm El Sheikh" (SHM VOR) along route R650.
- 2) From Cairo via "Nuweibaa" (NWB NDB) shall contact "South Identification" freq: PRI 122.750 MHz SRY 132.000 MHz, not later than position "SISIK".

72-3-9774569
72-3-9774599

aiip@mot.gov.il

STATE OF ISRAEL
MINISTRY OF TRANSPORT
CIVIL AVIATION AUTHORITY
AERONAUTICAL INFORMATION
SERVICES UNIT
GOLAN BUILDING, GOLAN STREET,
P.O.B. 1101, AIRPORT CITY, 70100

AIC 2\16
Series A
11 May 2016

3) Flights departing "Sharm El Sheikh" (SHM VOR) shall contact "South Identification" freq: PRI 122.750 MHz SRY 132.000 MHz not later than position "DELNA".

c. From the West and North West contact "Tel-Aviv identification" freq: PRI 124.300 MHz SRY 118.800 MHz, not later than 180 NM from BGN VOR/DME.

2.5. Flights entering Tel-Aviv FIR Southern Sector from the Arab Republic of Egypt shall establish and maintain communication with South Control as follows:

- a. Flights arriving from Sharm-el-Sheikh shall call South Control ACC unit (132.000 MHz) not later than reporting point DELMA (N28 30.7 003 13 21).

- b. Flights from Cairo to Tel-Aviv FIR via the sea:

AIS Route	COP	FL allocation	FL conditions
R650	NALSO	GLD	FL 290

Flights shall contact Tel-Aviv FIR South Control (132.000 MHz) for identification purposes 10 minutes before position SHARM EL-SHEIKH, or position DELMA for traffic departing Cairo or Sharm-el-Sheikh, and 10 NM before NALSO.

3. Departing flights

3.1. IFR flights departing from controlled aerodromes, will receive initial ATC clearance from the local aerodrome control tower. The clearance limit will normally be the aerodrome of destination.

3.2. Detailed instructions with regard to routes, turns, etc. will be issued by the ATIS.

Flights from Tel-Aviv FIR (South Sector) to Cairo FIR

AIS Route	COP	FL allocation	Special Comments
R650	NALSO	FL260 or FL290 FL120	All traffic entering Cairo FIR via NALSO. For flights departing from Tel-Aviv: Maintain FL260 or FL290 or FL120. If, for High levels will be assigned by Cairo ACC.

Flights shall contact Tel-Aviv FIR/South Control 10 minutes before NALSO and 10 minutes before Cairo ACC 5 minutes before NALSO.



29/08/2010

To: All airlines operating at Tel-Aviv/Ben-Gurion Airport

During the past months we have experienced repeated cases of aircraft crossing red stop-bars while taxiing to the take off waiting position for runway 12.

We would like to stress once more the utmost importance of adhering to the red-lit stop-bars and taking special care not to advance beyond the stop-bar, as this brings the taxiing aircraft in a potential safety conflict with aircraft on the approach and landing phases to runway 12. Furthermore, attention shall be given to the proximity of runways 08 and 12, and the necessity to line up on the correct runway for take off. It has happened before that aircraft intending to take off from runway 12, erroneously lined up on runway 08, despite the various signing and markings.

Haim Levy

Manager Coordination Center

Ben - Gurion Airport P O Box 7, Israel 70100
P - 03-9756209, M - 050-9756209

TEL 972-3-9774000
FAX 972-3-9774614
E-MAIL AIP@MOT.GOV.IL

STATE OF ISRAEL
MINISTRY OF TRANSPORT
CIVIL AVIATION AUTHORITY
AERONAUTICAL INFORMATION PUBLICATION
P.O. BOX 8 BEN GURION AIRPORT 78100

AIP
Supplement 2.10
28 April 2016

BEN GURION AERODROME, GROUND MOVEMENT

Ref. AIP Israel AD 2.5-14, AD2.5-14A

WIE

Holding point for RWY 26 is located before the end of RWY 03 and marked on chart.
When using "VENUS 3" and taxiing from TWY K to TWY U do not turn into TWY L.
Due to the addition of RWY 26 remark (No. 1), the "remarks" numbering has changed.

