

TECHNICAL SPECIFICATIONS

7.5 kVA / 10 kVA / 12.5 kVA / 15 kVA

PARAMETERS		DG MODELS				
50 HZ PRIME	Rating(kVA)	7.5 kVA	10 / 12.5 kVA	15 kVA		
	Rated(kWe)	6	8	12		
	Engine Model	1125GR	2185GM-C2	2205 GM C2	3255 GM C2	
No of Cylinders		1	2	2	3	
Rated Speed RPM		1500	1500	1500	1500	
Rated Current(AMP) Capacity @ 0.8PF	1 Phase	32.6	43.5	65.35		
	3 Phase	10.4	13.9	20.9		
Cooling System (Air Cooled/Water Cooled)		Water	Water	Water	Water	
Dimension	Length	1800	1800	1800		
	Width	900	900	900		
	Height	1290	1300	1300		
Intergrated Fuel Tank Capacity (lits)		42	90	90		
Approximate Dry Weight of DG set (Kg)		700	690	680	740	
Centre lifting DG set dimensions with top hood, if any (mm)	Length	1800	1800	1800	2150	
	Width	900	900	900	1030	
	Height	1250	1250	1250	1300	

SL = Side Lifting

CL = Center Lifting

SD = Single Door

DD = Double Door

For continuous improvement company reserves the right to change technical data without prior information