

Salim

Salim

Salim

B2_{Sali}SynthesissRigol

Salim

B-SYN-200

Salim

Salim

Salim

Salim

Salim

Salim

Salim

Salim

automakefile

Salim

autofalime-like, but was alimter

Salim

11

Salim

Salim





Salim

Salim

Salim Qutonsancefile Salim

Salim

binary name: skip-synthesis.sh, automakefile

repository name: SYN_automakefile_\$ACADEMICYEAR

repository rights: ramassage-tek

language: bash

Salim Salim

named bonus.

Salim

Salim

 Your repository must contain the totality of your source files, but no useless files (binary, temp files, obj files,...).



All the bonus files (including a potential specific Makefile) should be in a directory

Salim

Salim

 Error messages have to be written on the error output, and the program should then exit with the 84 error code (O if there is no error).

Salim

Salim

Salim

Salim

REQUIREMENT

Salim Salim Salim

Satim

Write a shell script named skip-synthesis.sh that will both read the output of the command 1s -1, and print the user and the name of the files starting with the string given as parameter.

Terminal

Zeus

 \sim /B-SYN-200> ls -1 | ./skip-synthesis.sh "to"

totoTest

torus4d

Zeils M tomatoketchup toutToutTout pierre.perret

Salim

Stallman

The rest of the project will not be corrected unless this requirement is fully functional

(and rewritten).

Salim

Salim

The file must be placed at the root of your git repository.

Salim

Salim

Salim

Salim

Salim





Salim

Salim

MAKEFILE GENERATION

Salim

Salim

-Salim

Write a shell script named automakefile, that generates a nice Makefile given a configuration file. This configuration file can contain the following (potentially unordered) lines:

source_filename;dependence1 dependence2...

(specify the full names of the files, from the header subfolder below)
Salimoject_DIR;name_of_theader_ot_folder
Salimoject_root_folder

Salim

- SOURCES_DIR;subfolder_containing_the_source_files
- HEADERS_DIR;subfolder_containing_the_header_files
- LIBS_DIR;subfolder_containing_librairies
- EXEC;executable_name
- CC;compilator_binary

Salimn_AGS;compilation_flag1Sanimion_flag1...

Salim

Salim

LDFLAGS;linking_flag1 linking_flag2...



The generated Makefile must contain at least the classic clean, fclean and re rules.

Salim

Salim

Salim



Salim

PROJECT_DIR is the only mandatory line, along with at least one source file.

Salim Salim Salim Salim

Salim Salim Salim Salim

Salim Salim Salim Salim

Salim Salim Salim Salim

Salim





Salim

Salim

Salim Salim

Salim

-Salim

Add the following rules to the generated Makefile:

archive

backup the source files in a compressed format, in the project folder

Şalim

Salim

Salim

Salim

recreate the project from last backup

num

print the current version number

Salim

Salim

Salim

Salim

delete last backup



While archiving, the message xxx file generated.\n must be printed, xxx being the name of the archive.

Salim

Salim

Salim

5 more fields will be necessary in your configuration file :

- BCK_DIR;name_of_the_backup_folder
- ZIP;compression_binary

SalimFLAGS;compression_opsalim
UNZIP;decompression_binary

Salim

Salim

UNZIPFLAGS;decompression_options

Salim





SAMPLE

Salim Salim Salim

Salim Salim Salim

Terminal \sim /B-SYN-200> ls . fakeProj/ automakefile \sim /B-SYN-200> ls -R fakeProj/ fakeProj/: Salim Salim Salim calc.c main.c config fakeProj/include: calc/ Salim Salim íakeProj.h fakeProj/include/calc: calc.h fakeProj/libs/: Salim Salim Salim fakeProj_backUp/:

Terminal - + x

~/B-SYN-200> ./automakefile fakeProj/config && ls fakeProj/

Salc.c Salim Salim

config

Makefile

Salim Salim Salim Salim

Salim Salim Salim Salim

Salim Salim Salim Salim

Salim Salim Salim

Salim Salim [EPITECH.]