

COMPARISON MATRIX · Industrial Chargers											
#	IMAGE	BRAND	MODEL	POWER	VOLTAGE	DIMENSIONS	IP	COOLING	CATEGORY	KEY FEATURES	DATASHEET
1		Delta-Q Technologies CA Canada	IC1200	1200 W	48 V / 25 A	335 × 179 × 102 mm	IP66	Passive — Finned Case	Market Leader	High vibration resistance · CAN bus support · USB host port · Multi-chemistry (Pb, Li)	View datasheet →
2		Lester Electrical US USA	Summit II 1050W	1050 W	36 – 48 V	341 × 208 × 107 mm	IP66	Passive — Natural Convection	Premium	Bluetooth configuration · Cloud connectivity · Multi-voltage · Compact cast aluminum	View datasheet →
3		Pro Charging Systems US USA	Eagle Performance	800 W	Multi (12 – 72 V)	254 × 182 × 102 mm	IP67	Fully Potted (Encapsulated)	Heavy-Duty	DeltaVolt™ technology · Optimized for on-board use · Made in USA	View datasheet →
4		Zivan IT Italy	NG3	1000 W	12 – 96 V DC	430 × 220 × 90 mm	IP65	Fan Cooled + Passive Fins	Industrial	CE certified · 85–90 % efficiency · Programmable curves · Multi-chemistry · ZAPI Group	View datasheet →
5		NOCO US USA	Genius GX4820	960 W	48 V / 20 A	305 × 216 × 99 mm	IP66	Passive — Cast Aluminum	Compact	Ultra-compact design · Fully sealed · Rapid charge optimization · Industrial-grade	View datasheet →