

Computer Vision

Approximate Nearest Neighbors Algorithms

Product Quantization

Vladislav Belov

FNSPE CTU

April 19, 2020



Product Quantization

In this report, we cover results of our experiments with the Product Quantization index (in particular, IVFPQ¹) [1] for the nearest neighbors search. The report includes the following:

- Showcase of IVFPQ performance on Oxford105K data (image descriptors with total number of samples $N = 104933$ of dimension $d = 128$);
- Comparison of IVFPQ with FLANN²[2].

Technical Details

The implementation was performed using Python 3.7.7. The respective notebook is available on our [GitHub](#) page.

¹We utilize Fair AI Similarity Search ([faiss](#)) library with fixed parameters of the index: `nlist= 100`, `m = 16`, `nbits= 8`, and `nprobe= 32` of IVFPQ index.

²[PyFLANN](#) library is used.



NN Search with IVFPQ on Old Image Descriptors



Figure 1: 5 Nearest neighbors for the sample image. Not exhilarating performance on older image descriptors.



NN Search with IVFPQ on CNN-based Image Descriptors




Figure 2: 5 Nearest neighbors for the sample image. Better performance on CNN-based image descriptors, as all images at least depict animals with common features.




Framework of the Experiment

- We compare performance of IVFPQ with the k-d-forest (FLANN-KDF), the priority search k-means tree (FLANN-KMT), and the auto-tuned FLANN with target precision set to 0.99 (FLANN-TARGET) by means of estimation of recall $R(k, K)$.³
- Recall is measured as the average fraction over 1000 queries (randomly selected images) of first k true nearest neighbors found during the search of K approximate nearest neighbors, $k \leq K$. Results for $K = 100$ can be viewed in Fig. 3.
- For each approach, we also measure the time to build the index and to perform the query. Results are presented in Tab. 1.

Method	Time to build the index, [s]	Time to perform the query, [s]
IVFPQ ⁴	5.64 + 0.584	0.104
FLANN-KDF	4.24	0.1
FLANN-KMT	28.4	0.0582
FLANN-TARGET	28.2	0.0544
Exact NN	-	26

Table 1: Timings of ANN methods to perform 1000 queries for 100 nearest neighbors.

³FLANN parameters we used are available in the appendix (see Tab. 2 and Tab. 3).

⁴Timings for both training on all data points and the point insertion are given. 






Figure 3: Values of $R(k, 100)$. In terms of recall, IVFPQ demonstrates superior performance to FLANN.



Appendix



FLANN Parameters in Our Experiments

- FLANN-KDF (T - number of randomized trees, C - number of leaves to check in one search):

T	C
32	32

Table 2: FLANN-KDF parameters.

- FLANN-KMT (B - branching factor for k-means tree construction, I - number of iterations for the tree construction, CB - cluster boundary index for the search in the tree, C - number of leaves to check in one search):

B	I	CB	C
100	20	0.2	32

Table 3: FLANN-KMT parameters.





H. Jégou, M. Douze, and C. Schmid.

Product quantization for nearest neighbor search.

IEEE Trans. Pattern Anal. Mach. Intell., 33(1):117–128, 2011.



M. Muja and D. Lowe.

Fast approximate nearest neighbors with automatic algorithm configuration.

VISAPP 2009 - Proceedings of the 4th International Conference on Computer Vision Theory and Applications, 1:331–340, Jan 2009.

