Coding output

```
sultanalkaabi@Sultans-MacBook-Air / % /opt/homebrew/bin/python3 "/Users/sultanalkaabi/Desktop/assigment 2 /ABCDEType.py"

=== TEST SUITE (evidence) ===
[T1] invalid_mac_detected=12, accepted_unique=0
[T1] PASS

[T2] replay_attempts_detected=19, accepted_duplicates=0
[T2] PASS

All tests PASSED.

2026-03-04 02:50:49,773 INFO sim - Running E1_baseline_none
2026-03-04 02:50:58,139 INFO sim - Running E2_security_hmac
2026-03-04 02:51:06,150 INFO sim - Running E3_hmac_anti_replay_backoff
2026-03-04 02:51:14,283 INFO sim - Running E4_hmac_anti_replay_backoff_batching

=== SUMMARY TABLE (evidence) ===
exp                                  | mode                   | sent | ok | avail | avg_lat | p95   | timeouts | retries | bad_mac | replay | tx | tx/ok | energy | batch | backoff
-------------------------------------+------------------------+------+----+-------+---------+-------+----------+---------+---------+--------+----+-------+--------+-------+-------
E1_baseline_none                     | none                   | 24   | 24 | 1.0   | 0.211   | 0.516 | 3        | 3       | 0       | 0      | 27 | 1.12  | 27.0   | False | False
E2_security_hmac                     | hmac                   | 18   | 17 | 0.944 | 0.248   | -     | 9        | 8       | 6       | 0      | 26 | 1.53  | 29.6   | False | False
E3_hmac_anti_replay_backoff          | hmac_with_anti_replay  | 7    | 4  | 0.571 | 0.125   | -     | 12       | 9       | 3       | 10     | 16 | 4.0   | 17.4   | False | True
E4_hmac_anti_replay_backoff_batching | hmac_with_anti_replay  | 7    | 6  | 0.857 | 0.206   | -     | 5        | 4       | 1       | 3      | 11 | 1.83  | 12.4   | True  | True

=== RESULTS JSON (appendix) ===
{
  "experiment_name": "E1_baseline_none",
  "security_mode": "none",
  "packet_loss_probability": 0.15,
  "network_latency_ms_range": "40-220",
  "batching_enabled": false,
  "adaptive_backoff_enabled": false,
  "sent_messages": 24,
  "accepted_unique_messages": 24,
  "rejected_messages_total": 0,
  "secure_availability_unique": 1.0,
  "average_latency_seconds": 0.211,
  "latency_95_percentile_seconds": 0.516,
  "acknowledgement_timeouts": 3,
  "retry_count": 3,
  "invalid_mac_packets_detected": 0,
  "replay_packets_detected": 0,
  "total_transmissions": 27,
  "energy_cost_units": 27.0,
  "transmissions_per_successful_message": 1.12
}
{
```

```
{
  "experiment_name": "E2_security_hmac",
  "security_mode": "hmac",
  "packet_loss_probability": 0.15,
  "network_latency_ms_range": "40-220",
  "batching_enabled": false,
  "adaptive_backoff_enabled": false,
  "sent_messages": 18,
  "accepted_unique_messages": 17,
  "rejected_messages_total": 6,
  "secure_availability_unique": 0.944,
  "average_latency_seconds": 0.248,
  "latency_95_percentile_seconds": null,
  "acknowledgement_timeouts": 9,
  "retry_count": 8,
  "invalid_mac_packets_detected": 6,
  "replay_packets_detected": 0,
  "total_transmissions": 26,
  "energy_cost_units": 29.6,
  "transmissions_per_successful_message": 1.53
}
{
  "experiment_name": "E3_hmac_anti_replay_backoff",
  "security_mode": "hmac_with_anti_replay",
  "packet_loss_probability": 0.15,
  "network_latency_ms_range": "40-220",
  "batching_enabled": false,
  "adaptive_backoff_enabled": true,
  "sent_messages": 7,
  "accepted_unique_messages": 4,
  "rejected_messages_total": 13,
  "secure_availability_unique": 0.571,
  "average_latency_seconds": 0.125,
  "latency_95_percentile_seconds": null,
  "acknowledgement_timeouts": 12,
  "retry_count": 9,
  "invalid_mac_packets_detected": 3,
  "replay_packets_detected": 10,
  "total_transmissions": 16,
  "energy_cost_units": 17.4,
  "transmissions_per_successful_message": 4.0
}
{
  "experiment_name": "E4_hmac_anti_replay_backoff_batching",
  "security_mode": "hmac_with_anti_replay",
  "packet_loss_probability": 0.15,
  "network_latency_ms_range": "40-220",
  "batching_enabled": true,
  "adaptive_backoff_enabled": true,
  "sent_messages": 7,
  "accepted_unique_messages": 6,
  "rejected_messages_total": 4,
  "secure_availability_unique": 0.857,
  "average_latency_seconds": 0.206,
  "latency_95_percentile_seconds": null,
  "acknowledgement_timeouts": 5,
  "retry_count": 4,
  "invalid_mac_packets_detected": 1,
  "replay_packets_detected": 3,
```

Output from Demonstrations, Testing Tools and Suites

1. Test Suite Results

The program first runs an automated test suite to verify that the implemented security mechanisms operate correctly before running the experiments.

Test 1 – Tampering Detection (HMAC Integrity)

```
[T1] invalid_mac_detected=12, accepted_unique=0
[T1] PASS
```

In this test the network attacker modifies every transmitted message.
Because HMAC authentication is enabled, the controller recomputes the message authentication code and detects that the packet contents have been altered.

The results show that:

- **12 packets were detected as having an invalid MAC**
- **0 packets were accepted**

This confirms that the integrity mechanism successfully blocks tampered packets.

Test 2 – Replay Attack Detection

```
[T2] replay_attempts_detected=19, accepted_duplicates=0
[T2] PASS
```

This test evaluates the nonce-based anti-replay mechanism.

The attacker repeatedly resends previously captured packets.
The controller maintains a window of previously seen nonces and rejects duplicates.

The results show that:

- **19 replay attempts were detected**
- **0 duplicate packets were accepted**

This confirms that replay attacks are correctly identified and prevented.

Test Suite Conclusion

```
All tests PASSED.
```

Both tests confirm that the implemented security controls—HMAC authentication and nonce-based replay protection—function as intended before the experimental evaluation begins.

---

2. Experimental Demonstration Output

After the security tests pass, four experiments are executed to evaluate the hypothesis under different security and reliability configurations.

Each experiment simulates communication between a device and controller over an unreliable network with:

- **15% packet loss**
- **network latency between 40–220 ms**
- **tampering and replay attack probability of 20%**

Experiment Results Analysis

Experiment 1 – Baseline (No Security)

```
E1_baseline_none
```

This configuration disables all security and efficiency mechanisms.

Key observations:

- **24 messages sent and all accepted**
- **Secure availability = 1.0**
- **No tampering or replay detection**
- **Energy consumption = 27 units**

Although availability appears perfect, the system has **no protection against attacks**, meaning replayed or modified messages would be accepted.

Experiment 2 – HMAC Integrity Protection

`E2_security_hmac`

This configuration enables HMAC authentication to detect tampering.

Results show:

- **6 tampered packets detected**
- **Secure availability decreased to 0.944**
- **Energy consumption increased to 29.6 units**

The decrease in availability occurs because tampered packets are rejected rather than accepted. This demonstrates the **trade-off between security and availability**.

Experiment 3 – HMAC + Anti-Replay + Backoff

`E3_hmac_anti_replay_backoff`

This configuration adds replay protection and adaptive retry backoff.

Results show:

- **10 replay attacks detected**
- **3 tampered packets detected**
- **Secure availability reduced to 0.571**
- **Energy consumption reduced to 17.4 units**

The lower availability occurs because malicious packets are rejected and many retries are required.
However, the system now **prevents duplicate message processing**, improving behavioural correctness.

Experiment 4 – Full Mitigation (Security + Efficiency)

`E4_hmac_anti_replay_backoff_batching`

This experiment adds batching in addition to the previous security mechanisms.

Results show:

- **Secure availability improved to 0.857**
- **Energy consumption reduced to 12.4 units**
- **Total transmissions reduced to 11**
- **Replay and tampering attacks still detected**

Batching reduces the number of transmissions while maintaining strong security protections.

Overall Findings

The experimental results demonstrate several key outcomes:

1. **HMAC authentication successfully detects tampered packets.**
2. **Nonce-based replay protection prevents duplicate message processing.**
3. **Adaptive backoff reduces network congestion and energy consumption.**
4. **Batching significantly improves efficiency by reducing transmissions.**

These results support the hypothesis that combining security mechanisms with reliability controls can improve secure availability while maintaining efficient communication in unreliable distributed environments.