





STRAIGHT SIDED DOUBLE CRANK POWER PRESSES


- ☐ Rigid frame design ensures less vibration and low noise, increasing tool life improves product accuracy
- Hydraulic overload protection
- ☐ Full length, High precision 8-point gib with bronze liners for accurate slide guidance
- ☐ Automatic recirculating lubrication with progressive block
- Pneumatic high torque wet clutch and brake unit with sintered multi-disc linings provides low noise, long life operation with minimal maintenance
- Long stroke drawing and blanking operations



USER FRIENDLY TOUCH SCREEN HMI WITH FUNCTION & FAULT FINDING DISPLAY



AUTOMATIC MOTORISED RECIRCULATING LUBRICATION



HIGH TORQUE WET CLUTCH & BRAKE UNIT WITH SINTERED MULTI DISC LININGS



SPECIFICATIONS FOR SDC SERIES STRAIGHT SIDED DOUBLE CRANK POWER PRESSES

Model			SDC-250		SDC-320		SDC-400		SDC-500		SDC-630		SDC-800	
		,	S	Н	S	Н	S	Н	S	Н	S	Н	S	Н
Capacity		Tonne	250		320		400		500		630		800	
Length of Stroke		mm	300	150	300	200	400	250	450	250	450	250	450	300
Speed Fixed		spm	25	40	20		20		15		15		12	
Variable Speed		spm	25-35	30-60	15-25	25-50	15-25	25-50	12-20	25-50	12-20	25-50	10-18	20-40
Rating Point		mm	9	6.5	13	6.5	13	6.5	13	6.5	13	6.5	13	6.5
Die Height		mm	630		630		700		700 / 800		700 / 800		800	
Slide Adjustment		mm	200		200		250		250		250		300	
Bolster Area (1) (2)		mm	1800 x 1200		2200 x 1370		2500 x 1400		2500 x 1550		2800 x 1550		3100 x 1550	
		mm	2200 x 1200		2500 x 1370		2800 x 1400		2800 x 1550		3100 x 1550		-	
Slide Area (1)		mm	1600 x 1100		2200 x 1200		2500 x 1400		2500 x 1550		2800 x 1550		3100 x 1550	
	(2)	mm	2100 x 1100		2500 x 1200		2800 x 1400		2800 x 1550		3100 x 1550		-	
Bolster Thickness		mm	180		190		190		190		250		250	
Window Opening		mm	800 x 400		1000 x 500		1100 x 650		1200 x 650		1300 x 650		1300 x 650	
Air Counter Balance Capacity		Kg	2800		3000		4000		4500		5000		5500	
Air Pressure Required		Kg/cm ²	5		5		5		5		5		5	
Floor to Top of Bolster with Pit		mm	850		850		850		850		850		850	
Main Motor		HP	25		30		40		50		75		100	
Type of Die Cushion			Bellow		Cylinder									
Capacity		Tonne	28		55		60		80		80		80	
Length of Stroke		mm	150		150		200		220		220		220	
Area of Cushion Pad		mm	1400 x 800		1700 x 900		2000 x 900		2000 x 950		2300 x 950		2600 x 950	
		mm	1800 x 800		2000 x 900		2300 x 900		2300 x 950		2600 x 950		-	

Standard Accessories

- Automatic Recirculating Lubrication System
- Hydraulic Overload Protection System
- Dual Solenoid Valve
- Die Height Indicator
- Air Counter Balancer System
- Digital Crank Angle Indicator
- * 8 Point Rotary cam Switch
- Product Counter
- Batch Counter

- Misfeed Sockets
- Air Outlet
- Control Console
- Combination Clutch & Brake
- Large Lockable Emergency Stop Buttom
- Die Light Device
- Safety Fence
- Ladder
- Operating Stand

Optional Attachment

- Die Cushion
- Photoelectric Safety Device
- Variable Speed Motor
- Flywheel Brake and Main Motor FWD/REV Controller
- Load Tonnage Monitor
- Quick Die Change System
- Anti Vibration Mounts
- Moving Bolster
- Knockout Device

THE MANUFACTURER RESERVES THE RIGHTS TO MODIFY DESIGN, SPECIFICATIONS, MECHANISM, ETC. TO IMPROVE THE PERFORMANCE OF THIS MACHINE WITHOUT NOTICE.

POWER PRESSES

CORP. OFFICE: 201-202, KARMA STAMBH INDUSTRIAL ESTATE, OPP. MTNL OFFICE, L. B. S. MARG, VIKHROLI (W), MUMBAI-400 083 TEL.: 67969719 / 20 / 21, 25784515 FAX: 91-22-25798809, 67969652 E-mail: info@sewpresses.com Web: www.sewpresses.com

PLANT: NH 8B, OPP. FIELD MARSHAL SCHOOL, SHAPAR, DIST. RAJKOT TEL.: 02827-252358, 253381 FAX: 02827-253278

SALES OFFICES —

BARODA:

282 / 1 / A, GIDC, Makarpura, 603 - A, Mittal Tower, M. G. Road, BARODA-390010

Telefax: 0265-2641121

BENGALURU:

BENGALURU-560 001

E-mail: singhalpresses@gmail.com

143, Angappa Naicken Street, CHENNAI-600 001

Tel.: 25587728 Telefax: 080-25594143 Tel.: 25221246 Telefax: 044-25221245

E-mail: mands@md4.vsnl.net.in

FARIDABAD:

53, 1st Floor, Neelam Flyover Market, FARIDABAD-121001 Tel.: 0129-2420150

E-mail: fbd@singhal.co.in spplf@bsnl.in