

# Image Gradients

## Goal

In this chapter, we will learn to:

- Find Image gradients, edges etc
- We will see following functions : `cv.Sobel()`, `cv.Scharr()`, `cv.Laplacian()` etc

## Theory

OpenCV provides three types of gradient filters or High-pass filters, Sobel, Scharr and Laplacian. We will see each one of them.

### 1. Sobel and Scharr Derivatives

Sobel operators is a joint Gaussian smoothing plus differentiation operation, so it is more resistant to noise. You can specify the direction of derivatives to be taken, vertical or horizontal (by the arguments, `yorder` and `xorder` respectively). You can also specify the size of kernel by the argument `ksize`. If `ksize = -1`, a 3x3 Scharr filter is used which gives better results than 3x3 Sobel filter. Please see the docs for kernels used.

### 2. Laplacian Derivatives

It calculates the Laplacian of the image given by the relation,  $\Delta src = \frac{\partial^2 src}{\partial x^2} + \frac{\partial^2 src}{\partial y^2}$  where each derivative is found using Sobel derivatives. If `ksize = 1`, then following kernel is used for filtering:

$$kernel = \begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$$

## Code

Below code shows all operators in a single diagram. All kernels are of 5x5 size. Depth of output image is passed -1 to get the result in `np.uint8` type.

```
import numpy as np
import cv2 as cv
from matplotlib import pyplot as plt


img = cv.imread('dave.jpg',0)

laplacian = cv.Laplacian(img,cv.CV_64F)
sobelx = cv.Sobel(img,cv.CV_64F,1,0,ksize=5)
sobely = cv.Sobel(img,cv.CV_64F,0,1,ksize=5)

plt.subplot(2,2,1),plt.imshow(img,cmap = 'gray')
plt.title('Original'), plt.xticks([], plt.yticks([]))
plt.subplot(2,2,2),plt.imshow(laplacian,cmap = 'gray')
plt.title('Laplacian'), plt.xticks([], plt.yticks([]))
plt.subplot(2,2,3),plt.imshow(sobelx,cmap = 'gray')
plt.title('Sobel X'), plt.xticks([], plt.yticks([]))
plt.subplot(2,2,4),plt.imshow(sobely,cmap = 'gray')
plt.title('Sobel Y'), plt.xticks([], plt.yticks([]))

plt.show()
```

Result:



image

## One Important Matter!

In our last example, output datatype is `cv.CV_8U` or `np.uint8`. But there is a slight problem with that. Black-to-White transition is taken as Positive slope (it has a positive value) while White-to-Black transition is taken as a Negative slope (It has negative value). So when you convert data to `np.uint8`, all negative slopes are made zero. In simple words, you miss that edge.

If you want to detect both edges, better option is to keep the output datatype to some higher forms, like `cv.CV_16S`, `cv.CV_64F` etc, take its absolute value and then convert back to `cv.CV_8U`. Below code demonstrates this procedure for a horizontal Sobel filter and difference in results.

```
import numpy as np
import cv2 as cv
from matplotlib import pyplot as plt

img = cv.imread('box.png',0)


# Output dtype = cv.CV_8U
sobelx8u = cv.Sobel(img,cv.CV_8U,1,0,ksize=5)

# Output dtype = cv.CV_64F. Then take its absolute and convert to cv.CV_8U
sobelx64f = cv.Sobel(img,cv.CV_64F,1,0,ksize=5)
abs_sobel64f = np.absolute(sobelx64f)
sobel_8u = np.uint8(abs_sobel64f)

plt.subplot(1,3,1),plt.imshow(img,cmap = 'gray')
plt.title('Original'), plt.xticks([], plt.yticks([]))
plt.subplot(1,3,2),plt.imshow(sobelx8u,cmap = 'gray')
plt.title('Sobel CV_8U'), plt.xticks([], plt.yticks([]))
plt.subplot(1,3,3),plt.imshow(sobel_8u,cmap = 'gray')
plt.title('Sobel abs(CV_64F)'), plt.xticks([], plt.yticks([]))

plt.show()
```

Check the result below:



image

Loading [MathJax]/extensions/MathZoom.js

Exercises