

Get started

SnapServe documentation

Build Indic-first AI voice agents for phone, WhatsApp, webcall, and meetings. Configure in the dashboard, then drive calls from your own product with the REST API.

Last updated 25 Aug 2026

SnapServe runs the live conversation (speech in, LLM, speech out, tools). You own the UI, leads, CRM, and business logic. These docs cover the dashboard product and the public API on <https://app.snapserve.ai/api>.

Platform URLs

[1App](#)

<https://app.snapserve.ai>

[Dashboard login & product](#)

[2Docs](#)

<https://app.snapserve.ai/docs>

[Guides & this documentation](#)

[3API base URL](#)

<https://app.snapserve.ai/api>

[For Bearer sk_live_... requests — not a browser page](#)

Start here

[Create an agent in Vibe](#)

[Chat, edit, connect, and test on one page](#)

[What you can build](#)

[Inbound, outbound, WhatsApp, meetings, campaigns](#)

[Connections](#)

[WhatsApp, email, calendar, forms, and ads](#)

[WhatsApp](#)

[Text chatbot, templates, and WhatsApp calling](#)

[Quick Start \(API\)](#)

[Bearer sk_live_... and your first outbound call](#)

[API Reference](#)

[Agents, calls, transcripts, phones, wallet](#)

Two tracks

Learn the product in the sidebar (Vibe, agents, WhatsApp, campaigns). **Integrate** with [Quick Start](#) and the [API Reference](#). Dashboard login uses a session cookie; servers use API keys — do not mix them.

How a call works

1. Caller speaks → STT (Sarvam, Deepgram, ...)
2. LLM decides what to say and which tools to run
3. TTS speaks (Cartesia, Sarvam Bulbul, ...)
4. Telephony (Vobiz / Twilio / Plivo), webcall, or a meeting bot plays audio

Full building blocks: [Platform concepts](#).

API base URL

textCopy
`https://app.snapserve.ai/api`

This is the prefix for REST calls (not a webpage — opening it in a browser shows `Cannot GET /api`). Auth: `Authorization: Bearer sk_live_...` — [Authentication](#). Browse endpoints in the [API Reference](#).

Popular guides

- [Vibe builder](#) — recommended first agent
- [WhatsApp](#) — chatbot vs calling vs templates
- [Bookings calendar](#) — Google Calendar on the call
- [Calls & history](#) — transcript and summary
- [Event subscriptions](#) — push results to your backend
- [Compliance](#) — TRAI, IRDAI, WhatsApp Business
- [FAQ](#)

Something missing? Email support@snapserve.ai.

[Next](#)

Get started

What you can build

SnapServe runs the live phone conversation. Your product owns UI, leads, CRM, and business logic.

Vibe (fastest first agent)

Describe the business in chat. Vibe writes the prompt and stays open as a studio (Chat, Agent, Connect, Test). [Vibe builder](#).

Inbound voice assistants

Buy or bring a number, assign it to an agent, and answer customers 24/7 — appointments, support, FAQs — with tools that check calendars or create tickets.

Outbound dialers & workflows

Trigger `POST /calls/outbound` from your backend when a lead fills a form, a deal moves stage, or a reminder is due. Pass per-call `variables` (name, questions) so one agent can handle many patients. Get transcript + summary back via webhooks. [Variables](#).

Booking agents

Connect Google Calendar (or SnapServe scheduling), put booking tools on the agent, and let callers schedule themselves. See [Calendar & booking](#).

Campaigns (dashboard)

Batch-dial CSV / Sheets / website / Meta leads with retries, dispositions, and lead transfer to webhook or Sheets. After-call WhatsApp/email rules live on the agent. See [Campaigns](#).

WhatsApp chatbot & calling

After-call templates, inbound AI text replies, or 1:1 WhatsApp voice — not a bulk WhatsApp campaign. [WhatsApp guide](#).

Meeting agents

Send the same agent into Google Meet, Zoom, or Teams — paste a link, auto-join calendar events, or dispatch from bookings. In-meeting tools cover leave, mute, chat, and slides. [Meetings guide](#).

Apps on top of the API

- Website voice widget — copy per-agent embed code from Settings → Website. [Website webcall embed](#)
- Custom CRM dialer UI
- Internal “call this contact” buttons
- Zapier-style automations / n8n workflows
- Post-call analytics from transcript + disposition

Next

Learn the building blocks in [Platform concepts](#), then configure an agent in the [dashboard builder](#) or jump to [Quick Start \(API\)](#).

Get started

Platform concepts

Who owns what — agents, campaigns, connections, dispositions, squads, and meetings.

Short rule: the **agent** owns the conversation and messages; the **campaign** owns the lead list and dial; **Connections** wires the outside world.

Jarvis

The in-app Jarvis overlay is removed. Use [Vibe](#) to build an agent. [Jarvis note](#).

Agent

A voice persona: system prompt, greeting, language, ASR/LLM/TTS (or BYOP), tools, knowledge base, phone number, variables, Outcomes / dispositions, after-call WhatsApp & email rules, and optional [meeting](#) settings. Create in [Vibe](#) or configure in [Agents](#). Toggle active before production calls.

Campaign

Outbound dialing at scale: lead sources (CSV, Sheets, Website, Meta, CRM), queue, retries, calling hours, and lead transfer (push matching dispositions to a webhook or Google Sheet). Messaging after the call is configured on the agent, not the campaign. [Campaigns guide](#).

Connections

Hub for wires used by agents and campaigns: WhatsApp, Email (Brevo), Google Sheets, Website form, Meta Lead Ads, Calendar & booking, and Meetings entry. [Connections guide](#) · [WhatsApp](#).

Disposition / Outcomes

After each call, AI picks an outcome from the agent's taxonomy and fills data fields you define. Map labels to funnel meanings (Interested / Callback / DNC) for analytics. Set under Agent Builder → After the call.

After-call messages

Agent-owned WhatsApp / email rules: every call, or only for matching dispositions. Connect WhatsApp and email under Connections, then pick the Meta template per

outcome on After the call. Campaigns no longer map WA/email branches — they only transfer leads.

Lead transfer

Campaign Configuration → when disposition matches, POST the lead to a webhook and/or append to a Google Sheet. Use this for CRM / ops handoff — not for customer messaging.

Squad

Multi-agent team: mid-call live handoff (`transfer_to_*`) and follow-up tasks for a later outbound. Callback *disposition* means “call later”; it is not automatically a live handoff.

Meeting

Same agent inside Google Meet / Zoom / Teams. Join via paste link, calendar Join toggles, or booking auto-dispatch. [Meetings guide](#).

Call

One phone (or meeting) conversation. SnapServe stores status, duration, cost, transcript, summary, evaluation, and disposition. Retrieve with [GET /calls/{id}](#) or listen on webhooks.

Phone number

Caller ID outbound and DID inbound. India numbers need KYC. [Phone numbers guide](#).

Wallet

Prepaid INR balance. Usage deducts per minute. [Wallet](#).

Variables

Placeholders like `{{customer_name}}` in the prompt, filled per call. [Variables](#).

Tools

Functions mid-conversation (book slot, transfer, HTTP webhook, meeting controls). Configured in the agent builder Actions tab. Connect WhatsApp, email, and Google Calendar under Connections, then pick the template or meeting on the agent.

Knowledge base

Documents the agent can search during a call (RAG). [Knowledge base](#).

Event subscriptions & related URLs

Do not confuse these four jobs that all used to say “webhook”:

- Event subscriptions — Developers → workspace-wide call events. [Guide](#).
- Post-call notify — Agent Builder → Settings → notify URL for that agent only.
- Form intake — Connections / Campaigns → website form POSTs leads into SnapServe.
- Lead transfer — Campaign Configuration → push matching dispositions to CRM / Sheets.

API key

`sk_live_...` for server-to-server REST. Create under [API Keys](#). [Authentication](#). Meeting bot launch typically uses a logged-in session (dashboard) — see [API Reference → Meetings](#).

Get started

Jarvis

The in-app Jarvis overlay has been removed. A new assistant plan is coming.

Last updated 22 Aug 2026

Create an agent from [Vibe](#) or the [Agents builder](#).

Quick Start (API)

Copy page

From a backend: authenticate, list agents, place one outbound PSTN call, then read transcript and summary. Campaigns stay in the dashboard.

Last updated 18 Aug 2026

Prerequisites

- An active agent — create in [Vibe](#) or the [builder](#).
- A `sk_live_...` key — [Authentication](#). Never put it in a browser.
- Wallet balance (₹500 welcome credit). Empty wallet → `402`.

- A from-number on the agent (SnapServe DID or your Twilio/Plivo/Vobiz creds). India DIDs need KYC. [Phone numbers](#).

Production

Register `call.completed` instead of polling — [Event subscriptions](#).

1. List agents

```
bashCopy
export SNAPSERVE_API_KEY=sk_live_YOUR_KEY

curl https://app.snapserve.ai/api/agents \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"

jsonCopy
[
  {
    "id": 123,
    "name": "Support desk",
    "status": "active",
    "language": "en-IN"
  }
]
```

Use an agent with `status: "active"`. Draft agents may still dial; do not rely on that in production.

2. Confirm wallet (optional)

```
bashCopy
curl https://app.snapserve.ai/api/wallet \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

`balanceCents` is paise. `50000` = ₹500 ≈ 100 minutes at ₹5/min. [Pricing](#).

3. Place an outbound call

Parameter	Type	Description
<code>agentId</code> ^{required}	integer	Agent you own
<code>toNumber</code> ^{required}	string	Destination E.164, e.g. +919876543210
<code>webhookBaseUrl</code>	string	Rare: override public base URL for telephony callbacks. Omit in production.

No variables on this endpoint

The public body is only `agentId`, `toNumber`, and optional `webhookBaseUrl`. Extra JSON fields are ignored. Per-lead `{{customer_name}}` injection is a [campaign](#) field-mapping feature, not this API. Put stable facts in the agent prompt, or run a campaign.

cURLNode / TypeScriptPython

bashCopy

```
curl -X POST https://app.snapserve.ai/api/calls/outbound \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "agentId": 123,
    "toNumber": "+919876543210"
  }'
```

jsonCopy

```
{
  "id": 456,
  "status": "initiated",
  "agentId": 123,
  "toNumber": "+919876543210",
  "fromNumber": "+917971543255"
}
```

Common failures:

- `401` — missing/invalid key
- `402` — wallet empty
- `403` — IRDAI prompt incomplete, TRAI quiet hours / DNC, or KYC required for own Vobiz
- `404` — agent or telephony provider missing

4. Get the result

Poll until `status` is terminal (`completed`, `failed`, `no_pickup`, ...), or handle `call.completed` on your webhook.

cURLNode / TypeScriptPython

bashCopy

```
curl https://app.snapserve.ai/api/calls/456 \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

jsonCopy

```
{
  "id": 456,
  "agentId": 123,
  "status": "completed",
  "toNumber": "+919876543210",
  "fromNumber": "+917971543255",
  "durationSeconds": 84,
  "costCents": 700,
  "transcript": "Agent: Hello...",
  "callSummary": "Caller asked about clinic hours.",
  "dispositionResult": "Interested",
  "recordingUrl": "https://..."
}
```

`costCents` is paise (700 = ₹7.00). Full field list: [Calls & history](#) · [GET /calls/{id}](#).

Next

- [Verify webhook signatures](#)
- Official SDK: `npm install @snapserveai/sdk` — [API Wrappers & SDKs](#)
- Batch dialing: [Campaigns](#) (dashboard, not this API)

Authentication

Copy page

Server-to-server requests use a developer API key (`sk_live_...`). Keys are shown once when created — store them in a secret manager.

Create a key

1. Sign in at app.snapserve.ai (the product lives here — not api.snapserve.ai).
2. Open [API Keys](#) in the dashboard.
3. Create a key, copy the full value immediately.

Up to 5 active keys per account. Revoke unused keys.

Never expose `sk_live_` in browsers

API keys authenticate as your full account. Use them only from your backend, workers, or secure server environments — not React, mobile apps, or public clients.

API base URL

Use <https://app.snapserve.ai/api> with a Bearer key from your server. Opening `/api` in a browser is not a page (Cannot GET /api). Requests to <https://api.snapserve.ai> return 404. Docs are at <https://app.snapserve.ai/docs>, not docs.snapserve.ai.

Authorization header

Every request needs:

```
httpCopy
Authorization: Bearer sk_live_YOUR_KEY
Content-Type: application/json

bashCopy
export SNAPSERVE_API_KEY=sk_live_YOUR_KEY

curl https://app.snapserve.ai/api/agents \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \
  -H "Content-Type: application/json"
```

Auth errors

```
jsonCopy
{ "error": "Unauthorized" }
{ "error": "Invalid or revoked API key" }
```

Both return HTTP 401. See [Errors](#).

Dashboard sessions

The web app uses a separate session JWT after login. That path is for browsers only. Your application should always use `sk_live_`.

Next

Follow the [Quick Start](#) to list agents and place a call, or connect [Claude skill & MCP](#) to operate SnapServe from Claude Desktop / Claude Code.

Claude skill & MCP

Copy page

Use Claude (Desktop or Claude Code) with the SnapServe skill and MCP so you can create agents, run campaigns, link website forms, and manage your account in plain English — backed by live API tools for app.snapserve.ai.

Connect SnapServe over MCP

Drive your whole SnapServe account — agents, calls, campaigns, journeys, WhatsApp, analytics — as tools from Claude, Cursor, Windsurf, and any MCP-aware client. 76 tools, plus a skill that teaches the assistant how SnapServe works.

[Full setup guide](#)

1 · Get your API key

Generate an `sk_live_...` key from Dashboard → API Keys.

2 · Add the SnapServe MCP server

Paste this into your client's MCP config and add your key.

jsonCopy

```
{
  "mcpServers": {
    "snapserve": {
      "command": "npx",
      "args": ["-y", "@snapserveai/mcp"],
```

```

    "env": {
      "SNAPSERVE_API_KEY": "sk_live_YOUR_KEY",
      "SNAPSERVE_BASE_URL": "https://app.snapserve.ai/api"
    }
  }
}

```

3 · Verify the connection

Ask your assistant to run a SnapServe tool:

textCopy

Using SnapServe, list my agents and show my wallet balance.

Skill vs MCP

The **skill** teaches Claude *how* SnapServe works (workflows, safe defaults). The **MCP server** gives Claude *tools* that call your account with your `sk_live_...` key. Use both together for the best experience.

What you can do in Claude

Once connected, ask Claude things like:

- “List my SnapServe agents”
- “Create an English Voiceathon agent with Sarvam STT”
- “Call +91... with agent 415”
- “Create a website lead campaign and give me the form webhook URL”
- “Show transcript and logs for call 4943”
- “What’s my wallet balance?”

Claude uses tools such as `list_agents`, `create_agent`, `outbound_call`, `get_website_webhook`, and `snapserve_api` for anything else on the API.

Prerequisites

1. A SnapServe account on app.snapserve.ai.
2. An API key from [Dashboard → API Keys](#) (`sk_live_...`). See [Authentication](#).
3. Claude Desktop or Claude Code, plus Node.js 20+ if you run the MCP from this repo.

Keep `sk_live_` secret

Put the key only in MCP `env` / your secret manager — never paste the full key into public chats or commit it to git.

1. Install the SnapServe MCP

Prefer the published npm package `@snapserveai/mcp` (stdio via `npx`). Or build from this monorepo at `lib/snapserve-mcp` (workspace package name `@snapserve/mcp`).

Hosted (no local install): Claude custom connector URL

<https://app.snapserve.ai/api/mcp> — see [API Wrappers & SDKs → MCP](#).

```
bashCopy
# Option A — npm (recommended for Claude Desktop / Cursor)
# see config JSON below with npx -y @snapserveai/mcp

# Option B — from this repo
git clone https://github.com/srundme/voiceorch.git
cd voiceorch
pnpm install
pnpm --filter @snapserve/mcp build
# binary: lib/snapserve-mcp/dist/index.js
```

2. Claude Desktop

Edit Claude's config file (macOS: `~/Library/Application Support/Claude/claude_desktop_config.json`). Recommended (npm):

```
jsonCopy
{
  "mcpServers": {
    "snapserve": {
      "command": "npx",
      "args": ["-y", "@snapserveai/mcp"],
      "env": {
        "SNAPSERVE_API_KEY": "sk_live_YOUR_KEY",
        "SNAPSERVE_BASE_URL": "https://app.snapserve.ai/api"
      }
    }
  }
}
```

Or point `command/args` at a built `lib/snapserve-mcp/dist/index.js` from the repo.

1. Replace the API key (and path if using the repo binary).
2. Fully quit and reopen Claude Desktop.
3. Confirm the SnapServe MCP appears under tools / connectors (wording varies by Claude version).

Skill: copy the folder `claude-skill/snapserve` (or `.claude/skills/snapserve` from the repo) into your Claude skills directory so Claude loads SnapServe workflows automatically. Restart Claude after copying.

3. Claude Code

```
bashCopy
# Hosted HTTP connector
claude mcp add snapserve --transport http \
  --url https://app.snapserve.ai/api/mcp \
  --header "Authorization: Bearer sk_live_YOUR_KEY"

# Or local stdio via npm
claude mcp add snapserve \
  --env SNAPSERVE_API_KEY=sk_live_YOUR_KEY \
  --env SNAPSERVE_BASE_URL=https://app.snapserve.ai/api \
  -- npx -y @snapserveai/mcp
```

With the repo open, Claude Code can also use `.claude/skills/snapserve/SKILL.md` for product guidance.

4. Try it

In a new Claude chat:

```
textCopy
Using SnapServe, list my agents and show my wallet balance.
```

Then try a website intake flow:

```
textCopy
Create a campaign named "Website leads" for agent <id>, then give me the
website webhook URL and a curl example to POST a test lead.
```

Paste the returned URL into your form / Sheet / Zap. Live intake path:

```
bashCopy
curl -X POST 'https://app.snapserve.ai/api/webhooks/lead/YOUR_TOKEN' \
  -H 'Content-Type: application/json' \
  -d '{"phone":"+919876543210","name":"Test Lead"}'
```

Skill only (no MCP)

If you only install the skill, Claude can still guide you and draft `curl` / SDK calls using your key — but it cannot call SnapServe live until MCP is connected. Prefer MCP for create-agent / campaign / dial actions.

Manual REST wrappers: [API Wrappers & SDKs](#). Full public HTTP surface: [API Reference](#).

Safety

- Confirm before delete agent / campaign.
- Don't invent transcripts — ask Claude to fetch call detail / logs.
- Phone purchase / KYC / Razorpay top-ups stay in the [dashboard](#) when checkout is required.

Also works in Cursor

Same MCP binary. Copy `.cursor/mcp.json.example` → `.cursor/mcp.json` in the repo and set `SNAPSERVE_API_KEY`. Project skill: `.agents/skills/snapserve`.

Source of truth

User how-to in the repo: `claude-skill/snapserve/README.md`. Install details:

`claude-skill/snapserve/references/install-mcp.md`. Workflows:

`references/workflows.md`.

Vibe builder

The recommended way to create an agent. Chat to design it, then stay on the same page to edit, connect channels, and test.

Last updated 18 Aug 2026

Open [Vibe](#) in the dashboard. After an agent exists, four tabs stay on one studio:

- Chat — describe the business, language, and call flow. Vibe writes the prompt, greeting, tools, and outcomes.
- Agent — full editor (prompt, voice, tools, outcomes). Same panel as [Agents & builder](#).
- Connect — phone number, knowledge, WhatsApp, calendar, CRM notify. Same hub as [Connections](#).
- Test — webcall, outbound test, tool simulator. [Test an agent](#).

Start here for a first agent

Open this page from “Build with AI”. Tell it who the agent is, what language they speak, and what a successful call looks like.

Which models Vibe uses

- Builder chat — Sarvam `sarvam-105b` with high reasoning on the SnapServe managed key. This designs the agent; it is not the voice on the call.
- Live agent (default) — Sarvam `sarvam-105b-conversations` for phone, webcall, and WhatsApp chat replies. Change provider and model on the Agent tab.

Partner / white-label workspaces

Managed partner clients do not see SnapServe branding or Vibe marketing. They create agents from the classic builder (`/app/agents?create=1`). Direct SnapServe hosts keep Vibe as the default studio.

Next

Attach a number and channels in [Connections](#), then [test](#) before a campaign.

Agents & builder

Create the voice persona in Vibe or the classic builder, then drive it from your app with the Agents API.

Recommended

New agents: start in [Vibe](#). This page is the full builder checklist (also the Agent tab inside Vibe).

Build in the dashboard

1. Open [Vibe](#) or [Agents](#) → create or open an agent.
2. Script — welcome (exact first line) then call instructions. Use [variables](#) like `{{ name }}`. The agent display name is an internal label — not automatically your company brand on the call.
3. Sound — voice, language, and Fast / Balanced / Patient turn-taking.
4. Actions — booking, transfer, mid-call WhatsApp / email. Connect the account once under [Connections](#), then pick the template or meeting here.
5. After the call — outcome labels, per-outcome WhatsApp templates, and voicemail. Mid-call send stays on Actions.
6. Activity — this agent's call volume, success rate, spend, and latency. Platform-wide funnel stays at [/app/analytics](#).
7. Knowledge — attach a [knowledge base](#).
8. Phone — assign a number for caller ID / inbound.
9. Meetings (optional) — meeting prompt + deck for Meet/Zoom/Teams. [Meetings guide](#).
10. Save, then toggle Active when ready.
11. Optional: Settings → Website — copy embed code so visitors can webcall this agent on your site. [Website embed guide](#).
12. Use Test / Publish flows in the builder before going live.

First agent: build in the UI. Day-to-day from your product: list / patch / toggle via API.

Agents API

Full schemas and cURL in the API Reference:

- [List agents](#)
- [Create agent](#)
- [Get agent](#)
- [Update \(save\) agent](#)
- [Toggle active](#)
- [Delete agent](#)

Using on a call

Pass `agentId` and optional `variables` (patient fields, questions) to [POST /calls/outbound](#). Wallet must cover ₹5/min. See [Variables](#) and [Calls & history](#).

Variables

Inject per-call data into the agent prompt so every conversation is personalized.

Syntax

In the agent system prompt (or greeting), use double curly braces:

```
textCopy
Hello {{customer_name}}, I'm calling about {{order_id}}.
```

In the dashboard

1. Open an agent → builder.
2. Add variables in the Variables section (name + optional default).

3. Reference them in the prompt as `{{name}}`.
4. Save / publish the agent.

Campaigns and lead CSVs can map columns onto the same variable names so each dial is unique without changing the agent.

Via API

Manage the registry with [list / create / update / delete agent variables](#).

For runtime values on each outbound call (patient name, category, questions), pass a `variables` object on [POST /calls/outbound](#). The same agent can dial hundreds of patients; only the payload changes. Keys fill `{{placeholders}}` in the prompt and greeting. The whole bag is also injected as a THIS CALL block, so a `questions` array is asked even if you did not list every item in the script.

```
bashCopy
curl -X POST https://app.snapserve.ai/api/calls/outbound \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "agentId": 36,
    "toNumber": "+919876543210",
    "variables": {
      "patient_name": "Priya Sharma",
      "category": "post-op knee",
      "questions": [
        "How is your pain today on a scale of 1 to 10?",
        "Have you been walking as advised?",
        "Any swelling, fever, or discharge from the wound?"
      ]
    }
  }'
```

One agent, many questionnaires

Keep the system prompt generic: greet `{{patient_name}}`, then ask every question listed under THIS CALL in order. Do not hardcode hospital categories. `parameters` is accepted as an alias of `variables`.

Next

[Agents & builder](#) · [Make a call](#)

Knowledge base

Upload documents so the agent can answer product/policy questions from your content during a call.

In the dashboard

1. Open [Knowledge bases](#).
2. Create a source and upload files (or paste text).
3. Attach the source to one or more agents in the agent builder.
4. Test the agent — answers should cite your material when relevant.

Tips

- Keep docs short and factual; prefer FAQs and SKUs over huge PDFs.
- Re-upload when policies change — stale docs confuse callers.
- Combine with a clear system prompt: when to search KB vs escalate.

Via API

Use [Knowledge Base endpoints](#) to list/create/upload sources and [attach](#) them to agents.

Caller memory updates

Push the latest status of a caller's request into agent memory so follow-up questions are answered from current ground truth — including campaign dials.

SnapServe already remembers durable identity (name, location, language) from past calls. Request status — refund approved, order shipped, appointment moved — used to live only in your CRM. Use the endpoints below, or Memory / campaign lead Memory in the dashboard, to write that status onto the caller so the next conversation uses it automatically.

Not runtime variables on outbound

`POST /calls/outbound` still accepts only `agentId` and `toNumber`. Per-caller updates go through caller memory (and campaign lead fields). See [Variables](#).

What the agent sees

- A freeform `note` is stored as `operator_update` and shown as Latest update.
- A `context` or `facts` map (for example `order_status: shipped`) is stored under `ext_order_status` and injected in an OPERATOR / CRM UPDATES block. The agent is told this is ground truth and must not re-ask.
- On a campaign dial, the same fields are merged into the lead so they also appear in LEAD CONTEXT (and as `{{order_status}}` if you mapped that variable).

API

Phone in the path must be URL-encoded. Auth is the same session or [API key](#) as the rest of the agents API.

```
bashCopy
curl -X POST
"https://app.snapserve.ai/api/agents/36/caller-memory/%2B919876543210/facts" \
-H "Authorization: Bearer $SNAPSERVE_API_KEY" \
-H "Content-Type: application/json" \
-d '{
  "note": "Refund of 1200 approved. Tracking TRK-441.",
  "context": {
    "order_status": "refund_approved",
    "tracking_id": "TRK-441"
  }
}
```

```
}  
}'
```

Full schema in the API Reference: [POST /agents/{id}/caller-memory/{phone}/facts](#) · [GET /agents/{id}/caller-memory/{phone}](#) to read back. Auth: same `sk_live_...` Bearer key as outbound calls.

Campaigns

From a campaign lead, either add a Note (automatically copied into caller memory) or POST structured fields:

```
bashCopy  
curl -X POST "https://app.snapserve.ai/api/campaigns/12/leads/88/memory" \  
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{"context": { "order_status": "shipped" } }'
```

That writes caller memory for the campaign's agent *and* updates `leadData`, so the next auto-dial already has the new status. Dashboard: open the lead → Overview or Memory → Save for next call. Same `sk_live_...` auth as the public agent endpoint above; this campaign path is for lead-scoped writes and is not listed in the curated API Reference.

In the dashboard

1. Campaigns → open a lead → Overview or the Memory tab → Save for next call.
2. Memory → pick an agent and caller → *Update for next call*.
3. Calls → open a call → Caller Memory sidebar → update for the next conversation.

Next

[Campaigns](#) · [Variables](#) · [Agents & builder](#)

Test an agent

Prove the prompt, tools, and voice before you spend wallet minutes on a campaign.

Last updated 18 Aug 2026

From [Vibe](#) → Test, or open [Test simulator](#).

Webcall

Browser audio to the same agent stack (STT → LLM → TTS) without a phone number. Use this to check greeting, barge-in, language, and tool calls. Share a webcall link when you need a stakeholder to try the agent without KYC.

To put that same webcall on your own website (floating button, iframe, or join link), copy the per-agent snippet from Settings → Website. [Website webcall embed](#).

Outbound test

Place one PSTN call to your phone. Requires an assigned number, an active agent, and wallet balance (₹5/min). This is a real call — it bills like production.

Tool simulator

Fire booking, HTTP, WhatsApp, or transfer tools without a live conversation. Use it to confirm arguments, calendar IDs, and webhook URLs before customers hit them.

WhatsApp and meetings are separate tests

WhatsApp text/calling is tested on the [WhatsApp](#) page (test message / test call). Meeting bots are tested by joining a Meet/Zoom/Teams link — [Meetings](#).

After the call

Open History for transcript, summary, disposition, and recording. Same fields as [Calls & history](#) and `call.completed` webhooks.

Connections

One hub for the outside world: messaging, lead intake, calendar, and meetings.
Agents own conversation rules; campaigns own the lead list.

Last updated 18 Aug 2026

Open [Connections](#). Vibe's Connect tab embeds the same hub.

What lives here

- WhatsApp — Meta Cloud API (WABA + Phone Number ID + token) is enough to send templates. Vobiz only if we sell you the WhatsApp number or you want WhatsApp calling. Webhook-only BSP still works. [WhatsApp guide](#).
- Email (Brevo) — email only, not WhatsApp. Paste a Brevo API key and a verified From address, then enable Send Email on the agent.
- Google Sheets — campaign lead source and/or lead-transfer destination.
- Website form — form POSTs into SnapServe as leads (form intake). For a live in-browser voice call on your site, use the agent's Settings → Website snippet instead. [Website webcall embed](#).
- Meta Lead Ads — Facebook / Instagram leads into a campaign.
- Bookings calendar — Google Calendar or SnapServe scheduling. [Calendar guide](#).
- Meetings — Meet / Zoom / Teams bots. [Meetings guide](#).

Four things people used to call “webhook”

- **Event subscriptions** — workspace call events. [Guide](#).
- **Post-call notify** — Agent Settings URL for that agent only.

- **Form intake** — website form → SnapServe leads.
- **Lead transfer** — campaign pushes matching dispositions to CRM / Sheets.

Who owns what

After-call WhatsApp and email rules sit on the agent Outcomes tab. Campaigns dial and transfer leads. Connecting a channel here does not send messages until the agent (or inbound WhatsApp chatbot) is configured.

WhatsApp

Meta is enough to send templates. Vobiz is only if SnapServe sells you the number or you want WhatsApp calling.

Last updated 23 Aug 2026

Open [Connections → WhatsApp](#). If the number is already on Meta Cloud API, paste WABA ID, Phone Number ID, and a permanent System User token. SnapServe talks to Meta only — no carrier channel.

Three paths

1. I already have Meta (default) — number already on your WABA. Paste WABA ID, Phone Number ID, and a permanent System User token. Connect saves the creds and fetches APPROVED templates. Voice “Send WhatsApp” and after-call templates go through Meta Graph. No Vobiz.
2. Buy a WhatsApp number from SnapServe — separate inventory from voice DID. We provision the line through Vobiz. You still paste WABA + token once (Meta owns the WABA).
3. Keep Wati / Gupshup / Zapier — SnapServe only posts to their webhook after a call. No in-app chatbot and no WhatsApp calling.

Meta is enough to send

You do not need a Vobiz channel to send an approved template from a voice agent. Vobiz is only if we sell you the WhatsApp number or you turn on WhatsApp calling.

Same number as calls

WhatsApp-enable a SnapServe voice DID still needs Meta IDs (Phone Number ID + token + WABA). Assigning the DID to an agent does *not* turn WhatsApp on. We do not create a Vobiz channel on this path unless you later enable WhatsApp calling.

Meta OTP on a SnapServe number

Click **Start capture** and wait for **listening...** before Meta rings. In Meta choose **Voice call** — SMS will never show on this page (the DID is a voice line). The 6-digit code appears after the call. That ring does not show in Call History. If you already verified the number on your WABA, skip OTP and paste Phone Number ID + token.

Text chatbot

After an own Vobiz channel is live (bought-from-us number, or a channel you linked), turn on AI chatbot replies and pick the agent. A number that already has a Meta text bot cannot also use SnapServe as the inbound bot — Meta allows one webhook.

- Inbound order: request-a-call → brochure → chatbot.
- Free-form replies only inside Meta's 24-hour customer-service window (after the customer's last inbound). First outreach to a new contact needs an approved template.
- Caps: about 30 chatbot replies per phone per 24 hours. **STOP** / unsubscribe stays silent.

WhatsApp calling

Shown only after an own Vobiz channel exists. Enable Calling on the number in Meta Business Manager first, then toggle WhatsApp calling on the SnapServe WhatsApp

page and pick the answering agent. This is 1:1 voice over WhatsApp, not a campaign.

Not a WhatsApp campaign

Campaigns dial PSTN. WhatsApp is after-call templates, inbound chat, or a 1:1 WhatsApp voice call. After-call WhatsApp / email rules live on the agent Outcomes tab, not on the campaign.

Will Meta block the chatbot?

Official Business API automation is allowed. Meta's 2026 rule bans general-purpose assistants (ChatGPT as the product on WhatsApp), not a clinic or shop answering its own customers. Keep the bot on-business, honour opt-out, and keep a human path (phone or email) on the WhatsApp profile. Quality rating still drops if people block or report you.

Next

Wire after-call templates on [Agents](#) → Outcomes. For email-only follow-up, use Brevo under [Connections](#) — Brevo is not WhatsApp.

Bookings calendar

Let agents check availability and book appointments on Google Calendar. Separate from Meeting bots that join video rooms.

Booking ≠ join

Connections → **Bookings calendar** creates invites (often with a Meet link). **Meeting bots** (`/app/meet`) join a room that already exists. See the [Meetings guide](#).

1. Connect Google

1. Go to [Connections → Bookings calendar](#) in the dashboard.
2. Create or open a calendar and connect a Google account.
3. Grant calendar read/write scopes SnapServe requests.

2. Event types & availability

Define what can be booked (duration, buffers) and when you are free. Availability rules drive slot search during the call.

3. Link the agent

1. Connect Google Calendar under Connections (once for the workspace).
2. Open the agent builder → Actions → Booking and pick the meeting callers can book.
3. Save the agent first before enabling calendar tools if the UI prompts you.
4. Test with a live or web-call: ask to book a slot and confirm it appears in Google.

Common mistakes

No Google account on the calendar, wrong calendar linked to the agent, or agent not saved after tool changes. Confirm Connections → Bookings calendar shows a connected account.

API note

Calendar connect and booking tools are configured in the dashboard. The public API Reference focuses on agents, calls, and webhooks — use Connections → Bookings calendar for Google setup rather than low-level calendar REST.

Next

[Agents & builder](#) · [Meeting agents](#) · [Variables](#) for guest name/email in prompts

Meeting agents

Send a SnapServe agent into Google Meet, Zoom, or Microsoft Teams — paste a link, auto-join calendar events, or dispatch from bookings.

What meetings are

A meeting agent is the same agent brain as phone calls, running inside a video room via a Recall.ai bot. Configure a meeting prompt (and optional slide deck) on the agent, then join from [Meetings](#) (`/app/meet`).

Meetings do not replace Campaigns. Campaigns dial phone leads; Meetings join a video URL that already exists.

Enable on an agent

1. Open the agent in the Builder.
2. Turn on Meetings / Phone+meetings and set a meeting prompt.
3. Optional: bot display name, duration, silence timeout, mute-when-idle, presentation URL, auto-start slides, who joins (self vs delegate agent).
4. The agent appears on the Meetings page.

Three join paths

Path	Where	When
Paste link	<code>/app/meet</code>	Ad-hoc join now
Google Calendar (AI meetings)	<code>/app/meet</code> → Connect Google → Join toggles	Auto-join upcoming events
Booking auto-dispatch	Scheduling / bookings with a Meet link	Bot joins near the slot

Two Google Calendar connects. Connections → Bookings calendar creates booking events (write). Meeting bots → Connect Google is readonly for AI meeting join. Do not treat them as the same button.

In-meeting capabilities

When the agent is inside a meeting, these tools are available:

- `leave_meeting` — exit cleanly
- `mute_meeting` / `unmute_meeting`
- `send_meeting_chat` — optional pin
- `start_presentation`, `stop_presentation`, `next_slide`, `previous_slide`, `goto_slide`
- `schedule_meet_rejoin` — rejoin the same URL later

Hosts may need to admit the bot from the Meet waiting room.

Meetings API

Session-authenticated endpoints are listed in the API Reference under Meetings:

- [POST /meet-bots](#) — launch
- [GET /meet-bots/{botId}](#) — status
- [DELETE /meet-bots/{botId}](#) — leave
- [GET /meet-bots/identity](#)
- [GET /meet-calendar/connection](#)
- [GET /meet-calendar/events](#)
- [POST /meet-calendar/events/{eventId}/bot](#)
- [DELETE /meet-calendar/events/{eventId}/bot](#)

Related

- [Platform concepts](#) — who owns what
- [Agents & builder](#) — Outcomes & prompts
- [Bookings calendar](#) — booking write path
- [Campaigns](#) — phone dialing at scale

Website webcall embed

Put a voice agent on your own site. Each agent has its own snippet — visitors talk in the browser, billed to your wallet.

Last updated 21 Aug 2026

Where to get the code

1. Open the agent → Settings → Website.
2. Click Generate embed code (once per agent).
3. Copy the snippet that matches how you want it to appear.

Deep link: `/app/agents/<id>?section=website`.

Floating widget

Paste this once before `</body>`. A mic button appears in the corner. Visitors allow the microphone, tap Start Call, and talk to that agent.

```
<script src="https://app.snapserve.ai/api/widget.js"
  data-agent-id="12"
  data-share="wcl_..."
  data-name="Support"
  data-color="#0ea5e9"

  data-position="bottom-right"></script>
```

- `data-agent-id` — this agent's numeric ID
- `data-share` — the per-agent token from Settings (required; without it visitors cannot connect)
- `data-name`, `data-color`, `data-position` — label and look (bottom-right, bottom-left, top-right, top-left)

HTTPS + microphone

The host page must be served over HTTPS (or localhost). Browsers block the mic on plain HTTP. Allow `https://app.snapserve.ai` in your Content-Security-Policy `script-src` if you lock scripts down.

Inline iframe

Use a fixed panel instead of a floating button. The iframe must include `allow="microphone"`.

```
<iframe
  src="https://app.snapserve.ai/api/widget/call?share=wcl_..."
  allow="microphone"
  title="Voice assistant"

  style="border:0;width:380px;height:560px"></iframe>
```

Direct join link

Same live call on a full SnapServe page — good for a “Talk to us” button or QR code. Opens `/join/<token>` for that agent.

Billing & safety

- Each visitor call uses the same webcall path as Live test and bills your wallet.
- Keep a positive wallet balance. If the wallet is empty, the widget cannot connect (payment required).
- New token in Settings invalidates the old snippet. Update your website if you rotate it.
- One floating widget per page. Use a different agent’s snippet on a different page.

Website form vs voice widget

Connections → Website form captures a phone number and starts an outbound campaign call. The Settings → Website snippet is a live in-browser voice call with this agent — no phone number required. [Connections](#) / [Campaigns](#).

Phone Numbers

Copy page

Caller ID for outbound and DID for inbound. Buy Indian numbers in the dashboard (card), then assign via API.

After purchase

The number appears in the dashboard as soon as payment and carrier provision succeed (usually seconds). Calling it from a mobile can still say **wrong number** for 5–30 minutes while the Indian terminating network updates. Assign it to the agent, dial it as `+91...` (or `0 + 10 digits` from India), and if it is still dead after an hour re-assign the number so inbound routing is linked

again. Team members see the owner's number on the shared agent — they should not buy a second one.

India pricing

Monthly rental by series: **80-series ₹599, 79-series ₹699, others ₹659** — plus ₹100 setup and 18% GST (card on first purchase). Renews every 30 days at the same price from your wallet.

KYC required before purchase.

GET

List your numbers

[Full schema](#)

```
GET https://app.snapserve.ai/api/phone-numbers
```

bashCopy

```
curl https://app.snapserve.ai/api/phone-numbers \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

PATCH

Assign to agent

[Full schema](#)

```
PATCH https://app.snapserve.ai/api/phone-numbers/{id}/assign
```

bashCopy

```
curl -X PATCH https://app.snapserve.ai/api/phone-numbers/789/assign \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{ "agentId": 123 }'
```

Purchase via API

GET /phone-numbers/available, POST /phone-numbers/purchase/initiate, POST /phone-numbers/purchase/confirm. Most apps still run purchase in the UI (card + KYC), then automate assign via API.

DEL

Release number

[Full schema](#)

```
DELETE https://app.snapserve.ai/api/phone-numbers/{id}
```

```
bashCopy
curl -X DELETE https://app.snapserve.ai/api/phone-numbers/789 \

  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

Next: [Outbound Calls](#).

Calls & history

Place outbound PSTN calls, watch live status, and pull transcript, summary, disposition, and cost into your app.

Last updated 18 Aug 2026

In the dashboard

[Calls](#) lists every conversation — phone, webcall, and meetings — with status, duration, cost, recording, transcript, and summary. Filter failed or completed dials. Vibe → Test places a single outbound or webcall without a campaign.

Place a call (API)

Body is `agentId + toNumber` (E.164). Optional `variables` (or `parameters`) injects patient fields and questions for that dial only — [Variables](#). Optional `webhookBaseUrl` only if you must override telephony callbacks.

```
cURLNode
bashCopy
curl -X POST https://app.snapserve.ai/api/calls/outbound \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{"agentId": 36, "toNumber": "+919876543210", "variables":
{"patient_name": "Priya", "questions": ["How is your pain today?"]}]'
```

Schema: [initiateOutboundCall](#).

Transcript, summary & disposition

After completion, [GET /calls/{id}](#) includes:

- `transcript` — full conversation text
- `callSummary` — short AI summary
- `successEvaluation` — outcome evaluation when enabled
- `dispositionResult` — label from the agent Outcomes taxonomy
- `costCents` — `paise` · `durationSeconds`
- `recordingUrl` — when recording is on and upload succeeded

bashCopy

```
curl https://app.snapserve.ai/api/calls/2920 \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

jsonCopy

```
{
  "id": 2920,
  "status": "completed",
  "durationSeconds": 84,
  "costCents": 700,
  "transcript": "Agent: Hello...",
  "callSummary": "Caller asked about pricing...",
  "dispositionResult": "Callback",
  "recordingUrl": "https://..."
}
```

Prefer [webhooks](#) (`call.completed`) over polling. Do not retry identical `POST /calls/outbound` on timeout without checking whether the call already exists.

More call APIs

- [List calls](#)
- [End live call](#)
- [Set disposition](#)
- [Transfer](#) (warm or cold)

Campaigns

Dashboard auto-dialer for PSTN. Upload or stream leads, pace concurrent calls from your wallet, retry no-answers, and push hot dispositions to CRM — not a WhatsApp blast.

Last updated 18 Aug 2026

Building your own product? Prefer [POST /calls/outbound](#) plus your CRM. Campaigns are for in-house sales ops on the SnapServe UI.

Typical flow

1. Create a campaign, pick an active agent and a from-number (assigned DID).
2. Choose a lead source and map columns to agent [variables](#).
3. Set concurrency (max 10), calling hours, retries, and optional AMD (voicemail detection on the agent).
4. Start / activate. SnapServe paces dials while wallet balance lasts.
5. Watch the batch: connected, no-pickup, DNC, callbacks. Transfer matching dispositions to webhook or Sheets.

Lead sources

Source	Mode	How leads arrive
CSV upload	Batch	One file → one or more batches. Map phone, name, email, extras.
Google Sheets	Batch / auto	Connect under Connections, then dial from rows.
Website form	Continuous	Form intake POST → new lead → dial when the campaign is active.
Meta Lead Ads	Continuous	Facebook / Instagram leads into the campaign.
CRM (e.g. Zoho)	Continuous	CRM-driven intake when connected.

Wire Sheets, website, and Meta under [Connections](#) first. Continuous sources keep accepting leads while the campaign is active; CSV is a finite batch.

Pacing, hours, retries

- Concurrent calls — platform ceiling `10` per campaign.
- Calling hours — optional window + timezone. TRAI-enabled agents also block quiet hours at dial time. [Compliance](#).
- Retries — `maxAttempts` (default 1) and `retryDelayMinutes` (default 60) for no-answer / busy. DNC and completed conversations are not redialed.
- Delay between dials — `callDelaySeconds` spaces the queue.
- AMD — voicemail detection is an *agent* setting, used on every campaign dial for that agent.

What campaigns own vs the agent

- Campaign: lead list, queue, retries, hours, concurrency, lead transfer (webhook and/or Google Sheet when disposition matches).
- Agent: prompt, voice, tools, outcomes taxonomy, after-call WhatsApp / email, IRDAI/TRAI flags. [Agents](#).

Not a WhatsApp campaign

Campaigns dial **PSTN** only. WhatsApp templates and the chatbot are not a bulk campaign product. After-call WhatsApp is configured on the agent Outcomes tab after [WhatsApp](#) is connected.

Caller memory on the next dial

After a request changes (refund, shipment, reschedule), write the new status onto the lead so the agent answers follow-ups from current ground truth — not last week's transcript. Use the lead Memory tab (or Overview). Notes also sync automatically. Guide: [Caller memory updates](#).

Lead transfer

Configuration tab: when the AI disposition matches (for example Interested), POST the lead to your CRM URL and/or append a Sheets row. That is ops handoff — not a customer message. Do not confuse it with [event subscriptions](#) (every call) or form intake (website → SnapServe).

Review

Open the campaign → batch for live queue, recordings, and disposition slices. Create a redial batch from no-pickup. Export CSV from the campaigns list. Call-level transcript lives in [Calls & history](#).

API note

Campaign REST exists for the dashboard but is not in the public API Reference. Automate one-off or CRM-triggered dials with [POST /calls/outbound](#). Personalization for those calls is your backend's job unless you use campaign field mappings.

Event subscriptions

Copy page

Workspace-wide: SnapServe POSTs call results to your HTTPS URL when a conversation finishes — transcript, summary, cost, and more.

Four different “webhook” jobs

- **Event subscriptions** (this page / Developers) — SnapServe → your app for every call
- **Post-call notify** — Agent Builder → Settings → one agent's CRM URL after its calls (optional custom JSON template)
- **Form intake** — Connections / Campaigns → website form → SnapServe → dial

- **Lead transfer** — Campaign Configuration → push hot leads to CRM URL / Sheets Dashboard: [Developers](#) → [Event subscriptions](#).

Post-call notify (one agent)

Agent Builder → Settings → Post-call notify POSTs JSON to *that* agent's HTTPS URL when its call ends. The default body is the inner `data` object below (camelCase) — not wrapped in `event` / `timestamp`.

Optional JSON body template: map fields and nesting for your backend. Leave blank to keep the default SnapServe schema. This does not change Developers event subscriptions (other consumers keep the standard envelope).

```
jsonCopy
{
  "id": "{{callId}}",
  "status": "{{status}}",
  "transcript": "{{transcript}}",
  "summary": "{{callSummary}}",
  "data": "{{dispositionResult}}"
}
```

- Quoted `{{path}}` becomes a typed JSON value (numbers stay numbers; objects nest).
- Paths are camelCase (`callId`, `dispositionResult.outcome`). Snake_case aliases like `call_id` also work.
- Missing paths become `null`.
- HMAC (`X-SnapServe-Signature`) is computed over the body we actually POST.
- Invalid JSON after substitution: we send the default payload and set `X-SnapServe-Payload: default` (otherwise `custom`).

Useful keys: `callId`, `agentId`, `status`, `fromNumber`, `toNumber`, `durationSeconds`, `transcript`, `callSummary`, `dispositionResult`, `recordingUrl`, `campaignLeadId`, `createdAt`, `endedAt`.

Events

Event	When
<code>call.completed</code>	Call finished (normal path). Prefer this in new subscriptions.
<code>call.failed</code>	Call ended with a failed status
<code>call.ended</code>	Legacy alias — still matched when we send <code>call.completed</code>

POST

Register endpoint

[Full schema](#)

POST `https://app.snapserve.ai/api/webhook-endpoints`

Parameter	Type	Description
<code>url</code> required	string	Your HTTPS URL that accepts POST
<code>events</code> required	string[]	e.g. ["call.completed", "call.failed"]

bashCopy

```
curl -X POST https://app.snapserve.ai/api/webhook-endpoints \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "url": "https://your-app.example.com/hooks/snapserve",
    "events": ["call.completed", "call.failed"]
  }'
```

Save the secret

The create response includes `secret` once. It is masked as `secretHint` afterward. Copy it immediately.

GET

List endpoints

[Full schema](#)

GET `https://app.snapserve.ai/api/webhook-endpoints`

bashCopy

```
curl https://app.snapserve.ai/api/webhook-endpoints \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

Delivery

- HTTP POST JSON body
- Respond 200 within ~10 seconds
- Failed deliveries are logged; keep your endpoint reliable

Verify signatures

httpCopy

X-SnapServe-Signature: sha256=<hmac-hex-digest>

X-SnapServe-Timestamp: 1718612345

HMAC-SHA256 of `{timestamp}.{rawBody}` using your endpoint secret:

javascriptCopy

```
import crypto from "crypto";
```

```
export function verifyWebhook(rawBody, signature, timestamp, secret) {  
  const payload = `${timestamp}.${rawBody}`;  
  const expected =  
    "sha256=" +  
    crypto.createHmac("sha256", secret).update(payload).digest("hex");  
  if (!signature || signature.length !== expected.length) return false;  
  return crypto.timingSafeEqual(Buffer.from(signature),  
    Buffer.from(expected));  
}
```

Example payload

jsonCopy

```
{  
  "event": "call.completed",  
  "timestamp": "2026-07-15T12:00:00.000Z",  
  "data": {  
    "callId": 2920,  
    "agentId": 36,  
    "status": "completed",  
    "toNumber": "+916383653279",  
    "fromNumber": "+917971543255",  
    "durationSeconds": 84,  
    "costCents": 700,  
  }  
}
```

```
    "transcript": "Agent: Hello...",
    "callSummary": "Caller asked about pricing...",
    "dispositionResult": null,
    "recordingUrl": null
  }
}
```

`costCents` is paise. You can also load the full record with [GET /calls/{id}](#).

Local development

Tunnel your laptop (ngrok / Cloudflare Tunnel) to an HTTPS URL SnapServe can reach.

Wallet

Copy page

Prepaid INR balance. Amounts in *Cents fields are paise (1 INR = 100 paise).

Platform voice fee is flat **₹5 / minute** (₹1/min off with your own telephony). WhatsApp on an own Vobiz channel is billed separately — [Pricing](#). Top-ups are card-only (+18% GST) in the dashboard — most apps only read balance.

GET

Get balance

[Full schema](#)

GET <https://app.snapserve.ai/api/wallet>

bashCopy

```
curl https://app.snapserve.ai/api/wallet \
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

jsonCopy

```
{
  "balanceCents": 50000,
  "balanceInr": 500,
  "currency": "INR",
```

```
"freeCreditsGranted": true  
}
```

50000 paise = ₹500.00 (~100 minutes at ₹5/min).

Transactions

```
bashCopy  
curl "https://app.snapserve.ai/api/wallet/transactions?limit=50" \  
  -H "Authorization: Bearer $SNAPSERVE_API_KEY"
```

Top-ups

Operators add funds in the SnapServe dashboard with card checkout (Razorpay).
Payable = wallet credit + 18% GST.

Insufficient funds

Outbound dials may fail with 402 when balance is too low. Prompt the account owner to top up. See [Errors](#).

Team workspace

Invite teammates to the same agents. Partner-managed clients never see SnapServe ads, docs, or support branding.

Last updated 18 Aug 2026

What is shared

A team invite shares agents, call history (logs, transcripts, recordings), callbacks, transfers, and any phone numbers already on that workspace. Teammates can see and assign those numbers; they cannot buy or release them — purchase and billing stay on the owner account. Wallet stays on the owner. Sign-in uses an HttpOnly session cookie — do not put API keys in frontend JavaScript.

Invites

Send an invite from workspace settings. The teammate opens the link with `?token=` and joins. They then see the shared agent list and can edit or test according to their role. History shows every workspace call, not only the calls each person placed while signed in as themselves.

API keys vs dashboard

Dashboard users authenticate with the session cookie. Server integrations use `sk_live_...` — [Authentication](#). Do not mix them: a browser JWT is not a public API key.

White-label partners

On a partner host, managed client workspaces must not show SnapServe documentation, SnapServe ads, or SnapServe support. Those users build agents in the classic builder, not the SnapServe-branded Vibe marketing surface. This docs site is only on `app.snapserve.ai`.

Next

Point teammates at [Vibe](#) (direct SnapServe) or [Agents & builder](#).

Compliance

India-first outbound: TRAI DND, IRDAI disclosure for insurance, DPDP-aware data collection, and WhatsApp Business rules. This is product behaviour — not legal advice.

Last updated 18 Aug 2026

You are responsible for consent, DND, and industry licences. SnapServe injects platform disclosures where configured; it does not replace your compliance program.

TRAI / DND (outbound phone)

Outbound campaigns should respect Do Not Call lists and calling hours. Honour opt-out language on the call (the agent must stop and mark DNC). Campaign retries skip DNC dispositions. See [Campaigns](#).

IRDAI (insurance voice)

When IRDAI checks are enabled on an agent, the saved system prompt is checked against disclosure guidelines. Outbound can be blocked until the prompt includes required disclosures (the agent is AI, who it represents, and so on). Turn this on in the agent builder when you sell or service insurance.

DPDP / personal data

Collect only what the call needs. Do not ask WhatsApp or voice agents to capture full PAN, Aadhaar, or card numbers in chat. Publish a privacy policy. Webhook payloads include phone numbers and transcripts — treat them as personal data on your side.

WhatsApp Business

- Contact people who opted in; honour STOP / unsubscribe.
- Free-form text only inside the 24-hour customer-service window.
- First message to a new contact must be a Meta-approved template.
- Use the chatbot as *that business's* support or sales agent — not a general-purpose ChatGPT. [WhatsApp guide](#).
- Meta requires a human escalation path (phone, email, or in-chat handoff) on the profile.

Recordings & transcripts

Calls may be recorded and transcribed for quality and dispositions. Tell callers when the law or your policy requires it. Access is limited to the workspace that owns the call.

SnapServe API

Public builder API only: agents, calls (transcript & summary), variables, webhooks, phone numbers, wallet, and knowledge base. 38 endpoints — campaigns, onboarding, CRM, providers, and other dashboard-internal APIs are not listed here.

Base URL

<https://app.snapserve.ai/api>

Introduction

Every endpoint accepts and returns JSON over HTTPS. Follow the [Quick Start](#) for a full list-agents → outbound → get call recipe (cURL, Node, Python). Use the sidebar for schemas and ready-to-run cURL per operation. Campaigns are dashboard-only and are not listed here.

Authentication

Use a developer API key from [Authentication](#) in the `Authorization` header:

`Authorization: Bearer sk_live_...`

Dashboard session JWTs work for the browser app only. Prefer `sk_live_` keys from your backend.

Pagination

List endpoints that can return large collections accept `page` and `limit` query parameters where applicable. Check each endpoint's Query Parameters section for the exact pagination it supports.

Rate Limiting

Requests are subject to fair-use rate limiting. If you exceed the allowed rate you will receive a `429 Too Many Requests` response; retry after a short backoff.

Errors

SnapServe uses conventional HTTP status codes. `2xx` indicates success, `4xx` indicates a client error (missing or invalid parameters, authentication failures), and `5xx` indicates a server error. Error responses include a JSON body describing what went wrong.

Resources

[Agents](#)⁸

[GETPOSTPATCHDEL](#)

[Calls](#)⁶

[GETPOSTPATCH](#)

[Meetings](#)⁹

[POSTGETDEL](#)

[Variables](#)⁴

[GETPOSTPATCHDEL](#)

[Event subscriptions](#)⁴

[GETPOSTPATCHDEL](#)

[Phone Numbers](#)²

[GETPATCH](#)

[Wallet](#)²

[GET](#)

[Knowledge Base](#)³

[GETPOST](#)

List all agents

GET <https://app.snapserve.ai/api/agents>

Try it

Authorizations

`Authorizationstring` · `headerrequired`

Bearer authentication. Provide your session token as `Authorization: Bearer <token>`.

Responses

200

List of agents

Array of Agent

idintegerrequired

namestringrequired

agentModeenum | null

managed = platform master keys; byop = user-supplied keys

Allowed: "managed", "byop", null

agentTypeenum | null

Allowed: "general", "lead_qualification", "customer_support", "appointment_booking", "survey", null

descriptionstring | null

statusenumrequired

Allowed: "active", "inactive", "draft"

asrProviderstringrequired

ASR provider: deepgram, azure, whisper

asrModelstring | null

asrLanguagestring | null

Language code for the ASR provider (e.g. en, es, hi-IN)

asrBackgroundDenoisingboolean | null

Filter background noise while the user is talking

asrConfidenceThresholdnumber | null

Transcripts below this confidence score (0–1) will be filtered out

asrEndOfTurnConfidencenumber | null

Confidence threshold (0.5–0.9) required to finish a turn (Deepgram)

asrEndOfTurnTimeoutinteger | null

Maximum time to wait (ms) after speech before finishing a turn

asrKeytermsstring | null

Comma-separated keywords to boost transcription accuracy

asrSmartEndpointingenum | null

Smart endpointing mode for more accurate speech endpoint detection

Allowed: "off", "vapi", "livekit", null

asrAutoFallbackboolean | null

Automatically pick a backup STT provider if the primary fails

asrFallbackProvidersobject[] | nullShow attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstringrequired

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox, openrouter

llmModelstring | null

ttsProviderstringrequired

TTS provider: elevenlabs, openai, aws_polly, azure, cartesia, deepgram

ttsVoicestring | null

ttsModelstring | null

telephonyProviderstringrequired

Telephony: twilio, plivo, vonage

systemPromptstringrequired

temperaturenumber | null

maxDurationinteger | null

Max call duration in seconds

greetingMessagestring | null

First thing the agent says when a call connects. If blank the LLM generates an opener.

firstSpeakerenum | null

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user" keeps the agent silent until the caller speaks.

Allowed: "assistant", "user", null

endCallPhrasesstring | null

Comma-separated phrases that trigger hangup (e.g. "goodbye,bye,thanks for calling")

silenceTimeoutSecondsinteger | null

Hang up automatically after this many seconds of caller silence

languagestring | null

Primary language code passed to ASR / TTS (e.g. en-US, es, fr, hi)

backchannelingEnabledboolean | null

Inject short acknowledgement phrases while the LLM is thinking

backchannelingFrequencynumber | null

Probability (0–1) of backchanneling on each turn

webhookUrlstring | null

URL to POST a call summary JSON to when the call ends

noiseCancellationEnabledboolean | null

Request noise reduction from the ASR provider on every transcription call

inactivityMessagestring | null

Message spoken to the caller before hanging up due to silence timeout

knowledgeBaseIdinteger | null

ID of an attached knowledge base for RAG context injection

knowledgeSourceIdsinteger[]

IDs of all attached knowledge sources (many-to-many)

toolsAgentTool[] | nullShow attributes

List of tools (functions) the LLM can invoke during a call

maxConcurrentCallsinteger | null

Per-agent concurrent call cap (null = use account limit)

monthlySpendLimitCentsinteger | null

Monthly spend cap in cents (null = no limit)

dispositionSchemaDispositionField[] | nullShow attributes

User-defined fields to extract from each call via LLM

agentConfigobject | null

Advanced per-tab configuration (LLM params, engine, call, inbound, WhatsApp, analytics)

leadSourceTypestring | null

Lead source platform (e.g. instagram)

leadSourceTokenstring | null

Masked hint of the lead source access token (last 4 chars)

leadFieldsstring[] | null

Lead fields to capture per incoming lead (name, email, message)

productDetailsstring | null

Product or service details the agent should know when calling leads

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM (null = unlimited)

tokenSummarizationEnabledboolean | null

Auto-compress old turns into a summary block when history exceeds threshold

tokenSummarizationThresholdTurnsinteger | null

Number of turns after which summarization is triggered

stagedPromptEnabledboolean | null

Send only the active stage block + core identity instead of the full system prompt

stagedPromptStagesobject[] | nullShow attributes

Named prompt stages (each with name + content)

stagedPromptCoreIdentitystring | null

Core identity block always included in staged-prompt mode

inboundPhoneNumberIdinteger | null

Phone number ID assigned for inbound routing to this agent

outboundPhoneNumberIdinteger | null

Phone number ID used as caller ID for outbound calls from this agent

totalCallsinteger

successfulCallsinteger

avgDurationSecondsinteger | null

avgSttLatencyMsinteger | null

Rolling average STT latency across all completed calls (ms)

avgLlmLatencyMsinteger | null

Rolling average LLM first-token latency across all completed calls (ms)

avgTtsFirstChunkMsinteger | null

Rolling average TTS first-audio-chunk latency across all completed calls (ms)

createdAtstring · date-timerequired

updatedAtstring · date-timerequired

Create a new agent

POST<https://app.snapserve.ai/api/agents>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Body application/json · required

namestringrequired

min length 1

agentModeenum

managed = use platform master keys; byop = user supplies their own provider keys

Allowed: "managed", "byop"

agentTypestring

descriptionstring

asrProviderstringrequired

asrModelstring

asrLanguagestring | null

asrBackgroundDenoisingboolean

asrConfidenceThresholdnumber

asrEndOfTurnConfidencenumber

asrEndOfTurnTimeoutinteger

asrKeytermsstring

asrSmartEndpointingstring

asrAutoFallbackboolean

asrFallbackProvidersobject[] Show attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstringrequired

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox,

openrouter

llmModelstring

ttsProviderstringrequired

ttsVoicestring

ttsModelstring

telephonyProviderstringrequired

systemPromptstringrequired

temperaturenumber

maxDurationinteger

greetingMessagestring

firstSpeakerenum

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user" keeps the agent silent until the caller speaks.

Allowed: "assistant", "user"
endCallPhrasesstring
silenceTimeoutSecondsinteger
languagestring
backchannelingEnabledboolean
backchannelingFrequencynumber
webhookUrlstring
noiseCancellationEnabledboolean
inactivityMessagestring
toolsAgentTool[] Show attributes

List of tools (functions) the LLM can invoke during a call

agentConfigobject

Advanced per-tab configuration

leadSourceTypestring

Lead source platform (e.g. instagram)

leadSourceTokenstring

Page Access Token for the lead source (encrypted at rest)

leadFieldsstring[]

Lead fields to capture per incoming lead

productDetailsstring

Product or service details for the agent's context

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM

tokenSummarizationEnabledboolean

Auto-compress old turns into a summary block when history exceeds threshold

tokenSummarizationThresholdTurnsinteger | null

Number of turns after which summarization is triggered

stagedPromptEnabledboolean

Send only the active stage block + core identity instead of the full system prompt

stagedPromptStagesobject[] Show attributes

Named prompt stages (each with name + content)

stagedPromptCoreIdentitystring

Core identity block always included in staged-prompt mode

wizardInputsobject

Raw wizard answers passed from the dashboard. May include the ordered

micro-question/answer pairs (microAnswers) and any uploaded job description content

(jdFileContent, jdFileName). When present, the server generates the agent's system prompt server-side using the active admin master template (Qwen) and stores the result. Never returned in responses.

systemPromptGenMetaobject

Version traceability stamped when a system prompt generated via the layered System Prompt Templates store is applied and saved.

Responses

201400

Created agent

idintegerrequired

namestringrequired

agentModeenum | null

managed = platform master keys; byop = user-supplied keys

Allowed: "managed", "byop", null

agentTypeenum | null

Allowed: "general", "lead_qualification", "customer_support", "appointment_booking", "survey", null

descriptionstring | null

statusenumrequired

Allowed: "active", "inactive", "draft"

asrProviderstringrequired

ASR provider: deepgram, azure, whisper

asrModelstring | null

asrLanguagestring | null

Language code for the ASR provider (e.g. en, es, hi-IN)

asrBackgroundDenoisingboolean | null

Filter background noise while the user is talking

asrConfidenceThresholdnumber | null

Transcripts below this confidence score (0–1) will be filtered out

asrEndOfTurnConfidencenumber | null

Confidence threshold (0.5–0.9) required to finish a turn (Deepgram)

asrEndOfTurnTimeoutinteger | null

Maximum time to wait (ms) after speech before finishing a turn

asrKeytermsstring | null

Comma-separated keywords to boost transcription accuracy

asrSmartEndpointingenenum | null

Smart endpointing mode for more accurate speech endpoint detection

Allowed: "off", "vapi", "livekit", null

asrAutoFallbackboolean | null

Automatically pick a backup STT provider if the primary fails

asrFallbackProvidersobject[] | nullShow attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstringrequired

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox, openrouter

llmModelstring | null

ttsProviderstringrequired

TTS provider: elevenlabs, openai, aws_polly, azure, cartesia, deepgram

ttsVoicestring | null

ttsModelstring | null

telephonyProviderstringrequired

Telephony: twilio, plivo, vonage

systemPromptstringrequired

temperaturenumber | null

maxDurationinteger | null

Max call duration in seconds

greetingMessagestring | null

First thing the agent says when a call connects. If blank the LLM generates an opener.

firstSpeakerenum | null

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user" keeps the agent silent until the caller speaks.

Allowed: "assistant", "user", null

endCallPhrasesstring | null

Comma-separated phrases that trigger hangup (e.g. "goodbye,bye,thanks for calling")

silenceTimeoutSecondsinteger | null

Hang up automatically after this many seconds of caller silence

languagestring | null

Primary language code passed to ASR / TTS (e.g. en-US, es, fr, hi)

backchannelingEnabledboolean | null

Inject short acknowledgement phrases while the LLM is thinking

backchannelingFrequencynumber | null

Probability (0–1) of backchanneling on each turn

webhookUrlstring | null

URL to POST a call summary JSON to when the call ends

noiseCancellationEnabledboolean | null

Request noise reduction from the ASR provider on every transcription call

inactivityMessagestring | null

Message spoken to the caller before hanging up due to silence timeout

knowledgeBaseIdinteger | null

ID of an attached knowledge base for RAG context injection

knowledgeSourceIdsinteger[]

IDs of all attached knowledge sources (many-to-many)

toolsAgentTool[] | nullShow attributes

List of tools (functions) the LLM can invoke during a call

maxConcurrentCallsinteger | null

Per-agent concurrent call cap (null = use account limit)

monthlySpendLimitCentsinteger | null

Monthly spend cap in cents (null = no limit)

dispositionSchemaDispositionField[] | nullShow attributes

User-defined fields to extract from each call via LLM

agentConfigobject | null

Advanced per-tab configuration (LLM params, engine, call, inbound, WhatsApp, analytics)

leadSourceTypestring | null

Lead source platform (e.g. instagram)

leadSourceTokenstring | null

Masked hint of the lead source access token (last 4 chars)

leadFieldsstring[] | null

Lead fields to capture per incoming lead (name, email, message)

productDetailsstring | null

Product or service details the agent should know when calling leads

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM (null = unlimited)

tokenSummarizationEnabledboolean | null

Auto-compress old turns into a summary block when history exceeds threshold

tokenSummarizationThresholdTurnsinteger | null

Number of turns after which summarization is triggered

stagedPromptEnabledboolean | null

Send only the active stage block + core identity instead of the full system prompt

stagedPromptStagesobject[] | nullShow attributes

Named prompt stages (each with name + content)

stagedPromptCoreIdentitystring | null

Core identity block always included in staged-prompt mode

inboundPhoneNumberIdinteger | null

Phone number ID assigned for inbound routing to this agent

outboundPhoneNumberIdinteger | null

Phone number ID used as caller ID for outbound calls from this agent

```
totalCallsinteger
successfulCallsinteger
avgDurationSecondsinteger | null
avgSttLatencyMsinteger | null
```

Rolling average STT latency across all completed calls (ms)

```
avgLlmLatencyMsinteger | null
```

Rolling average LLM first-token latency across all completed calls (ms)

```
avgTtsFirstChunkMsinteger | null
```

Rolling average TTS first-audio-chunk latency across all completed calls (ms)

```
createdAtstring · date-timerequired
updatedAtstring · date-timerequired
```

Get a single agent

GET <https://app.snapserve.ai/api/agents/{id}>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Responses

200404

Agent details

```
idintegerrequired
namestringrequired
agentModeenum | null
```

managed = platform master keys; byop = user-supplied keys

```
Allowed: "managed", "byop", null
agentTypeenum | null
```

```
Allowed: "general", "lead_qualification", "customer_support", "appointment_booking",
"survey", null
```

```
descriptionstring | null
statusenumrequired
```

```
Allowed: "active", "inactive", "draft"
asrProviderstringrequired
```

ASR provider: deepgram, azure, whisper

```
asrModelstring | null
asrLanguagestring | null
```

Language code for the ASR provider (e.g. en, es, hi-IN)

asrBackgroundDenoisingboolean | null

Filter background noise while the user is talking

asrConfidenceThresholdnumber | null

Transcripts below this confidence score (0–1) will be filtered out

asrEndOfTurnConfidencenumber | null

Confidence threshold (0.5–0.9) required to finish a turn (Deepgram)

asrEndOfTurnTimeoutinteger | null

Maximum time to wait (ms) after speech before finishing a turn

asrKeytermsstring | null

Comma-separated keywords to boost transcription accuracy

asrSmartEndpointingenum | null

Smart endpointing mode for more accurate speech endpoint detection

Allowed: "off", "vapi", "livekit", null

asrAutoFallbackboolean | null

Automatically pick a backup STT provider if the primary fails

asrFallbackProvidersobject[] | nullShow attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstringrequired

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox, openrouter

llmModelstring | null

ttsProviderstringrequired

TTS provider: elevenlabs, openai, aws_polly, azure, cartesia, deepgram

ttsVoicestring | null

ttsModelstring | null

telephonyProviderstringrequired

Telephony: twilio, plivo, vonage

systemPromptstringrequired

temperaturenumber | null

maxDurationinteger | null

Max call duration in seconds

greetingMessagestring | null

First thing the agent says when a call connects. If blank the LLM generates an opener.

firstSpeakerenum | null

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user" keeps the agent silent until the caller speaks.

Allowed: "assistant", "user", null

endCallPhrasesstring | null

Comma-separated phrases that trigger hangup (e.g. "goodbye,bye,thanks for calling")

silenceTimeoutSecondsinteger | null

Hang up automatically after this many seconds of caller silence

languagestring | null

Primary language code passed to ASR / TTS (e.g. en-US, es, fr, hi)

backchannelingEnabledboolean | null

Inject short acknowledgement phrases while the LLM is thinking

backchannelingFrequencynumber | null

Probability (0–1) of backchanneling on each turn

webhookUrlstring | null

URL to POST a call summary JSON to when the call ends

noiseCancellationEnabledboolean | null

Request noise reduction from the ASR provider on every transcription call

inactivityMessagestring | null

Message spoken to the caller before hanging up due to silence timeout

knowledgeBaseIdinteger | null

ID of an attached knowledge base for RAG context injection

knowledgeSourceIdsinteger[]

IDs of all attached knowledge sources (many-to-many)

toolsAgentTool[] | nullShow attributes

List of tools (functions) the LLM can invoke during a call

maxConcurrentCallsinteger | null

Per-agent concurrent call cap (null = use account limit)

monthlySpendLimitCentsinteger | null

Monthly spend cap in cents (null = no limit)

dispositionSchemaDispositionField[] | nullShow attributes

User-defined fields to extract from each call via LLM

agentConfigobject | null

Advanced per-tab configuration (LLM params, engine, call, inbound, WhatsApp, analytics)

leadSourceTypestring | null

Lead source platform (e.g. instagram)

leadSourceTokenstring | null

Masked hint of the lead source access token (last 4 chars)

leadFieldsstring[] | null

Lead fields to capture per incoming lead (name, email, message)

productDetailsstring | null

Product or service details the agent should know when calling leads

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM (null = unlimited)

`tokenSummarizationEnabled` `boolean` | `null`

Auto-compress old turns into a summary block when history exceeds threshold

`tokenSummarizationThresholdTurns` `integer` | `null`

Number of turns after which summarization is triggered

`stagedPromptEnabled` `boolean` | `null`

Send only the active stage block + core identity instead of the full system prompt

`stagedPromptStages` `object[]` | `null` Show attributes

Named prompt stages (each with name + content)

`stagedPromptCoreIdentity` `string` | `null`

Core identity block always included in staged-prompt mode

`inboundPhoneNumberId` `integer` | `null`

Phone number ID assigned for inbound routing to this agent

`outboundPhoneNumberId` `integer` | `null`

Phone number ID used as caller ID for outbound calls from this agent

`totalCalls` `integer`

`successfulCalls` `integer`

`avgDurationSeconds` `integer` | `null`

`avgSttLatencyMs` `integer` | `null`

Rolling average STT latency across all completed calls (ms)

`avgLlmLatencyMs` `integer` | `null`

Rolling average LLM first-token latency across all completed calls (ms)

`avgTtsFirstChunkMs` `integer` | `null`

Rolling average TTS first-audio-chunk latency across all completed calls (ms)

`createdAt` `string` · `date-time` `required`

`updatedAt` `string` · `date-time` `required`

Update an agent

PATCH <https://app.snapserve.ai/api/agents/{id}>

Try it

Authorizations

`Authorization` `string` · `header` `required`

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

`id` `integer` `required`

Body `application/json` · `required`

`name` `string`

min length 1

agentModeenum

managed = use platform master keys; byop = user supplies their own provider keys

Allowed: "managed", "byop"

agentTypestring

descriptionstring

asrProviderstring

asrModelstring

asrLanguagestring | null

asrBackgroundDenoisingboolean

asrConfidenceThresholdnumber

asrEndOfTurnConfidencenumber

asrEndOfTurnTimeoutinteger

asrKeytermsstring

asrSmartEndpointingstring

asrAutoFallbackboolean

asrFallbackProvidersobject[] Show attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstring

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox,

openrouter

llmModelstring

ttsProviderstring

ttsVoicestring

ttsModelstring

telephonyProviderstring

systemPromptstring

temperaturenumber

maxDurationinteger

greetingMessagestring

firstSpeakerenum

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user"

keeps the agent silent until the caller speaks.

Allowed: "assistant", "user"

endCallPhrasesstring

silenceTimeoutSecondsinteger

languagestring

backchannelingEnabledboolean

backchannelingFrequencynumber

webhookUrlstring

noiseCancellationEnabledboolean

inactivityMessagestring

knowledgeBaseIdinteger

ID of an attached knowledge base for RAG context injection

knowledgeSourceIdsinteger[]

IDs of all attached knowledge sources (many-to-many)

toolsAgentTool[] Show attributes

List of tools (functions) the LLM can invoke during a call

statusstring
maxConcurrentCallsinteger
monthlySpendLimitCentsinteger
dispositionSchemaDispositionField[] Show attributes
agentConfigobject

Advanced per-tab configuration

leadSourceTypestring

Lead source platform (e.g. instagram)

leadSourceTokenstring

Page Access Token for the lead source (encrypted at rest)

leadFieldsstring[]

Lead fields to capture per incoming lead

productDetailsstring

Product or service details for the agent's context

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM

tokenSummarizationEnabledboolean

Auto-compress old turns into a summary block when history exceeds threshold

tokenSummarizationThresholdTurnsinteger | null

Number of turns after which summarization is triggered

stagedPromptEnabledboolean

Send only the active stage block + core identity instead of the full system prompt

stagedPromptStagesobject[] Show attributes

Named prompt stages (each with name + content)

stagedPromptCoreIdentitystring

Core identity block always included in staged-prompt mode

inboundPhoneNumberIdinteger | null

Phone number ID for inbound routing to this agent

outboundPhoneNumberIdinteger | null

Phone number ID used as caller ID for outbound calls

systemPromptGenMetaobject

Version traceability stamped when a system prompt generated via the layered System Prompt

Templates store is applied and saved.

Responses

Updated agent

idinteger**required**

namestring**required**

agentModeenum | null

managed = platform master keys; byop = user-supplied keys

Allowed: "managed", "byop", null

agentTypeenum | null

Allowed: "general", "lead_qualification", "customer_support", "appointment_booking", "survey", null

descriptionstring | null

statusenum**required**

Allowed: "active", "inactive", "draft"

asrProviderstring**required**

ASR provider: deepgram, azure, whisper

asrModelstring | null

asrLanguagestring | null

Language code for the ASR provider (e.g. en, es, hi-IN)

asrBackgroundDenoisingboolean | null

Filter background noise while the user is talking

asrConfidenceThresholdnumber | null

Transcripts below this confidence score (0–1) will be filtered out

asrEndOfTurnConfidencenumber | null

Confidence threshold (0.5–0.9) required to finish a turn (Deepgram)

asrEndOfTurnTimeoutinteger | null

Maximum time to wait (ms) after speech before finishing a turn

asrKeytermsstring | null

Comma-separated keywords to boost transcription accuracy

asrSmartEndpointingenenum | null

Smart endpointing mode for more accurate speech endpoint detection

Allowed: "off", "vapi", "livekit", null

asrAutoFallbackboolean | null

Automatically pick a backup STT provider if the primary fails

asrFallbackProvidersobject[] | nullShow attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstring**required**

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox, openrouter

llmModelstring | null

ttsProviderstring**required**

TTS provider: elevenlabs, openai, aws_polly, azure, cartesia, deepgram

ttsVoicestring | null

ttsModelstring | null
telephonyProviderstringrequired

Telephony: twilio, plivo, vonage

systemPromptstringrequired
temperaturenumber | null
maxDurationinteger | null

Max call duration in seconds

greetingMessagestring | null

First thing the agent says when a call connects. If blank the LLM generates an opener.

firstSpeakerenum | null

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user" keeps the agent silent until the caller speaks.

Allowed: "assistant", "user", null
endCallPhrasesstring | null

Comma-separated phrases that trigger hangup (e.g. "goodbye,bye,thanks for calling")

silenceTimeoutSecondsinteger | null

Hang up automatically after this many seconds of caller silence

languagestring | null

Primary language code passed to ASR / TTS (e.g. en-US, es, fr, hi)

backchannelingEnabledboolean | null

Inject short acknowledgement phrases while the LLM is thinking

backchannelingFrequencynumber | null

Probability (0–1) of backchanneling on each turn

webhookUrlstring | null

URL to POST a call summary JSON to when the call ends

noiseCancellationEnabledboolean | null

Request noise reduction from the ASR provider on every transcription call

inactivityMessagestring | null

Message spoken to the caller before hanging up due to silence timeout

knowledgeBaseIdinteger | null

ID of an attached knowledge base for RAG context injection

knowledgeSourceIdsinteger[]

IDs of all attached knowledge sources (many-to-many)

toolsAgentTool[] | nullShow attributes

List of tools (functions) the LLM can invoke during a call

maxConcurrentCallsinteger | null

Per-agent concurrent call cap (null = use account limit)

monthlySpendLimitCentsinteger | null

Monthly spend cap in cents (null = no limit)

dispositionSchemaDispositionField[] | nullShow attributes

User-defined fields to extract from each call via LLM

agentConfigobject | null

Advanced per-tab configuration (LLM params, engine, call, inbound, WhatsApp, analytics)

leadSourceTypestring | null

Lead source platform (e.g. instagram)

leadSourceTokenstring | null

Masked hint of the lead source access token (last 4 chars)

leadFieldsstring[] | null

Lead fields to capture per incoming lead (name, email, message)

productDetailsstring | null

Product or service details the agent should know when calling leads

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM (null = unlimited)

tokenSummarizationEnabledboolean | null

Auto-compress old turns into a summary block when history exceeds threshold

tokenSummarizationThresholdTurnsinteger | null

Number of turns after which summarization is triggered

stagedPromptEnabledboolean | null

Send only the active stage block + core identity instead of the full system prompt

stagedPromptStagesobject[] | nullShow attributes

Named prompt stages (each with name + content)

stagedPromptCoreIdentitystring | null

Core identity block always included in staged-prompt mode

inboundPhoneNumberIdinteger | null

Phone number ID assigned for inbound routing to this agent

outboundPhoneNumberIdinteger | null

Phone number ID used as caller ID for outbound calls from this agent

totalCallsinteger

successfulCallsinteger

avgDurationSecondsinteger | null

avgSttLatencyMsinteger | null

Rolling average STT latency across all completed calls (ms)

avgLlmLatencyMsinteger | null

Rolling average LLM first-token latency across all completed calls (ms)

avgTtsFirstChunkMsinteger | null

Rolling average TTS first-audio-chunk latency across all completed calls (ms)

createdAtstring · date-timerequired
updatedAtstring · date-timerequired

Delete an agent

DEL<https://app.snapserve.ai/api/agents/{id}>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Responses

204404

Deleted

No response body.

Toggle agent active status

PATCH<https://app.snapserve.ai/api/agents/{id}/toggle>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Responses

200404

Toggled agent

idintegerrequired

namestringrequired

agentModeenum | null

managed = platform master keys; byop = user-supplied keys

Allowed: "managed", "byop", null

agentTypeenum | null

Allowed: "general", "lead_qualification", "customer_support", "appointment_booking", "survey", null

descriptionstring | null

statusenum**required**

Allowed: "active", "inactive", "draft"

asrProviderstring**required**

ASR provider: deepgram, azure, whisper

asrModelstring | null

asrLanguagestring | null

Language code for the ASR provider (e.g. en, es, hi-IN)

asrBackgroundDenoisingboolean | null

Filter background noise while the user is talking

asrConfidenceThresholdnumber | null

Transcripts below this confidence score (0–1) will be filtered out

asrEndOfTurnConfidencenumber | null

Confidence threshold (0.5–0.9) required to finish a turn (Deepgram)

asrEndOfTurnTimeoutinteger | null

Maximum time to wait (ms) after speech before finishing a turn

asrKeytermsstring | null

Comma-separated keywords to boost transcription accuracy

asrSmartEndpointingenum | null

Smart endpointing mode for more accurate speech endpoint detection

Allowed: "off", "vapi", "livekit", null

asrAutoFallbackboolean | null

Automatically pick a backup STT provider if the primary fails

asrFallbackProvidersobject[] | nullShow attributes

Ordered list of backup STT providers tried when the primary fails

llmProviderstring**required**

LLM provider: openai, deepseek, anthropic, mistral, cohere, qwen, groq, sarvam, ultravox,

openrouter

llmModelstring | null

ttsProviderstring**required**

TTS provider: elevenlabs, openai, aws_polly, azure, cartesia, deepgram

ttsVoicestring | null

ttsModelstring | null

telephonyProviderstring**required**

Telephony: twilio, plivo, vonage

systemPromptstring**required**

temperaturenumber | null

maxDurationinteger | null

Max call duration in seconds

greetingMessagestring | null

First thing the agent says when a call connects. If blank the LLM generates an opener.

`firstSpeakerenum | null`

Who speaks first when a call connects. "assistant" plays the greeting (or LLM opener); "user" keeps the agent silent until the caller speaks.

`Allowed: "assistant", "user", null`

`endCallPhrasesstring | null`

Comma-separated phrases that trigger hangup (e.g. "goodbye,bye,thanks for calling")

`silenceTimeoutSecondsinteger | null`

Hang up automatically after this many seconds of caller silence

`languagestring | null`

Primary language code passed to ASR / TTS (e.g. en-US, es, fr, hi)

`backchannelingEnabledboolean | null`

Inject short acknowledgement phrases while the LLM is thinking

`backchannelingFrequencynumber | null`

Probability (0–1) of backchanneling on each turn

`webhookUrlstring | null`

URL to POST a call summary JSON to when the call ends

`noiseCancellationEnabledboolean | null`

Request noise reduction from the ASR provider on every transcription call

`inactivityMessagestring | null`

Message spoken to the caller before hanging up due to silence timeout

`knowledgeBaseIdinteger | null`

ID of an attached knowledge base for RAG context injection

`knowledgeSourceIdsinteger[]`

IDs of all attached knowledge sources (many-to-many)

`toolsAgentTool[] | null`Show attributes

List of tools (functions) the LLM can invoke during a call

`maxConcurrentCallsinteger | null`

Per-agent concurrent call cap (null = use account limit)

`monthlySpendLimitCentsinteger | null`

Monthly spend cap in cents (null = no limit)

`dispositionSchemaDispositionField[] | null`Show attributes

User-defined fields to extract from each call via LLM

`agentConfigobject | null`

Advanced per-tab configuration (LLM params, engine, call, inbound, WhatsApp, analytics)

`leadSourceTypestring | null`

Lead source platform (e.g. instagram)

`leadSourceTokenstring | null`

Masked hint of the lead source access token (last 4 chars)

leadFieldsstring[] | null

Lead fields to capture per incoming lead (name, email, message)

productDetailsstring | null

Product or service details the agent should know when calling leads

snapserveAgentIdstring | null

SnapServe platform agent ID used to fetch executions from the SnapServe API

contextWindowTurnsinteger | null

Sliding-window context: only the last N turns are sent to the LLM (null = unlimited)

tokenSummarizationEnabledboolean | null

Auto-compress old turns into a summary block when history exceeds threshold

tokenSummarizationThresholdTurnsinteger | null

Number of turns after which summarization is triggered

stagedPromptEnabledboolean | null

Send only the active stage block + core identity instead of the full system prompt

stagedPromptStagesobject[] | nullShow attributes

Named prompt stages (each with name + content)

stagedPromptCoreIdentitystring | null

Core identity block always included in staged-prompt mode

inboundPhoneNumberIdinteger | null

Phone number ID assigned for inbound routing to this agent

outboundPhoneNumberIdinteger | null

Phone number ID used as caller ID for outbound calls from this agent

totalCallsinteger

successfulCallsinteger

avgDurationSecondsinteger | null

avgSttLatencyMsinteger | null

Rolling average STT latency across all completed calls (ms)

avgLlmLatencyMsinteger | null

Rolling average LLM first-token latency across all completed calls (ms)

avgTtsFirstChunkMsinteger | null

Rolling average TTS first-audio-chunk latency across all completed calls (ms)

createdAtstring · date-timerequired

updatedAtstring · date-timerequired

Update caller-specific memory for the next call

POST <https://app.snapserve.ai/api/agents/{id}/caller-memory/{phone}/facts>

Try it

Write operator/CRM facts for this caller. The agent injects them as ground truth on the next inbound, outbound, or campaign call so it can answer follow-ups without re-asking.

`note` becomes `operator\_update`. `context` / `facts` keys are stored as `ext\_<key>`.

For a single dial's patient fields and questions, pass `variables` on POST
/calls/outbound. Phone must be URL-encoded.

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

phonestringrequired

Body application/json · required

notestring

Freeform update (refund approved, appointment moved). Stored as operator_update.

factsobject[] Show attributes

contextobject

Map of request fields, e.g. order_status=shipped

Responses

201400403404

Facts written

phoneNumberstringrequired

writtenobject[]required

Full memory detail for one caller — current facts with history chains, episodes with sentences

GET <https://app.snapserve.ai/api/agents/{id}/caller-memory/{phone}>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

phonestringrequired

Responses

200404

Caller memory detail

factsCallerDetailFact[]requiredShow attributes
episodesCallerDetailEpisode[]required

List calls with optional agent filter

GET <https://app.snapserve.ai/api/calls>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Query Parameters

agentIdinteger | nulloptional
statusstring | nulloptional

Responses

200

List of calls

Array of [Call](#)

idintegerrequired
agentIdintegerrequired
agentNamestringrequired
statusenumrequired
Allowed: "pending", "ringing", "in_progress", "connected", "completed", "failed",
"cancelled", "transferred", "no_pickup", "voicemail", "busy", "booked",
"callback_scheduled"
toNumberstringrequired
fromNumberstringrequired
durationSecondsinteger | null
transcriptstring | null
recordingUrlstring | null
recordingEnabledboolean | null

Whether the "Record Calls" toggle was enabled on the agent for this call

recordingErrorstring | null

Reason the recording failed to finalize/upload when recording was enabled

errorMessagestring | null
metadatastring | null
createdAtstring · date-timerequired
endedAtstring · date-time | null
sttLatencyMsinteger | null

Average STT round-trip latency across all turns (ms)

llmLatencyMsinteger | null

Average LLM time-to-first-token across all turns (ms)

ttsFirstChunkMsinteger | null

Average TTS time-to-first-audio-chunk across all turns (ms)

executionIdstring | null

Unique execution identifier for this call (exec_XXXXXXX)

costCentsinteger | null

Platform orchestration fee charged for this call in cents

callSummarystring | null

AI-generated 3-line post-call summary

successEvaluationstring | null

Post-call LLM evaluation — PASS or FAIL on first line, one-sentence reason on the second line

dispositionResultobject | null

Extracted disposition values keyed by field name

tokensSavedinteger | null

Estimated number of input tokens saved by token optimization (sliding window + summarization)

campaignIdinteger | null

ID of the outbound campaign that placed this call, derived from the call_executions linkage. Null for manual/direct/web calls.

directionenum

Call direction derived server-side. Outbound for campaign calls, webcalls, and calls where metadata.direction=outbound; inbound otherwise.

Allowed: "inbound", "outbound"

Get call details

GET <https://app.snapserve.ai/api/calls/{id}>

Try it

Authorizations

Authorizationstring · header**required**

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idinteger**required**

Responses

200404

Call details

idinteger**required**

agentIdintegerrequired
agentNamestringrequired
statusenumrequired

Allowed: "pending", "ringing", "in_progress", "connected", "completed", "failed",
"cancelled", "transferred", "no_pickup", "voicemail", "busy", "booked",
"callback_scheduled"

toNumberstringrequired
fromNumberstringrequired
durationSecondsinteger | null
transcriptstring | null
recordingUrlstring | null
recordingEnabledboolean | null

Whether the "Record Calls" toggle was enabled on the agent for this call

recordingErrorstring | null

Reason the recording failed to finalize/upload when recording was enabled

errorMessagestring | null
metadatastring | null
createdAtstring · date-timerequired
endedAtstring · date-time | null
sttLatencyMsinteger | null

Average STT round-trip latency across all turns (ms)

llmLatencyMsinteger | null

Average LLM time-to-first-token across all turns (ms)

ttsFirstChunkMsinteger | null

Average TTS time-to-first-audio-chunk across all turns (ms)

executionIdstring | null

Unique execution identifier for this call (exec_XXXXXXX)

costCentsinteger | null

Platform orchestration fee charged for this call in cents

callSummarystring | null

AI-generated 3-line post-call summary

successEvaluationstring | null

Post-call LLM evaluation — PASS or FAIL on first line, one-sentence reason on the second line

dispositionResultobject | null

Extracted disposition values keyed by field name

tokensSavedinteger | null

Estimated number of input tokens saved by token optimization (sliding window + summarization)

campaignIdinteger | null

ID of the outbound campaign that placed this call, derived from the call_executions linkage. Null
for manual/direct/web calls.

directionenum

Call direction derived server-side. Outbound for campaign calls, webcalls, and calls where `metadata.direction=outbound`; inbound otherwise.

Allowed: "inbound", "outbound"

Initiate an outbound phone call via the agent's telephony provider

POST <https://app.snapserve.ai/api/calls/outbound>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Body application/json · required

agentIdintegerrequired

toNumberstringrequired

E.164 destination number (e.g. +1234567890)

webhookBaseUrlstring

Override public base URL for webhooks (auto-detected if omitted)

variablesobject

Per-call values for this dial. Substituted into {{placeholders}} in the agent prompt/greeting and injected as a THIS CALL context block so the agent can use patient fields and a dynamic question list without hardcoding them. Arrays (e.g. questions) become a numbered list. Alias: parameters.

parametersobject

Alias of variables

Responses

201400404

Outbound call initiated

idintegerrequired

agentIdintegerrequired

agentNamestringrequired

statusenumrequired

Allowed: "pending", "ringing", "in_progress", "connected", "completed", "failed", "cancelled", "transferred", "no_pickup", "voicemail", "busy", "booked", "callback_scheduled"

toNumberstringrequired

fromNumberstringrequired

durationSecondsinteger | null

transcriptstring | null

recordingUrlstring | null
recordingEnabledboolean | null

Whether the "Record Calls" toggle was enabled on the agent for this call

recordingErrorstring | null

Reason the recording failed to finalize/upload when recording was enabled

errorMessagestring | null
metadatastring | null
createdAtstring · date-timerequired
endedAtstring · date-time | null
sttLatencyMsinteger | null

Average STT round-trip latency across all turns (ms)

llmLatencyMsinteger | null

Average LLM time-to-first-token across all turns (ms)

ttsFirstChunkMsinteger | null

Average TTS time-to-first-audio-chunk across all turns (ms)

executionIdstring | null

Unique execution identifier for this call (exec_XXXXXXX)

costCentsinteger | null

Platform orchestration fee charged for this call in cents

callSummarystring | null

AI-generated 3-line post-call summary

successEvaluationstring | null

Post-call LLM evaluation — PASS or FAIL on first line, one-sentence reason on the second line

dispositionResultobject | null

Extracted disposition values keyed by field name

tokensSavedinteger | null

Estimated number of input tokens saved by token optimization (sliding window + summarization)

campaignIdinteger | null

ID of the outbound campaign that placed this call, derived from the call_executions linkage. Null for manual/direct/web calls.

directionenum

Call direction derived server-side. Outbound for campaign calls, webcalls, and calls where metadata.direction=outbound; inbound otherwise.

Allowed: "inbound", "outbound"

Transfer an active call to another number or SIP URI

POST <https://app.snapserve.ai/api/calls/{id}/transfer>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Body application/json · required

typeenumrequired

warm = agent announces handoff before bridging; cold = immediate blind transfer

Allowed: "warm", "cold"

targetstringrequired

E.164 phone number (e.g. +15551234567) or SIP URI to transfer to

warmMessagestring

Optional message spoken to caller before the transfer (warm only)

webhookBaseUrlstring

Override public base URL for the transfer XML callback (auto-detected if omitted)

Responses

200400404409

Transfer initiated

idintegerrequired

agentIdintegerrequired

agentNamestringrequired

statusenumrequired

Allowed: "pending", "ringing", "in_progress", "connected", "completed", "failed", "cancelled", "transferred", "no_pickup", "voicemail", "busy", "booked", "callback_scheduled"

toNumberstringrequired

fromNumberstringrequired

durationSecondsinteger | null

transcriptstring | null

recordingUrlstring | null

recordingEnabledboolean | null

Whether the "Record Calls" toggle was enabled on the agent for this call

recordingErrorstring | null

Reason the recording failed to finalize/upload when recording was enabled

errorMessagestring | null

metadatastring | null

createdAtstring · date-timerequired

endedAtstring · date-time | null

sttLatencyMsinteger | null

Average STT round-trip latency across all turns (ms)

llmLatencyMsinteger | null

Average LLM time-to-first-token across all turns (ms)

`ttsFirstChunkMsinteger | null`

Average TTS time-to-first-audio-chunk across all turns (ms)

`executionIdstring | null`

Unique execution identifier for this call (exec_XXXXXXX)

`costCentsinteger | null`

Platform orchestration fee charged for this call in cents

`callSummarystring | null`

AI-generated 3-line post-call summary

`successEvaluationstring | null`

Post-call LLM evaluation — PASS or FAIL on first line, one-sentence reason on the second line

`dispositionResultobject | null`

Extracted disposition values keyed by field name

`tokensSavedinteger | null`

Estimated number of input tokens saved by token optimization (sliding window + summarization)

`campaignIdinteger | null`

ID of the outbound campaign that placed this call, derived from the `call_executions` linkage. Null for manual/direct/web calls.

`directionenum`

Call direction derived server-side. Outbound for campaign calls, webcalls, and calls where `metadata.direction=outbound`; inbound otherwise.

Allowed: "inbound", "outbound"

End an active call

PATCH <https://app.snapserve.ai/api/calls/{id}/end>

Try it

Authorizations

`Authorizationstring` · header**required**

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

`idinteger`**required**

Body `application/json`

`sttLatencyMsinteger`

Average STT latency measured for this call (ms)

`llmLatencyMsinteger`

Average LLM first-token latency measured for this call (ms)

`ttsFirstChunkMsinteger`

Average TTS first-audio-chunk latency measured for this call (ms)

tokensSavedinteger

Estimated input tokens saved via context optimization this call

Responses

200404

Call ended

idintegerrequired

agentIdintegerrequired

agentNamestringrequired

statusenumrequired

Allowed: "pending", "ringing", "in_progress", "connected", "completed", "failed", "cancelled", "transferred", "no_pickup", "voicemail", "busy", "booked", "callback_scheduled"

toNumberstringrequired

fromNumberstringrequired

durationSecondsinteger | null

transcriptstring | null

recordingUrlstring | null

recordingEnabledboolean | null

Whether the "Record Calls" toggle was enabled on the agent for this call

recordingErrorstring | null

Reason the recording failed to finalize/upload when recording was enabled

errorMessagestring | null

metadatastring | null

createdAtstring · date-timerequired

endedAtstring · date-time | null

sttLatencyMsinteger | null

Average STT round-trip latency across all turns (ms)

llmLatencyMsinteger | null

Average LLM time-to-first-token across all turns (ms)

ttsFirstChunkMsinteger | null

Average TTS time-to-first-audio-chunk across all turns (ms)

executionIdstring | null

Unique execution identifier for this call (exec_XXXXXXX)

costCentsinteger | null

Platform orchestration fee charged for this call in cents

callSummarystring | null

AI-generated 3-line post-call summary

successEvaluationstring | null

Post-call LLM evaluation — PASS or FAIL on first line, one-sentence reason on the second line

dispositionResultobject | null

Extracted disposition values keyed by field name

tokensSavedinteger | null

Estimated number of input tokens saved by token optimization (sliding window + summarization)

campaignIdinteger | null

ID of the outbound campaign that placed this call, derived from the call_executions linkage. Null for manual/direct/web calls.

directionenum

Call direction derived server-side. Outbound for campaign calls, webcalls, and calls where metadata.direction=outbound; inbound otherwise.

Allowed: "inbound", "outbound"

Manually set or override disposition fields for a call

PATCH <https://app.snapserve.ai/api/calls/{id}/disposition>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Body application/json · required

dispositionResultobject

Responses

200404

Disposition updated

idintegerrequired

agentIdintegerrequired

agentNamestringrequired

statusenumrequired

Allowed: "pending", "ringing", "in_progress", "connected", "completed", "failed", "cancelled", "transferred", "no_pickup", "voicemail", "busy", "booked", "callback_scheduled"

toNumberstringrequired

fromNumberstringrequired

durationSecondsinteger | null

transcriptstring | null

recordingUrlstring | null

recordingEnabledboolean | null

Whether the "Record Calls" toggle was enabled on the agent for this call

recordingErrorstring | null

Reason the recording failed to finalize/upload when recording was enabled

errorMessagestring | null

metadatastring | null

createdAtstring · date-time^{required}

endedAtstring · date-time | null

sttLatencyMsinteger | null

Average STT round-trip latency across all turns (ms)

llmLatencyMsinteger | null

Average LLM time-to-first-token across all turns (ms)

ttsFirstChunkMsinteger | null

Average TTS time-to-first-audio-chunk across all turns (ms)

executionIdstring | null

Unique execution identifier for this call (exec_XXXXXXX)

costCentsinteger | null

Platform orchestration fee charged for this call in cents

callSummarystring | null

AI-generated 3-line post-call summary

successEvaluationstring | null

Post-call LLM evaluation — PASS or FAIL on first line, one-sentence reason on the second line

dispositionResultobject | null

Extracted disposition values keyed by field name

tokensSavedinteger | null

Estimated number of input tokens saved by token optimization (sliding window + summarization)

campaignIdinteger | null

ID of the outbound campaign that placed this call, derived from the call_executions linkage. Null for manual/direct/web calls.

directionenum

Call direction derived server-side. Outbound for campaign calls, webcalls, and calls where

metadata.direction=outbound; inbound otherwise.

Allowed: "inbound", "outbound"

List variable registry for an agent

GET <https://app.snapserve.ai/api/agents/{id}/variables>

Try it

Authorizations

Authorizationstring · header^{required}

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Responses

200401

Variable list

Array of AgentVariable

idintegerrequired

agentIdintegerrequired

variableNamestringrequired

displayLabelstringrequired

isRequiredbooleanrequired

defaultValuestring | null

dataTypeenumrequired

Allowed: "string", "number", "date", "boolean"

createdAtstring · date-timerequired

Add a variable to an agent's registry

POST <https://app.snapserve.ai/api/agents/{id}/variables>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Body application/json · required

variableNamestringrequired

displayLabelstringrequired

isRequiredboolean

Default: false

defaultValuestring

dataTypeenumrequired

Allowed: "string", "number", "date", "boolean"

Responses

201401

Created

idintegerrequired

agentIdintegerrequired

variableNamestringrequired

displayLabelstringrequired

isRequiredbooleanrequired
defaultValuestring | null
dataTypeenumrequired
Allowed: "string", "number", "date", "boolean"
createdAtstring · date-timerequired

Update a variable in an agent's registry

PATCH<https://app.snapserve.ai/api/agents/{id}/variables/{varId}>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired
varIdintegerrequired
Body application/json · required

displayLabelstring
isRequiredboolean
defaultValuestring | null
dataTypeenum
Allowed: "string", "number", "date", "boolean"

Responses

200401404

Updated

idintegerrequired
agentIdintegerrequired
variableNamestringrequired
displayLabelstringrequired
isRequiredbooleanrequired
defaultValuestring | null
dataTypeenumrequired
Allowed: "string", "number", "date", "boolean"
createdAtstring · date-timerequired

Remove a variable from an agent's registry

DEL<https://app.snapserve.ai/api/agents/{id}/variables/{varId}>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

`idintegerrequired`
`varIdintegerrequired`

Responses

204401404

Deleted

No response body.

List all knowledge sources for the current user

GET <https://app.snapserve.ai/api/knowledge-sources>

Try it

Authorizations

`Authorizationstring · headerrequired`

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Responses

200

List of knowledge sources

Array of `KnowledgeSource`

`idintegerrequired`
`namestringrequired`
`typeenumrequired`
Allowed: "faq", "text", "website", "file"
`statusenumrequired`

Lifecycle statuses: validating (URL checks, website only), processing (ingesting), crawling (multi-page fetch, website only), ready (fully indexed), partial (website partially indexed), failed (ingestion error). Legacy values: active (= ready), error (= failed) — kept for backward compat with older rows.

Allowed: "validating", "processing", "crawling", "ready", "partial", "failed", "active", "error"
`entryCountintegerrequired`
`createdAtstring · date-timerequired`
`updatedAtstring · date-timerequired`

Attach a ready knowledge source to an agent (idempotent)

POST <https://app.snapserve.ai/api/knowledge-sources/{id}/attach-agent/{agentId}>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

agentIdintegerrequired

Responses

200404409

Source attached (or was already attached)

attachedbooleanrequired

Full-text search within a knowledge source (test AI knowledge)

POST <https://app.snapserve.ai/api/knowledge-sources/{id}/search>

Try it

Authorizations

Authorizationstring · headerrequired

Bearer authentication. Provide your session token as Authorization: Bearer <token>.

Path Parameters

idintegerrequired

Body application/json · required

querystringrequired

min length 1

limitinteger

Default: 5

Responses

200400404

Search results with matched entries and scores

answerstringrequired

LLM-generated answer based on matched entries

matchedEntriesKnowledgeSearchResult[]required

MCP Server — use SnapServe from Claude, Cursor & other AI tools

The official MCP server lets Claude (and Cursor) operate the SnapServe account behind your API key: agents, calls, campaigns, journeys, WhatsApp, Google Sheets automatic calls, knowledge, squads, webcall links, numbers, wallet, and analytics. Anything without a named tool is reachable via `snapserve_api`.

Hosted remote MCP (Claude custom connectors)

Use this URL in Claude → Customize → Connectors → Add custom connector (name `snapserve`):

textCopy
`https://app.snapserve.ai/api/mcp`

Click Connect, then paste a Dashboard → API Keys `sk_live_...` key on the SnapServe authorize page. Or, if your Claude plan shows Request headers, set `authorization` to `Bearer sk_live_...`

bashCopy
`claude mcp add snapserve --transport http \
--url https://app.snapserve.ai/api/mcp \
--header "Authorization: Bearer sk_live_..."`

Local studio (Claude Desktop / Cursor)

Requires Node.js on your machine:

jsonCopy

```
{  
  "mcpServers": {  
    "snapserve": {  
      "command": "npx",  
      "args": ["-y", "@snapserveai/mcp"],  
      "env": {  
        "SNAPSERVE_API_KEY": "sk_live_...",  
        "SNAPSERVE_BASE_URL": "https://app.snapserve.ai/api"  
      }  
    }  
  }  
}
```

```

    }
  }
}
}

```

Package on npm: [@snapserveai/mcp](https://www.npmjs.com/package/@snapserveai/mcp). Full setup (hosted HTTP + skill): [Claude skill & MCP](#). Add this to `claude_desktop_config.json` (Claude Desktop → Settings → Developer → Edit Config) or your MCP client's config, restart the app, and ask: *"List my SnapServe agents"* or *"Call +91... with my sales agent"*. A ready-made Claude skill (for Claude Code / claude.ai) is also available at github.com/srundme/snapserve-claude-skill.

Zero-dependency wrappers

Zero Dependencies

Prefer not to add a package? These production-grade client wrappers use native environment features (Node `fetch`, Python `urllib`, Go `net/http`). You can copy them directly into your codebase without installing external package dependencies.

1. TypeScript / JavaScript (Node.js 18+, Bun, Deno)

Save as `snapserve.ts` in your project:

```

typescriptCopy
/**
 * SnapServe API Client Wrapper
 * Zero dependencies (requires Node 18+ fetch)
 */
export class SnapServeClient {
  private baseUrl: string;
  private apiKey: string;

  constructor(opts?: { apiKey?: string; baseUrl?: string }) {
    this.apiKey = opts?.apiKey || process.env.SNAPSERVE_API_KEY || "";
    if (!this.apiKey) {
      throw new Error("SNAPSERVE_API_KEY is required");
    }
  }
}

```

```

    this.baseUrl = (opts?.baseUrl ||
"https://app.snapserve.ai/api").replace(/\/\$/, "");
}

private async request<T>(method: string, path: string, body?: unknown):
Promise<T> {
    const res = await fetch(`${this.baseUrl}${path}`, {
        method,
        headers: {
            "Authorization": `Bearer ${this.apiKey}`,
            "Content-Type": "application/json",
        },
        body: body ? JSON.stringify(body) : undefined,
    });
    const data = await res.json();
    if (!res.ok) {
        throw new Error(data.error || data.message || `SnapServe API Error
[${res.status}]`);
    }
    return data as T;
}

// — Agents —
async listAgents() {
    return this.request<any[]>("GET", "/agents");
}

async getAgent(agentId: number) {
    return this.request<any>("GET", `/agents/${agentId}`);
}

// — Outbound Calls —
async initiateOutboundCall(payload: { agentId: number; toNumber: string;
variables?: Record<string, any> }) {
    return this.request<{ id: number; status: string; agentId: number;
toNumber: string }>("POST", "/calls/outbound", payload);
}

async getCall(callId: number) {
    return this.request<any>("GET", `/calls/${callId}`);
}

// — Webhooks —
async listWebhookEndpoints() {
    return this.request<any[]>("GET", "/webhook-endpoints");
}

async createWebhookEndpoint(payload: { url: string; events: string[] }) {
    return this.request<{ id: number; url: string; secret: string }>("POST",
"/webhook-endpoints", payload);
}

// — Wallet & Account —

```

```

    async getWallet() {
        return this.request<{ balance: number }>("GET", "/wallet");
    }
}

// — Example Usage —
/*
const client = new SnapServeClient({ apiKey: "sk_live_YOUR_KEY" });
const agents = await client.listAgents();
const call = await client.initiateOutboundCall({
    agentId: agents[0].id,
    toNumber: "+919876543210",
    variables: { customer_name: "Karthik" }
});
console.log("Call initiated:", call.id);
*/

```

2. Python (Python 3.8+)

Save as `snapserve.py` in your project:

```

pythonCopy
"""
SnapServe API Client Wrapper (Python)
Zero dependencies — uses Python standard library.
"""

import json
import os
import urllib.request
import urllib.error

class SnapServeClient:
    def __init__(self, api_key: str = None, base_url: str =
"https://app.snapserve.ai/api"):
        self.api_key = api_key or os.environ.get("SNAPSERVE_API_KEY")
        if not self.api_key:
            raise ValueError("SNAPSERVE_API_KEY is required")
        self.base_url = base_url.rstrip("/")

    def _request(self, method: str, path: str, payload: dict = None):
        url = f"{self.base_url}{path}"
        headers = {
            "Authorization": f"Bearer {self.api_key}",
            "Content-Type": "application/json"
        }
        data = json.dumps(payload).encode("utf-8") if payload else None
        req = urllib.request.Request(url, data=data, headers=headers,
method=method)

```

```

    try:
        with urllib.request.urlopen(req) as resp:
            return json.loads(resp.read().decode("utf-8"))
    except urllib.error.HTTPError as e:
        err_body = e.read().decode("utf-8")
        raise RuntimeError(f"SnapServe API Error [{e.code}]: {err_body}")

def list_agents(self):
    return self._request("GET", "/agents")

def get_agent(self, agent_id: int):
    return self._request("GET", f"/agents/{agent_id}")

def initiate_outbound_call(self, agent_id: int, to_number: str,
variables: dict = None):
    payload = {"agentId": agent_id, "toNumber": to_number}
    if variables:
        payload["variables"] = variables
    return self._request("POST", "/calls/outbound", payload)

def get_call(self, call_id: int):
    return self._request("GET", f"/calls/{call_id}")

def get_wallet(self):
    return self._request("GET", "/wallet")

# — Example Usage —
# client = SnapServeClient(api_key="sk_live_YOUR_KEY")
# agents = client.list_agents()
# call = client.initiate_outbound_call(agent_id=agents[0]["id"],
to_number="+919876543210")
# print("Call ID:", call["id"])

```

3. Go Native Client

Save as `snapserve.go` in your project:

```

goCopy
package snapserve

import (
    "bytes"
    "encoding/json"
    "fmt"
    "io"
    "net/http"
    "time"
)

```

```

type Client struct {
    BaseURL    string
    APIKey     string
    HTTPClient *http.Client
}

func NewClient(apiKey string) *Client {
    return &Client{
        BaseURL:    "https://app.snapserve.ai/api",
        APIKey:     apiKey,
        HTTPClient: &http.Client{Timeout: 10 * time.Second},
    }
}

func (c *Client) InitiateOutboundCall(agentID int, toNumber string, variables
map[string]interface{}) (map[string]interface{}, error) {
    payload := map[string]interface{}{
        "agentId": agentID,
        "toNumber": toNumber,
    }
    if variables != nil {
        payload["variables"] = variables
    }
    data, _ := json.Marshal(payload)

    req, _ := http.NewRequest("POST", c.BaseURL+"/calls/outbound",
bytes.NewBuffer(data))
    req.Header.Set("Authorization", "Bearer "+c.APIKey)
    req.Header.Set("Content-Type", "application/json")

    resp, err := c.HTTPClient.Do(req)
    if err != nil {
        return nil, err
    }
    defer resp.Body.Close()

    body, _ := io.ReadAll(resp.Body)
    if resp.StatusCode >= 400 {
        return nil, fmt.Errorf("SnapServe API Error [%d]: %s",
resp.StatusCode, string(body))
    }

    var result map[string]interface{}
    json.Unmarshal(body, &result)
    return result, nil
}

```

OpenAPI Specification

For full endpoint schemas and interactive testing, explore the [API Reference](#).

Prefer chatting with Claude instead of writing wrappers? See [Claude skill & MCP](#).

Reference

Errors

Copy page

Failed requests return JSON { "error": "..." } (sometimes with code or issues). Treat non-2xx as failures.

HTTP status codes

Status	Meaning
401	Missing/invalid session or sk_live_ key
400	Validation failed — check issues[] or error string
402	Payment / wallet — often insufficient balance
403	Forbidden (suspended account, compliance block)
404	Resource not found, or you hit api.snapserve.ai / docs.snapserve.ai (use app.snapserve.ai)
409	Conflict (e.g. number already taken)
429	Rate limited — back off and retry
5xx	Server / upstream provider error — retry with jitter

Auth examples

```
jsonCopy
{ "error": "Unauthorized" }
{ "error": "Invalid or revoked API key" }
```

Prefer [webhooks](#) over tight polling loops to avoid 429.

Rate limits

Authenticated traffic has a higher per-user allowance than anonymous IP limits. On 429, wait and retry with backoff.

Idempotency

Do not spam identical `POST /calls/outbound` on network timeouts without checking whether a call was already created (list recent calls or store your own idempotency key).

Pricing

[Copy page](#)

Prepaid INR wallet — no monthly SaaS tiers. Card top-up (Razorpay), then usage deducts as voice, WhatsApp, and numbers run. Amounts in *Cents / paise are INR × 100.

Last updated 18 Aug 2026

[Live rates](#)

Dashboard and API can override WhatsApp message rates in platform settings. Figures below are the shipped defaults. Voice is a flat ₹5/min for both managed keys and BYOP.

Voice (phone & webcall)

Item	Price	Notes
Welcome credit (new accounts)	₹500	No GST on the grant
Orchestration (managed or BYOP LLM/STT/TTS)	₹5.00 / min	Answered minutes, pro-rata
Own telephony discount	– ₹1.00 / min	Your Twilio / Plivo / Vobiz creds + fromNumber
Partner-managed client	Partner-set	Partner wallet; client does not pick SnapServe list price

₹500 ≈ 100 minutes at ₹5/min. A ₹1,000 top-up: you pay ₹1,180 (18% GST); wallet gains ₹1,000 ≈ 200 minutes. Failed / no-pickup legs that never connect are not charged as answered minutes.

Phone numbers

Item	Price	Notes
80-series DID	₹599 / 30 days	Plus 18% GST on first card purchase
79-series DID	₹699 / 30 days	Plus 18% GST on first card purchase
Other series	₹659 / 30 days	Plus 18% GST on first card purchase
Setup (first purchase)	₹100	Once per number, + GST
Renewal	Same as rental	Debited from wallet every 30 days

High wallet balance (above ₹20,000) can pay the first purchase from wallet instead of a fresh card charge. KYC is required before buy. [Phone numbers](#).

WhatsApp (own Vobiz channel)

Billed from the SnapServe wallet only when the channel is own (paths 1–3 on [WhatsApp](#)). Path 4 (Wati / Gupshup webhook) and Meta-only BYO BSP sends are not billed here — you pay that provider. Shared Instant WhatsApp is platform-subsidized and capped, not this rate card.

Item	Price	Notes
Utility template	₹0.40	40 paise · Meta-approved UTILITY
Authentication template	₹0.50	OTP / AUTHENTICATION
Default / unknown template	₹0.50	When category is missing
Marketing template	₹1.20	120 paise · MARKETING
Free-form text or media	₹0.25	Inside the 24-hour window only
WhatsApp calling	₹1.50 / min	Answered WhatsApp voice, not PSTN

Chatbot replies are free-form sends (₹0.25 each, plus the 30/phone/day cap). After-call templates use the template row that matches Meta's category.

Read rates from the API

Session cookie or `sk_live_` — same auth as the rest of the API.

```
httpCopy
GET https://app.snapserve.ai/api/billing/rates
GET https://app.snapserve.ai/api/whatsapp/rates
GET https://app.snapserve.ai/api/wallet
```

`/billing/rates` returns managed and BYOP voice tiers (both ₹5/min today).
`/whatsapp/rates` returns the live WhatsApp paise card plus defaults. Wallet helpers:
[Wallet](#).

Payments

- Checkout is card only (Razorpay). No UPI in-product.
- Minimum top-up credit: ₹100 + 18% GST on the payable.
- Outbound PSTN fails with `402` when wallet is empty. [Errors](#).

FAQ

Short answers to the issues builders hit most often.

What is the app URL and API base URL?

App: `https://app.snapserve.ai` (dashboard). Docs: `https://app.snapserve.ai/docs`. API base URL: `https://app.snapserve.ai/api` — use this only with `Authorization: Bearer sk_live_...` from your server. Opening `/api` in a browser shows `Cannot GET /api` (expected — it is not a webpage). Prefer [API Reference](#). `api.snapserve.ai` and `docs.snapserve.ai` are not SnapServe hosts — they 404. Guide: [Authentication](#).

Where is support on the dashboard?

In-app Jarvis is off while we rebuild it. Use [Vibe](#) or the [Agents builder](#).

Where do I start a first agent?

Direct SnapServe: [Vibe](#) (Chat → Agent → Connect → Test). Partner-managed workspaces use the classic [Agents builder](#).

I assigned a call number — why isn't WhatsApp working?

A voice DID is not WhatsApp until you connect it on Connections → WhatsApp. If the number is already on Meta, paste WABA ID, Phone Number ID, and a System User token — you do not need a Vobiz channel just to send templates. Personal WhatsApp cannot share that number. Guide: [WhatsApp](#).

Will Meta block the WhatsApp chatbot?

Not for a business answering its own customers on the official API. Meta blocks general-purpose ChatGPT-style bots and spam (blocks/reports). Stay inside the 24-hour window, use templates to start new threads, honour STOP. [WhatsApp](#) · [Compliance](#).

Do I create the Vobiz channel in the Vobiz console?

Usually no. If the number is already on Meta Cloud API, SnapServe talks to Meta only — skip Vobiz. Vobiz is used when SnapServe sells you the WhatsApp number or you turn on WhatsApp calling. [WhatsApp](#).

I pressed Start capture in Meta OTP but the code never appears

Click Start capture and wait for listening..., then in Meta choose Voice call — not SMS (a SnapServe DID cannot receive SMS). The spoken 6-digit code shows on that page after Meta rings the number. The OTP call will not appear in Call History — capture answers it instead of your agent. If a player appears, listen and type the digits into Meta. If the number is already verified on your WABA, skip OTP and paste Phone Number ID + token on Connections. [WhatsApp](#).

Can I pass {{customer_name}} on POST /calls/outbound?

No. That endpoint only accepts `agentId` and `toNumber`. Map columns in a [campaign](#), or put stable copy in the prompt. [Quick Start](#).

Why did my outbound call fail with 401?

Missing or wrong key, or the request went to the wrong host. Use `https://app.snapserve.ai/api` with `Authorization: Bearer sk_live_...` from

[Authentication](#). Session JWTs are for the browser dashboard only.
`api.snapserve.ai` is not the API (it 404s).

Agent is draft — can I still call?

The API may still dial draft agents, but for production toggle the agent to active in the builder so behavior is intentional and published.

Where are transcript and summary?

On the call record: [GET /calls/{id}](#) fields `transcript`, `callSummary`, `successEvaluation`, `dispositionResult`. Also delivered on `call.completed` webhooks when configured.

How do I connect Google Calendar?

Dashboard → Connections → Bookings calendar → connect Google → link that calendar on the agent's booking tools. Full steps: [Bookings calendar](#). To *join* Meet/Zoom/Teams as a bot, use Meeting bots ([Meetings guide](#)), not Bookings calendar.

How do variables work?

Define names on the agent, use `{{name}}` in the prompt, map values from campaigns or your app. Guide: [Variables](#).

How long until a purchased number can receive calls?

It shows in the dashboard immediately after payment. The carrier can still treat it as a wrong number for 5–30 minutes (rarely up to an hour) while routing updates. Assign it to the agent and dial +91.... If it is still unreachable, re-assign the number on Phone Numbers so inbound routing is linked again.

Why don't teammates see the number I bought?

They should — the workspace now lists the owner's numbers on shared agents. Teammates must not buy a second number. If they still see a purchase prompt, refresh or re-open the agent. See [Team workspace](#).

Why can't I buy a phone number?

Complete KYC, pay by card (₹599–₹699/mo by series + ₹100 setup + 18% GST), and have wallet funds for renewals. See [Phone numbers](#).

What does costCents mean?

Paise (INR × 100). Example: 700 = ₹7.00. Platform rate is ₹5/min. [Pricing](#).

UPI for top-up?

Not offered — card checkout via Razorpay only.

How do I verify webhooks?

HMAC of `{timestamp}.{rawBody}` vs `X-SnapServe-Signature`. [Event subscriptions](#).

Can I use SnapServe from Claude?

Yes — install the SnapServe Claude skill + MCP with your `sk_live_...` key. Guide: [Claude skill & MCP](#).

Changelog

Notable documentation and API-consumer changes.

2026-08-25 — MCP docs: npm name + tool count

- Claude skill & MCP docs now recommend published `@snapserveai/mcp` (`npx -y @snapserveai/mcp`) and note 76 tools (was listed as 67).

- Hosted connector remains <https://app.snapserve.ai/api/mcp> (see [SDKs → MCP](#)).

2026-08-25 — Platform URLs (Hosts renamed)

- Intro page Hosts is now labeled Platform URLs: App, Docs, and API base URL (<https://app.snapserve.ai/api>).
- Opening `/api` in a browser is not a page (Cannot GET /api). The card links to [API Reference](#) instead; use the base URL only with a Bearer API key.

2026-08-24 — Claude MCP: full product tools

- Hosted connector <https://app.snapserve.ai/api/mcp> now exposes the full SnapServe tool set (campaigns, journeys, WhatsApp, Sheets automatic calls, knowledge, squads, webcall) rather than agents/calls/wallet only.
- Older tool names (`create_outbound_call`, `snapserve_api_request`, analytics aliases) still work.

2026-08-23 — Published hosts (API + docs)

- The only public API base is <https://app.snapserve.ai/api>. api.snapserve.ai is not a SnapServe API host (it 404s).
- Docs live at <https://app.snapserve.ai/docs>, not docs.snapserve.ai.
- Dashboard → API Keys curl sample now uses the live base URL.

2026-08-22 — Jarvis: Karthikeyan voice, colloquial Tamil, creates as you talk

- In-app Jarvis UI has been removed (overlay and rail). A new assistant plan is incoming.
- Guide: [Jarvis](#).

2026-08-20 — Voice Memory: address the caller on match

- When a voiceprint match lands, the agent now speaks immediately — *Hi Priya — good to hear from you again* — instead of waiting for the next LLM turn. If they are still talking, it waits for the pause, then takes the floor. Match without stored facts still greets them.

2026-08-20 — Agent Builder: every tab is panels

- Script, Sound, Actions, After the call, and Settings use the same filled panel: title inside the box, not floating above it. Welcome and Talk sit in one shape each; Fast / Balanced / Patient are equal cards; Actions groups (booking, messaging, recording) are stacked rows inside a panel instead of loose uppercase labels.
- The editor column sits on a muted page with a bordered sheet. At a glance is a checklist block, not three separate chips.

2026-08-20 — Agent Builder: one column, aligned layout

- Header, tabs, and every builder page now share the same left edge and page width. Tabs split *Build* (Overview → After the call) from *Review* (Activity, Settings, Versions). Script and Sound show ready/not-ready chips in the header.
- Overview sections are real panels now: title inside the box, equal-height Phone and Knowledge, trial line nested in Phone. Builder no longer flattens card corners.

2026-08-20 — Connections vs Agent Builder

- Connections is the raw-material page: WhatsApp number, Brevo, Google Calendar. Agent Builder only *uses* those — turn on send, pick a Meta template, map it to an outcome, pick a meeting.
- After the call: each outcome rule can pick which approved WhatsApp template to send. Fast / Balanced / Patient stays on Sound. Settings no longer duplicates STT endpointing.

2026-08-20 — Agent Builder: Actions in one place

- Tabs are job-named: Script, Sound, Actions, After the call, Activity. Voicemail moved onto After the call. Connecting WhatsApp / email / Google stays under Connections.
- After the call maps each outcome to an approved WhatsApp template. Fast / Balanced / Patient lives on Sound.

2026-08-20 — Agent Builder: Sarvam realtime settings

- Transcriber is a no-code screen: language, how speech is written, and brand terms. The language picker is the 23-code Sarvam table (`en-IN`, Odia as `or-IN`). Switch language during call still sends `language_code=auto`.
- Model/provider pickers and millisecond VAD sliders are gone from Transcriber. Fast / Balanced / Patient on Sound set turn-taking (`silence_duration_ms` 300 / 500 / 700). Settings no longer repeats those STT sliders.

2026-08-19 — Sarvam STT: realtime partials

- Live Sarvam STT now uses `saaras:v3-realtime (/speech-to-text-realtime/ws)`: real `transcript.partial` events, millisecond VAD, and mid-call `config.update` without reconnecting. Saarika stays on the legacy finals-only socket.
- Indic script on an English-configured agent is treated as a language switch, not garbled audio — Tamil inbound is no longer answered with "I didn't get that."
- Server VAD (`endpointing=vad, stream_type=fast`) owns turns. Barge-in uses `vad.speech_start` and early partials — not energy and not `transcript.final`. Language/mode changes go out as `config.update`. Call logs record Sarvam's billed `session.end.audio_duration_s`. Transcriber → Partial transcripts picks `fast` (default), `balanced`, or `simulated` (finals only). The socket now sends the full connect query: 8 kHz linear16, millisecond VAD, `return_timestamps`, and an optional terminology `prompt` for finals. Auto-detect uses the 24-code table (`or-IN` for Odia, not legacy `od-IN`) and reads `language / language_confidence` on transcripts.

2026-08-19 — Voice Memory: recognize mid-call

- Cross-number match runs at the first ~2.5s of caller speech, so the agent can use the previous number's memory while the call is still live. A ~5s refine and hangup re-embed still upgrade the stored print.
- On a new phone number, "do you remember me?" is no longer a hard deny while matching is still running. When a match lands, the agent cuts in to acknowledge (by name when known), even if this call started with an empty caller memory.

2026-08-19 — Gemini Live 3.1 in Agent Builder

- Model → Voice stack lists Gemini Live 3.1 again (native speech-to-speech). Classic STT + LLM + TTS stays the default. Live needs a Google API key on the workspace.

2026-08-19 — Voice Memory: telephony scores

- Cross-number voice match now uses ~5s of caller speech (or the full call at hangup), not the first 2.5s of short replies. Same-person 8 kHz scores around 0.42 now link when that voice is the only candidate.

2026-08-19 — Multilingual: Devanagari “English” requests

- Callers who ask for English in Hindi script (इंग्लिश मैडम, इंग्लिश में बात करो) now switch the agent to English. Sarvam often writes “English” as इंग्लिश, which the previous detector missed.

2026-08-19 — Cartesia Sonic 3.6 (beta)

- Agent Builder → Voice now lists Sonic 3.6 (beta) for Cartesia. API id is `sonic-preview`. Existing agents stay on `sonic-3.5` unless you switch them.
- Beta: Cartesia can change 3.6 without notice. Flip back to Sonic 3.5 if a call sounds off.

2026-08-18 — Custom post-call notify JSON

- Agent Builder → Settings → Post-call notify accepts an optional JSON template so your backend can consume the call result without transforming the payload.
- Leave the template blank for the default SnapServe body. Workspace [event subscriptions](#) are unchanged. HMAC signs the body actually POSTed. Invalid JSON falls back to the default payload (`X-SnapServe-Payload: default`).

2026-08-18 — Caller memory updates (API + campaigns)

- `POST /agents/{id}/caller-memory/{phone}/facts` writes operator/CRM facts (`note`, `context`, `facts`) that the agent injects as ground truth on the next call.
- Campaigns: lead Notes sync to the same memory; `POST /campaigns/{id}/leads/{leadId}/memory` also merges fields into lead data for the next auto-dial.

- Guide: [Caller memory updates](#). `POST /calls/outbound` still has no `variables` body field. Public API Reference: [upsertCallerMemoryFacts](#).

2026-08-18 — Docs coverage for the live product

- New guides: Vibe builder, WhatsApp (text, calling, Meta rules), Connections, Test an agent, Team workspace, Compliance.
- Sidebar grouped by job (build, connect, calls, account) with prev/next and search.
- Vibe builder chat uses managed `sarvam-105b` with high reasoning; live agents still default to `sarvam-105b-conversations`.
- Deepened Quick Start, Campaigns, and Pricing — WhatsApp pause rate card, campaign sources/pacing, and honest outbound API body (no `variables` field).

2026-08-10 — Rename the four “webhook” surfaces

- Event subscriptions — Developers (was “Webhooks”)
- Post-call notify — Agent Settings (was “Webhooks” / CRM webhook)
- Form intake — Campaigns / Connections website (was “form webhook”)
- Lead transfer — Campaign push to CRM URL / Sheets (label clarified)
- Mid-call HTTP — Agent Tools custom function

2026-08-10 — Analytics inside Agent Builder

- Agent Builder top-level Analytics tab — call volume, success, spend, latency for that agent (same data as `/app/analytics/agents/:id`).

- Settings → former Analytics sub-tab is Post-call notify (CRM URL for that agent).

2026-08-10 — Analytics in primary nav

- Platform Analytics moved from sidebar More into the primary nav (with History).

2026-08-10 — Outcomes tab & naming clarity

- Agent Builder: top-level Outcomes tab (taxonomy + after-call messages) — no longer buried under Settings → Analytics.
- Naming: Bookings calendar vs Meeting bots; mid-call WhatsApp (Tools) vs after-call (Outcomes); display name ≠ spoken brand callout on Prompt.
- Squads: edit members in-app; Callback disposition ≠ live handoff callout.

2026-08-10 — Product clarity, meetings, playbook

- Platform concepts — agent vs campaign vs Connections vs Outcomes / after-call messages vs lead transfer vs squads vs meetings.
- Meetings guide — paste link, calendar Join, booking dispatch, in-meeting tools; API Reference tag Meetings.
- Agents / Campaigns guides — Outcomes + after-call on agent; lead transfer on campaign.
- Voiceathon playbook — rewritten for Connections hub, disposition dynamics, meetings, and current nav (see repo [docs/voiceathon-participant-playbook.md](#)).

2026-07-30 — Claude skill & MCP

- Docs — new guide [Claude skill & MCP](#) for Claude Desktop / Claude Code (agents, campaigns, website webhooks, and more via live tools).
- MCP — `@snapserve/mcp` (`lib/snapserve-mcp`) with `SNAPSERVE_API_KEY` against `https://app.snapserve.ai/api`.

2026-07-15 — Docs restructure

- Learning guides — what you can build, platform concepts, agents builder, variables, knowledge base, calendar, campaigns, FAQ.
- Curated API Reference — Bolna-style public surface only (agents, calls / transcript+summary, variables, webhooks, phones, wallet, knowledge, scheduling). Campaigns and admin APIs hidden from the sidebar.
- API key auth — `Bearer sk_live_...` on the public API.
- INR billing — ₹500 welcome, ₹5/min, phones ₹800+GST, card only.