```
1 0.000000000
                      10.1.39.99
                                           255.255.255.255
                                                                UDP
                                                                         76
                                                                                50630 → 7533 Len=34
Frame 1: 76 bytes on wire (608 bits), 76 bytes captured (608 bits) on interface 0
    Interface id: 0 (eth0)
   Encapsulation type: Ethernet (1)
   Arrival Time: Feb 18, 2018 17:55:55.625865097 IST
    [Time shift for this packet: 0.000000000 seconds]
   Epoch Time: 1518956755.625865097 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 0.000000000 seconds]
   Frame Number: 1
   Frame Length: 76 bytes (608 bits)
   Capture Length: 76 bytes (608 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:data]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: AsustekC_2b:9e:81 (70:8b:cd:2b:9e:81), Dst: Broadcast (ff:ff:ff:ff:ff)
   Destination: Broadcast (ff:ff:ff:ff:ff)
       Address: Broadcast (ff:ff:ff:ff:ff)
        .... ..1. .... .... = LG bit: Locally administered address (this is NOT the factory
default)
        .... 1 .... = IG bit: Group address (multicast/broadcast)
   Source: AsustekC_2b:9e:81 (70:8b:cd:2b:9e:81)
       Address: AsustekC_2b:9e:81 (70:8b:cd:2b:9e:81)
        .... ..0. .... (factory default)
        .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 10.1.39.99, Dst: 255.255.255.255
   0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
       0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
   Total Length: 62
   Identification: 0x3fab (16299)
   Flags: 0x00
       0... = Reserved bit: Not set
        .0.. .... = Don't fragment: Not set
       ..0. .... = More fragments: Not set
   Fragment offset: 0
   Time to live: 128
   Protocol: UDP (17)
   Header checksum: 0xc9a0 [validation disabled]
   [Header checksum status: Unverified]
   Source: 10.1.39.99
   Destination: 255.255.255.255
    [Source GeoIP: Unknown]
    [Destination GeoIP: Unknown]
User Datagram Protocol, Src Port: 50630, Dst Port: 7533
   Source Port: 50630
   Destination Port: 7533
   Length: 42
   Checksum: 0x75f3 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 0]
Data (34 bytes)
     22 00 00 00 00 04 00 00 00 50 6f 72 74 27 00 00
                                                      ".....Port'..
0010 00 04 6e 1d 00 00 00 00 00 01 00 00 00 00 00
                                                      ..n.........
0020 00 00
   Data: 220000000004000000506f727427000000046e1d000000000...
    [Length: 34]
```