Microprocessor programming

This worksheet and all related files are licensed under the Creative Commons Attribution License, version 1.0. To view a copy of this license, visit http://creativecommons.org/licenses/by/1.0/, or send a letter to Creative Commons, 559 Nathan Abbott Way, Stanford, California 94305, USA. The terms and conditions of this license allow for free copying, distribution, and/or modification of all licensed works by the general public.

Resources and methods for learning about these subjects (list a few here, in preparation for your research):

Question 1

What is the difference between a JMP ("jump") instruction and a CALL ("call") instruction? Where might each type of branching command be used? Hint: one of these is used to execute a subroutine. $\underline{file~01426}$

Answer 1

A JMP instruction simply tells the microprocessor to "jump" to a specified address. A CALL instruction similarly redirects program flow to a specified address, but remembers its place so the program may "return" where it left off.

Notes 1

Discuss the concept of a *subroutine* with your students, and how subroutines economize program size.

Question 2

An important feature of microprocessors is the use of *flag* registers. What, exactly, is a "flag", and what are they used for in microprocessor programming? Identify some common machine-language commands that set flags, and some common commands that read flags.

file 01431

Answer 2

Flags are single-bit registers in a microprocessor set according to the results of an operation. Arithmetic and logical operations are common examples of commands that set flags. Conditional operations such as "Jump if Zero" are based on flag status: that is, the status of certain flags dictate what a conditional operation will do.

Notes 2

When I began learning microprocessor programming, I wondered how conditional operations such as JZ "knew" whether to jump or not. It was apparent from inspection of various programs that these conditional operations based their "decision" on the command immediately preceding, but I had no idea how this communicative link was made. Once I researched flags, though, it all made sense.