

DFG Proposal - State of the Art

Dr. Joachim Wassermann, Johannes Salvermoser

Objectives

In order to assess seismic hazard and the different types of volcanic hazards, it is crucial to have a profound knowledge about source mechanisms. Seismic signals, the recordings of ground displacement, -velocity and -acceleration of different spatial directions yield the most promising results for investigations of physical processes inside volcanoes.

More precisely, we are able to identify seismic signals that accompany volcanic eruptions. Nevertheless, to date it is not possible to accurately predict eruptions, neither in exact timing, place nor volume of erupted material. For intensively investigated volcanoes (e.g. Etna, Merapi, Piton de la Fournaise, etc.), due to recent technical effort and expertise, we can at least roughly estimate timing and eruption styles via seismological methods. However, the important question whether a volcanic surface eruption is immanent or the activity is reflecting an intrusion which may act as a future source of volcanic activity is unanswered, as the question about the erupted volume is. Our goal is to shed light on the physical processes going along with different seismo-volcanic signals to better understand the link between source mechanisms (derived from observed signals) and eruption styles.

Source mechanisms of long period events and very long period events on volcanoes were investigated by several authors (e.g. [Ohminato *et al.*, 1998; Chouet *et al.*, 2003; Cesca *et al.*, 2008; Cannata *et al.*, 2009; De Barros *et al.*, 2011]), as they often offer insights into the dynamics of the fluid flow in the volcanic feeder system and thus let us determine the upcoming eruption style. The important tool for determination of source mechanisms is moment tensor inversion from seismometer recordings. The moment tensor of a seismic signal is the mathematical description of the processes in the source region and can be obtained by processing recordings of (large) seismometer arrays.

Problems with MTI

Various studies dealt with source inversion at active volcanoes. Due to different parameters, especially data deficiency (poor instrument coverage), unknown or simplified velocity models, near field observation and the associated very local effect of strain-rotation coupling (SRC), they are confronted with non-uniqueness in our moment tensor inversions. That means, different source mechanisms are found that could explain the same observations, which makes it hard or even impossible to determine the true solution.

The problem associated with every source inversion, processed with real seismic data, is to find a proper velocity model of the subsurface. Velocity models are the fundamental sources of ambiguity in most studies as they are hard to determine from seismic signals only. Often borehole measurements could improve the models by yielding additional geological information, but these measurements are expensive, consume vast amounts of energy and require large machinery. Moreover in volcanic regions, temperature gradients of the subsurface and topography are generally inconvenient for sufficiently deep drilling.

Velocity models

In terms of shallow-surface velocity models, the most prominent and established methods are the horizontal-to-vertical spectral ratio (**HVSR**) and the spatial autocorrelation (**SPAC**) method.

The SPAC method was first described by *Aki* [1957] and an accurate review can be found in *Chavez-Garcia et al.* [2005]: the specific measurement setup and processing allows to determine phase velocities using the records of ambient vibrations (e.g. microtremor). The seismometers are arranged such that they form a spatial filter for the signal, i.e. they are put at constant distances forming pairs along different azimuths. Usually, circular arrays with a sensor in the center (cf. *Aki* [1965]) are used to measure phase velocities of wave fields crossing it. By averaging over several of these circular arrays, one can estimate azimuthal averages of the spatial auto-correlation for a fixed inter-receiver distance. This is used to infer shear-velocity profiles under the array.

Obviously, this array method requires a large number of instruments which makes it less attractive for monitoring badly accessible areas like volcanoes. Nevertheless, SPAC certainly yields the most accurate shear-velocity models of the subsurface.

Here goes HVSR

Advantages ensue from investigating rotational ground motions. *Igel et al.* [2005] proposed a method to determine surface-wave phase velocities from the ratio of vertical rotation rate $\dot{\Omega}_z$ and transversal acceleration a_τ :

$$v_{ph} = \frac{1}{2} \cdot \frac{a_\tau}{\dot{\Omega}_z} \quad (1)$$

As a part of a Master's thesis *Wietek et al.* [2013] used this principle to derive shallow-subsurface velocity profiles by evaluation of dispersion curves, obtained from processing the Love-wave fraction of ambient seismic noise. They related seismometer recordings to rotational data retrieved from array derived rotations (ADR) but also motivate the use of rotational point measurements if suitable devices are available.

Our intent is to use portable 6-component stations in the field to gain shallow 1D velocity models from point measurements. These can be performed subsequently, thus with one 6-C sensor we are able to estimate 2D velocity models from local microseismicity on a volcano.

A well-defined velocity model yields the opportunity to reduce the non-uniqueness of source mechanisms from MTI without being dependent on using large seismometer arrays. Moreover as explained below, we simultaneously solve the problem of SRC by employing rotational measurements.

We want to test if we can put constraints on the source mechanisms by that and will relate the measured data to the theoretically possible source mechanisms.

Strain-rotation coupling

Strain-rotation coupling is an effect that acts in a local scale, i.e. large scale strain is converted to small scale rotational motions. Under the condition of linear elasticity and small strain values, the effect can be approximated as linear [*van Driel et al.*, 2012]. After *Harrison* [1976] the associated, dimensionless coupling constants are defined as:

$$c_{ij} = \frac{\omega_j}{\epsilon_i} = \frac{\text{strain} - \text{induced rotation around } j - \text{axis}}{\text{strain component } i} \quad (2)$$

Typically, SRC is caused by inhomogeneities in the subsurface which are especially common in volcanic environments. *van Driel et al.* [2012] conducted finite element simulations related to small scale inhomogeneities in order to determine coupling constants for different random ground models but also for practical 3D examples.

Important findings of their simulations were that coupling constants are largest for rotation around the z-axis. Additionally, larger constants were determined for larger correlation length, respectively contrast in elastic constants. Therefore, the effect of SRC seems negligible for short correlation lengths or small contrast which is not the case for volcanoes where material contrasts are naturally high (unconsolidated ash vs. breccia/tuff).

Strain rotation coupling is problematic due to its effect on moment tensor inversion. There are two possibilities to deal with this issue:

1. Point measurements of rotational motions (e.g. ring laser, fiber optic gyroscopes, multi-pendulums, etc):
A 3-component rotational sensor is attached to a 3-component (3-C) seismometer to obtain the complete trajectory of the wave field.
2. Array measurements (e.g. seismogeodetic method):
The full spatial gradient of the wave field (rotation, normal strain, shear strain) can be estimated, but only under the assumption that the rotation is linear over the array. Thus, site effects like SRC at single stations are averaged out (not measurable) if the array is large enough.

Graizer [2010] described the effect of rotations on translational seismograms: they change the projection of gravity onto horizontal seismometer components due to the tilt, they cause. In the case of high strain-rotation coupling constants, we need to correct the affected seismograms for the tilt effect which is only possible via point measurements as described in (1). Therefore, in order to preserve the complete information about the moment tensor of a seismic event (cf. source mechanism), the tilt effect has to be considered.

Note that different factors are crucial for the effective influence of strain induced rotations on seismograms:

- coupling constants
- relative magnitude of strain and rotation
- radiation pattern of the source
- source receiver distance
- seismic phases

However as mentioned above, large arrays are often not feasible at volcanoes. We want to show if source inversion on an active volcano with a smaller number of 6-C stations yield reasonable results and can confirm the improved results of previous numerical simulations. The findings shall be compared to measurements with a small array of 3-C stations in order to ascertain the influence of SRC on moment tensor inversion.

Recapitulation of this section: the main source for non-uniqueness in seismic inverse problems are under-determined velocity models for the shallow subsurface. Strain-rotation coupling (definition below) also plays a role, especially for small arrays. There are clear signs that rotational measurements additional to 3-C recordings can improve the determination of source mechanisms (see Approaches).

We want to verify and utilize the principle of point measurements in field at the Stromboli volcano, where large arrays are hardly manageable due to topography and often not feasible for reasons of economy.

In the following sections, the impact of poor velocity models on MTI shall be exemplified and eventually recent approaches to reducing non-uniqueness will be argued.

Moment tensor inversions on active volcanoes

This section deals with source inversion solutions of previous studies and shall motivate why we want/need to constrain the number of theoretical source mechanisms.

Recently, *Chouet et al.* [2010] performed waveform inversion on VLP (very long period) waveforms of the 2008/2009 eruptive activity of Kilauea volcano, Hawaii. The authors considered three different classes of source mechanisms:

1. three single-force components only
2. six moment tensor components only
3. three single-force + six moment tensor components

Their selection of the best fitting solutions was based on minimized residual error, the relevance of free parameters used in the model (Akaike's Information Criterion) and the physical significance of the resulting mechanisms (plausibility). Eventually, they could confine the solution space to volumetric component and a vertical single force component. Nevertheless, this allowed for a wide range of different solutions especially for the volumetric component, that could be explained by various pipe and dike geometries, intersecting or dipping at multiple angles and interacting with cracks.

Before *Cesca et al.* [2008] had similar problems with finding a unique source mechanism for long period events during the 2001 Kilauea eruptions. They especially investigated the impact of topography on the source inversion. In synthetic tests, they tested different velocity models, including layering for the caldera area and homogeneous profiles outside. Uncertainties were discovered for layered models that have been proposed by several authors and are associated with strongly varying thicknesses of layers. Of course

the variety of models and the homogeneous velocity assumption in the surroundings respectively, contributed to increase the non-uniqueness in their subsequent 3D-modeling. An important factor associated with source mechanisms surely is the source location. Especially, the depth estimates may vary strongly according to the employed velocity model.

Etna: *Cannata et al.* [2009]; *De Barros et al.* [2011]

Stromboli: *Chouet et al.* [1997, 2003]; *Auger et al.* [2006]

→ Go more into detail about source mechanisms, they found? on stromboli?

Approaches

In the past years several approaches were made with the purpose to come up with solutions for the problems stated above. Some of these studies, mainly based on synthetic inversions, are presented to show that there is progress in the field of MTI.

Maeda et al. [2011]; *van Driel et al.* [2012] showed recently that the tilt effect (SRC) caused by near source observations at active volcanoes can be computed in advance. Thus, it is possible to estimate the true source mechanism when using corresponding tilt-including Green's function.

To overcome the problem of non-uniqueness of MTIs *Bernauer et al.* [2014] proposed a probabilistic source inversion approach which also includes additional information of 6-C recordings (3 components of translation and 3 components of rotation). Testing millions of scenarios and adding rotational ground motion data to their numerical simulations, they could reduce the non-uniqueness of their subsurface velocity models.

That works because additional ground rotation data ω yield information about space derivatives (velocities) in z-direction (see eq. 3) in their horizontal components. This

$$\begin{pmatrix} \omega_x \\ \omega_y \\ \omega_z \end{pmatrix} = \frac{1}{2} \begin{pmatrix} \delta_x \\ \delta_y \\ \delta_z \end{pmatrix} \times \begin{pmatrix} u_x \\ u_y \\ u_z \end{pmatrix} = \frac{1}{2} \begin{pmatrix} \delta_y u_z - \delta_z u_y \\ \delta_z u_x - \delta_x u_z \\ \delta_x u_y - \delta_y u_x \end{pmatrix} \quad (3)$$

$\mathbf{u} = (u_x, u_y, u_z)$ translation vector
 $\omega = (\omega_x, \omega_y, \omega_z)$ ground rotation
 $\nabla = (\delta_x, \delta_y, \delta_z)$ nabla operator

theoretically allows to infer gradients of the wave field at depth which greatly contributes to finding a well-defined ground velocity model.

In that context, they refer to the seismogeodetic method [*Spudich et al.*, 1995; *Spudich*

and Fletcher, 2008] to infer array derived rotations (ADR).

On the other hand, they motivate the utilization of rotational point measurements (e.g. fiber-optic gyroscopes) and combine them with 3-component seismometer to 6-C sensors. In their simulations, the precise, point-wise measurement of rotations allowed for a substantially better reduction of the non-uniqueness of seismic inverse problems compared to the averaged measurements via ADR. Moreover, less 6-C sensors were needed to obtain reasonable or better results than with many 3-C stations.

Numerical simulations showed that both issues, SCR and uncertain velocity models, can be reduced by measuring 3-component rotational motions additional to the 3-C seismometer recordings. Nevertheless, this has to be proved by real data processing which we want to conduct after field measurements on an active volcano (Stromboli, Italy). In addition, our goal is to beforehand check with synthetics if the advantages associated with 6-C sensors allow for constraints, and therefore help to determine physical mechanisms in the source region of volcanic microseismicity.

Synthetics

Synthetic tests: How do rotational signals of magma rising in a cylindrical dyke look like? (Bernauer paper?)

Can we see anything with rotational measurements?

Bibliography

- AKI, K. (1957), Space and time spectra of stationary stochastic waves, with special reference to microtremors.
- AKI, K. (1965), A note on the use of microseisms in determining the shallow structures of the earth's crust, *GEOPHYSICS*, 30(4), 665–666, doi:10.1190/1.1439640.
- AUGER, E., L. D'AURIA, M. MARTINI, B. CHOUET, AND P. DAWSON (2006), Real-time monitoring and massive inversion of source parameters of very long period seismic signals: An application to Stromboli volcano, Italy, *Geophysical Research Letters*, 33(4), n/a–n/a, doi:10.1029/2005GL024703.
- BERNAUER, M., A. FICHTNER, AND H. IGEL (2014), Reducing nonuniqueness in finite source inversion using rotational ground motions, *Journal of Geophysical Research: Solid Earth*, 119(6), 4860–4875, doi:10.1002/2014JB011042.
- CANNATA, A., M. HELLWEG, G. D. GRAZIA, S. FORD, S. ALPARONE, S. GRESTA, P. MONTALTO, AND D. PATAN (2009), Long period and very long period events at Mt. Etna volcano: Characteristics, variability and causality, and implications for their sources,

- Journal of Volcanology and Geothermal Research*, 187(34), 227 – 249, doi:http://dx.doi.org/10.1016/j.jvolgeores.2009.09.007.
- CESCA, S., J. BATTAGLIA, T. DAHM, E. TESSMER, S. HEIMANN, AND P. OKUBO (2008), Effects of topography and crustal heterogeneities on the source estimation of lp event at kilauea volcano, *Geophysical Journal International*, 172(3), 1219–1236, doi:10.1111/j.1365-246X.2007.03695.x.
- CHAVEZ-GARCIA, F. J., M. RODRIGUEZ, AND W. R. STEPHENSON (2005), An alternative approach to the spac analysis of microtremors: Exploiting stationarity of noise, *Bulletin of the Seismological Society of America*, 95(1), 277–293, doi:10.1785/0120030179.
- CHOUET, B., P. DAWSON, T. OHMINATO, M. MARTINI, G. SACCOROTTI, F. GIUDICEPIETRO, G. DE LUCA, G. MILANA, AND R. SCARPA (2003), Source mechanisms of explosions at stromboli volcano, italy, determined from moment-tensor inversions of very-long-period data, *Journal of Geophysical Research: Solid Earth*, 108(B1), ESE 7–1–ESE 7–25, doi:10.1029/2002JB001919.
- CHOUET, B., G. SACCOROTTI, M. MARTINI, P. DAWSON, G. DE LUCA, G. MILANA, AND R. SCARPA (1997), Source and path effects in the wave fields of tremor and explosions at stromboli volcano, italy, *Journal of Geophysical Research: Solid Earth*, 102(B7), 15129–15150, doi:10.1029/97JB00953.
- CHOUET, B. A., P. B. DAWSON, M. R. JAMES, AND S. J. LANE (2010), Seismic source mechanism of degassing bursts at kilauea volcano, hawaii: Results from waveform inversion in the 1050 s band, *Journal of Geophysical Research: Solid Earth*, 115(B9), n/a–n/a, doi:10.1029/2009JB006661.
- DE BARROS, L., I. LOKMER, C. J. BEAN, G. S. O'BRIEN, G. SACCOROTTI, J.-P. MTAXIAN, L. ZUCCARELLO, AND D. PATAN (2011), Source mechanism of long-period events recorded by a high-density seismic network during the 2008 eruption on mount etna, *Journal of Geophysical Research: Solid Earth*, 116(B1), n/a–n/a, doi:10.1029/2010JB007629.
- GRAIZER, V. (2010), Strong motion recordings and residual displacements: What are we actually recording in strong motion seismology?, *Seismological Research Letters*, 81(4), 635–639, doi:10.1785/gssrl.81.4.635.
- HARRISON, J. C. (1976), Cavity and topographic effects in tilt and strain measurement, *Journal of Geophysical Research*, 81(2), 319–328, doi:10.1029/JB081i002p00319.
- IGEL, H., U. SCHREIBER, A. FLAWS, B. SCHUBERTH, A. VELIKOSELTSEV, AND A. COCHARD (2005), Rotational motions induced by the m8.1 tokachi-oki earthquake, september 25, 2003, *Geophysical Research Letters*, 32(8), n/a–n/a, doi:10.1029/2004GL022336.
- MAEDA, Y., M. TAKEO, AND T. OHMINATO (2011), A waveform inversion including tilt: method and simple tests, *Geophysical Journal International*, 184(2), 907–918, doi:10.1111/j.1365-246X.2010.04892.x.
- OHMINATO, T., B. A. CHOUET, P. DAWSON, AND S. KEDAR (1998), Waveform inversion of very long period impulsive signals associated with magmatic injection beneath kilauea volcano, hawaii, *Journal of Geophysical Research: Solid Earth*, 103(B10), 23839–23862, doi:10.1029/98JB01122.
- SPUDICH, P. AND J. B. FLETCHER (2008), Observation and prediction of dynamic ground strains, tilts, and torsions caused by the mw 6.0 2004 parkfield, california, earthquake and aftershocks, derived from upsar array observations, *Bulletin of the Seismological Society of America*, 98(4), 1898–1914, doi:10.1785/0120070157.
- SPUDICH, P., L. K. STECK, M. HELLWEG, J. B. FLETCHER, AND L. M. BAKER (1995), Transient stresses at parkfield, california, produced by the m 7.4 landers earthquake of june 28, 1992: Observations from the upsar dense seismograph array, *Journal of Geophysical Research: Solid Earth*, 100(B1), 675–690, doi:10.1029/94JB02477.

- VAN DRIEL, M., J. WASSERMANN, M. NADER, B. SCHUBERTH, AND H. IGEL (2012), Strain rotation coupling and its implications on the measurement of rotational ground motions, *Journal of Seismology*, 16(4), 657–668, doi:10.1007/s10950-012-9296-5.
- WIETEK, A., J. WASSERMANN, C. HADZIIOANNOU, AND H. IGEL (2013), Array derived rotation estimation of phase velocities using spatial autocorrelation arrays, Master's Thesis, Ludwig-Maximilians-University Munich, proc.