

Clipboard Paste

Font Arial 12 A A I U

Alignment

Number

Conditional Formatting

Cells

Editing

POLICY TIP Your organization recommends that you apply the sensitivity: Confidential.

Apply sensitivity

A1 Instruction:

- 1) The ProgMods tab can be copied (as required) to create multiple ProgMods tabs, according to the programming module in the study
- 2) Update the "Title" of the ProgMods to be descriptive (e.g. 5A.Baseline Characteristics)
- 3) List the newly added ProgMods tab(s) in Section C of the Cover tab
- 4) Delete any examples in grey italic text that are not relevant/applicable to the study once the programming specification has been finalized

Title 7.SCT

Section A: Defining Medication Available Period (MAP) medications

Time Period	Variable	Label	Values	Definition	Code Lists Group	Additional Notes	Date (Initial)
FU_PD	LOT1_TX_AUTO_DT_1	Date of patient's first transplant after LOT1_START_DT	date, missing	For each patient: Identify a patient's earliest SCT TX_AUTO{t} where: if LOT1_START_DT <= TX_AUTO{t} <= ENDDATE then = TX_AUTO{t}	Tab 47		
FU_PD	LOT1_TX_AUTO_DT_2	Date of patient's second transplant after date, missing LOT1_START_DT		For each patient: Let the subsequent AUTO SCT date following the AUTO SCT date used to define LOT1_TX_AUTO_DT_1 be TX_AUTO{t+1}. if not missing(LOT1_TX_AUTO_DT_1) then = TX_AUTO{t+1} if missing(TX_AUTO{t+1}) then = missing.	Tab 47		



A	B	C	D	E	F	G
FU_PD	TX_YYYY	Date of YYYY sct X	date, missing	Where: YYYY: AUTO, ALLO or CART A patient may have X AUTO/ALLO transplants where X = 1,2,3,... If a patient has no sct YYYY claims then their values for TX_YYYYX will be set to missing for all X. For each patient: Iterate over the patient's ordered AUTO sct claim's sct_DT_SOURCE: if earliest sct_DT_SOURCE: set TX_AUTO1 to equal max(sct_DT_SOURCE) occurring in (earliest sct_DT_SOURCE + 13) Tab 47/48	Starting with multiple sct claims to define, patient level for sct dataset. For each patient: Iterate over the patient's ordered ALLO sct claim's sct_DT_SOURCE and set TX_ALLO1 = sct_DT_SOURCE for the first ALLO claim, TX_ALLO2 = sct_DT_SOURCE for the second ALLO claim, ... and so on. Iterate over the patient's ordered CAR-T claim's sct_DT_SOURCE and set TX_ALLO1 = sct_DT_SOURCE for the first CART claim, TX_ALLO2 = sct_DT_SOURCE for the second CART claim, ... and so on.	
				If X>1 and not missing(sct_DT_SOURCE) then: if (sct_DT_SOURCE - TX_AUTO(X-1) = 1) >= 60 then: sct_DT_SOURCE is the earliest_date and marks the start of the next 14 day window. Iterate over the claims {i} occurring in this window and let TX_AUTOX = sct_DT_SOURCE for claim{i} where: earliest_date <= sct_DT_SOURCE{i} <= earliest_date+13 and not((earliest_date <= sct_DT_SOURCE{i+1} <= earliest_date+13) or (sct_DT_SOURCE{i+1} >= TX_AUTO(X-1) + 179)) Otherwise set to TX_YYYYX to missing		
8						

