...ink for records where molecular_marker='BCL6'.

		C	D	E	F
			Values	Definition	Additional Notes
BCL2		BCL2 Expression or Rearrangement Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	BCL2 status based all records in the molecular_market table where molecular_marker='BCL2' AND assessed='true' in the time period. Positive if there is at least one record with a positive interpretation, negative if there is at least one record with negative interpretation, unknown otherwise, missing if patient has no record. Using all records in molecular_marker where molecular_marker='BCL2' AND assessed='true' in the time period, assign BCL2 as following: 1) If interpretation IN ('positive', 'high', 'partial') for at least one record, then BCL2='Positive'; 2) Else if interpretation IN ('negative', 'low', 'intermediate', 'normal_range', 'no_over_expression', 'no_loss_of_expression') for at least one record AND no interpretation IN ('positive', 'high', 'partial'), then BCL2='Negative'; 3) If interpretation IN ('equivocal', 'inconclusive', 'null'), then BCL2='Unknown'; 4) Else BCL2='Missing' when there is no record where molecular_marker='BCL2' in the time period.	This is the biomarker status definition according to Method 1, Baseline Ever Status, in the protocol: If any results are positive, then patient is positive; If any results are negative and none are positive, then patient is negative; If no results are positive or negative, then unknown status; If no results available, then missing. Note that in CDTA: interpretation IN ('positive', 'high', 'partial') = positive result; interpretation IN ('negative', 'low', 'intermediate', 'normal_range', 'no_over_expression', 'no_loss_of_expression') = negative result.
	PRE_BIO	BCL2N	BCL2 Expression or Rearrangement Status (N)	1,2,3,4	Numeric version of BCL2: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
3	PRE_BIO	BCL2CDT	BCL2 Expression or Rearrangement Status - Closest Date	Date	Date with positive or negative status closest to the index date in the time period. Assign a value to BCL2CDT as following: 1) Select all records in molecular_marker where molecular_marker='BCL2' AND assessed='true' AND either 'collected_timedelta', 'reported_timedelta' or 'documented_timedelta' is not missing or NULL in the time period; if there is no record, then BCL2CDT= (missing); 2) Keep only records where interpretation IN ('positive', 'high', 'partial', 'negative', 'low', 'intermediate', 'normal_range', 'no_over_expression', 'no_loss_of_expression'); if there is no record, then BCL2CDT= (missing); 3) Assign a timedelta for each record as following: - If collected_timedelta is not missing or NULL, use collected_timedelta; - Else if reported_timedelta is not missing or NULL, use reported_timedelta; - Else use documented_timedelta; 4) Select the record with timedelta corresponding to the date closest to index. If there are 2 or more records that are equally close to index date but respectively before and after index date, select the record(s) before index date; 5) Convert the timedelta to a date using disease_initial diagnosis/date_initial_diagnosis and assign to BCL2DT.	
4	PRE_BIO	BCL2C	BCL2 Expression or Rearrangement Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	BCL2 status based on the test result closest to the index date in the time period. If BCL2='Unknown', then BCL2C='Unknown'; If BCL2='Missing', then BCL2C='Missing'; Else select record(s) where molecular_marker='BCL2' AND assessed='true' AND date on closest date BCL2CDT, and assign BCL2C as following: If all interpretation IN ('positive', 'high', 'partial'), then BCL2C='Positive'; If all interpretation IN ('negative', 'low', 'intermediate', 'normal_range', 'no_over_expression', 'no_loss_of_expression'), then BCL2C='Negative'; If there are records with both positive and negative interpretations, then BCL2C='Unknown'; If there are records with positive interpretation and interpretation IN ('equivocal', 'inconclusive', 'null'), then BCL2C='Positive'; If there are records with negative interpretation and interpretation IN ('equivocal', 'inconclusive', 'null'), then BCL2C='Negative';	This is the biomarker status definition according to Method 2, Status - Closest to Index, in the protocol. Assigns value using the test with status positive or negative closest to the index date during the time period. 10/6/2023 | 15/6/2023 | 20/6/2023 | status | closest date Patient 1 | Positive | Indexdt | Negative | Positive | 10/6/2023 Patient 2 | Unknown | Indexdt | Negative | Negative | 20/6/2023 Patient 3 | Positive | Indexdt | Negative | Unknown | 10/6/2023 Negative
5	PRE_BIO	BCL2CN	BCL2 Expression or Rearrangement Status - Closest (N)	1,2,3,4	Numeric version of BCL2C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
6	PRE_BIO	BCL6	BCL6 Expression or Rearrangement Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='BCL6'.	
7	PRE_BIO	BCL6N	BCL6 Expression or Rearrangement Status (N)	1,2,3,4	Numeric version of BCL6: 1='Positive';	

Numeric version of BCL6:
1='Positive';

Time Period	Variable	Label	Values	Definition	Additional Notes
PRE_BIO	BCL6N	BCL6 Expression or Rearrangement Status (N)	1,2,3,4	Numeric version of BCL6: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	BCL6CDT	BCL6 Expression or Rearrangement Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='BCL6'	
PRE_BIO	BCL6C	BCL6 Expression or Rearrangement Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with BCL6DT and BCL6C	
PRE_BIO	BCL6CN	BCL6 Expression or Rearrangement Status - Closest (N)	1,2,3,4	Numeric version of BCL6C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	MYC	MYC Expression or Rearrangement Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='C-MYC'	
PRE_BIO	MYCN	MYC Expression or Rearrangement Status (N)	1,2,3,4	Numeric version of MYC: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	MYCCDT	MYC Expression or Rearrangement Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='C-MYC'	
PRE_BIO	MYCC	MYC Expression or Rearrangement Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with MYCDT and MYCC	
PRE_BIO	MYCCN	MYC Expression or Rearrangement Status - Closest (N)	1,2,3,4	Numeric version of MYCC: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD10	CD10 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD10'	
PRE_BIO	CD10N	CD10 Expression Status (N)	1,2,3,4	Numeric version of CD10: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD10DT	CD10 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD10'	
PRE_BIO	CD10C	CD10 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD10DT and CD10C.	
PRE_BIO	CD10CN	CD10 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD10C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	

1.Cover | 2.QC Review | 3.Data Prep | 4.StudyPop | 5A. Demos | 5B.ClinChars | 5C.BioVars | 5D.LabVars | 6.TreatVars | 7.Outcomes

AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help
Paste Cut Copy Format Painter Clipboard Font Alignment Number Styles Cells Editing Sensitivity Add-ins Copilot
Conditional Formatting Format as Table Cell Styles Insert Delete Format AutoSum Fill Clear Sort & Filter Find & Select
E22 Same as BCL2, but for records where molecular_marker='CD19'.

	A	B	C	D	E	F
1	Time Period	Variable	Label	Values	Definition	Additional Notes
22	PRE_BIO	CD19	CD19 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD19'.	
23	PRE_BIO	CD19N	CD19 Expression Status (N)	1,2,3,4	Numeric version of CD19: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
24	PRE_BIO	CD19DT	CD19 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD19'.	
25	PRE_BIO	CD19C	CD19 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD19DT and CD19C.	
26	PRE_BIO	CD19CN	CD19 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD19C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
27	PRE_BIO	CD20	CD20 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD20'.	
28	PRE_BIO	CD20N	CD20 Expression Status (N)	1,2,3,4	Numeric version of CD20: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
29	PRE_BIO	CD20DT	CD20 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD20'.	
30	PRE_BIO	CD20C	CD20 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD20DT and CD20C.	
31	PRE_BIO	CD20CN	CD20 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD20C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
32	PRE_BIO	CD3	CD3 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD3'.	
33	PRE_BIO	CD3N	CD3 Expression Status (N)	1,2,3,4	Numeric version of CD3: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
34	PRE_BIO	CD3DT	CD3 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD3'.	
35	PRE_BIO	CD3C	CD3 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD3DT and CD3C.	
					Numeric version of CD3C:	

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings

AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help
Paste Cut Copy Format Painter Clipboard Arial 11 Font Wrap Text Merge & Center Alignment General Number Conditional Formatting Format as Table Cell Styles Styles Insert Delete Format Cells AutoSum Fill Clear Sort & Filter Find & Select Editing Sensitivity Add-ins Copilot

E36 Numeric version of CD3C:
1='Positive';

Time Period	Variable	Label	Values	Definition	Additional Notes
PRE_BIO	CD3CN	CD3 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD3C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD30	CD30 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD30'	
PRE_BIO	CD30N	CD30 Expression Status (N)	1,2,3,4	Numeric version of CD30: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD30DT	CD30 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD30'	
PRE_BIO	CD30C	CD30 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD30DT and CD30C	
PRE_BIO	CD30CN	CD30 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD30C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD45	CD45 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD45'	
PRE_BIO	CD45N	CD45 Expression Status (N)	1,2,3,4	Numeric version of CD45: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD45DT	CD45 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD45'	
PRE_BIO	CD45C	CD45 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD45DT and CD45C	
PRE_BIO	CD45CN	CD45 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD45C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD5	CD5 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='CD5'	
PRE_BIO	CD5N	CD5 Expression Status (N)	1,2,3,4	Numeric version of CD5: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	CD5DT	CD5 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='CD5'	

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings

E50

Time Period	Variable	Label	Values	Definition	Additional Notes
PRE_BIO	CD5C	CD5 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with CD5DT and CD5C.	
PRE_BIO	CD5CN	CD5 Expression Status - Closest (N)	1,2,3,4	Numeric version of CD5C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	IRF4	IRF4/MUM1 Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='IRF4/MUM1'.	
PRE_BIO	IRF4N	IRF4/MUM1 Expression Status (N)	1,2,3,4	Numeric version of IRF4: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	IRF4DT	IRF4/MUM1 Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='IRF4/MUM1'.	
PRE_BIO	IRF4C	IRF4/MUM1 Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with IRF4DT and IRF4C.	
PRE_BIO	IRF4CN	IRF4/MUM1 Expression Status - Closest (N)	1,2,3,4	Numeric version of IRF4C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	TP53	TP53 Mutation, Deletion or Expression Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='TP53'.	
PRE_BIO	TP53N	TP53 Mutation, Deletion or Expression Status (N)	1,2,3,4	Numeric version of TP53: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	TP53DT	TP53 Mutation, Deletion or Expression Status - Closest Date	Date	Same as BCL2, but for records where molecular_marker='TP53'.	
PRE_BIO	TP53C	TP53 Mutation, Deletion or Expression Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with TP53DT and TP53C.	
PRE_BIO	TP53CN	TP53 Mutation, Deletion or Expression Status - Closest (N)	1,2,3,4	Numeric version of TP53C: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	D17P	17P Deletion Status	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but for records where molecular_marker='del(17p)'.	
				Numeric version of D17P: 1='Positive';	

1.Cover | 2.QC Review | 3.Data Prep | 4.StudyPop | 5A. Demos | 5B.ClinChars | 5C.BioVars | 5D.LabVars | 6.TreatVars | 7.Outcomes

Ready Accessibility: Investigate Display Settings

E63 1='Positive';

Time Period	Variable	Label	Values	Definition	Additional Notes
PRE_BIO	D17PN	17P Deletion Status (N)	1,2,3,4	Numeric version of D17P 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	
PRE_BIO	D17PDT	17P Deletion Status - Closest Date	Date	Same as BCL2, but for records where molecular_markers='del(17p)';	
PRE_BIO	D17PC	17P Deletion Status - Closest	'Positive'; 'Negative'; 'Unknown'; 'Missing'	Same as BCL2, but with D17PDT and D17PC	
PRE_BIO	D17PCN	17P Deletion Status - Closest (N)	1,2,3,4	Numeric version of D17PC: 1='Positive'; 2='Negative'; 3='Unknown'; 4='Missing'	

1.Cover | 2.QC Review | 3.Data Prep | 4.StudyPop | 5A. Demos | 5B.ClinChars | 5C.BioVars | 5D.LabVars | 6.TreatVars | 7.Outcomes

Ready Accessibility: Investigate