AutoSave Off | PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only | Proprietary* • Last Modified: 12 February | Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help
Comments Share
Paste Cut Copy Format Painter Clipboard | Arial 11 Font | Wrap Text Merge & Center Alignment | General Number | Conditional Formatting Format as Table Cell Styles Styles | Insert Delete Format Cells | AutoSum Fill Clear Sort & Filter Find & Select Editing | Sensitivity Add-ins Copilot
K10 fx

we don't have any case where expired='false' and dod_timedelta is not null ; don't understand why if expired= true, death date= date of last contact; why not ' Define only for DTHFL=1(=patient/expired=TRUE) and if death date not unknown then INIT + patient/dod_timedelta' -> GS edits: Ok, I updated like this, it's much clearer.

Section A: Defining Analytic Variables

Note to Programmer: Use the naming convention 'TimePeriod_Variable'

Label	Values	Definition	Code Lists Group	Additional Notes	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)	
End of follow-up date	date	Minimum of: Date of death (INIT + patient/dod_timedelta); Date of 2nd malignancy diagnosis or cancer history recurrence (INIT + patient/censored_timedelta); Date of last contact (INIT + patient/contacted_timedelta); Date of last structured activity (LSTACTDT); Data cut date (MAXINDEX)	N/A	Specs note: Linked from variable FUED in 3 DataPrep		DDE19DEC25	FUED in dataprep to check
At least 90 days of potential follow-up flag	1=Yes; 0=No;	If (MAXINDEX - INDEX +-1) >= 90 days then 1 else 0	N/A	Because outcomes are only to be conducted in patients with index date at least 90 days prior to study cut off (i.e., where ID3MOSFU= 1)		DDE16JAN26	protocol mentions 3months(with 1 M = 30.4375 days) /NSCLC def = 'IF MAXINDEX minus INDEXDT is greater than 91, then = 1; else 0.
Patient death flag	1,0	If patient/expired= TRUE, then DTHFL= 1, otherwise DTHFL=0	N/A			DDE16JAN26	rather flag=1 if 'expired' in patient table='true', there are 6 dead patients where date of death is unknown -> GS edits: Ok, I updated like this, it's much clearer.
Date of death	date	Define only for DTHFL=1; if patient/dod_timedelta is not missing, then DTHDT=INIT + patient/dod_timedelta; else if patient/dod_timedelta is missing, then INIT + patient/contacted_timedelta	N/A			DDE16JAN26	we don't have any case where expired= 'false' and dod_timedelta is not null ; don't understand why if expired= true, death date= date of last contact; why not ' Define only for DTHFL=1(=patient/expired=TRUE) and if death date not unknown then INIT + patient/dod_timedelta' -> GS edits: Ok, I updated like this, it's much clearer.
Date of last structured activity	date	Maximum of INIT + any _timedelta variables across all tables	NA	Will be used as censoring time for overall survival		DDE16JAN26	

Overall Survival, months	continuous	Not defined for patients with less than 3 months of potential follow-up.
		
		If ID3MOSFU= 0, then OS= .
		else if DTHFL= 1 then OS=(DTHDT - INDEX +-1)/30.4375;
		else if DTHFL=0 then OS=(LSTACTDT - INDEX +-1)/30.4375;
			N/A	Note that censoring is defined on the date of last structured activity, not at the end of FU
				
				Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package
						DDE16JAN26	

Visit 250 Days After Index TRT End	*1=Yes 0=No*	*If patient has VISITDATE_SASDT from c_8cohort_visit_8 date occuring 250 days or more after the last episode date of the index line of therapy OR VISITDATE_SASDT from c_8cohort_telemedicine_8 date occuring 250 days or more after the last episode date of the index line of therapy then 1 else 0*	*N/A*	HOLD, see if it makes sense with COTA LOT algorithm			probably not, don't see where it's used in NSCLC/OC

Progression Event Flag	1=Yes;
	0=No;
	Missing
		Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up.
		If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0;
		PFSFL= . (missing);
		
		For cohorts L1+ to L4+, a progression event happens if the patient has a documented progression, initiates a next LOT, or dies.
		For i in 1-4: COHORT='Li+ treated LBCL':
		If LOTiSD not missing, then assign value as follows:
		if LOTN > i OR DTHDT is not missing OR (patient has at least one row in regimen table where regimen/line_of_therapy=i AND regimen/reason='progression') then PFSFL=1;
		else PFSFL=0;
		else if LOTiSD missing, then PFSFL= . (missing);
			N/A	(14-day gap to confirm)
				
				Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package.
						DDE16JAN26	

Progression Event Date	Date	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, the progression event date is the earliest of a documented progression, initiation a next LOT, or death. Patient without a progression event have missing PFSDT. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR PFSFL= . OR PFSFL=0; PFSDT= . (missing);	N/A	(14-day gap to confirm) Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package.		DDE16JAN26	

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings

AutoSave Off | PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only | Proprietary* • Last Modified: 12 February | Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help | Comments
Paste | Cut | Copy | Format Painter | Clipboard | Arial 11 | Font | Wrap Text | Merge & Center | Alignment | General | Number | Conditional Formatting | Format as Table | Cell Styles | Styles | Insert | Delete | Format | Cells | AutoSum | Fill | Clear | Sort & Filter | Find & Select | Editing | Sensitivity | Add-ins | Copilot
K18

Section A: Defining Analytic Variables

Note to Programmer: Use the naming convention 'TimePeriod_Variable'

Label	Values	Definition	Code List Group	Additional Notes	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)	
Progression Event Date	Date	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, the progression event date is the earliest of a documented progression, initiation a next LOT, or death. Patient without a progression event have missing PFSDT. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR PFSFL=. OR PFSFL=0, PFSDT= (missing). For i in 1-4 COHORT='Li+ treated LBCL' If PFSFL=1, then PFSDT is the minimum of LOT(i+1)SD, DTHDT, min(regimen/end_time-delta [converted to a date] among rows in regimen table where regimen/line_of_therapy=i AND regimen/reason='progression').	N/A	(14-day gap to confirm) Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If progression is due to death but CENSDT < DTHDT, then set PFSFL=0 and PFSDT=CENSDT. This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26	
Progression-free survival time, months	Numeric	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, patients without a progression event are censored at their COTA-defined censor date or last contact with healthcare provider. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR PFSFL= PFS= (missing) COHORT IN('L1+ treated LBCL', 'L2+ treated LBCL', 'L3+ treated LBCL', 'L4+ treated LBCL'), then assign value as follows: If PFSFL=1, then PFS=((PFSDT - INDEX) +1)/30.4375; else if PFSFL=0, then PFS=((CENSDT - INDEX) +1)/30.4375;	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If progression is due to death but CENSDT < DTHDT, then set PFSFL=0 and PFSDT=CENSDT. This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE19DEC25	LASTCLINICNOTEDATE : comes from NSCLC/ not defined
Presence of treatment discontinuation event	1=Yes; 0=No; Missing	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, a treatment discontinuation event happens if current LOT ends, next LOT starts, or patient dies. This definition is consistent with the COTA R package implementation. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0; TTDFL= (missing). For i in 1-4 COHORT='Li+ treated LBCL' If LOTiSD not missing, then assign value as follows: if LOTN > i OR DTHDT is not missing OR LOTiED is not missing then TTDFL=1; else TTDFL=0; else if LOTiSD missing, then TTDFL= (missing).	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: In NSCLC specs, TTDFL was named TRTDIS but inconsistent with other variables.		DDE16JAN26	same comment for the 3 months condition, to discuss with Sandra (+VIS250)
Treatment discontinuation event date	Date	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, the treatment discontinuation event date is the earliest of end of current LOT, initiation a next LOT, or death. Patient without a treatment discontinuation event have missing TRTDISDT. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TTDFL= or TTDFL=0; TTDDT= (missing); For i in 1-4 COHORT='Li+ treated LBCL' If TTDFL=1, then TTDDT is the minimum of LOTiED, LOT(i+1)SD, DTHDT;	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. For missing LOT end date, see "Solutions for missing line of therapy end dates for treatment related endpoints" in COTA R package user guide. NOTE: If treatment discontinuation event is due to death but CENSDT < DTHDT, then set TRTDIS=0 and TRTDISDT= (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26	
		Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, patients without a treatment discontinuation event are censored at the COTA-defined censor date or last contact with healthcare provided, whichever is earliest. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TTDFL=		Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package.			not a big issue since we're going to use the COTA algorithm but for the formula I think it also should

Ready | Accessibility: Investigate | Display Settings

AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help Comments Share
Paste Cut Copy Format Painter Clipboard Arial 11 Font Wrap Text Merge & Center Alignment General Number Conditional Formatting Format as Table Cell Styles Styles Insert Delete Format Cells AutoSum Fill Clear Sort & Filter Find & Select Editing Sensitivity Add-ins Copilot
K22 same comment as above -> GS: updated

Section A: Defining Analytic Variables

Note to Programmer: Use the naming convention 'TimePeriod_Variable'

	Label	Values	Definition	Code Lists Group	Additional Notes	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)	
19	Time to treatment discontinuation, months	Numeric	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, patients without a treatment discontinuation event are censored at the COTA-defined censor date or last contact with healthcare provided, whichever is earliest. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TTDFL= .; TTD= (missing); COHORT IN('L1+ treated LBCL', 'L2+ treated LBCL', 'L3+ treated LBCL', 'L4+ treated LBCL'), then assign value as follows: If TTDFL=1, then TTD=(TTDDT - INDEX)/30.4375; else if TTDFL=0, then TTD=(CENSDT - INDEX)/30.4375;	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If treatment discontinuation event is due to death but CENSDT < DTHDT, then set TRTDIS=0 and TRTDISDT= (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE19DEC25	not a big issue since we're going to use the COTA algorithm but for the formula I think it also should be TTD=((TTDDT - INDEX) +1)/30.4375 since I assume we don't want to include index date -> GS: agreed, I update here and all below. Is there are reason why you didn't suggest this update for PFS and OS as well since they use similar calculations?	

20	Presence of Next LOT or Death	1=Yes;
		0=No;
		Missing
			Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, a next treatment event happens if next LOT starts or patient dies.
			
			If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0;
			TTNTFL= (missing);
			
			For i in 1-4: COHORT='Li+ treated LBCL';
			If LOTISD not missing, then assign value as follows:
			if LOTN > i OR DTHDT is not missing then TTNTFL=1;
			else TTNTFL=0;
			else if LOTISD missing, then TTNTFL= (missing);
				N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package.		DDE16JAN26		

21	Presence of Next LOT or Death event date	Date	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, the next treatment event date is the earliest of initiation a next LOT or death. Patient without a next treatment event have missing TTNDT. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TTNTFL= or TTNTFL=0; TTNTDT= (missing); For i in 1-4: COHORT='Li+ treated LBCL'; If TTNTFL=1, then TTNTDT is the minimum of: LOT(i+1)SD, DTHDT;	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If next treatment event is due to death but CENSDT < DTHDT, then set TTNTFL=0 and TTNTDT= (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26		
22	Time to Next Treatment, months	Numeric	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, patients without a next treatment event are censored at the COTA-defined censor date or last contact with healthcare provided, whichever is earliest. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TTNTFL= .; TTNT= (missing); COHORT IN('L1+ treated LBCL', 'L2+ treated LBCL', 'L3+ treated LBCL', 'L4+ treated LBCL'), then assign value as follows: If TTNTFL=1, then TTNT=(TTNTDT - INDEX)/30.4375; else if TTNTFL=0, then TTNT=(CENSDT - INDEX)/30.4375;	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If next treatment event is due to death but CENSDT < DTHDT, then set TTNTFL=0 and TTNTDT= (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26	same comment as above -> GS: updated	
		1=Yes;	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, a next 2 LOT event happens if next subsequent LOT starts or patient dies. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0; TSSTFL= (missing);						

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings 70%

AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help Comments Share
Paste Cut Copy Format Painter Clipboard Arial 11 Font Wrap Text Merge & Center Alignment General Number Conditional Formatting Format as Table Cell Styles Styles Insert Delete Format Cells AutoSum Fill Clear Sort & Filter Find & Select Editing Sensitivity Add-ins Copilot
K26

Section A: Defining Analytic Variables

Note to Programmer: Use the naming convention 'TimePeriod_Variable'

Label	Values	Definition	Code Lists Group	Additional Notes	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)	
Presence of Next 2 LOTs or Death	1=Yes; 0=No; Missing	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, a next 2 LOT event happens if next subsequent LOT starts or patient dies. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0, TSSTFL= (missing). For i in 1-4: COHORT='Li+ treated LBCL' If LOTiSD not missing, then assign value as follows: if LOTN > (i+1) OR DTHDT is not missing then TSSTFL=1, else TSSTFL=0; else if LOTiSD missing, then TSSTFL= (missing).	N/A			DDE16JAN26	
Presence of Next 2 LOTs or Death event date	Date	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, the next 2 LOT event date is the earliest of initiation a next subsequent LOT or death. Patient without a next 2 LOT event have missing TSSTDT. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TSSTFL=. or TSSTFL=0, TSSTDT= (missing). For i in 1-4: COHORT='Li+ treated LBCL' If TSSTFL=1, then TSSTDT is the minimum of: LOT(i+2)SD, DTHDT,	N/A	NOTE: If next 2 LOT event is due to death but CENSDT < DTHDT, then set TSSTFL=0 and TSSTDT= (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26	

Time to 2nd Subsequent LOT, months	Numeric	Not defined for Overall and Untreated cohorts and for patients with less than 3 months of potential follow-up. For cohorts L1+ to L4+, patients without a next 2 LOT event are censored at the COTA-defined censor date or last contact with healthcare provided, whichever is earliest.
		
		If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR TSSTFL= ;
		TSST= (missing).
		
		COHORT IN('L1+ treated LBCL', 'L2+ treated LBCL', 'L3+ treated LBCL', 'L4+ treated LBCL'), then assign value as follows:
		if TSSTFL=1, then TSST=(TSSTDT - INDEXX)/30.4375;
		else if TSSTFL=0, then TSST=(CENSDT - INDEXX)/30.4375;
			N/A	NOTE: If next 2 LOT event is due to death but CENSDT < DTHDT, then set TSSTFL=0 and TSSTDT= (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26	same comment as above -> GS: updated

Best documented response	'Progression'; 'No response'; 'Partial response'; 'MLFS'; 'Complete response'; 'Missing';	Use mapping response_mapping object in COTA R package to map outcome/response_type to OR	N/A	Refer to COTA R package for implementation, see function best_response_by_idx() Definition is consistent with implementation in COTA R package.		DDE16JAN26	
Best documented response (numeric)	Numeric	Numeric of OR: 1='Progression'; 2='No response'; 3='Partial response'; 4='MLFS'; 5='Complete response'; 6='Missing';	N/A			DDE16JAN26	
Best documented response date	Date	Date of best documented response. Available using best_response_by_idx() in COTA R package.	N/A	Refer to COTA R package for implementation, see function best_response_by_idx()		DDE16JAN26	
		Not defined for:					

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate

AutoSave Off | PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only | Proprietary* • Last Modified: 12 February | Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help | Comments | Share
Cut | Copy | Format Painter | Paste | Clipboard | Arial 11 | Font | Wrap Text | Merge & Center | Alignment | General | Number | Conditional Formatting | Format as Table | Cell Styles | Styles | Insert | Delete | Format | Cells | AutoSum | Fill | Clear | Sort & Filter | Find & Select | Editing | Sensitivity | Add-ins | Copilot
K32

Section A: Defining Analytic Variables

Note to Programmer: Use the naming convention 'TimePeriod_Variable'

Label	Values	Definition	Code List Group	Additional Notes	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)	

Presence of end of response event	1=Yes;
	0=No;
	Missing
		Not defined for:
		- Overall and Untreated cohorts
		- patients with less than 3 months of potential follow-up
		- patients who did not achieve PR or CR during the given LOT
		For cohorts L1+ to L4+, an end of response event happens if patient has documented progression, initiates a next LOT or dies.
		
		If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR OR not in ("Complete response", "Partial response"),
		DORFL=. (missing),
		
		For i in 1-4: COHORT='Li+ treated LBCL':
		If LOTiSD not missing, then assign value as follows:
		if PFSFL=1 then DORFL=1;
		else DORFL=0;
		else if LOTiSD missing, then DORFL=. (missing),
			N/A	This is a flag to identify patients who had best response partial or complete AND who had an end of response event (progression)
				
				NOTE: If duration of respoRefer to COTA R package for implementation. Definition is consistent with implementation in COTA R package.
						DDE16JAN26	presence of DOR= 1= yes = presence of end of response
							0= censored = no end of response, correct? => could we call it 'flag for DOR'? -> GS: I used the same style as how the other similar variables (PFSFL, ORFL, TTDFL, TSSTFL) are defined (it never says "flag" in the definition). But I agree the current label is hard to understand. I proposed another version that matches the similar variables. What do you think?
							Ok, good, thanks!

End of response date	Date	Not defined for: - Overall and Untreated cohorts - patients with less than 3 months of potential follow-up - patients who did not achieve PR or CR during the given LOT For cohorts L1+ to L4+, the end of response event date is the earliest of a progression event, initiation a next LOT or death. Patient without a duration of event have missing DORDT. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR DORFL=. or DORFL=0; DORDT=. (missing); For i in 1-4: COHORT='Li+ treated LBCL': If DORFL=1, then DORDT=PFSDT	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If duration of response event is due to death but CENSDT < DTHDT, then set DORFL=0 and DORDT=. (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE22JAN26	
Duration of response, months	Numeric	Not defined for: - Overall and Untreated cohorts - patients with less than 3 months of potential follow-up - patients who did not achieve PR or CR during the given LOT For cohorts L1+ to L4+, patients without an end of response event are censored at the COTA-defined censor date or last contact with healthcare provided, whichever is earliest. If COHORT='Overall LBCL' or 'Untreated LBCL' OR ID3MOSFU=0 OR DORFL=.; DOR=. (missing); COHORT IN('L1+ treated LBCL', 'L2+ treated LBCL', 'L3+ treated LBCL', 'L4+ treated LBCL'), then assign value as follows: If DORFL=1, then DOR=(DORDT - ORDT)/30.4375; else if DORFL=0, then DOR=(CENSDT - ORDT)/30.4375;	N/A	Refer to COTA R package for implementation. Definition is consistent with implementation in COTA R package. NOTE: If duration of response event is due to death but CENSDT < DTHDT, then set DORFL=0 and DORDT=. (missing). This is consistent with implementation in COTA R package and should be automatically handled by the function(s).		DDE16JAN26	same comment as above for duration computation -> GS: updated

1.Cover | 2.QC Review | 3.Data Prep | 4.StudyPop | 5A. Demos | 5B.ClinChars | 5C.BioVars | 5D.LabVars | 6.TreatVars | 7.Outcomes
Ready | Accessibility: Investigate