AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help
Paste Cut Copy Format Painter Clipboard Calibri 12 Font Wrap Text Merge & Center Alignment General Number Conditional Formatting Format as Table Cell Styles Styles Insert Delete Format Cells AutoSum Fill Clear Sort & Filter Find & Select Editing Sensitivity Add-ins Copilot
A3

Instruction: Delete any examples in grey italic text that are not relevant/applicable to the study once the programming specification has been finalized

Section A: Inclusion / Exclusion Criteria

Note to Programmer: Use the naming convention 'TimePeriod_Variable'

Time Period	Variable	Label	Values	Definition	Additional Notes	Code Lists Group	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)
STUDY_PD	~~DLBCL~~	~~DLBCL during study period~~	~~1='Yes'; 0='No'~~	~~if INIT between MININDEX and MAXINDEX (see DEMOS tab forvar definition) AND histology/histology_description='Diffuse large B-cell lymphoma, NOS', then = 1; else = 0~~ ~~TODO: check if some patients with histology_description='Diffuse large B-cell lymphoma, NOS' also have another value for histology_description. If yes, need to decide if we want to exclude or keep~~	~~Inclusive of both the start and end date of the period;~~ ~~Also need to confirm which histology description to use: (IN THE MEANTIME SELECT only the 'Diffuse large B-cell lymphoma, NOS' catefory)~~ ~~•Diffuse large B-cell lymphoma; NOS~~ ~~•Malignant lymphoma; large B-cell; diffuse; NOS~~ ~~•Malignant lymphoma; large B-cell; diffuse; immunoblastic; NOS~~ ~~•Malignant lymphoma; large B-cell; diffuse; centroblastic; NOS~~ ~~•EBV positive diffuse large B-cell lymphoma~~	N/A		DDE 04dec25

Section B: Cohort definition

Variable	Label	Values	Definition	Additional Notes	Code Lists Group	Date Modified (Initials + Date)	QC Reviewed (Initials + Date)
LOTN	Number of LOTs	numeric	max(line_of_therapy/line_of_therapy)	Patients who have no row in line_of_therapy will have 0 (Untreated)			DDE 08dec25
LOT1SD	LOT1 Start Date	date	If LOTN>=1, then assign LOT1SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=1; else if LOTN=0, then assign LOT1SD=. (missing).			DDE16JAN26 (name changed)	DDE 08dec25
LOT2SD	LOT2 Start Date	date	If LOTN>=2, then assign LOT2SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=2; else if LOTN<2, then assign LOT2SD=. (missing).			DDE16JAN26 (name changed)	DDE 08dec25
LOT3SD	LOT3 Start Date	date	If LOTN>=3, then assign LOT3SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=3; else if LOTN<3, then assign LOT3SD=. (missing).			DDE16JAN26 (name changed)	DDE 08dec25
			If LOTN>=4, then assign LOT4SD = INIT +				

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings

Draw Page Layout Formulas Data Review View Automate Help
Arial 11 Wrap Text General
Merge & Center
Conditional Formatting Format as Table Cell Styles
Insert Delete Format
AutoSum Fill Clear
Sort & Filter Find & Select
Sensitivity Add-ins Copilot
Format Painter
Font Alignment Number Styles Cells Editing Sensitivity Add-ins

COHORTN

A	B	C	D	E	F	G	H	I
DT4SD	LOT4 Start Date		date	If LOTN>=4, then assign LOT4SD = INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy = 4; else if LOTN<4, then assign LOT4SD= (missing).			DDE 16JAN26 (name changed)	DDE 08dec25
COHORT	Analysis Cohort		Overall LBCL; L1+ treated LBCL; L2+ treated LBCL; L3+ treated LBCL; L4+ treated LBCL	COHORT='Overall LBCL'; output row; COHORT='L1+ treated LBCL' if LOT1SD between INIT and MAXINDEX AND LOTN >= 1; output row; COHORT='L2+ treated LBCL' if LOT2SD between LOT1SD and MAXINDEX AND LOTN >= 2; output row; COHORT='L3+ treated LBCL' if LOT3SD between LOT2SD and MAXINDEX AND LOTN >= 3; output row; COHORT='L4+ treated LBCL' if LOT4SD between LOT3SD and MAXINDEX AND LOTN >= 4; output row;	Output one row per patient per cohort; e.g., a patient treated with 1L will have 2 rows - one with cohort= 'Overall LBCL' and one with cohort='L1+ treated LBCL'. GS: I updated the definition to avoid recursive definition with MININDEX. Does it makes sense to use diagnosis date or the start of the previous LOT as the boundaries? Or do we want to ask e.g. LOT3SD between LOT2ED and MAXINDEX.	N/A		DDE 04dec25
COHORTN	Analysis Cohort (N)		1,2,3,4,5	Numeric code for COHORT: 1=Overall LBCL; 2=L1+ treated LBCL; 3=L2+ treated LBCL; 4=L3+ treated LBCL; 5=L4+ treated LBCL		N/A		DDE 04dec25
COHORTU	Analysis Cohort - Untreated		Treated LBCL; Untreated LBCL	If COHORT='Overall LBCL' AND LOTN>0 then COHORTU='Treated LBCL'; else COHORTU='Untreated LBCL';				DDE 04dec25
COHORTUN	Analysis Cohort - Untreated (N		1,2	Numeric code for COHORT: 1=Treated LBCL; 2=Untreated LBCL				DDE 04dec25